



# **UVVM Utility Library** – Quick Reference

```
Checks and awaits

[v_bool :=] check_value(value, [exp], [alert_level], msg, [...])

[v_bool :=] check_value_in_range(value, min_value, max_value, [alert_level], msg, [...])

check_stable(target, stable_req, [alert_level], msg, [...])

await_change(target, min_time, max_time, [alert_level], msg, [...])

await_value(target, exp, min_time, max_time, [alert_level], msg, [...])

await_stable(target, stable_req, stable_req_from, timeout, timeout_from, [alert_level], msg, [...])
```

# Logging and verbosity control set\_log\_file\_name(file\_name) log([msg\_id], msg, [...]) log\_text\_block(msg\_id, text\_block, formatting, [...]) enable\_log\_msg(msg\_id, [...]) disable\_log\_msg (msg\_id, [...]), is\_log\_msg\_enabled (msg\_id, [msg\_id\_panel])

```
Alert handling

set_alert_file_name(file_name)

alert(alert_level, msg, scope)

[tb_]note(msg, [scope])

[tb_]warning(msg, [scope])

[tb_]error(msg, [scope])

[tb_]error(msg, [scope])

set_alert_stop_limit(alert_level, limit)

v_int := get_alert_stop_limit(alert_level)

set_alert_attention(alert_level, attention, [msg])

v_attention := get_alert_attention(alert_level, number)

increment_expected_alerts_and_stop_limit(alert_level, [number, [msg, [scope]]])
```

## Reporting

set\_log\_destination (log\_destination, [quietness])

```
report_global_ctrl(VOID)
report_msg_id_panel(VOID)
report_alert_counters(VOID)
report_alert_counters(vOID)
report_alert_counters(order)
v_natural := shared_uvvm_status.found_unexpected_simulation_warnings_or_worse
v_natural := shared_uvvm_status.found_unexpected_simulation_errors_or_worse
v_natural := shared_uvvm_status.mismatch_on_expected_simulation_warnings_or_worse
v_natural := shared_uvvm_status.mismatch_on_expected_simulation_errors_or_worse
```

#### Randomization

```
v_slv := random(length)
v_sl := random(VOID)
{v_int, v_real, v_time} := random(min_value, max_value)
random([min_value, [max_val]], v_seed1, v_seed2, v_target)
randomize(seed1, seed2)
```

```
String handling
           := to_string(val, [...])
v strina
v_string
           := justify(val, justified, width, format_spaces, truncate)
           := fill string(val, width)
v string
v string
           := to upper(val)
v character := ascii to char(ascii pos, [ascii allow])
v_int
            := char_to_ascii(character)
v_natural := pos_of_leftmost(character, string, [result_if_not_found])
          := pos of rightmost(character, string, [result if not found])
v strina
           := remove initial chars(string, number of chars(natural))
v_string
           := get procedure name from instance name(string)
v string
           := get process name from instance name(string)
v string
           := get entity name from instance name(string)
v strina
           := replace(string, target_character, exchange_character)
replace(inout line, target_character, exchange_character)
          := pad_string(val, char, width, [side])
v_string
```

## Signal generators

clock\_generator(clock, [clock\_count], clock\_period, [clock\_high\_percentage] / [clock\_high\_time])
clock\_generator(clock, clock\_ena, [clock\_count], clock\_period, clock\_name, [clock\_high\_...])
adjustable\_clock\_generator(clock\_signal, clock\_ena, clock\_period, clock\_high\_percentage)
adjustable\_clock\_generator(clock\_signal, clock\_ena, clock\_period, clock\_name, clock\_high\_percentage)
adjustable\_clock\_generator(clock\_signal, clock\_ena, clock\_count, clock\_period, clock\_name, clock\_high\_percentage)
gen\_pulse (target, [pulse\_value] pulse\_duration, [blocking\_mode], msg) or (target, [pulse\_value], clock\_signal, num\_periods, msg)

## Synchronisation

block\_flag(flag\_name, msg, [already\_blocked\_severity, [scope]])
unblock\_flag(flag\_name, msg, trigger, [scope])
await\_unblock\_flag(flag\_name, timeout, msg, [flag\_returning, [timeout\_severity, [scope]]]
await\_barrier(barrier\_signal, timeout, msg, [timeout\_severity, [scope]])

normalize\_and\_check(value, target, mode, value\_name, target\_name, msg)

#### BFM Common Package

wait\_until\_given\_time\_after\_rising\_edge(clk, wait\_time)
wait\_until\_given\_time\_before\_rising\_edge(clk, time\_to\_edge, clk\_period)
wait\_num\_rising\_edge(clk, num\_rising\_edge)
wait\_num\_rising\_edge\_plus\_margin(clk, num\_rising\_edge, margin)
wait\_on\_bfm\_sync\_start(clk, bfm\_sync, setup\_time, config\_clock\_period, time\_of\_falling\_edge, time\_of\_rising\_edge)
wait\_on\_bfm\_exit(clk, bfm\_sync, hold\_time, time\_of\_falling\_edge, time\_of\_rising\_edge)
check\_clock\_period\_margin(clock, bfm\_sync, time\_of\_falling\_edge, time\_of\_rising\_edge, config\_clock\_period,
config\_clock\_period\_margin, config\_clock\_margin\_severity)

### Watchdog

watchdog\_timer(watchdog\_ctrl, timeout, [alert\_level, [msg]])
extend\_watchdog(watchdog\_ctrl, [time\_extend])
reinitialize\_watchdog(watchdog\_ctrl, timeout)
terminate\_watchdog(watchdog\_ctrl)



# 1 Method descriptions

Note 1: Arguments common for most methods (green text) are described in chapter 1.12.

Note 2: All methods are defined in uvvm util.methods pkg, unless otherwise noted.

Legend: bool=boolean, sl=std\_logic, slv=std\_logic\_vector, u=unsigned, s=signed, int=integer \*IEEE=Method is native for VHDL2008 (Method is listed here for completeness.)

## 1.1 Checks and awaits

Name	Parameters and examples	Description	
[v_bool :=]	value(bool), [exp(bool)], [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]		xp, and alerts with severity alert_level if the
check_value()	value(sl), exp(sl), [match_strictness], [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	values do not match.	
	<pre>value(slv), exp(slv), [match_strictness], [alert_level], msg, [scope, [radix, [format, [msg_id,</pre>	called as a function.	k is returned as a boolean if the method is
	<pre>value(t_slv_array), exp(t_slv_array), [match_strictness], [alert_level], msg, [scope, [radix, [format,</pre>	If <i>val</i> is of type <i>slv</i> , <i>ur</i> arguments:	nsigned or signed, there are additional optional
	value(u), exp(u), [alert_level], msg, [scope, [radix, [format, [msg_id, [msg_id_panel]]]]]	- match_strictness:	Specifies if match needs to be exact or std_match, e.g. 'H' = '1'.
	<pre>value(t_unsigned_array), exp(t_unsigned_array), [match_strictness], alert_level, msg, [scope, [radix,</pre>		(MATCH_EXACT, MATCH_STD, MATCH_STD_INCL_Z)
	value(s), exp(s), [alert_level], msg, [scope, [radix, [format, [msg_id, [msg_id_panel]]]]]	- radix:	For the vector representation in the log:
	<pre>value(t_signed_array), exp(t_signed_array), [match_strictness], alert_level, msg, [scope, [radix, [format, [msg_id, [msg_id_panel]]]]]</pre>	radix.	BIN, HEX, DEC or HEX_BIN_IF_INVALID. (HEX BIN IF INVALID means hexadecimal,
	value(int), exp(int), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]		unless there are the vector contains any U,
	value(real), exp(real), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]		X, Z or W, - in which case it is also logged
	<pre>value(time), exp(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]</pre>	- format:	in binary radix.) KEEP LEADING 0 or SKIP LEADING 0.
	Evamples	- TOTTITAL.	Controls how the vector is formatted in the
	Examples check_value(v_int_a, 42, WARNING, "Checking the integer");		log.
	v_check := check_value(v_slv5_a, "11100", MATCH_EXACT, "Checking the SLV", "My Scope",	<b>Note</b> that vectors are checked with MSB as left most and that the range is converted from "0 to N" to "N downto 0".	
	HEX, SKIP_LEADING_0, ID_SEQUENCER, shared_msg_id_panel);		f arrays are of defined with opposite directions. y dimension will not match.
		Defaults:	
		alert_level	ERROR
		scope	C_TB_SCOPE_DEFAULT
		match_strictness	MATCH_STD
		radix	HEX_BIN_IF_INVALID
		format	KEEP_LEADING_0
		msg_id	ID_POS_ACK
		msg_id_panel	shared_msg_id_panel
[v_bool :=] check_value_in_range()	<pre>value(u), min_value(u), max_value(u), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]] value(s), min_value(s), max_value(s), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]</pre>	Checks if <i>min_value</i> ≤ <i>alert_level</i> if <i>val</i> is out	≤ val ≤ max_value, and alerts with severity tside the range.
	<pre>value(int), min_value(int), max_value(int), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]] value(time), min_value(time), max_value(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]] value(real), min_value(real), max_value(real), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]</pre>	The result of the check called as a function.	k is returned as a boolean if the method is



		Defaults:	
	Example	alert_level	ERROR
	check_value_in_range(v_int_a, 10, 100, "Checking that integer is in range");	scope	C_TB_SCOPE_DEFAULT
		msg_id	ID_POS_ACK
		msg_id_panel	shared_msg_id_panel
check_stable()	target(bool), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	Checks if the targe	t signal has been stable in stable_req time.
	target(sl), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]] target(slv), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	If not, an alert is a	sserted.
	target(u), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	Defaults:	
	target(s), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	alert_level	ERROR
	target(int), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	scope	C_TB_SCOPE_DEFAULT
	target(real), stable_req(time), [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	msg_id	ID_POS_ACK
		msg_id_panel	shared_msg_id_panel
	Example check_stable(slv8, 9 ns, "Checking if SLV is stable");		
await_change()	target(bool), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	Waits until the targ	get signal changes, or times out after max_time.
	target(sl), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]		
	target(slv), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	An alert is asserted and max_time.	d if the signal does not change between <i>min_time</i>
	target(u), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	and max_ume.	
	target(s), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]] target(int), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	Note that if the val	lue changes at exactly <i>max_time</i> , the timeout gets
	target(mc), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]  target(real), min_time, max_time, [alert_level], msg, [scope, [msg_id, [msg_id_panel]]]	precedence.	
	target(rear), mini_time, max_time, [alert_lever], may, [acope, [mag_id, [mag_id_paner]]]		
	Example	Defaults:	
	await_change(bol, 3 ns, 5 ns, "Awaiting change on bol signal");	alert_level	ERROR
		scope	C_TB_SCOPE_DEFAULT
		msg_id	ID_POS_ACK
		msg_id_panel	shared_msg_id_panel
await_value()	target(sl), exp(sl), [match_strictness], min_time, max_time, [alert_level], msg, [scope, (etc.)] target(slv), exp(slv), [match_strictness], min_time, max_time, [alert_level], msg, [scope, (etc.)]	Waits until the targ max_time.	get signal equals the exp signal, or times out after
	target(bool), exp(bool), min_time, max_time, [alert_level], msg, [scope, (etc.)]]	An alort is asserted	d if the signal does not equal the expected value
	target(u), exp(u), min_time, max_time, [alert_level], msg, [scope, (etc.)]	between <i>min time</i>	
	target(s), exp(s), min_time, max_time, [alert_level], msg, [scope, (etc.)]	_	ue changes to the expected value at exactly
	target(int), exp(int), min_time, max_time, [alert_level], msg, [scope, (etc.)]	max_time, the time	eout gets precedence.
	target(real), exp(real), min_time, max_time, [alert_level], msg, [scope, (etc.)]		
		- match_strictness	: Specifies if match needs to be exact or std_match
	Examples		, e.g. `H' = `1'. (MATCH_EXACT, MATCH_STD)
	await_value(bol, true, 10 ns, 20 ns, "Waiting for bol to become true");	Defaults:	
	await_value(slv8, "10101010", MATCH_STD, 3 ns, 7 ns, WARNING, "Waiting for slv8 value");	alert_level	ERROR
		scope	C_TB_SCOPE_DEFAULT
		match_strictness	
		msg_id	ID_POS_ACK
		msg_id_panel	shared_msg_id_panel



await_stable()	target(bool),	stable_req(time), stable_req_from(t_from_point_in_time),	Wait until the target s	ignal has been stable for at least 'stable_req'.
		timeout (time), timeout_from(t_from_point_in_time), [alert_level], msg, [scope, (etc.)]	Report an error if this 'timeout'.	does not occurr within the time specified by
	target(sl),	stable_req(time), stable_req_from(t_from_point_in_time), timeout (time), timeout_from(t_from_point_in_time), [alert_level], msg, [scope, (etc.)]	Note: 'Stable' refers to that the signal has not had an event (i changed value).	
	target(slv),	stable_req(time), stable_req_from(t_from_point_in_time),	Description of special	arguments:
		timeout (time), timeout_from(t_from_point_in_time), [alert_level], msg, [scope, (etc.)]	stable_req_from :	
	target(u),	stable_req(time), stable_req_from(t_from_point_in_time),	- FROM_NOW	Target must be stable 'stable_req' from now.
		timeout (time), timeout_from(t_from_point_in_time), [alert_level], msg, [scope, (etc.)]	- FROM_LAST_EVENT	Target must be stable 'stable_req' from the last event of target.
	target(s),	stable_req(time), stable_req_from(t_from_point_in_time),	timeout_from :	
		timeout (time), timeout_from(t_from_point_in_time), [alert_level], msg, [scope, (etc.)]	- FROM_NOW	The timeout argument is given in time from now.
	target(int),	stable_req(time), stable_req_from(t_from_point_in_time),	- FROM_LAST_EVENT	The timeout argument is given in time the last event of target.
		timeout (time), timeout_from(t_from_point_in_time), [alert_level], msg, [scope, (etc.)]	Defaults:	cime one rade event of cargee.
	target(real),	target(real), stable_req(time), stable_req_from(t_from_point_in_time),	alert_level	ERROR
	<b>Example</b> await_stable		scope	C_TB_SCOPE_DEFAULT
			msg_id	ID_POS_ACK
		(u8, 20 ns, FROM_LAST_EVENT, 100 ns, FROM_NOW, ERROR, "Waiting for u8 to stabilize");	msg_id_panel	shared_msg_id_panel

Note: Although all check and await methods have optional [alert\_level], it is best practice to always evaluate and assign the most fitting alert\_level for any given check or await.

# 1.2 Logging and verbosity control

Name	Parameters and examples	Description
set_log_file_name()	[file_name(string)]  Example set_log_file_name("new_log_file_name.txt");	Sets the log file name. To ensure that the entire log transcript is written to single file, this should be called prior to any other procedures (except set_alert_file_name()). If file name is set after a log message has been written to the log file, a warning will be reported. This warning can be disable by setting C_WARNING_ON_LOG_ALERT_FILE_RUNTIME_RENAME false in the adaptations_pkg.  Defaults:    File_name
log()	[msg_id], msg, [scope, [msg_id_panel, [log_destination(t_log_destination), [log_file_name(string), [open_mode(file_open_kind)]]]]  Examples log(ID_SEQUENCER, "message to log"); log(ID_BFM, "Msg", "MyScope", local_msg_id_panel, LOG_ONLY, "new_log.txt", write_mode);	Writes message to log. If the <code>msg_id</code> is enabled in <code>msg_id_panel</code> , log the <code>msg_id_panel</code> , log destination defines where the message will be written to (CONSOLE_AND_LOG, CONSOLE_ONLY, LOG_ONLY). If log destination is not specified, the default value in shared_default_log_destination found in the adaptations_pkg.vhd will be used. log_file_name defines the log file that the text block shall be written to. The "open_mode" parameter indicates how the log file shall be opened (write_mode, append_mode).  **Defaults:
		msg_id C_TB_MSG_ID_DEFAULT
		scope C_TB_SCOPE_DEFAULT
		msg_id_panel shared_msg_id_panel
		log_destination shared_default_log_destination
		log_file_name
		open_mode append_mode



log_text_block()	msg_id, text_block(line), formatting(t_log_format), [msg_header(string), [scope, [msg_id_panel, [log_if_block_empty(t_log_if_block_empty), [log_destination(t_log_destination), [log_file_name(string), [open_mode(file_open_kind)]]]]]]  Examples  log_text_block(ID_SEQUENCER, v_line, UNFORMATTED);  log_text_block(ID_BFM, v_line, FORMATTED, "Header", "MyScope");	UNFORMATTED. msg_ text_block. log_if_blo (WRITE_HDR_IF_BLOCK_ Log destination define (CONSOLE_AND_LOG, CO file that the text block	n VHDL line to log. Formatting either FORMATTED or header is an optional header message for the ck_empty defines how an empty text block is handled LEMPTY/SKIP_LOG_IF_BLOCK_EMPTY/NOTIFY_IF_BLOCK_EMPTY). The swhere the message will be written to DNSOLE_ONLY, LOG_ONLY). Log file name defines the log continues the log write_mode, append_mode).
		Defaults:	
		msg_header	N/I
		scope	C TB SCOPE DEFAULT
		msq_id_panel	shared_msg_id_panel
		log_if_block_empty	WRITE HDR IF BLOCK EMPTY
		log_destination	shared_default_log_destination,  C_LOG_FILE_NAME
		log_file_name	
	was 14 feetabase/baselsbases Feeta 11	open_mode	append_mode
enable_log_msg ()	msg_id, [quietness(t_quietness), [scope]] msg_id, msg, [quietness(t_quietness), [scope]]	purpose IDs).	e given <i>msg_id</i> . (See ID-list on front page for special
	msg_id, msg_id_panel, [msg, [scope, [quietness(t_quietness)]]]	Logging of enable_log	_msg() can be turned off by setting quietness=QUIET.
	Example		
	enable_log_msg(ID_SEQUENCER);	Defaults:	\$
		msg_id_panel	shared_msg_id_panel
		msg	N//
		scope	C_TB_SCOPE_DEFAULT
		quietness	NON_QUIET
disable_log_msg()	msg_id, [quietness(t_quietness), [scope]] msg_id, msg, [quietness(t_quietness), [scope]] msg_id, msg_id_panel, [msg, [scope, [quietness(t_quietness)]]]		he given <i>msg_id</i> . (See ID-list on front page for special g of disable_log_msg() can be turned off by setting
	Example	Defaults:	
	disable_log_msg(ID_LOG_HDR);	msg_id_panel	shared msg id panel
		msga_pae.	w//
		scope	C TB SCOPE DEFAULT
		quietness	NON_QUIET
[v_bool :=]	msg_id, [msg_id_panel]		' if given message ID is enabled. Otherwise 'false'
is_log_msg_enabled	Example	Defaults:	in given message to is enabled. Otherwise Talse
()	v_is_enabled := is_log_msg_enabled(ID_SEQUENCER);	msq_id_panel	shared_msg_id_panel
0		<u></u>	:
set_log_destination ()	t_log_destination, [quietness(t_quietness)]		estination for all log procedures (CONSOLE_AND_LOG, NLY). The destination specified in this log destination will
()	Example set_log_destination(CONSOLE_ONLY);		g_destination argument in the log procedure is specified.
	set_log_destination(Consolt_ONLT),	A log message is writt NON_QUIET.	ten to log ID ID_LOG_MSG_CTRL if quietness is set to
		Defaults:	
		Quietness	NON_QUIET



# 1.2.1 General string handling features for log()

- All log messages will be given using the user defined layout in adaptations pkg.vhd
- \n may be used to force line shifts. Line shift will occur after scope column, before message column
- \r may be used to force line shift at start of log message. The result will be a blank line apart from prefix (message ID, timestamp and scope will be omitted on the first line)



# 1.3 Alert handling

Name	Parameters and examples	Description
set_alert_file_name()	file_name(string)]  Example set_alert_file_name("new_alert_log_file.txt");	Sets the alert file name. To ensure that the entire log transcript is written to a single file, this should be called prior to any other procedures (except set_alert_file_name()). If file name is set after a log message has been written to the log file, a warning will be reported. This warning can be disabled by setting C_WARNING_ON_LOG_ALERT_FILE_RUNTIME_RENAME false in the adaptations_pkg.  Defaults:  file_name  C_ALERT_FILE_NAME
alert()	alert_level, msg , [scope]  Example alert(TB_WARNING, "This is a TB warning");	- Asserts an alert with severity given by alert_level Increment the counters for the given alert_level If the stop_limit for the given alert_level is reached, stop the simulation.  Defaults:  scope
note() error() tb_note() tb_error() warning() failure() tb_warning() tb_failure() manual_check() increment_expected_alerts()	msg, [scope]  Examples note("This is a note"); tb_failure("This is a TB failure", "tb_scope"); alert_level, [number (natural) , [msg, [scope]]]  Example	Overloads for alert().  Note that: warning(msg, [scope]) = alert(warning, msg, [scope]).  Defaults:  scope
	<pre>increment_expected_alerts(WARNING, 2, "Expecting two more warnings");</pre>	number1msg""scopeC_TB_SCOPE_DEFAULT
set_alert_stop_limit()	alert_level, number (natural)  Example set_alert_stop_limit(ERROR, 2);	Simulator will stop on hitting <number> of specified alert type (0 means never stop).</number>
increment_expected_alerts_and_stop_limit()	<pre>alert_level, [number, [msg, [scope]]] Example increment_expected_alerts_and_stop_limit(WARNING, 2, "Expecting two more warnings");</pre>	Increments the expected alert counter and stop limit for the given alert_level.  Defaults:  number 1 msg "" scope C_TB_SCOPE_DEFAULT
v_int := get_alert_stop_limit()	<pre>alert_level Example v_int := get_alert_stop_limit(FAILURE);</pre>	Returns current stop limit for given alert type.
set_alert_attention()	alert_level, attention (t_attention), [msg]  Example  set_alert_attention(NOTE, IGNORE, "Ignoring all note-alerts");	Set given alert type to t_attention: IGNORE or REGARD.  Defaults:  msg ""
v_attention := get_alert_attention()	alert_level  Example v_attention := get_alert_attention(WARNING)	Returns current attention (IGNORE or REGARD) for given alert type.



# 1.4 Reporting

Name	Parameters	Description
report_global_ctrl()	VOID	Logs the values in the global_ctrl signal, which is described in chapter 1.13
report_msg_id_panel()	VOID	Logs the values in the msg_id_panel, which is described in chapter 1.13
report_alert_counters()	VOID	Logs the status of all alert counters, typically at the end of simulation.
	order (t_order)	For each alert_level, the alert counter is compared with the expected counter.
	Example	If parameter is FINAL, an additional summary concluding success or failure is logged.
	report_alert_counters(VOID);	- type t_order is (FINAL, INTERMEDIATE)
	report_alert_counters(FINAL);	VOID parameter gives same result as FINAL.
	report_alert_counters(INTERMEDIATE);	
report_check_counters()	VOID	Logs the status of all check counters, typically at the end of simulation.
	order (t_order)	- type t_order is (FINAL, INTERMEDIATE)
	Example	VOID parameter gives same result as FINAL.
	report_check_counters(VOID);	
	report_check_counters(FINAL);	
	report_check_counters(INTERMEDIATE);	

Shared variable	Signal type	Description
shared_uvvm_status.found_unexpected_simulation_warnings_or_worse	Natural, read only	Status is '0' on success and '1' on failure. The variable is set when actual > expected for WARNING, ERROR or FAILURE alerts.
shared_uvvm_status.found_unexpected_simulation_errors_or_worse	Natural, read only	Status is '0' on success and '1' on failure. The variable is set when actual > expected for ERROR or FAILURE alerts.
shared_uvvm_status.mismatch_on_expected_simulation_warnings_or_worse	Natural, read only	Status is '0' on success and '1' on failure.
		The variable is set when there is a mismatch between the expected and the actual WARNING, ERROR or FAILURE alerts.
shared_uvvm_status.mismatch_on_expected_simulation_errors_or_worse	Natural, read only	Status is '0' on success and '1' on failure.
		The variable is set when there is a mismatch between the expected and the actual ERROR or FAILURE alerts.



## 1.5 Randomization

Name	Parameters and examples	Description
v_slv := random()	length(int)	Returns a random std_logic_vector of size <i>length</i> . The function uses and
	Example	updates a global seed.
	v_slv := random(v_slv'length);	
v_sl := random()	VOID	Returns a random std_logic. The function uses and updates a global seed
	Example	
	v_sl := random(VOID);	
{v_int,v_real,v_time}	min_value(int), max_value(int)	Returns a random <i>integer</i> , <i>real</i> or <i>time</i> between min_value and max_value.
:= random()	min_value(real), max_value(real)	The function uses and updates a global seed
	min_value(time), max_value(time)	
	Example	
	v_int := random(1, 10);	
random()	v_seed1(positive <i>variable</i> ), v_seed2(positive <i>variable</i> ), v_target(slv <i>variable</i> )	Sets v_target to a random value. The procedure uses and updates v_seed1
	Example	and v_seed2.
	random(v_seed1, v_seed2, v_slv)	
random()	min_value(int), max_value(int), v_seed1(positive <i>var</i> ), v_seed2(positive <i>var</i> ), v_target(int <i>var</i> )	Sets v_target to a random value between min_value and max_value.
	min_value(real), max_value(real), v_seed1(positive var), v_seed2(positive var), v_target(real var)	The procedure uses and updates v_seed1 and v_seed2.
	min_value(time), max_value(time), v_seed1(positive var), v_seed2(positive var), v_target(time var)	
	Example	
	random(0.01, 0.03, v_seed1, v_seed2, v_real);	
randomize()	seed1(positive), seed2(positive) , [msg, [scope]]	Sets the global seeds to seed1 and seed2.
	Example	
	randomize(12, 14, "Setting global seeds");	



1.6 String handling
(Methods are defined in uvvm util.string methods)

Name	Parameters and examples	Description
v_string := to_string()	value({ANY_SCALAR_TYPE})	IEEE defined to_string functions.
*IEEE	value(slv)	Return a string with the value of the argument 'value'.
	value(time), unit(time)	
	value(real), digits(natural)	
	value(real), format(string) C-style formatting	
v_string := to_string()	<pre>val(bool), width(natural), justified(side), format_spaces(t_format_spaces),     [truncate(t_truncate_string)] val(int), width(natural), justified(side), format_spaces(t_format_spaces),     [truncate(t_truncate_string), [radix(t_radix), [prefix(t_radix_prefix),     [format(t_format_zeros)]]]] val(int), radix(t_radix), prefix(t_radix_prefix), [format(t_format_zeros)] val(slv), radix(t_radix), [format(t_format_zeros), [prefix(t_radix_prefix)]] val(t_slv_array), radix(t_radix), [format(t_format_zeros), [prefix(t_radix_prefix)]] val(u), radix(t_radix), [format(t_format_zeros), [prefix(t_radix_prefix)]] val(t_unsigned_array), radix(t_radix), [format(t_format_zeros), [prefix(t_radix_prefix)]] val(s), radix(t_radix), [format(t_format_zeros), [prefix(t_radix_prefix)]] val(t_signed_array), radix(t_radix), [format(t_format_zeros),     [prefix(t_radix_prefix)]] val(string) Removes non printable ascii characters  Examples v_string := to_string(v_u8, DEC); v_string := to_string(v_slv8, HEX, AS_IS, INCL_RADIX);</pre>	Additions to the IEEE defined to_string functions.  Return a string with the value of the argument 'val'.  - type t_radix is (BIN, HEX, DEC, HEX_BIN_IF_INVALID)  - type t_format_spaces is (KEEP_LEADING_SPACE, SKIP_LEADING_SPACE)  - type t_truncate_string is (DISALLOW_TRUNCATE, ALLOW_TRUNCATE)  - type t_format_zeros is (AS_IS, SKIP_LEADING_0)  - type t_radix_prefix is (EXCL_RADIX, INCL_RADIX)  - type t_format_zeros is (KEEP_LEADING_0, SKIP_LEADING_0)  Defaults:  justified RIGHT  truncate DISALLOW_TRUNCATE  prefix EXCL_RADIX
v_string := to_upper()	<pre>val(string) Example v_string := to_upper("lowercase string");</pre>	Returns a <i>string</i> containing an upper case version of the argument 'val'
v_string := justify() *IEEE	value(string), [justified(side)], [field(width)]	IEEE implementation of justify. Returns a <i>string</i> where 'value' is justified to the side given by 'justified' (right, left).  Defaults:  Justified right  field 0
v_string := justify()	<pre>val(string), justified(side), width(natural), format_spaces(t_format_spaces),</pre>	Addition to the IEEE implementation of justify(). Returns a <i>string</i> where 'val' is justified to the side given by 'justified' (right, left, center). In addition to right and left, center is also an option. The string can be truncated with the 'truncate' parameter (ALLOW_TRUNCATE, DISALLOW_TRUNCATE) or leading spaces can be removed with 'format_spaces' (KEEP_LEADING_SPACE, SKIP_LEADING_SPACE).
v_string := fill_string()	<pre>val(character), width(natural) Example v_string := fill_string('X', 10);</pre>	Returns a <i>string</i> filled with the character 'val'.



v_character := ascii_to_char()	ascii_pos(int), [ascii_allow (t_ascii_allow)]	Return the ASCII to character located at the argument 'ascii_pos'
	Example	- type t_ascii_allow is (ALLOW_ALL, ALLOW_PRINTABLE_ONLY)
	v_char := ascii_to_char(65); ASCII `A'	
		Defaults:
		ascii_allow ALLOW_ALL
v_int := char_to_ascii()	char (character)	Return the ASCII value (integer) of the argument 'char'
	Example	
	v_int := char_to_ascii('A'); Returns 65	
v_natural := pos_of_leftmost()	target(character), vector(string), [result_if_not_found (natural)]	Returns position of left most 'character' in 'string', alternatively return-value
	Example	if not found.
	v_natural := pos_of_leftmost('x', v_string);	
		Defaults:
		result_if_not_found 1
v_natural := pos_of_rightmost()	target(character), vector(string), [result_if_not_found (natural)]	Returns position of right most 'character' in 'string', alternatively return-
	Example	value if not found.
	v_natural := pos_of_rightmost('A', v_string);	
		Defaults:
		result_if_not_found 1
v_string := remove_initial_chars()	source(string), num(natural)	Return string less the num (number of chars) first characters
	Example	
	v_string :=remove_initial_chars("abcde",1); Returns "bcde"	
v_string :=	val(string)	Returns procedure, process or entity name from the given instance name as
get_procedure_name_from_instance_name()	Example	string.
	v_string := get_procedure_name_from_instance_name(c_int'instance_name);	The instance name must be <object>'instance_name, where object is a</object>
v_string :=	val(string)	signal, variable or constant defined in the procedure, process and entity or
get_process_name_from_instance_name()	Example	process respectively.
	v_string := get_process_name_from_instance_name(c_int'instance_name);	
v_string :=	val(string)	E.g.
get_entity_name_from_instance_name()	Example	get_entity_name_from_instance_name(my_process_variable'instance-name)
	v_string := get_entity_name_from_instance_name(c_int'instance_name);	
v_string := replace()	val(string), target_char(character), exchange_char(character)	String function returns a <i>string</i> where the target character has been replaced
	Example	by the exchange character.
	v_string := replace("string_x", 'x', 'y'); Returns "string_y"	
replace()	variable text_line(inout line), target_char(character), exchange_char(character)	Similar to function version of replace(). Line procedure replaces the input with
	Example	a line where the target character has been replaced by the exchange
	replace(str, 'a', 'b');	character.
v_string := pad_string()	val(string), char(character), width(natural), [side(side)]	Returns a string of width 'width' with the string 'val' on the side of the string
	Example	given in 'side' (LEFT, RIGHT). The remaining width is padded with 'char'.
	v_string := pad_string("abcde", '-', 10, LEFT);	
		Defaults:
		side LEFT

Note: See section 1.2.1 for general string handling features for the log() procedure



# 1.7 Signal generators

Name	Parameters and examples	Description	
clock_generator()	<pre>clock_signal(sl), [clock_count (natural)], clock_period(time), [clock_high_percentage(natural)] clock_signal(sl), [clock_count (natural)], clock_period(time), [clock_high_time(time)] clock_signal(sl), clock_ena(boolean), [clock_count(natural)], clock_period(time),</pre>	Generates a clock signal.  Usage: Include the clock_generator as a concurrent procedure from your test bench.  By using the variant with the clock_ena input, the clock can be started and stopped during simulation. Each start/stop is logged (if the msg_id ID_CLOCK_GEN is enabled).  Duty cycle can be set either by percentage or time.  An optional output signal clock_count can be used to keep track of the number of clock cycles that have passed. Always starts on 0.  Defaults:  clock_high_percentage 50	
adjustable_clock_generator()	clock_signal(sl), clock_ena(boolean), clock_period(time), clock_high_percentage(natural) clock_signal(sl), clock_ena(boolean), clock_period(time), clock_name(string), clock_high_percentage(natural) clock_signal(sl), clock_ena(boolean), clock_count(natural), clock_period(time), clock_name(string), clock_high_percentage(natural)  Examples adjustable_clock_generator(clk50M, clk50M_ena, 20 ns, 50); adjustable_clock_generator(clk50M, clk50M_ena, 20 ns, "100MHz clock with 50% duty cycle", 50); adjustable_clock_generator(clk50M, clk50M_ena, clk50M_cnt, 20 ns, "100MHz clock with 60% duty cycle", 60);	Generates a clock with adjustable duty cycle.  Usage: Include the adjustable_clock_generator as a concurrent procedure from your test bench.  Duty cycle can be adjusted by changing the clock_high_percentage.  Note that clock_high_percentage has to be set in the range of 1 to 99, and that an TB_ERROR will be raised if scale limits are exceeded. Input parameter clock_period and clock_name are constants.  An optional output signal clock_count can be used to keep track of the number of clock cycles that have passed. Always starts on 0.	
gen_pulse()	target(sl), [pulse_value(sl)], pulse_duration(time), [blocking_mode(t_blocking_mode)], msg, [scope, [msg_id, [msg_id_panel]]] target(sl), [pulse_value(sl)], clock_signal(sl), num_periods(int), msg, [scope, [msg_id, [msg_id_panel]]] target(boolean), [pulse_value(boolean)], pulse_duration(time), [blocking_mode(t_blocking_mode)], msg, [scope, [msg_id, [msg_id_panel]]] target(boolean), [pulse_value(boolean)], clock_signal(sl), num_periods(int), msg, [scope, [msg_id, [msg_id_panel]]]] target(slv), [pulse_value(slv)], pulse_duration(time), [blocking_mode(t_blocking_mode)], msg, [scope, [msg_id, [msg_id_panel]]]] target(slv), [pulse_value(slv)], clock_signal(sl), num_periods(int), msg, [scope, [msg_id, [msg_id_panel]]]  Examples gen_pulse(sl_1, 50 ns, BLOCKING, "Pulsing for 50 ns"); gen_pulse(slv8, 50 ns, "Pulsing SLV for 50 ns", ALLOW_PULSE_CONTINUATION); gen_pulse(slv8, x"AB", clk100M, 2, "Pulsing SLV for 2 clock periods");	Generates a pulse on the target signal for a certain amount of time or a number of clock cycles.  - If blocking_mode = BLOCKING: Procedure blocks the caller (e.g. the test sequencer) until the pulse is done. (default)  - If blocking_mode = NON_BLOCKING: Procedure starts the pulse and schedules the end of the pulse, so that the caller can continue immediately. Note that the clock_signal version will synchronize the pulse to clock signal and begin the pulse on falling edge and end the pulse on a succeeding falling edge.    Defaults:   pulse_value	



## 1.8 Synchronisation

**Note:** It is recommended to use a constant for flag\_name to avoid typing errors in methods block\_flag(), unblock\_flag() and await\_unblock\_flag().

Name	Parameters and examples	Description
block_flag()	flag_name(string), msg, [already_blocked_severity(t_alert_level), [scope]]  Example  block_flag("my_flag","blocking my flag")  block_flag(C_MY_FLAG_1,"blocking " & C_MY_FLAG_1, WARNING, "My Scope")	Blocks a flag to allow synchronisation between processes. Adds a new blocked flag if it does not already exist. Maximum number of flags can be modified in adaptation_pkg.  Sets an alert with already_blocked_severity if the flag already is blocked.
		Defaults:  already_blocked_severity WARNING  scope C_TB_SCOPE_DEFAULT
unblock_flag()	flag_name(string), msg, trigger(sl), [scope]  Example unblock_flag("my_flag","unblocking my flag", global_trigger) unblock_flag(C_MY_FLAG_1,"unblocking" & C_MY_FLAG_1, global_trigger, "My Scope")	Unblocks a flag to allow a process that is waiting on that flag to continue. Adds a new unblocked flag if it does not already exist.  Parameter trigger is included to pulse the global signal global_trigger used to allow await_unblock_flag() to detect unblocking.  Mandatory:  trigger global_trigger
		Defaults:       scope     C_TB_SCOPE_DEFAULT
await_unblock_flag()	flag_name(string), timeout(time), msg, [flag_returning(t_flag_returning), [timeout_severity(t_alert_level), [scope]]]  Examples  await_unblock_flag("my_flag", 0 ns, "waiting for my_flag to be unblocked)  await_unblock_flag("my_flag", 10 us, "waiting for my_flag to be unblocked", RETURN_TO_BLOCK, WARNING)  await_unblock_flag(C_MY_FLAG_1, 10 us, "waiting for "C_MY_FLAG_1 & " to be unblocked",  RETURN_TO_BLOCK, WARNING, "My Scope")	Waits for a flag to be unblocked. Continues immediately if the flag already is unblocked. Adds a new blocked flag if it does not already exist. If so <code>await_unblock_flag()</code> will wait for the flag to be unblocked. Sets an alert with <code>timeout_severity</code> if the flag is not unblocked within <code>timeout</code> . A timeout of 0 ns means wait forever.  The flag can be re-blocked when leaving the process by setting <code>flag_returning=RETURN_TO_BLOCK</code> .
		Defaults:       flag_returning     KEEP_UNBLOCKED       timeout_severity     ERROR       scope     C_TB_SCOPE_DEFAULT
await_barrier()	barrier_signal(sl), timeout(time), msg, [timeout_severity(t_alert_level), [scope]]  Example await_barrier(global_barrier, 100 us, "waiting for global barrier", ERROR, "My Scope")	For the barrier_signal you may use the predefined global_barrier or define your own barrier_signal of type sl.  The function can be used to synchronise between several sequencers. When the function is called, it waits for all sequencer using the same barrier_signal to reach their call of await_barrier.



# 1.9 BFM Common package

(Methods are defined in uvvm util.bfm common pkg)

[Methods are defined in uvvm_util.bjm_		
Name	Parameters and examples	Description
{slv, u, s, t_slv_array, t_signed_array, t_unsigned_array} := normalize_and_check()	<pre>value(slv), target(slv), mode (t_normalization_mode), value_name,     target_name, msg value(t_slv_array), target(t_slv_array), mode (t_normalization_mode),     value_name, target_name, msg value(u), target (u), mode (t_normalization_mode), value_name,     target_name, msg value(t_unsigned_array), target(t_unsigned_array),     mode(t_normalization_mode), value_name, target_name, msg value(s), target (s), mode (t_normalization_mode), value_name,     target_name, msg value(t_signed_array), target(t_signed_array), mode (t_normalization_mode),     value_name, target_name, msg  Example v_slv8 := normalize_and_check(v_slv5, v_slv8, ALLOW_NARROWER,</pre>	Normalize 'value' to the width given by 'target'.  If value'length > target'length, remove leading zeros (or sign bits) from value.  If value'length < target'length, add padding (leading zeros, or sign bits) to value.  Mode (t_normalization_mode) is used for sanity checks, and can be one of:  ALLOW_WIDER : Allow only value'length >= target'length  ALLOW_NARROWER : Allow only value'length <= target'length  ALLOW_WIDER_NARROWER : Allow both of the above  ALLOW_EXACT_ONLY : Allow only value'length = target'length
wait_until_given_time_after_rising_edge()	clk(sl), wait_time(time)  Example  wait_until_given_time_after_rising_edge(clk50M, 5 ns);	Wait until wait_time after rising_edge(clk)  If the time passed since the previous rising_edge is less than wait_time, don't wait until the next rising_edge, just wait_time after the previous rising_edge.
Wait_until_given_time_before_rising_edge()	clk(sl), time_to_edge(time), clk_period(time) <b>Example</b> wait_until_given_time_after_rising_edge(clk50M, 2 ns, 10 ns);	Wait until time_to_edge before rising_edge(clk)  If the time until rising_edge is less than time_to_edge, wait until the next rising_edge and afterwards until time_to_edge before rising_edge
wait_num_rising_edge()	clk(sl), num_rising_edge(natural) <b>Example</b> wait_num_rising_edge(clk10M, 5);	Waits for 'num_rising_edge' rising edges of the clk signal
wait_num_rising_edge_plus_margin()	clk(sl), num_rising_edge(natural), margin(time) <b>Example</b> wait_num_rising_edge_plus_margin(clk50M, 3, 4 ns);	Waits for 'num_rising_edge' rising edges of the clk signal, and then waits for 'margin'.
wait_on_bfm_sync_start()	clk(sl), bfm_sync(t_bfm_sync), setup_time(time), config_clock_period(time), time_of_falling_edge(time), time_of_rising_edge(time)  Example  wait_on_bfm_sync_start(clk, config.bfm_sync, 2.5 ns, 10 ns, v_time_of_falling_edge, v_time_of_rising_edge);	Synchronizes the start of a BFM procedure depending on bfm_sync: -SYNC_ON_CLOCK_ONLY: waits until the falling_edge of the clk signalSYNC_WITH_SETUP_AND_HOLD: waits until the setup time before the clock's rising_edge.  It returns the times of falling and rising edges. When not found returns -1 ns.
wait_on_bfm_exit()	clk(sl), bfm_sync(t_bfm_sync), hold_time(time), time_of_falling_edge(time), time_of_rising_edge(time) <b>Example</b> wait_on_bfm_exit(clk, config.bfm_sync, 2.5 ns, v_time_of_falling_edge, v_time_of_rising_edge);	Synchronizes the exit of a BFM procedure depending on bfm_sync: -SYNC_ON_CLOCK_ONLY: waits until one quarter of the clock period (measured with the falling and rising edges) after the clock's rising_edgeSYNC_WITH_SETUP_AND_HOLD: waits until the hold time after the clock's rising_edge. The times of falling and rising edges must be consecutive to be able to calculate the correct clock period.



check_clock_period_margin()	clock(sl), bfm_sync(t_bfm_sync), time_of_falling_edge(time),     time_of_rising_edge(time), config_clock_period(time),     config_clock_period_margin(time),     config_clock_margin_severity(t_alert_level)	Checks that the clock signal behaves according to configured specifications. Only when bfm_sync = SYNC_WITH_SETUP_AND_HOLD. The procedure must be called after the clock's rising_edge.
	Example	
	check_clock_period_margin(clk, config.bfm_sync, v_time_of_falling_edge, v_time_of_rising_edge, 10 ns, 2 ns, TB_ERROR);	

## 1.10 General Watchdog

Name	Parameters and examples	Description
watchdog_timer()	watchdog_timer(t_watchdog_ctrl), timeout (time), [alert_level, [msg]]	This procedure has to be instantiated as a concurrent procedure in the testbench or test harness.
	Example watchdog_timer(watchdog_ctrl, 500 us, ERROR, "Watchdog timer");	Initializes the watchdog timer as a concurrent procedure that will run until the timeout expires. A signal of the type t_watchdog_ctrl must be defined in the testbench, this is needed to call the other procedures on the watchdog.
extend_watchdog()	extend_watchdog (t_watchdog_ctrl), [time_extend (time)]	Extends the timeout of the watchdog timer by the specified time.
	Example	If no time is given, the original timeout will be used as the time extension.
	extend_watchdog(watchdog_ctrl, 100 us)	
reinitialize_watchdog()	reinitialize_watchdog(t_watchdog_ctrl), timeout (time)	Reinitializes the watchdog timer with a new timeout.
	Example	
	reinitialize_watchdog(watchdog_ctrl, 1 ms)	
terminate_watchdog()	terminate_watchdog (t_watchdog_ctrl)	Terminates the concurrent procedure where the watchdog timer is running.
	Example	Once this is done the watchdog can't be started again. This should normally
	terminate_watchdog(watchdog_ctrl)	be called at the end of the simulation.

Note 1 – the general watchdog will terminate with the alert level when timeout expires.

Note 2 – the VVCs support an activity watchdog. See UVVM Essential Mechanisms PDF in UVVM VVC Framework for more details.



## **Message IDs**

A sub set of message IDs is listed in this table. All the message IDs are defined in uvvm util.adaptations pkg.

Message ID	Description
ID_LOG_HDR	For all test sequencer log headers. Special format with preceding empty line and underlined message (also applies to ID_LOG_HDR_LARGE and ID_LOG_HDR_XL).
ID_SEQUENCER	For all other test sequencer messages
ID_SEQUENCER_SUB	For general purpose procedures defined inside TB and called from test sequencer
ID_POS_ACK	A general positive acknowledge for check routines (incl. awaits)
ID_BFM	BFM operation (e.g. message that a write operation is completed) (BFM: Bus Functional Model, basically a procedure to handle a physical interface)
ID_BFM_WAIT	Typically BFM is waiting for response (e.g. waiting for ready, or predefined number of wait states)
ID_BFM_POLL	Used inside a BFM when polling until reading a given value, i.e., to show all reads until expected value found.
ID_PACKET_INITIATE	A packet has been initiated (Either about to start or just started)
ID_PACKET_COMPLETE	Packet completion
ID_PACKET_HDR	Packet header information
ID_PACKET_DATA	Packet data information
ID_LOG_MSG_CTRL	Dedicated ID for enable/disable_log_msg
ID_CLOCK_GEN	Used for logging when clock generators are enabled or disabled
ID_GEN_PULSE	Used for logging when a gen_pulse procedure starts pulsing a signal
ID_NEVER	Used for avoiding log entry. Cannot be enabled.
ALL_MESSAGES	Not an ID. Applies to all IDs (apart from ID_NEVER)

Message IDs are used for verbosity control in many of the procedures and functions in UVVM-Util, and are toggled by using the procedures enable log msg() and disable log msg() that are described in this document.

Example: A check is performed each clock cycle;

check value(my boolean condition, error, "Verifying condition", C SCOPE, ID POS ACK, my msg id panel);

The message ID "ID\_POS\_ACK" is enabled by default, and will report a positive acknowledge if the check passes. Since the check is performed each clock cycle, the positive acknowledge will be printed each clock cycle. There are two possibilities if you wish to turn off the positive acknowledge message:

- Disable "ID\_POS\_ACK" in my\_msg\_id\_panel (or use another msg\_id\_panel) by calling disable\_log\_msg(ID\_POS\_ACK, my\_msg\_id\_panel). This will disable positive acknowledge messages for any procedure call that uses this msg\_id\_panel.
- Call *check\_value()* with "ID\_NEVER" instead of "ID\_POS\_ACK". This will disable the positive acknowledge for this particular call of *check\_value()*, but all other calls to *check\_value()* will report a positive acknowledge.



## 1.12 Common arguments in checks and awaits

Most check and await methods have two groups of arguments:

- arguments specific to this function/procedure
- **common args**: arguments common for all functions/procedures:
  - o alert level, msg, [scope], [msg id], [msg id panel]

For example: check\_value(val, exp, ERROR, "Check that the val signal equals the exp signal", C\_SCOPE);

The common arguments are described in the following table.

Argument	Type	Example	Description
alert_level	t_alert_level;	ERROR	Set the severity for the alert that may be asserted by the method.
msg	string;	"Check that bus is stable"	A custom message to be appended in the log/alert.
scope	string;	"TB Sequencer"	A string describing the scope from which the log/alert originates.
msg_id	t_msg_id	ID_BFM	Optional message ID, defined in the adaptations package.  Default value for check routines = ID_POS_ACK;
msg_id_panel	t_msg_id_panel	local_msg_id_panel	Optional msg_id_panel, controlling verbosity within a specified scope.  Defaults to a common ID panel defined in the adaptations package.

## 1.13 Using Hierarchical Alert Reporting

Enable hierarchical alerts via the constant C\_ENABLE\_HIERARCHICAL\_ALERTS in the adaptations package.

The procedures used for hierarchical alert reporting are described in the following table.

Name	Parameters and examples	Description		
add_to_alert_hierarchy()	scope(string), [parent_scope(string), [stop_limit(t_alert_counters)]]	Add a scope in the alert hierarchy tree.  Defaults:		
	Example			
	<pre>add_to_alert_hierarchy("tier_2", "tier_1");</pre>	parent_scope	C_BASE_HIERARCHY_LEVEL	
		stop_limit	(others => `0')	
increment_expected_alerts()	scope(string), alert_level, [amount(natural)]	Increment the exp	ected alert counter for a scope.	
	Example			
	<pre>increment_expected_alerts("tier_2", ERROR, 2);</pre>	Defaults:		
		amount	1	
set_expected_alerts()	scope(string), alert_level, expected_alerts(natural)	Set the expected a	alert counter for a scope.	
	Example			
	<pre>set_expected_alerts("tier_2", WARNING, 5);</pre>			
increment_stop_limit()	<pre>scope(string), alert_level, [amount(natural)]</pre>	Increment the stop	p limit for a scope.	
	Example			
	<pre>increment_stop_limit("tier_1", ERROR);</pre>	Defaults:		
		amount	1	



set_stop_limit()	scope(string), alert_level, stop_limit (natural)	Set the stop limit for a scope.
	Example	
	<pre>set_stop_limit("tier_1", ERROR, 5);</pre>	

- By default, there is only one level in the hierarchy tree, and one scope with name given by C\_BASE\_HIERARCHY\_LEVEL in the adaptations package. This scope has a stop limit of 0 by default.
- To add a scope to the hierarchy, call *add\_to\_alert\_hierarchy()*.
- Any scope that is not registered in the hierarchy will be automatically registered if an alert is triggered in that scope. The parent scope will then be C\_BASE\_HIERARCHY\_LEVEL. Changing the parent is possible by calling add\_to\_alert\_hierarchy() with another scope as parent. This is only allowed if the parent is C\_BASE\_HIERARCHY\_LEVEL and may cause an odd-looking summary (total summary will be correct).

## Intended use:

In UVVM mostly use the scope to describe components, e.g. VVCs. It can also be smaller structures, but it has to have its own sequencer. A good way to set up the hierarchy is to let every scope register themselves with the default parent scope, and then in addition make every parent register each of its children. This is because the child scope doesn't have to have the same parent scope in all testbenches/testharnesses, i.e. the child doesn't know its parent.

- In the child, call add\_to\_alert\_hierarchy(<child scope>). This will add the scope of the child to the hierarchy with the default (base) parent.
- In the parent, first call add\_to\_alert\_hierarchy(<parent scope>). Then call immediately add\_to\_alert\_hierarchy(<child scope>, <parent scope>) for each of the scopes that shall be children of this parent scope. This will re-register the children to the correct parent.

## Example output:

=======================================											
*** FINAL SUMMARY OF AL	L ALERTS	*** For	mat: REGARDE	O/EXPECTED/	IGNORED						
	=======	========					=======				
		NOTE	TB_NOTE	WARNING	TB_WARNING	MANUAL_CHECK	ERROR	TB_ERROR	FAILURE	TB_FAILURE	
TB seq	:	5/5/5	5/5/5	5/5/5	5/5/5	5/5/5	5/5/5	5/5/5	5/5/5	5/5/5	
`- scope_1	:	4/4/4	4/4/4	4/4/4	4/4/4	4/4/4	4/4/4	4/4/4	4/4/4	4/4/4	
- scope 2	:	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	
`- scope_3	:	2/2/2	2/2/2	2/2/2	2/2/2	2/2/2	2/2/2	2/2/2	2/2/2	2/2/2	
`- scope_4	:	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	

>> Simulation SUCCESS: No mismatch between counted and expected serious alerts



## 1.14 Adaptation package

The adaptations pkg.vhd is intended for local modifications to library behaviour and log layout.

This way only one file needs to merge when a new version of the library is released.

This package may of course also be used to set up a company or project specific behaviour and layout.

The layout constants and global signals are described in the following tables.

Constant	Description
C ALERT FILE NAME	Name of the alert file.
C LOG FILE NAME	Name of the log file.
C SHOW UVVM UTILITY LIBRARY INFO	General information about the UVVM Utility Library will be shown when this is enabled.
C SHOW UVVM UTILITY LIBRARY RELEASE INFO	Release information will be shown when this is enabled.
C_UVVM_TIMEOUT	General timeout for UVVM wait statements.
C LOG PREFIX	The prefix to all log messages. "UVVM: " by default.
C_LOG_PREFIX_WIDTH	Number of characters to be used for the log prefix.
C_LOG_MSG_ID_WIDTH	Number of characters to be used for the message ID.
C_LOG_TIME_WIDTH	Number of characters to be used for the log time. Three characters are used for time unit, e.g., 'ns'.
C_LOG_TIME_BASE	The unit in which time is shown in the log. Either ns or ps.
C_LOG_TIME_DECIMALS	Number of decimals to show for the time.
C_LOG_SCOPE_WIDTH	Number of characters to be used to show log scope.
C_LOG_LINE_WIDTH	Number of characters allowed in each line in the log.
C_LOG_INFO_WIDTH	Number of characters of information allowed in each line in the log. By default, this is set to
	C_LOG_LINE_WIDTH - C_LOG_PREFIX_WIDTH.
C_LOG_HDR_FOR_WAVEVIEW_WIDTH	Number of characters for a string in the waveview indicating last log header.
C_WARNING_ON_LOG_ALERT_FILE_RUNTIME_RENAME	Whether or not to report a warning if the log or alert files are renamed after they have been written.
C_USE_BACKSLASH_N_AS_LF	If true '\n' will be interpreted as line feed.
C_USE_BACKSLASH_R_AS_LF	If true '\r' placed as the first character in the string will be interpreted as a LF where the timestamp, Id etc. will be omitted.
C_SINGLE_LINE_ALERT	If true prints alerts on a single line. Default false.
C_SINGLE_LINE_LOG	If true prints logs messages on a single line. Default false.
C_TB_SCOPE_DEFAULT	The default scope in the test sequencer.
C_LOG_TIME_TRUNC_WARNING	Yields a single TB_WARNING if time stamp truncated. Otherwise none.
C_DEFAULT_MSG_ID_PANEL	Sets the default message IDs that shall be shown in the log.
C_MSG_ID_INDENT	Sets the indentation for each message ID.
C_DEFAULT_ALERT_ATTENTION	Sets the default alert attention.
C_DEFAULT_STOP_LIMIT	Sets the default alert stop limit.
C_ENABLE_HIERARCHICAL_ALERTS	Whether or not to enable hierarchical alert summary. Default false.
C_BASE_HIERARCHY_LEVEL	The name of the base/top level node that all other nodes in the tree will originate from.
C_DEPRECATE_SETTING	Sets how the user is to be notified if a procedure has been deprecated and will be removed in later versions.
C_VVC_RESULT_DEFAULT_ARRAY_DEPTH	Default for how many results (e.g. reads) a VVC can store before overwriting old results
C_VVC_MSG_ID_PANEL_DEFAULT	Default message ID panel to use in VVCs
C_SHOW_LOG_ID	Whether or not to show the Log ID field
C_SHOW_LOG_SCOPE	Whether or not to show the Log Scope field



Global signal	Signal type	Description
global_show_msg_for_uvvm_cmd	boolean	If true messages for Bitvis UVVM commands will be shown if applicable.

Shared variable	Signal type	Description
shared_default_log_destination	t_log_destination	The default destination for the log messages (Default: CONSOLE_AND_LOG)



## Additional Documentation

There are two other main documents for the UVVM Utility Library (available from our Downloads page)

- 'Making a simple, structured and efficient VHDL testbench Step-by-step'
- 'Bitvis Utility Library Concepts and Usage'

There is also a webinar available on 'Making a simple, structured and efficient VHDL testbench – Step-by-step' (via Aldec). Link on our downloads page.

## 2 Compilation

UVVM Utility Library may only be compiled with VHDL 2008.

Compile order for UVVM Utility Library:

Compile to library	File
uvvm_util	uvvm_util/src/types_pkg.vhd
uvvm_util	uvvm_util/src/adaptations_pkg.vhd
uvvm_util	uvvm_util/src/string_methods_pkg.vhd
uvvm_util	uvvm_util/src/protected_types_pkg.vhd
uvvm_util	<pre>uvvm_util/global_signals_and_shared_variables_pkg.vhd</pre>
uvvm_util	<pre>uvvm_util/src/hierarchy_linked_list_pkg.vhd</pre>
uvvm_util	<pre>uvvm_util/src/alert_hierarchy_pkg.vhd</pre>
uvvm_util	<pre>uvvm_util/src/license_pkg.vhd</pre>
uvvm_util	<pre>uvvm_util/src/methods_pkg.vhd</pre>
uvvm_util	uvvm_util/src/bfm_common_pkg.vhd
uvvm_util	<pre>uvvm_util/src/generic_queue_pkg.vhd</pre>
uvvm_util	uvvm_util/src/data_queue_pkg.vhd
uvvm_util	uvvm_util/src/data_fifo_pkg.vhd
uvvm_util	uvvm_util/src/data_stack_pkg.vhd
uvvm_util	uvvm_util/src/uvvm_util_context.vhd

Modelsim and Riviera-PRO users can compile the library by sourcing the following files:  $script/compile\_src.do$ 

Note that the compile script compiles the Utility Library with the following Modelsim directives for the vcom command:

Directive	Description
-suppress 1346,1236	Suppress warnings about the use of protected types. These can be ignored.

The uvvm\_util project is opened by opening sim/uvvm\_util.mpf in Modelsim.



# 3 Simulator compatibility and setup

UVVM Utility Library has been compiled and tested with Modelsim, Riviera-PRO and Active HDL. See README.md for a list of supported simulators.

## **Required setup:**

- Textio buffering should be removed or reduced. (Modelsim.ini: Set UnbufferedOutput to 1)
- Simulator transcript (and log file viewer) should be set to a fixed width font type for proper alignment (e.g. Courier New 8)
- Simulator must be set up to break the simulation on failure (or lower severity)



Copyright (c) 2017 by Bitvis AS. All rights reserved. See VHDL code for complete Copyright notice.

Disclaimer: UVVM Utility Library and any part thereof are provided "as is", without warranty of any kind, express or implied, including but not limited to the warranties of merchantability, fitness for a particular purpose and noninfringement. In no event shall the authors or copyright holders be liable for any claim, damages or other liability, whether in an action of contract, tort or otherwise, arising from, out of or in connection with UVVM Utility Library.