

# **RGMII VVC** – Quick Reference

For general information see UVVM VVC Framework Essential Mechanisms located in uvvm vvc framework/doc. CAUTION: shaded code/description is preliminary.

### rgmii\_write (VVCT, vvc\_instance\_idx, channel, data\_array, msg, [scope])

Example: rgmii\_write(RGMII\_VVCT, 0, TX, v\_data\_array(0 to v\_numBytes-1), "Write v\_numBytes to DUT", C\_SCOPE);

Example: rgmii\_write(RGMII\_VVCT, 0, TX, (x"01", x"02", x"03", x"04"), "Write 4 bytes to DUT");



### rgmii\_read (VVCT, vvc\_instance\_idx, channel, [TO\_SB,] msg, [scope])

Example: rgmii\_read(RGMII\_VVCT, 1, RX, "Read data which is stored in VVC and will be fetched later using fetch\_result() ");
rgmii\_read(RGMII\_VVCT, 1, RX, TO\_SB, "Read data which is stored in VVC and will be fetched later using fetch\_result() ");

### rgmii\_expect (VVCT, vvc\_instance\_idx, channel, data\_exp, msg, [alert\_level, [scope]])

Example: rgmii\_expect(RGMII\_VVCT, 1, RX, v\_data\_array(0 to v\_numBytes-1), "Expect v\_numBytes from DUT", ERROR, C\_SCOPE);

Example: rgmii expect(RGMII VVCT, 1, RX, (x"01", x"02", x"03", x"04"), "Expect 4 bytes from DUT");

#### RGMII VVC Configuration record 'vvc\_config' -- accessible via shared\_rgmii\_vvc\_config

Record element	Type	C_RGMII_VVC_CONFIG_DEFAULT
inter_bfm_delay	t_inter_bfm_delay	C_RGMII_INTER_BFM_DELAY_DEFAULT
cmd_queue_count_max	natural	C_CMD_QUEUE_COUNT_MAX
cmd_queue_count_threshold	natural	C_CMD_QUEUE_COUNT_THRESHOLD
cmd_queue_count_threshold_severity	t_alert_level	C_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY
result_queue_count_max	natural	C_RESULT_QUEUE_COUNT_MAX
result_queue_count_threshold	natural	C_RESULT_QUEUE_COUNT_THRESHOLD
result_queue_count_threshold_severity	t_alert_level	C_RESULT_QUEUE_COUNT_THRESHOLD_SEVERITY
bfm_config	t_rgmii_bfm_config	C_RGMII_BFM_CONFIG_DEFAULT
msg_id_panel	t_msg_id_panel	C_VVC_MSG_ID_PANEL_DEFAULT

#### RGMII VVC Status record signal 'vvc status' -- accessible via shared rgmii vvc status

Record element	Type	
current_cmd_idx	natural	
previous_cmd_idx	natural	
pending_cmd_cnt	natural	

### Common VVC procedures applicable for this VVC

- See UVVM Methods QuickRef for details.

await\_[any]completion()

enable\_log\_msg()

disable\_log\_msg()

fetch\_result()

flush\_command\_queue()

terminate\_current\_command()

terminate all commands()

insert\_delay()

get\_last\_received\_cmd\_idx()



Copyright © 2019 by Bitvis AS. All rights reserved.



# VVC target parameters

Name	Туре	Example(s)	Description
VVCT	t_vvc_target_record	RGMII_VVCT	VVC target type compiled into each VVC in order to differentiate between VVCs.
vvc_instance_idx	integer	0	Instance number of the VVC
channel	t channel	TX, RX	The VVC channel of the VVC instance

### VVC functional parameters

Name	Туре	Example(s)	Description
data_array	t_byte_array	(x"D0", x"D1", x"D2", x"D3")	An array of bytes containing the data to be written/read.
data_exp			data_array(0) is written/read first, while data_array(data_array'high) is written/read last.
			For clarity, data_array is required to be ascending, for example defined by the test sequencer as follows:
			<pre>variable v_data_array : t_byte_array(0 to C_MAX_BYTES-1);</pre>
alert_level	t_alert_level	ERROR or TB_WARNING	Set the severity for the alert that may be asserted by the procedure.
msg	string	"Write bytes"	A custom message to be appended in the log/alert
scope	string	"RGMII_VVC"	A string describing the scope from which the log/alert originates.
			In a simple single sequencer typically "RGMII_BFM". In a verification component typically "RGMII_VVC ".

# VVC entity signals

Name	Туре	Description
rgmii_vvc_tx_if	t_rgmii_tx_if	See RGMII BFM documentation.
rgmii_vvc_rx_if	t_rgmii_rx_if	See RGMII BFM documentation.

# VVC entity generic constants

Name	Туре	Default	Description
GC_INSTANCE_IDX	natural		Instance number to assign the VVC.
GC_RGMII_BFM_CONFIG	t_rgmii_bfm_config	C_RGMII_BFM_ CONFIG_DEFAULT	Configuration for the RGMII BFM, see RGMII BFM documentation.
GC_CMD_QUEUE_COUNT_MAX	natural	1000	Absolute maximum number of commands in the VVC command queue.
GC_CMD_QUEUE_COUNT_THRESHOLD	natural	950	An alert will be generated when reaching this threshold to indicate that the command queue is almost full. The queue will still accept new commands until it reaches C_CMD_QUEUE_COUNT_MAX.
GC_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY	t_alert_level	WARNING	Alert severity which will be used when command queue reaches GC_CMD_QUEUE_COUNT_THRESHOLD.
GC_RESULT_QUEUE_COUNT_MAX	natural	1000	Maximum number of unfetched results before result_queue is full.
GC_RESULT_QUEUE_COUNT_THRESHOLD	natural	950	An alert with severity 'result_queue_count_threshold_severity' will be issued if result queue exceeds this count. Used for early warning if result queue is almost full. Will be ignored if set to 0.
GC_RESULT_QUEUE_COUNT_THRESHOLD_SEVERITY	t_alert_level	WARNING	Severity of alert to be initiated if exceeding result_queue_count_threshold.



# VVC details

All VVC procedures are defined in vvc\_methods\_pkg (dedicated this VVC), and uvvm\_vvc\_framework.td\_vvc\_framework\_common\_methods\_pkg (common VVC procedures). It is also possible to send a multicast to all instances of a VVC with ALL\_INSTANCES as parameter for vvc\_instance\_idx.

Note: Every procedure here can be called without the optional parameters enclosed in [].

# 1 VVC procedure details

Procedure	Description		
gmii_write()	rgmii_write (VVCT, vvc_instance_idx, channel, data_array, msg, [scope])		
	The rgmii_write() VVC procedure adds a write command to the RGMII VVC executor queue, which will run as soon as all preceding commands have		
	completed. When the command is scheduled to run, the executor calls the RGMII BFM rgmii_write() procedure, described in the RGMII BFM QuickRef.		
gmii_read()	rgmii_read (VVCT, vvc_instance_idx, channel, [TO_SB,] msg, [scope])		
	The rgmii_read() VVC procedure adds a read command to the RGMII VVC executor queue, which will run as soon as all preceding commands have completed. When the command is scheduled to run, the executor calls the RGMII BFM rgmii_read() procedure, described in the RGMII BFM QuickRef.		
	The value received from the DUT will not be returned in this procedure call since it is non-blocking for the sequencer/caller, but the received data and metadata will be stored in the VVC for a potential future fetch (see example with fetch_result below).		
	If the option TO_SB is applied, the received data will be sent to the RGMII dedicated scoreboard. There it is checked against the expected value (provided by the testbench).		
	Example with fetch_result() call: Result is placed in v result		
	variable v_cmd_idx : natural; Command index for the last receive		
	<pre>variable v_result : work.vvc_cmd_pkg.t_vvc_result; Result from read (data and metadata)</pre>		
	()		
	rgmii_read(RGMII_VVCT, 1, RX, "Read data in VVC");		
	<pre>v_cmd_idx := get_last_received_cmd_idx(RGMII_VVCT, 1, RX);</pre>		
	<pre>await_completion(RGMII_VVCT, 1, RX, 1 ms, "Wait for read to finish"); fetch result(RGMII VVCT, 1, RX, v cmd idx, v result, "Fetching result from read operation");</pre>		
	recon_result(RGM11_VVC1, 1, KA, V_CMd_rdx, V_result, reconning result from read operation);		
gmii_expect()	rgmii_expect (VVCT, vvc_instance_idx, channel, data_exp, msg, [alert_level, [scope]])		
	The rgmii_expect() VVC procedure adds an expect command to the RGMII VVC executor queue, which will run as soon as all preceding commands have completed. When the command is scheduled to run, the executor calls the RGMII BFM rgmii_expect() procedure, described in the RGMII BFM QuickRef.		



# 2 VVC Configuration

Record element	Туре	C_RGMII_VVC_CONFIG_DEFAULT	Description
inter_bfm_delay	t_inter_bfm_delay	C_RGMII_INTER_BFM_DELAY_DEFAULT	Delay between any requested BFM accesses towards the DUT.
			- TIME_START2START: Time from a BFM start to the next BFM start
			(A TB_WARNING will be issued if access
			takes longer than TIME_START2START).
			- TIME_FINISH2START: Time from a BFM end to the next BFM start.
			Any insert_delay() command will add to the above minimum delays, giving for
			instance the ability to skew the BFM starting time.
cmd_queue_count_max	natural	C_CMD_QUEUE_COUNT_MAX	Maximum pending number in command queue before queue is full. Adding
			additional commands will result in an ERROR.
cmd_queue_count_threshold	natural	C_CMD_QUEUE_COUNT_THRESHOLD	An alert with severity "cmd_queue_count_threshold_severity" will be issued if
			command queue exceeds this count. Used for early warning if command queue
			is almost full. Will be ignored if set to 0.
cmd_queue_count_threshold_severity	t_alert_level	C_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY	Severity of alert to be initiated if exceeding cmd_queue_count_threshold
result_queue_count_max	natural	C_RESULT_QUEUE_COUNT_MAX	Maximum number of unfetched results before result_queue is full.
result _queue_count_threshold	natural	C_RESULT_QUEUE_COUNT_THRESHOLD	An alert with severity 'result_queue_count_threshold_severity' will be issued if
			result queue exceeds this count. Used for early warning if result queue is
			almost full. Will be ignored if set to 0.
result _queue_count_threshold_severity	t_alert_level	C_RESULT_QUEUE_COUNT_THRESHOLD_SEVERITY	Severity of alert to be initiated if exceeding result_queue_count_threshold.
bfm_config	t_rgmii_bfm_config	C_RGMII_BFM_CONFIG_DEFAULT	Configuration for RGMII BFM. See quick reference for RGMII BFM.
msg_id_panel	t_msg_id_panel	C_VVC_MSG_ID_PANEL_DEFAULT	VVC dedicated message ID panel. See section 16 of
			uvvm_vvc_framework/doc/UVVM_VVC_Framework_Essential_Mechanisms.pdf
			for how to use verbosity control.

The configuration record can be accessed from the Central Testbench Sequencer through the shared variable array, e.g.:

shared\_rgmii\_vvc\_config(1).inter\_bfm\_delay.delay\_in\_time := 50 ns; shared\_rgmii\_vvc\_config(1).bfm\_config.clock\_period := 10 ns;

### 3 VVC Status

The current status of the VVC can be retrieved during simulation. This is achieved by reading from the shared variable shared\_rgmii\_vvc\_status record from the test sequencer. The record contents can be seen below:

Record element	Type	Description
current_cmd_idx	natural	Command index currently running
previous_cmd_idx	natural	Previous command index to run
pending_cmd_cnt	natural	Pending number of commands in the command queue



### 4 Activity watchdog

The VVCs support an activity watchdog which monitors VVC activity and will alert if no VVC activity is registered within a selected timeout value. The VVCs will register their presence to the activity watchdog at start-up, and report when busy and not, using dedicated activity watchdog methods and triggering the global\_trigger\_activity\_watchdog signal, during simulations.

Include activity\_watchdog(num\_exp\_vvc, timeout, alert\_level, msg) in the testbench to start using the activity watchdog. More information can be found in UVVM Essential Mechanisms PDF in the UVVM VVC Framework doc folder.

#### 5 Transaction Info

This VVC supports transaction info, a UVVM concept for distributing transaction information in a controlled manner within the complete testbench environment. The transaction info may be used in many different ways, but the main purpose is to share information directly from the VVC to a DUT model.

See UVVM VVC Framework Essential Mechanisms PDF, section 6, for additional information.

Info field Default Description Type NO OPERATION Current VVC operation, e.g. INSERT DELAY, POLL UNTIL, READ, WRITE. operation t operation t byte array(0 to 299) (others => (others => '0')) An array of bytes containing the data to be written/read. data array data array(0) is written/read first, while data array(data array'high) is written/read last. C VVC META DEFAULT VVC meta data of the executing VVC command. vvc meta t vvc meta Message of executing VVC command. → msg string Command index of executing VVC command. → cmd idx integer C TRANSACTION STATUS DEFAULT Set to INACTIVE, IN PROGRESS, FAILED or SUCCEEDED during a transaction. transaction status t transaction status

Table 1 RGMII transaction info record fields. Transaction type: t base transaction (BT).

### 6 Scoreboard

This VVC has built in Scoreboard functionality where data can be routed by setting the T0\_SB parameter in supported method calls. Note that the data is only stored in the scoreboard and not accessible with the fetch result() method when the T0\_SB parameter is applied.

See the Generic Scoreboard Quick Reference PDF in the Bitvis VIP Scoreboard document folder for a complete list of available commands and additional information. The RGMII VVC scoreboard is accessible from the testbench as a shared variable RGMII\_VVC\_SB, located in the vvc\_methods\_pkg.vhd. All of the listed Generic Scoreboard commands are available for the RGMII VVC scoreboard using this shared variable.

### 7 VVC Interface

In this VVC, the interface has been encapsulated in two signal records of type t\_rgmii\_tx\_if for the signals going to the DUT and t\_rgmii\_rx\_if for the signals coming from the DUT in order to improve readability of the code.



#### **Additional Documentation**

Additional documentation about UVVM and its features can be found under "/uvvm vvc framework/doc/".

For additional documentation on the RGMII standard, see the specification "Reduced Gigabit Media Independent Interface (RGMII) Version 2.0".

## Compilation

RGMII VVC must be compiled with VHDL 2008.

It is dependent on the following libraries

- UVVM Utility Library (UVVM-Util), version 2.13.0 and up
- UVVM VVC Framework, version 2.8.0 and up
- RGMII BFM
- Bitvis VIP Scoreboard

Before compiling the RGMII VVC, assure that uvvm vvc framework, uvvm util and bitvis vip scoreboard have been compiled.

See UVVM Essential Mechanisms located in uvvm vvc framework/doc for information about compile scripts.

#### Compile order for the RGMII VVC:

Compile to library	File	Comment
bitvis_vip_rgmii	rgmii_bfm_pkg.vhd	RGMII BFM
bitvis_vip_rgmii	transaction_pkg.vhd	RGMII transaction package with DTT types, constants etc.
bitvis_vip_rgmii	vvc_cmd_pkg.vhd	RMGII VVC command types and operations
bitvis_vip_rgmii	/uvvm_vvc_framework/src_target_dependent/td_target_support_pkg.vhd	UVVM VVC target support package, compiled into the RGMII VVC library.
bitvis_vip_rgmii	/uvvm_vvc_framework/src_target_dependent/td_vvc_framework_common_methods_pkg.vhd	UVVM framework common methods compiled into the RGMII VVC library
bitvis_vip_rgmii	vvc_methods_pkg.vhd	RGMII VVC methods
bitvis_vip_rgmii	/uvvm_vvc_framework/src_target_dependent/td_queue_pkg.vhd	UVVM queue package for the VVC
bitvis_vip_rgmii	/uvvm_vvc_framework/src_target_dependent/td_vvc_entity_support_pkg.vhd	UVVM VVC entity support compiled into the RGMII VVC library
bitvis_vip_rgmii	rgmii_tx_vvc.vhd	RGMII TX VVC
bitvis_vip_rgmii	rgmii_rx_vvc.vhd	RGMII RX VVC
bitvis vip rgmii	rgmii vvc.vhd	RGMII VVC

### 10 Simulator compatibility and setup

See README.md for a list of supported simulators.

For required simulator setup see **UVVM-Util** Quick reference.

#### **IMPORTANT**

This is a simplified Verification IP (VIP) for RGMII. The given VIP complies with the basic RGMII protocol and thus allows a normal access towards an RGMII interface. This VIP is not RGMII protocol checker. For a more advanced VIP please contact Bitvis AS at support@bitvis.no



**RGMII VVC** - Quick Reference

Disclaimer: This IP and any part thereof are provided "as is", without warranty of any kind, express or implied, including but not limited to the warranties of merchantability, fitness for a particular purpose and noninfringement. In no event shall the authors or copyright holders be liable for any claim, damages or other liability, whether in an action of contract, tort or otherwise, arising from, out of or in connection with this IP.

support@bitvis.no +47 66 98 87 59 www.bitvis.no