



Helvetica N...



Step 7 of 7



Hands-on Lab: Informational, File, and Directory Commands

Estimated time needed: **40** minutes

Objectives

In this lab, you will be introduced to the use of basic Unix commands related to the following categories:

- Informational commands
- File and Directory Management Commands
- Access control commands

About Skills Network Cloud IDE


Skills Network Cloud IDE (based on Theia and Docker) provides an environment for hands on labs for course and project related labs. Theia is an open source IDE (Integrated Development Environment), that can be run on desktop or on the cloud. To complete this lab, you will be using the Cloud IDE based on Theia.

Important notice about this lab environment


Please be aware that sessions for this lab environment are not persisted. Thus, every time you connect to this lab, a new environment is created for you and any data or files you may have saved in a previous session will be lost. To avoid losing your data, plan to complete these labs in a single session.

Setup

Open a new terminal by clicking on the menu bar and selecting **Terminal->New Terminal**, as in the image below.



This will open a new terminal at the bottom of the screen as seen below.



You can run the commands provided in the following exercises in your newly opened terminal. You can copy the code to your clipboard if you like by clicking on the little copy button on the bottom right of each codeblock, and then paste it on the command line.

Exercise 1 - Informational Commands

In this exercise, you will familiarize yourself with useful commands for providing system and user information.

1.1. Display the name of the current user

```
whoami
```

whoami

It will display the user name as theia. You are logged into this lab as theia.

You can get a list of currently logged in users using the command who. But this command doesn't work in the theia environment yet.

1.2. Get basic information about the operating system

uname

By default the command prints the kernel name.

uname

You will see Linux printed in the output.

Using the -a option prints all the system information in the following order: Kernel name, network node hostname, kernel release date, kernel version, machine hardware name, hardware platform, operating system.

uname -a

1.3. Obtain the user and group identity information

id

This command displays the user id and group id information of the current user.

id

It will display the uid (user id) and gid (group id) for the user theia.

1.4 Get available disk space

df

The df command is used to display available disk space. Entering

df

It will display available disk space in 512-byte blocks. To get available disk space in a "human-readable" format, enter:

df -h

1.5. View currently running processes

ps

The ps command lists each processes that is currently running and its PID (process id).

ps

However, the output only contains the processes that are owned by you.

By using the -e option, you can display all of the processes running on the system. This includes processes owned by other users.

ps -e

1.6. Get information on the running processes and system resources

top

The top command provides a dynamic, real-time view of your system.

It shows summary information of the system and a table of more detailed information related to the processes or threads which are currently running and managed by the kernel. This includes information related to cpu and memory usage per process.

top

Here is a sample output.

```
top - 07:47:21 up 23 days, 16:16, 0 users, load average: 3.74, 2.67, 2.38
Tasks: 11 total, 1 running, 10 sleeping, 0 stopped, 0 zombie
%Cpu(s): 7.2 us, 4.4 sy, 0.2 ni, 86.2 id, 0.0 wa, 0.0 hi, 0.0 si, 1.9 st
KiB Mem : 65955464 total, 21591660 free, 6893160 used, 37470644 buff/cache
KiB Swap: 0 total, 0 free, 0 used. 58959348 avail Mem

  PID USER      PR  NI   VIRT   RES   SHR  S  %CPU  %MEM     TIME+ COMMAND
 334 theia    20   0 906024 42428 29556 S   0.7   0.1   0:01.13 node
 323 theia    20   0 968236 81428 31576 S   0.3   0.1   0:04.31 node
   1 theia    20   0  4636    872   804 S   0.0   0.0   0:00.05 sh
   7 theia    20   0 12892   3180  2884 S   0.0   0.0   0:00.01 entrypoint.sh
 294 theia    20   0 893640 51792 27044 S   0.0   0.1   0:00.46 node
 315 theia    20   0  4652    884   796 S   0.0   0.0   0:00.00 sh
 316 theia    20   0 590404 47860 29704 S   0.0   0.1   0:00.68 node
 357 theia    20   0 710272 56864 30836 S   0.0   0.1   0:01.21 node
 379 theia    20   0  21628  4092   3488 S   0.0   0.0   0:00.00 bash
 416 theia    20   0 587520 45708 29520 S   0.0   0.1   0:00.71 node
 441 theia    20   0  41660   3564   3100 R   0.0   0.0   0:00.09 top
```

When you start top, you'll be presented with the following elements on the main top screen.

1. Summary area - shows information like system uptime, number of users, load average, and overall memory usage
2. Column header - attribute names
3. Task area - displays the data for each process, or PID

The output keeps refreshing until you press q or Ctrl+c.

If you want to exit automatically after a specified number of repetitions, use the -n option as follows:

```
top -n 10
```

You can press the following keys while top is running to sort the table:

Key	Sorts by
M	Memory Usage
P	CPU Usage
N	Process ID (PID)
T	Running Time.

For example, you can find out which process is consuming the most memory by entering shift + m.

1.7. Display Messages

echo

The echo command displays the given text on the screen. For example, entering:

```
echo "Welcome to the linux lab"
```

prints Welcome to the linux lab.

These special characters help you better format your output.

Special Character	Effect
\n	start a new line
\t	insert a tab

Use the -e option of the echo command when working with special characters. For example:

```
echo -e "This will be printed \nin two lines"
```

1.8. Display date and time

date

The date command displays the current date and time.

```
date
```

It has several options which help you display the current date and time in your favourite format. For example, the following command displays the current date in mm/dd/yy format.

```
date "+%D"
```

Here are some of the popular format specifiers that you can try out:

Specifier	Explanation
%d	Display the day of the month (01 to 31)
%h	Displays the abbreviated month name (Jan to Dec)
%m	Displays the month of year (01 to 12)
%Y	Displays the four-digit year
%T	Displays the time in 24 hour format as HH:MM:SS
%H	Displays the hour

```
date "+%"
```

1.9. View the Reference Manual For a Command

```
man
```

The `man` command displays the user manual for any command that you provide as its argument.

For example, to see the manual page for the `ls` command, enter:

```
man date
```

Scroll through the command's manual to find any info you may need. When you're done, press `q` to quit.

Excercise 2: File and directory management commands

In this exercise, you will practice using commands for managing files and directories.

2.1. Get the location of the current working directory

```
pwd
```

When working in a Linux terminal, you will always be working from a directory. By default, you will start in your home directory. To get the absolute path of your current working directory, enter:

```
pwd
```

2.2. List the files and directories

```
ls
```

To list the files and directories in the current directory, enter:

```
ls
```

If your directory happens to be empty, `ls` will not return anything.

The following command will list the many binary and executable files which are present in your `/bin` directory.

```
ls /bin
```

The `/bin` directory happens to be where Linux commmands such as `ls` and `pwd` are stored. For example, you can see that `ls` is present by entering:

```
ls /bin/ls
```

To list all files starting with `b` in the `/bin` directory, try entering:

```
ls /bin/b*
```

To list all files ending in `r` in the `/bin` directory, enter:

```
ls /bin/*r
```

To print a long list of files that has additional information compared to the simple `ls` command, such as the last modified date, enter:

```
ls -l
```

Here are some popular options that you can try with the `ls` command.

Option	Description
<code>-a</code>	list all files, including hidden files
<code>-d</code>	list directories only, do not include files
<code>-h</code>	with <code>-l</code> and <code>-s</code> , print sizes like 1K, 234M, 2G
<code>-l</code>	include attributes like permissions, owner, size, and last-modified date
<code>-S</code>	sort by file size, largest first
<code>-t</code>	sort by last-modified date, newest first
<code>-r</code>	reverse the sort order

To get a long listing of all files in `/etc`, including any hidden files, enter:

```
ls -la /etc
```

Here we combined the options `-l` and `-a` using the shorter notation, `-la`.

2.3. Create a directory

mkdir

The `mkdir` command is used to create a new directory.

To create a directory named `scripts` in your current directory, run the following command:

```
mkdir scripts
```

Use the `ls` command to verify whether the `scripts` directories got created:

```
ls
```

2.4. Change your current working directory.

cd

To get into the directory `scripts` directory, run the following command:

```
cd scripts
```

Now use the `pwd` command to verify whether your current working directory has changed as expected:

```
pwd
```

If you use `cd` without any directory name as follows, it will move you back to your home directory:

```
cd
```

Again, enter the `pwd` command to verify whether your current working directory has changed:

```
pwd
```

The syntax `..` is a shortcut that refers to the parent directory of your current directory. Run the following command to change directories up one level:

```
cd ..
```

2.5. Create an empty file

touch

First, return to your home directory by entering:

```
cd
```

Next, use the `touch` command to create an empty file named `myfile.txt`:

```
touch myfile.txt
```

Now use the `ls` command to verify creation of `myfile.txt`:

```
ls
```

If the file already exists, the `touch` command updates the access timestamp, or last-modified date of the file. To see this, enter:

```
touch myfile.txt
```

and use the `date` command to verify the date change:

```
date -r myfile.txt
```

2.6. Search and locate files

find

The `find` command is used to search for files in a directory. You can search for files based on different attributes, such as the file's name, type, owner, size, or timestamp.

The `find` command conducts a search of the entire directory tree starting from the given directory name.

For example, the following command finds all `.txt` files in the subfolders of the `/etc` directory:

```
find /etc -name '*.txt'
```

Along with the listing of all `.txt` files, you may get some `Permission denied` errors.

These errors are normal, as you have limited access on the lab machine.

2.7. Remove files

rm

The `rm` command is used to delete files, and is ideally used along with the `-i` option, which makes it ask for confirmation before every deletion.

To remove the file `myfile.txt`, enter the following command and press `y` to confirm deletion, or `n` to cancel:

```
rm -i myfile.txt
```

Use the `ls` command to verify removal:

```
ls
```

2.8. Move, Rename a file

mv

First, make a file called `users.txt`:

```
touch users.txt
```

The `mv` command moves a file from one directory to another.

Use caution when moving a file, because if the target file already exists, it will be overwritten by the source file.

Conveniently however, if the source and target directories are the same, you can employ `mv` as a rename operation.

To illustrate this, rename `users.txt` as `user-info.txt` by entering the following command:

```
mv users.txt user-info.txt
```

Now use the `ls` command to verify the name change:

```
ls
```

Now move `user-info.txt` to the `/tmp` directory, as follows:

```
mv user-info.txt /tmp
```

Now use the `ls` command twice to verify the move, as follows:

```
ls
```

```
ls -l /tmp
```

2.9. Copy files

cp

You can use the `cp` command to copy `user-info.txt`, which is now in your `/tmp` directory, to your current working directory as follows:

```
cp /tmp/user-info.txt user-info.txt
```

Now use the `ls` command to verify whether the copy was successful:

```
ls
```

The following command copies the content of `/etc/passwd` to a file named `users.txt` under the current directory:

```
cp /etc/passwd users.txt
```

Now use the `ls` command to verify whether the copy was successful:

```
ls
```

Exercise 3 - Access control commands

Required files:

Run the following code to acquire the required files for this exercise:

```
wget https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-LX0117EN-SkillsNetwork/labs/module%201/usdoi.txt
```

Each file and each directory has permissions set for three permission categories: the 'owner', the 'group' and 'all users'.

The following permissions are set for each file and directory:

Permission symbol

read	r
write	w
execute	x

To see the permissions currently set for a file, run the command `ls -l`.

For example, to see the permissions for the file named `usdoi.txt` in your current directory, run:

```
ls -l usdoi.txt
```

A sample output looks like:

```
-rw-r--r-- 1 theia theia 8121 May 31 16:45 usdoi.txt
```

The permissions set here are `rw-r--r--`. The `-` preceding these permissions indicates that `usdoi.txt` is a file. If it were a directory, you would see a `d` instead of the `-`.

The first three entries correspond to the owner, the next three correspond to the group, and the last three are for all others. You can see the owner of the file has read and write permissions, while the user group only has read permissions, and all other users have read permission. No users have execute permissions, as indicated by the `-` instead of an `x` in the third position for each user category.

3.1. Change permissions

chmod

The `chmod` (change mode) command lets you change the permissions set for a file.

The change of permissions is specified with the help of a combination of the following characters:

Option	Description
r, w and x permissions:	read, write and execute, respectively
u, g and o	user categories: owner, group and all others, respectively
+, -	operations: grant and revoke, respectively

The command below removes read permission for all users (user, group and other) on the file `usdoi.txt`:

```
chmod -r usdoi.txt
```

You can verify the changed permissions by entering:

```
ls -l usdoi.txt
```

To add read access to all users on `usdoi.txt`, enter:

```
chmod +r usdoi.txt
```

Now verify the changed permissions:

```
ls -l usdoi.txt
```

To remove the read permission for 'all other users' category, enter:

```
chmod o-r usdoi.txt
```

Verify the changed permissions:

```
ls -l usdoi.txt
```

Practice exercises

1. Problem:

Display the content of /home directory.

▼ Click here for Hint

Use `ls` command.

▼ Click here for Solution

```
ls /home
```

2. Problem:

Ensure that you are in your home directory.

▼ Click here for Hint

Use `cd` to move to the home directory and then use `pwd` to verify.

▼ Click here for Solution

```
cd  
pwd
```

3. Problem:

Create a new directory called `final` in your home directory.

▼ Click here for Hint

Use `mkdir` command.

▼ Click here for Solution

```
mkdir final
```

4. Problem:

View the permissions of the newly created directory, `final`.

▼ Click here for Hint

Use `-d` and `-l` options of the `ls` command.

▼ Click here for Solution

```
ls -ld final
```

5. Problem:

Create a new blank file named 'display.sh' in the final directory

▼ Click here for Hint

use 'cd' and 'touch' commands.

▼ Click here for Solution

```
cd final  
touch display.sh
```

6. Problem:

Create a copy of display.sh called report.sh.

► Click here for Hint

▼ Click here for Solution

```
cp display.sh report.sh
```

7. Problem:

Delete the file 'display.sh'.

▼ Click here for Hint

Use rm command.

▼ Click here for Solution

```
rm -i display.sh
```

8. Problem:

List the files in /etc directory in the ascending order of their access time.

▼ Click here for Hint

Use the ls command with the right options.

▼ Click here for Solution

```
ls -ltr /etc/
```

9. Problem:

Display the current time.

▼ Click here for Hint

Use the format option %T of the date command.

▼ Click here for Solution

```
date "+%T"
```

10. Problem:

Copy the file /var/log/bootstrap.log to your current directory.

▼ Click here for Hint

Use the cp command to copy the file to your current directory .

▼ [Click here for Solution](#)

```
cp /var/log/bootstrap.log .
```

Authors

Ramesh Sannareddy Sam Prokopchuk

Other Contributors

Rav Ahuja Jeff Grossman

Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2021-05-30	0.1	Ramesh Sannareddy	Created initial version of the lab
2021-11-29	0.2	Sam Prokopchuk	Update lab contents and split
2021-12-02	0.3	Jeff Grossman	Review and Update lab

Copyright (c) 2021 IBM Corporation. All rights reserved.

[Previous](#)