

Hands-on Lab: Using Views

Estimated time needed: 10 minutes

In this lab, you will learn about using views. In SQL, a view is an alternative way of representing data that exists in one or more tables. Just like a real table, it contains rows and columns. The fields in a view are fields from one or more real tables in the database. Though views can be queried like a table, views are dynamic; only the definition of the view is stored, not the data.

How does the syntax of a CREATE VIEW statement look?

```
CREATE VIEW view_name AS
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

How does the syntax of a REPLACE VIEW statement look?

```
CREATE OR REPLACE VIEW view_name AS
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

How does the syntax of a DROP VIEW statement look?

```
DROP VIEW view_name;
```

Software Used in this Lab

In this lab, you will use [IBM Db2 Database](#). Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve the data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow the lab below first:

- [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Database Used in this Lab

The database used in this lab is an internal database. You will be working on a sample HR database. This HR database schema consists of 5 tables called **EMPLOYEES**, **JOB_HISTORY**, **JOBS**, **DEPARTMENTS** and **LOCATIONS**. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry ln, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	M	291 Springs, Gary,IL	300	50000	30002	5

EMPL_ID	START_DATE	JOBS_ID	DEPT_ID
E1001	2000-01-30	100	2
E1002	2010-08-16	200	5
E1003	2016-08-10	300	5

JOB_IDENT	JOB_TITLE	MIN_SALARY	MAX_SALARY
100	Sr. Architect	60000	100000
200	Sr.SoftwaredDeveloper	60000	80000
300	Jr.SoftwaredDeveloper	40000	60000

DEPT_ID_DEP	DEP_NAME	MANAGER_ID	LOC_ID
2	Architect Group	30001	L0001
5	Software Development	30002	L0002
7	Design Team	30003	L0003
5	Software	30004	L0004

LOCT_ID	DEP_ID_LOC
L0001	2
L0002	5
L0003	7

- [Hands-on Lab : Create tables using SQL scripts and Load data into tables](#)

After completing this lab, you will be able to:


- ## Instructions


When you approach the exercises in this lab, follow the instructions to run the queries on Db2:


- ## Exercise 1: Create a View


1. Let's create a view called **EMPSALARY** to display salary along with some basic sensitive data of employees from the HR database. To create the **EMPSALARY** view from the **EMPLOYEES** table, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.


- ```
SELECT * FROM EMPSALARY;
```























 Syntax assistant







1 `SELECT * FROM EMPLOYEES;`

2

Result - Dec 14, 2020 11:11:11





 `SELECT * FROM EMPLOYEES;`


Run time: 0.008 s

Result set 1

Search







| EMP_ID | F_NAME  | L_NAME  | B_DATE     | SEX | SALARY    |
|--------|---------|---------|------------|-----|-----------|
| E1001  | John    | Thomas  | 1976-01-09 | M   | 100000.00 |
| E1002  | Alice   | James   | 1972-07-31 | F   | 80000.00  |
| E1003  | Steve   | Wells   | 1980-08-10 | M   | 50000.00  |
| E1004  | Santosh | Kumar   | 1985-07-20 | M   | 60000.00  |
| E1005  | Ahmed   | Hussain | 1981-01-04 | M   | 70000.00  |
| E1006  | Nancy   | Allen   | 1978-02-06 | F   | 90000.00  |
| E1007  | Mary    | Thomas  | 1975-05-05 | F   | 65000.00  |
| E1008  | Bharath | Gupta   | 1985-05-06 | M   | 65000.00  |
| E1009  | Andrea  | Jones   | 1990-07-09 | F   | 70000.00  |
| E1010  | Ann     | Jacob   | 1982-03-30 | F   | 70000.00  |

Show Less

In this exercise, you will update a View to combine two or more tables in meaningful ways.

Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

**NOTE:** Don't worry if you don't understand how to combine two tables using implicit inner join. You will learn more about joins later on. For now, just think you are combining the data of two different tables, **EMPLOYEES** and **JOBS** by connecting their respective columns **JOB\_ID** and **JOB\_IDENT** since both the columns contain common unique data. You can have a look at the diagram (at the beginning of the lab) showing the tables for the HR database to observe how the **JOB\_ID** and **JOB\_IDENT** columns from the **EMPLOYEES** and **JOBS** tables respectively contain common unique data.

```
SELECT * FROM EMPSALARY;
```

| Result set 1 |         |         |            |     |                 |            |            | Search |  | ↑ |
|--------------|---------|---------|------------|-----|-----------------|------------|------------|--------|--|---|
| EMP_ID       | F_NAME  | L_NAME  | B_DATE     | SEX | JOB_TITLE       | MIN_SALARY | MAX_SALARY |        |  |   |
| E1001        | John    | Thomas  | 1976-01-09 | M   | Sr. Architect   | 60000.00   | 100000.00  |        |  |   |
| E1002        | Alice   | James   | 1972-07-31 | F   | Sr.Software Dev | 60000.00   | 80000.00   |        |  |   |
| E1003        | Steve   | Wells   | 1980-08-10 | M   | Jr.Software Dev | 40000.00   | 60000.00   |        |  |   |
| E1004        | Santosh | Kumar   | 1985-07-20 | M   | Jr.Software Dev | 40000.00   | 60000.00   |        |  |   |
| E1005        | Ahmed   | Hussain | 1981-01-04 | M   | Jr. Architect   | 50000.00   | 70000.00   |        |  |   |
| E1006        | Nancy   | Allen   | 1978-02-06 | F   | Lead Architect  | 70000.00   | 100000.00  |        |  |   |
| E1007        | Mary    | Thomas  | 1975-05-05 | F   | Jr. Designer    | 60000.00   | 70000.00   |        |  |   |
| E1008        | Bharath | Gupta   | 1985-05-06 | M   | Jr. Designer    | 60000.00   | 70000.00   |        |  |   |
| E1009        | Andrea  | Jones   | 1990-07-09 | F   | Sr. Designer    | 70000.00   | 90000.00   |        |  |   |
| E1010        | Ann     | Jacob   | 1982-03-30 | F   | Sr. Designer    | 70000.00   | 90000.00   |        |  |   |

# Exercise 3: Drop a View

In this exercise, you will drop a created View.

1. Let's delete the created **EMPSALARY** view. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

DROP VIEW EMPSALARY;

1

2

DROP VIEW EMPSALARY;

Syntax assistant

Result - Dec 14, 2020 11...

✓

DROP VIEW EMPSALARY

Run time: 0.010 s

Status: Success

Affected Rows: 0

2. Using SELECT, you can verify whether the **EMPSALARY** view has been deleted or not. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

SELECT \* FROM EMPSALARY;

1

2

SELECT \* FROM EMPSALARY;

Syntax assistant

Result - Dec 14, 2020 11...

✗

SELECT \* FROM EMPSALARY

Run time: 0.008 s

Status: Failed

Error message

"ZJH17769.EMPSALARY" is an undefined name.. SQLCODE=-204, SQLSTATE=42704, DRIVER=4.26.14

Learn more about this error

Congratulations! You have completed this lab, and you are ready for the next topic.

## Author(s)

- [Sandip Saha Joy](#)

## Other Contributor(s)

-

# Changelog

| Date       | Version | Changed by      | Change Description      |
|------------|---------|-----------------|-------------------------|
| 2020-12-24 | 1.1     | Steve Ryan      | ID reviewed             |
| 2020-12-14 | 1.0     | Sandip Saha Joy | Created initial version |

© IBM Corporation 2020. All rights reserved.