

DBMS LAB – 8: TRANSACTION ISOLATION LEVELS

Name: Bhavani S

SRN: PES1UG24CS144

Section: 5A

Subject: Database Management Systems Lab

Date: 17-10-2025

Question 1: Identify the Default Isolation Level

Code

```
SELECT @@transaction_isolation;
SELECT @@global.transaction_isolation;
```

Output

```
owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current
statement.

mysql> SELECT @@transaction_isolation;
+-----+
| @@transaction_isolation |
+-----+
| REPEATABLE-READ         |
+-----+
1 row in set (0.00 sec)

mysql> SELECT @@global.transaction_isolation;
+-----+
| @@global.transaction_isolation |
+-----+
| REPEATABLE-READ                 |
+-----+
1 row in set (0.00 sec)

mysql> |
```

By default, MySQL uses the **REPEATABLE READ** isolation level.

Question 2: Database Setup

Code

```
CREATE DATABASE airlines_db;
USE airlines_db;

CREATE TABLE Flight (
    flight_number VARCHAR(10) PRIMARY KEY,
    departure_time DATETIME NOT NULL,
    arrival_time DATETIME NOT NULL,
    origin VARCHAR(50) NOT NULL,
    destination VARCHAR(50) NOT NULL,
    economy_seats INT NOT NULL,
    business_seats INT NOT NULL,
    first_class_seats INT NOT NULL
);

CREATE TABLE Passenger (
    passenger_id VARCHAR(10) PRIMARY KEY,
    name VARCHAR(50) NOT NULL,
    gender ENUM('Male', 'Female', 'Other'),
    date_of_birth DATE,
    phone_number VARCHAR(15),
    seat_preference ENUM('Window', 'Aisle', 'Middle'),
    class_preference ENUM('Economy', 'Business', 'First'),
    loyalty_program_points INT DEFAULT 0
);

INSERT INTO Flight VALUES
('SKY101', '2025-07-12 06:00:00', '2025-07-12 10:30:00', 'Delhi',
'Singapore', 180, 30, 10),
('SKY202', '2025-07-13 14:00:00', '2025-07-13 18:00:00', 'Mumbai', 'Dubai',
160, 25, 8),
('SKY303', '2025-07-14 22:00:00', '2025-07-15 02:30:00', 'Chennai',
'Bangkok', 150, 20, 5);

INSERT INTO Passenger VALUES
('P001', 'Aarav Sharma', 'Male', '1990-08-15', '9876543210', 'Window',
'Economy', 12000),
('P002', 'Meera Patel', 'Female', '1985-02-20', '9123456789', 'Aisle',
'Business', 22000),
('P003', 'Riya Das', 'Female', '1998-11-10', '9988776655', 'Window',
'First', 30000);
```

Output

```
mysql> USE airlines_db;
Database changed
mysql>
mysql> CREATE TABLE Flight (
-> flight_number VARCHAR(10) PRIMARY KEY,
-> departure_time DATETIME NOT NULL,
-> arrival_time DATETIME NOT NULL,
-> origin VARCHAR(50) NOT NULL,
-> destination VARCHAR(50) NOT NULL,
-> economy_seats INT NOT NULL,
-> business_seats INT NOT NULL,
-> first_class_seats INT NOT NULL
-> );
Query OK, 0 rows affected (0.13 sec)

mysql>
mysql> CREATE TABLE Passenger (
-> passenger_id VARCHAR(10) PRIMARY KEY,
-> name VARCHAR(50) NOT NULL,
-> gender ENUM('Male', 'Female', 'Other'),
-> date_of_birth DATE,
-> phone_number VARCHAR(15),
-> seat_preference ENUM('Window', 'Aisle', 'Middle'),
-> class_preference ENUM('Economy', 'Business', 'First'),
-> loyalty_program_points INT DEFAULT 0
```

```
MySQL 8.0 Command Line Cli  x + v
mysql>
mysql> CREATE TABLE Passenger (
-> passenger_id VARCHAR(10) PRIMARY KEY,
-> name VARCHAR(50) NOT NULL,
-> gender ENUM('Male', 'Female', 'Other'),
-> date_of_birth DATE,
-> phone_number VARCHAR(15),
-> seat_preference ENUM('Window', 'Aisle', 'Middle'),
-> class_preference ENUM('Economy', 'Business', 'First'),
-> loyalty_program_points INT DEFAULT 0
-> );
Query OK, 0 rows affected (0.06 sec)

mysql>
mysql> INSERT INTO Flight VALUES
-> ('SKY101', '2025-07-12 06:00:00', '2025-07-12 10:30:00', 'Delhi', 'Singapore', 180, 30, 10),
-> ('SKY202', '2025-07-13 14:00:00', '2025-07-13 18:00:00', 'Mumbai', 'Dubai', 160, 25, 8),
-> ('SKY303', '2025-07-14 22:00:00', '2025-07-15 02:30:00', 'Chennai', 'Bangkok', 150, 20, 5);
Query OK, 3 rows affected (0.02 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql>
mysql> INSERT INTO Passenger VALUES
-> ('P001', 'Aarav Sharma', 'Male', '1990-08-15', '9876543210', 'Window', 'Economy', 12000),
-> ('P002', 'Meera Patel', 'Female', '1985-02-20', '9123456789', 'Aisle', 'Business', 22000),
-> ('P003', 'Riya Das', 'Female', '1998-11-10', '9988776655', 'Window', 'First', 30000);
Query OK, 3 rows affected (0.01 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql>
```

Question 3: READ UNCOMMITTED

Code

Session A

```
SET SESSION TRANSACTION ISOLATION LEVEL READ UNCOMMITTED;
START TRANSACTION;
```

```
UPDATE Passenger
SET seat_preference = 'Aisle'
WHERE passenger_id = 'P001';
-- Do not commit yet
```

```
mysql> SET SESSION TRANSACTION ISOLATION LEVEL READ UNCOMMITTED;
Query OK, 0 rows affected (0.02 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> UPDATE Passenger
      -> SET seat_preference = 'Aisle'
      -> WHERE passenger_id = 'P001';
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> -- Do not commit yet
mysql> |
```

Session B

```
SET SESSION TRANSACTION ISOLATION LEVEL READ UNCOMMITTED;
START TRANSACTION;
```

```
SELECT name, seat_preference
FROM Passenger
WHERE passenger_id = 'P001';
```

Output

```
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> UPDATE Passenger
      -> SET seat_preference = 'Aisle'
      -> WHERE passenger_id = 'P001';
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> -- Do not commit yet
mysql> SET SESSION TRANSACTION ISOLATION LEVEL READ UNCOMMITTED;
Query OK, 0 rows affected (0.00 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.02 sec)

mysql>
mysql> SELECT name, seat_preference
      -> FROM Passenger
      -> WHERE passenger_id = 'P001';
+-----+-----+
| name      | seat_preference |
+-----+-----+
| Aarav Sharma | Aisle          |
+-----+-----+
1 row in set (0.00 sec)

mysql>
```

Even though Session A has **not committed**, Session B can see the updated value.
This is a **Dirty Read**.

Question 4: READ COMMITTED

Code

Session A

```
SET SESSION TRANSACTION ISOLATION LEVEL READ COMMITTED;  
START TRANSACTION;
```

```
SELECT seat_preference  
FROM Passenger  
WHERE passenger_id = 'P001';
```

```
mysql> START TRANSACTION;  
Query OK, 0 rows affected (0.00 sec)
```

```
mysql>  
mysql> SELECT seat_preference  
-> FROM Passenger  
-> WHERE passenger_id = 'P001';
```

```
+-----+  
| seat_preference |  
+-----+  
| Aisle          |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql>
```

Session B

```
SET SESSION TRANSACTION ISOLATION LEVEL READ COMMITTED;  
START TRANSACTION;
```

```
UPDATE Passenger  
SET seat_preference = 'Window'  
WHERE passenger_id = 'P001';  
COMMIT;
```

```
mysql> SET SESSION TRANSACTION ISOLATION LEVEL READ COMMITTED;  
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> START TRANSACTION;  
Query OK, 0 rows affected (0.00 sec)
```

```
mysql>  
mysql> UPDATE Passenger  
-> SET seat_preference = 'Window'  
-> WHERE passenger_id = 'P001';  
Query OK, 1 row affected (0.01 sec)  
Rows matched: 1 Changed: 1 Warnings: 0
```

```
mysql> COMMIT;  
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
```

Session A (again)

```
SELECT seat_preference
FROM Passenger
WHERE passenger_id = 'P001';
```

Output

```
mysql> SELECT seat_preference
      -> FROM Passenger
      -> WHERE passenger_id = 'P001';
+-----+
| seat_preference |
+-----+
| Window          |
+-----+
1 row in set (0.00 sec)

mysql> ^N
```

The value read by Session A changes within the same transaction, showing a **Non-Repeatable Read**.

Question 5: REPEATABLE READ

Code

Session A

```
SET SESSION TRANSACTION ISOLATION LEVEL REPEATABLE READ;
START TRANSACTION;
```

```
SELECT passenger_id, name, seat_preference
FROM Passenger
WHERE class_preference = 'Economy';
```

```
mysql> SET SESSION TRANSACTION ISOLATION LEVEL REPEATABLE READ;
Query OK, 0 rows affected (0.00 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> SELECT passenger_id, name, seat_preference
      -> FROM Passenger
      -> WHERE class_preference = 'Economy';
+-----+-----+-----+
| passenger_id | name       | seat_preference |
+-----+-----+-----+
| P001         | Aarav Sharma | Window          |
+-----+-----+-----+
1 row in set (0.00 sec)
```

Session B

```
SET SESSION TRANSACTION ISOLATION LEVEL REPEATABLE READ;
START TRANSACTION;
```

```
UPDATE Passenger
SET seat_preference = 'Aisle'
WHERE passenger_id = 'P001';
COMMIT;
```

```
mysql> SET SESSION TRANSACTION ISOLATION LEVEL REPEATABLE READ;
Query OK, 0 rows affected (0.00 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> UPDATE Passenger
      -> SET seat_preference = 'Aisle'
      -> WHERE passenger_id = 'P001';
Query OK, 1 row affected (0.02 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> COMMIT;
Query OK, 0 rows affected (0.01 sec)
```

Session A (again)

```
SELECT passenger_id, name, seat_preference
FROM Passenger
WHERE class_preference = 'Economy';
```

Output

```
mysql> SELECT passenger_id, name, seat_preference
      -> FROM Passenger
      -> WHERE class_preference = 'Economy';
+-----+-----+-----+
| passenger_id | name       | seat_preference |
+-----+-----+-----+
| P001         | Aarav Sharma | Aisle          |
+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

Session A still sees the **old value**, proving **Repeatable Read** consistency.

Question 6: SERIALIZABLE

Code

Session A

```
SET SESSION TRANSACTION ISOLATION LEVEL SERIALIZABLE;
START TRANSACTION;
```

```
SELECT COUNT(*)
FROM Flight
WHERE DATE(departure_time) = '2025-07-14'
FOR UPDATE;
```

```
mysql> SET SESSION TRANSACTION ISOLATION LEVEL SERIALIZABLE;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
mysql> SELECT COUNT(*)
      -> FROM Flight
      -> WHERE DATE(departure_time) = '2025-07-14'
      -> FOR UPDATE;
```

```
+-----+
| COUNT(*) |
+-----+
|         1 |
+-----+
1 row in set (0.01 sec)
```

```
mysql> |
```

Session B

```
SET SESSION TRANSACTION ISOLATION LEVEL SERIALIZABLE;
START TRANSACTION;
```

```
INSERT INTO Flight
VALUES ('SKY404', '2025-07-14 08:00:00', '2025-07-14 12:30:00', 'Delhi',
'Colombo', 170, 25, 6);
```

Output

```
mysql>
mysql> SELECT COUNT(*)
      -> FROM Flight
      -> WHERE DATE(departure_time) = '2025-07-14'
      -> FOR UPDATE;
+-----+
| COUNT(*) |
+-----+
|         1 |
+-----+
1 row in set (0.01 sec)

mysql> SET SESSION TRANSACTION ISOLATION LEVEL SERIALIZABLE;
Query OK, 0 rows affected (0.00 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> INSERT INTO Flight
      -> VALUES ('SKY404', '2025-07-14 08:00:00', '2025-07-14 12:30:00', 'Delhi', 'Colombo', 170, 25, 6);
Query OK, 1 row affected (0.01 sec)

mysql>
```

Session B is blocked until Session A commits — showing full **serialization** and prevention of concurrent updates.

Question 7: Observation Table

Isolation Level	Dirty Read	Non-Repeatable Read	Phantom Read	Comment
Read Uncommitted	Allowed	Possible	Possible	Lowest consistency
Read Committed	Prevented	Possible	Possible	Default in Oracle
Repeatable Read	Prevented	Prevented	Possible	MySQL default
Serializable	Prevented	Prevented	Prevented	Highest consistency, slowest concurrency

Question 8: Conclusion

In this experiment, we observed how **isolation levels** affect data visibility across concurrent transactions.

As we move from **Read Uncommitted** → **Serializable**, data consistency improves but concurrency decreases.

MySQL's default level (**Repeatable Read**) balances performance and consistency for most applications.