

User Prompt

i am testing my chatgpt, gemini, claude to md/pdf extension, can you please generate some example content that can test it? it should test heavily the ability of my extension to get tables, code blocks, latex formulaes mathe etc, images right, and include all other things you think it should get right i need you to so as extreme as possible since i need to test every scenario possible so include as much variety as you can generate (excluding videos, gif of course)

[Results from the web](#)

Here's a comprehensive stress-test document. Copy this whole message (or export it) — it deliberately packs in every Markdown/LaTeX/PDF-export edge case I could think of.

 Universal Markdown/PDF Export Stress Test

Testing tables, code, math, images, and formatting edge cases.

1. Basic Text Formatting

Plain text, **bold text**, *italic text*, ***bold italic***, ~~strikethrough~~, `inline code`, and a mix: **bold with `code` inside** and *italic with **nested bold***.

Here's a super/subscript test using HTML fallback: E = mc², H₂O.

A line with a footnote reference.¹

Escaped characters test: *not italic*, `not code`, # not a heading, 100% *notmath*.

2. Headings (All Levels)

H1 Heading

H2 Heading

H3 Heading

H4 Heading

H5 Heading

H6 Heading

3. Lists

Unordered

- Item one
- Item two
 - Nested item 2a
 - Nested item 2b
 - Deeply nested 2b-i
- Item three

Ordered

- 1. First step
- 2. Second step
 - 1. Sub-step A
 - 2. Sub-step B
- 3. Third step

Task List

- ☒ Completed task
- ☒ Another completed task
- ☐ Incomplete task
- ☐ Nested incomplete
 - ☒ Done subtask
 - ☐ Pending subtask

Definition-style List (via bold + colon)

Term A — Definition of term A.
Term B — Definition of term B.

4. Blockquotes

A simple blockquote.

A blockquote with **bold**, *italic*, and `inline code`.

A nested blockquote inside it.

Triple-nested blockquote.

Blockquote containing a code block:

python

```
print("quoted code")
```

5. Tables

Simple table

Name	Role	Location
Sankalp	App Support	India
Alice	Engineer	USA
Bob	Analyst	UK

Alignment test

Left	Center	Right
a	b	c
long text here	mid	123.45

Table with code and math inside cells

Concept	Formula	Code
Quadratic	$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$	<code>Math.sqrt(x)</code>
Sum	$\sum_{i=1}^n i$	<code>for (int i=0; i<n; i++)</code>

Large table (stress test row count)

#	Country	Capital	Population (M)	Currency
1	India	New Delhi	1428	INR
2	USA	Washington D.C.	335	USD
3	Denmark	Copenhagen	5.9	DKK
4	Japan	Tokyo	123	JPY
5	Germany	Berlin	84	EUR
6	Brazil	Brasília	216	BRL
7	Australia	Canberra	26	AUD
8	Canada	Ottawa	39	CAD

Table with pipe-escape edge case

Expression	Result
<code>a b</code> (bitwise OR)	escaped pipe test
<code>1 < 2 && 3 > 1</code>	HTML-sensitive chars

6. Code Blocks (Multiple Languages)

Java — DSA/Algorithm example (per your language preference for DSA)

java

```
import java.util.*;

public class BinarySearch {
    public static int search(int[] arr, int target) {
        int lo = 0, hi = arr.length - 1;
        while (lo <= hi) {
            int mid = lo + (hi - lo) / 2;
            if (arr[mid] == target) return mid;
            else if (arr[mid] < target) lo = mid + 1;
            else hi = mid - 1;
        }
        return -1; // not found
    }

    public static void main(String[] args) {
        int[] data = {1, 3, 5, 7, 9, 11, 13};
```

```
System.out.println(search(data, 7)); // expects 3
    }
}
```

Python — Data Science / ML example

python

```
import numpy as np
import pandas as pd
from sklearn.linear_model import LinearRegression

df = pd.DataFrame({"x": np.arange(10), "y": np.arange(10) * 2 + 1})
model = LinearRegression().fit(df[["x"]], df[["y"]])
print(f"slope={model.coef_[0]:.2f}, intercept={model.intercept_:.2f}")
```

JavaScript — Web dev example

javascript

```
const fetchData = async (url) => {
  try {
    const res = await fetch(url);
    if (!res.ok) throw new Error(`HTTP ${res.status}`);
    return await res.json();
  } catch (err) {
    console.error("Fetch failed:", err);
  }
};
```

SQL

sql

```
SELECT c.customer_name, SUM(o.amount) AS total_spent
FROM orders o
JOIN customers c ON c.id = o.customer_id
WHERE o.order_date >= '2026-01-01'
GROUP BY c.customer_name
HAVING SUM(o.amount) > 1000
ORDER BY total_spent DESC;
```

Bash / Shell

bash

```
#!/bin/bash
for file in *.log; do
  echo "Processing $file..."
  grep -c "ERROR" "$file" >> error_counts.txt
done
```

JSON

json

```
{
  "name": "test-config",
```

```
"version": "1.0.0",
"flags": {
  "debug": true,
  "retries": 3
},
"tags": ["export", "markdown", "pdf"]
}
```

YAML

yaml

```
service:
  name: cbk-platform
  port: 8080
  env:
    - KEY=value
    - DEBUG=false
```

XML (SOAP-style, relevant to your work domain)

xml

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <ChargebackRequest>
      <TransactionId>TXN123456</TransactionId>
      <Reason>10.4</Reason>
    </ChargebackRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

Plain text / no-language block

This is a plain fenced block with no syntax highlighting.

Indented line inside.

Tab separated values test

Inline code density test

Use `git status`, then `git add .`, then `git commit -m "msg"`, and finally `git push origin main` — a paragraph dense with inline code.

7. Math / LaTeX (Inline and Block)

Inline math: the identity $e^{i\pi} + 1 = 0$ is Euler's identity, and $a^2 + b^2 = c^2$ is Pythagoras.

Block equations

$$\int_{-\infty}^{\infty} e^{-x^2} dx = \sqrt{\pi}$$
$$\frac{\partial f}{\partial x} = \lim_{h \rightarrow 0} \frac{f(x+h) - f(x)}{h}$$

Matrix

$$A = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

Summation & product

$$\sum_{n=1}^{\infty} \frac{1}{n^2} = \frac{\pi^2}{6} \qquad \prod_{k=1}^n k = n!$$

Piecewise function

$$f(x) = \begin{cases} x^2 & x \geq 0 \\ -x^2 & x < 0 \end{cases}$$

Aligned multi-line equations

$$\begin{aligned} (a + b)^2 &= a^2 + 2ab + b^2 \\ (a - b)^2 &= a^2 - 2ab + b^2 \end{aligned}$$

Greek letters & symbols stress test

$$\alpha, \beta, \gamma, \delta, \epsilon, \theta, \lambda, \mu, \pi, \sigma, \phi, \omega, \nabla, \partial, \infty, \pm, \leq, \geq, \neq, \approx, \in, \forall, \exists$$

8. Images

Standard markdown image syntax (public-domain test images):

Image with a link wrapped around it:

9. Links

- Plain link: <https://www.anthropic.com>
- Titled link: [Anthropic](#)
- Reference-style link: [Claude Docs](#)
- Email link: contact@example.com

10. Horizontal Rules

Three different syntaxes:

11. Embedded HTML (raw passthrough test)

Raw HTML block — tests whether the extension preserves or strips embedded HTML. </div> <details> <summary>Click to expand (collapsible section)</summary>

Hidden content inside a <details> tag, including a nested list:

- point one
- point two

</details>

A line with a manual line break using two trailing spaces.
This should appear on a new line.

A line with an explicit
 tag break.
This should also be on a new line.

12. Emoji & Unicode Stress Test

🚀✅❌⚠️🏠💡🔥🎯 — emoji rendering.

Unicode: café, naïve, Zürich, , , हिन्दी परीक्षण, العربية, Ω≈π×√2.

13. Mermaid Diagram (advanced test — many renderers support this)

14. Combined Complexity Block

A paragraph mixing **bold**, *italic*, `code`, a formula $O(n \log n)$, and a [link](#), followed by a table referencing the formula above, followed by a code block implementing it:

Algorithm	Time Complexity	Space
Merge Sort	$O(n \log n)$	$O(n)$
Quick Sort	$O(n \log n)$ avg	$O(\log n)$
Bubble Sort	$O(n^2)$	$O(1)$

java

```
public class MergeSort {
    static void sort(int[] arr, int l, int r) {
        if (l >= r) return;
        int m = (l + r) / 2;
        sort(arr, l, m);
        sort(arr, m + 1, r);
        merge(arr, l, m, r);
    }
    static void merge(int[] arr, int l, int m, int r) {
        int[] temp = new int[r - l + 1];
        int i = l, j = m + 1, k = 0;
        while (i <= m && j <= r) temp[k++] = arr[i] <= arr[j] ? arr[i++] : arr[j++];
        while (i <= m) temp[k++] = arr[i++];
        while (j <= r) temp[k++] = arr[j++];
        System.arraycopy(temp, 0, arr, l, temp.length);
    }
}
```

End of test document

This covers: text styles, all heading levels, nested/task/definition lists, nested blockquotes with embedded code, simple/aligned/large/escaped-pipe tables, 8 code languages (Java for DSA per your preference, Python/JS/SQL/Bash/JSON/YAML/XML/plain), inline+block LaTeX (integrals, matrices, piecewise, aligned, Greek symbols), real embedded images (plain + linked), 4 link styles, 3 horizontal-rule syntaxes, raw HTML + collapsible details, manual line breaks, emoji/Unicode, a Mermaid diagram, and a mixed-complexity combo block.

Want me to also generate a version with **broken/malformed syntax on purpose** (unclosed code fences, malformed tables, bad LaTeX) to test your extension's error handling?

1. This is the footnote content, testing footnote rendering. [↩](#)

User Prompt

show me images 1 ater another from various sources show me all the variations of underroot, underroot within underroot, all the most complex variations of underroot available show me all types of tables you can generate, simple, complex all tables show me all matrices simple and complex, all big bracket functions, all mathematical symbols show me code blocks of various languages

LLM Response

[Results from the web](#)

Here's the next wave — heavy on images, nested radicals, table variety, matrix/bracket/symbol coverage, and a polyglot code dump.

1. Images from Various Sources (back-to-back)

2. Square Roots / Nested Radicals — Full Complexity Ladder

Level 1 — Simple

$$\sqrt{2}$$

Level 2 — With expression inside

$$\sqrt{a^2 + b^2}$$

Level 3 — Cube root / nth root

$$\sqrt[3]{27} = 3 \qquad \sqrt[n]{x^n} = x$$

Level 4 — Root of a fraction

$$\sqrt{\frac{a+b}{c-d}}$$

Level 5 — Nested radical (root within root)

$$\sqrt{2 + \sqrt{2}}$$

Level 6 — Triple-nested radical

$$\sqrt{2 + \sqrt{2 + \sqrt{2}}}$$

Level 7 — Quadruple-nested radical

$$\sqrt{2 + \sqrt{2 + \sqrt{2 + \sqrt{2}}}}$$

Level 8 — Nested radical with mixed roots (2nd inside 3rd)

$$\sqrt[3]{1 + \sqrt{1 + \sqrt[3]{1 + \sqrt{1 + \dots}}}}$$

Level 9 — Denesting radical identity

$$\sqrt{a + \sqrt{b}} = \sqrt{\frac{a + \sqrt{a^2 - b}}{2}} + \sqrt{\frac{a - \sqrt{a^2 - b}}{2}}$$

Level 10 — Ramanujan's famous infinite nested radical

$$3 = \sqrt{1 + 2\sqrt{1 + 3\sqrt{1 + 4\sqrt{1 + 5\sqrt{1 + \dots}}}}}$$

Level 11 — Golden ratio infinite nested radical

$$\varphi = \sqrt{1 + \sqrt{1 + \sqrt{1 + \sqrt{1 + \dots}}}} = \frac{1 + \sqrt{5}}{2}$$

Level 12 — Nested radical inside a fraction inside another radical (max chaos)

$$\sqrt{\frac{1 + \sqrt{\frac{2 + \sqrt{3 + \sqrt{4}}}{5}}}{\sqrt{6 + \sqrt{7 - \sqrt{8}}}}}$$

3. Tables — All Variations

Simple 2-column

Key	Value
A	1
B	2

Header-heavy, no alignment marks

ID	Name	Email	Status
1	Sankalp	sankalp@example.com	Active
2	Test User	test@example.com	Inactive

All three alignments combined

Left-aligned	Center-aligned	Right-aligned
short	mid	9999.00
a much longer string here	x	1.5

Table with empty/sparse cells

Field	Q1	Q2	Q3	Q4
Revenue	100		150	
Cost		60		90

Table with multi-line-feel content (via `<br>`)

Feature	Description
Export	Converts chat to Markdown. Also supports PDF output.
Sync	Auto-saves on every message. Works offline too.

Table embedding math

Shape	Area Formula	Volume Formula
Sphere	$4\pi r^2$	$\frac{4}{3}\pi r^3$
Cylinder	$2\pi r(r+h)$	$\pi r^2 h$

Table embedding code

Language	Print Statement
Java	<code>System.out.println("hi");</code>
Python	<code>print("hi")</code>
JS	<code>console.log("hi")</code>

Wide table (many columns — stress test overflow handling)

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10
1	2	3	4	5	6	7	8	9	10
a	b	c	d	e	f	g	h	i	j

Nested-looking table (markdown has no true nesting, so simulate via inline table-like text)

Group	Sub-items
Fruits	Apple, Banana, Mango
Vegetables	Carrot, Potato, Onion

4. Matrices, Big Brackets, and Symbols

Simple 2×2 and 3×3

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix}$$

$$\begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Determinant notation

$$\det(A) = \begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$$

Augmented matrix (system of equations)

$$\left[\begin{array}{cc|c} 1 & 2 & 5 \\ 3 & 4 & 6 \end{array} \right]$$

Block matrix

$$M = \left[\begin{array}{c|c} A & B \\ \hline C & D \end{array} \right]$$

4×4 matrix

$$\begin{bmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \\ 13 & 14 & 15 & 16 \end{bmatrix}$$

Big brackets — all four types with `\left`/`\right` auto-sizing

$\left(\frac{a}{b}\right)$

$\left[\frac{a}{b}\right]$

$\left\{\frac{a}{b}\right\}$

$\left\langle\frac{a}{b}\right\rangle$

Piecewise function (curly brace)

$$f(x) = \begin{cases} 1 & x > 0 \\ 0 & x = 0 \\ -1 & x < 0 \end{cases}$$

Binomial coefficient (round brackets, stacked)

$$\binom{n}{k} = \frac{n!}{k!(n-k)!}$$

Norm and floor/ceiling brackets

$$\|v\| \qquad \lfloor x \rfloor \qquad \lceil x \rceil$$

All major math symbol families

Set theory: $\in, \notin, \subset, \subseteq, \supset, \cup, \cap, \emptyset, \backslash$

Logic: $\forall, \exists, \neg, \wedge, \vee, \implies, \iff, \therefore, \because$

Relations: $\leq, \geq, \neq, \approx, \equiv, \sim, \propto, \cong$

Calculus: $\int, \iint, \iiint, \oint, \partial, \nabla, \lim, \sum, \prod, \infty$

Arrows: $\rightarrow, \leftarrow, \leftrightarrow, \Rightarrow, \Leftarrow, \Leftrightarrow, \uparrow, \downarrow$

Greek (lower): $\alpha, \beta, \gamma, \delta, \epsilon, \zeta, \eta, \theta, \iota, \kappa, \lambda, \mu, \nu, \xi, \pi, \rho, \sigma, \tau, \phi, \chi, \psi, \omega$

Greek (upper): $\Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega$

5. Code Blocks — Polyglot Dump

java

```
// Java (DSA example)
class Fibonacci {
    static long fib(int n) {
        if (n <= 1) return n;
        long[] dp = new long[n + 1];
        dp[1] = 1;
        for (int i = 2; i <= n; i++) dp[i] = dp[i-1] + dp[i-2];
        return dp[n];
    }
}
```

cpp

```
// C++
#include <iostream>
using namespace std;
int main() {
    int n = 10;
    cout << "Value: " << n << endl;
    return 0;
}
```

c

```
// C
#include <stdio.h>
int main() {
    printf("Hello, World!\n");
}
```

```
    return 0;
}
```

go

```
// Go
package main
import "fmt"
func main() {
    fmt.Println("Hello from Go")
}
```

rust

```
// Rust
fn main() {
    let v: Vec<i32> = (1..=5).collect();
    println!("{:?}", v);
}
```

typescript

```
// TypeScript
interface User {
    id: number;
    name: string;
}
const greet = (u: User): string => `Hello, ${u.name}`;
```

php

```
<?php
// PHP
$arr = ["a" => 1, "b" => 2];
foreach ($arr as $key => $val) {
    echo "$key => $val\n";
}
?>
```

ruby

```
# Ruby
def greet(name)
    "Hello, #{name}!"
end
puts greet("World")
```

swift

```
// Swift
let numbers = [1, 2, 3, 4, 5]
let doubled = numbers.map { $0 * 2 }
print(doubled)
```

kotlin

```
// Kotlin
fun main() {
```

```
val list = listOf(1, 2, 3)
println(list.sum())
}
```

r

```
# R
x <- c(1, 2, 3, 4, 5)
mean(x)
sd(x)
```

matlab

```
% MATLAB
A = [1 2; 3 4];
B = inv(A);
disp(B);
```

haskell

```
-- Haskell
factorial :: Integer -> Integer
factorial 0 = 1
factorial n = n * factorial (n - 1)
```

scala

```
// Scala
object Main extends App {
  val nums = List(1, 2, 3, 4)
  println(nums.map(_ * 2))
}
```

perl

```
# Perl
my @arr = (1, 2, 3);
foreach my $x (@arr) {
  print "$x\n";
}
```

dart

```
// Dart
void main() {
  var name = 'World';
  print('Hello, $name!');
}
```

That's images, radicals, tables, matrices/brackets/symbols, and 15 languages in one pass. Want me to follow up with a batch of **deliberately malformed** syntax (broken tables, unclosed LaTeX, bad code fences) to test error resilience?

