

Московский государственный технический университет им. Н.Э. Баумана
Факультет «Информатика и системы управления»
Кафедра «Автоматизированные системы обработки информации и управления»



Отчет
Рубежный контроль № 2
По курсу «Технологии машинного обучения»

ИСПОЛНИТЕЛЬ:

Группа ИУ5-65Б

Уристимбек Г.

" " _____ 2021 г.

ПРЕПОДАВАТЕЛЬ:

Гапанюк Ю.Е.

" " _____ 2021 г.

Москва 2021

РК2

ТМО

Вариант 20, ИУ5-65Б

Уристимбек Г.

Задание.

Для заданного набора данных (по Вашему варианту) постройте модели классификации или регрессии (в зависимости от конкретной задачи, рассматриваемой в наборе данных). Для построения моделей используйте методы линейная/логистическая регрессия и градиентный бустинг. Оцените качество моделей на основе подходящих метрик качества (не менее двух метрик). Какие метрики качества Вы использовали и почему? Какие выводы Вы можете сделать о качестве построенных моделей? Для построения моделей необходимо выполнить требуемую предобработку данных: заполнение пропусков, кодирование категориальных признаков, и т.д.

-

При решении задач можно выбирать любое подмножество признаков из приведенного набора данных.

- Для сокращения времени построения моделей можно использовать фрагмент набора данных (например, первые 200-500 строк).

Датасет: <https://www.kaggle.com/san-francisco/sf-restaurant-scores-lives-standard>

In [1]:

```
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt

from sklearn.linear_model import LinearRegression
from sklearn.linear_model import LogisticRegression
```

In [2]:

```
data = pd.read_csv("data/restaurant-scores-lives-standard.csv", sep=',')
data.dtypes
```

Out[2]:

business_id	int64
business_name	object
business_address	object
business_city	object
business_state	object
business_postal_code	object
business_latitude	float64
business_longitude	float64
business_location	object
business_phone_number	float64
inspection_id	object
inspection_date	object
inspection_score	float64
inspection_type	object
violation_id	object
violation_description	object
risk_category	object
Neighborhoods (old)	float64

```
Police Districts          float64
Supervisor Districts     float64
Fire Prevention Districts float64
Zip Codes                 float64
Analysis Neighborhoods float64dtype:
object
```

```
In [3]: data.isnull().sum()
```

```
Out[3]: business_id          0
business_name              0
business_address          0
business_city              0
business_state             0
business_postal_code      1018
business_latitude         19556
business_longitude        19556
business_location         19556
business_phone_number     36938
inspection_id             0
inspection_date            0
inspection_score          13610
inspection_type            0
violation_id              12870
violation_description      12870
risk_category              12870
Neighborhoods (old)       19594
Police Districts          19594
Supervisor Districts      19594
Fire Prevention Districts  19646
Zip Codes                 19576
Analysis Neighborhoods     19594
dtype: int64
```

```
In [4]: data.shape
```

```
Out[4]: (53973, 23)
```


```
In [5]: data.head()
```

```
Out[5]:
```

	business_id	business_name	business_address	business_city	business_state	business_postal
--	-------------	---------------	------------------	---------------	----------------	-----------------

0	101192	Cochinita #2	2 Marina Blvd Fort Mason	San Francisco	CA	
1	97975	BREADBELLY	1408 Clement St	San Francisco	CA	
2	92982	Great Gold Restaurant	3161 24th St.	San Francisco	CA	
3	101389	HOMAGE	214 CALIFORNIA ST	San Francisco	CA	
4	85986	Pronto Pizza	798 Eddy St	San Francisco	CA	

5 rows × 23 columns



```
In [6]:
```

```
data2 = data.copy().dropna(axis=0, how='any')
data2.drop_duplicates(keep=False, inplace=True)
```


```
In [7]: for col in data2.columns:
        unique_nums = data2[col].unique()
        if unique_nums.size < 10:
            print("{}: {}".format(col, unique_nums))
```

```
business_city: ['San Francisco']business_state:
['CA']
inspection_type: ['Routine - Unscheduled']
risk_category: ['Low Risk' 'High Risk' 'Moderate Risk']
```

business_city: ['San Francisco'], business_state: ['CA'], inspection_type: ['Routine - Unscheduled'] - имеют 1 уникальное значение. Можно убрать.

```
In [8]: fig, ax = plt.subplots(figsize=(15,7))
        sns.heatmap(data2.corr(method='pearson'), ax=ax, annot=True, fmt='.2f')
```

Out[8]: <AxesSubplot:>



```
In [9]: data2["risk_category"] = data2["risk_category"].astype('category')
        data2["risk_category_cat"] = data2["risk_category"].cat.codes

        data2.drop(["business_city", "business_state", "business_location", "business
                    "business_address", "violation_description", "risk_category", "Ne
                    "inspection_id", "violation_id", "inspection_date"
                    ],
                    axis=1, inplace=True)
```

```
In [10]: data2["business_postal_code"].unique()
```

```
Out[10]: array(['94107', '94131', '94112', '94121', '94110', '94109', '94115',
                '94111', '94118', '94103', '94134', '94117', '94114', '94123',
                '94124', '94104', '94122', '94108', '94133', '94132', '941102019',
                '94127', '94102', '92672', '94105', '94116', '94158'], dtype=object)
```

```
In [11]: data2["business_postal_code"] = data2["business_postal_code"].astype(int)
```

```
In [12]: data2["Police Districts"] = data2["Police Districts"].astype(int)
data2["inspection_score"] = data2["inspection_score"].astype(int)
data2["Supervisor Districts"] = data2["Supervisor Districts"].astype(int)
data2["Fire Prevention Districts"] = data2["Fire Prevention Districts"].astype(int)
data2["Zip Codes"] = data2["Zip Codes"].astype(int)
data2["Analysis Neighborhoods"] = data2["Analysis Neighborhoods"].astype(int)
```


```
In [13]: data2.isnull().sum()
```

```
Out[13]: business_id          0
business_postal_code        0
business_latitude           0
business_longitude          0
business_phone_number       0
inspection_score            0
Police Districts            0
Supervisor Districts        0
Fire Prevention Districts    0
Zip Codes                   0
Analysis Neighborhoods      0
risk_category_cat           0
dtype: int64
```

```
In [14]: data2.head()
```

```
Out[14]:
```

	business_id	business_postal_code	business_latitude	business_longitude	business_phone_n
11	4794	94107	37.778634	-122.393089	1.41556
372	2684	94131	37.746759	-122.426995	1.41552
464	3256	94112	37.709737	-122.450070	1.41553
484	3951	94121	37.779962	-122.485087	1.41553
496	4864	94110	37.759174	-122.419066	1.41558



```
In [15]: data2.dtypes
```

```
Out[15]: business_id          int64
business_postal_code        int64
business_latitude           float64
business_longitude          float64
business_phone_number       float64
inspection_score            int64
Police Districts            int64
Supervisor Districts        int64
Fire Prevention Districts    int64
Zip Codes                   int64
Analysis Neighborhoods      int64
risk_category_cat           int8
dtype: object
```


```
In [16]: target = "Supervisor Districts"
```

```
In [17]: # Масштабирование
from sklearn.preprocessing import StandardScaler

scaler = StandardScaler()
for col in data2.columns:
    if col != target:
        data2[col] = scaler.fit_transform(data2[[col]])
```

```
In [18]: fig, ax = plt.subplots(figsize=(15,7))
sns.heatmap(data2.corr(method='pearson'), ax=ax, annot=True, fmt='.2f')
```

Out[18]: <AxesSubplot:>



```
In [19]: from sklearn.model_selection import train_test_split

feature_cols = ["business_latitude", "business_longitude", "Zip Codes"]

X_train, X_test, y_train, y_test = train_test_split(
    data2[feature_cols],
    data2[target],
    test_size=0.3,
    random_state=1,
)
```

Линейная регрессия

```
In [20]: from sklearn.linear_model import LinearRegression

linreg = LinearRegression().fit(X_train, y_train)
```

```
In [21]: from sklearn.metrics import r2_score, mean_absolute_error

linreg_predict = linreg.predict(X_test)
r2_score(y_test, linreg_predict), \
    mean_absolute_error(y_test, linreg_predict)
```

```
Out[21]: (0.32634156097620515, 1.8639363772620643)
```

Градиентный бустинг

```
In [22]: from sklearn.ensemble import GradientBoostingRegressor

gboostreg = GradientBoostingRegressor(random_state=10).fit(X_train, y_train)
```

```
In [23]: gboostreg_predict = gboostreg.predict(X_test)
r2_score(y_test, gboostreg_predict), \
    mean_absolute_error(y_test, gboostreg_predict)
```

```
Out[23]: (0.9155392208894986, 0.4158270828303186)
```

Вывод

Как видно по тепловой карте, данные плохо коррелируют друг с другом. Поэтому для построения модели был выбран целевой признак

"Supervisor Districts", а в качестве

ключевых признаков - ["business_latitude", "business_longitude", "Zip Codes"]. Как видно по оценкам, модель линейной регрессии недообучается, а модель градиентного бустинга хорошо обучается. Вторая модель имеет высокую оценку r^2 (близкую к 1) и низкую абсолютную ошибку (<1 , что для целочисленного признака дает хороший результат).

```
In [ ]:
```