

Московский государственный технический университет им. Н.Э. Баумана  
Факультет «Информатика и системы управления»  
Кафедра «Автоматизированные системы обработки информации и управления»



**Отчет**  
**Лабораторная работа № 2**  
**По курсу «Технологии машинного обучения»**

**ИСПОЛНИТЕЛЬ:**

Группа ИУ5-65Б

Уристимбек Г.

" " \_\_\_\_\_ 2021 г.

**ПРЕПОДАВАТЕЛЬ:**

Гапанюк Ю.Е.

\_\_\_\_\_

" " \_\_\_\_\_ 2021 г.

Москва 2021

---

# Обработка пропусков в данных, кодирование категориальных признаков, масштабирование данных.

## Загрузка и первичный анализ данных

```
In [1]: import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
import sklearn.impute
import sklearn.preprocessing
%matplotlib inline
sns.set(style="ticks")
```

```
In [2]: data=pd.read_csv("Video_Games_Sales_as_at_22_Dec_2016.csv")
```

```
In [3]: from IPython.display import set_matplotlib_formats
set_matplotlib_formats("retina")
```

<ipython-input-3-be4156809ec5>:2: DeprecationWarning: `set\_matplotlib\_formats` is deprecated since IPython 7.23, directly use `matplotlib\_inline.backend\_inline.set\_matplotlib\_formats()`  
set\_matplotlib\_formats("retina")

```
In [4]: # Первые 5 строк датасета
data.head()
```

```
Out[4]:
```

	Name	Platform	Year_of_Release	Genre	Publisher	NA_Sales	EU_Sales	JP_Sales
0	Wii Sports	Wii	2006.0	Sports	Nintendo	41.36	28.96	3.77
1	Super Mario Bros.	NES	1985.0	Platform	Nintendo	29.08	3.58	6.81
2	Mario Kart Wii	Wii	2008.0	Racing	Nintendo	15.68	12.76	3.79
3	Wii Sports Resort	Wii	2009.0	Sports	Nintendo	15.61	10.93	3.28
4	Pokemon Red/Pokemon Blue	GB	1996.0	Role-Playing	Nintendo	11.27	8.89	10.22

```
In [5]: total_count = data.shape[0]
print('Всего строк: {}'.format(total_count))
```

Всего строк: 16719

```
In [6]: # ТИПЫ КОЛОНОК
data.dtypes
```

```
Out[6]: Name                object
Platform                object
Year_of_Release         float64
Genre                   object
Publisher               object
NA_Sales                float64
EU_Sales                float64
JP_Sales                float64
Other_Sales             float64
Global_Sales            float64
Critic_Score            float64
Critic_Count            float64
User_Score              object
User_Count              float64
Developer               object
Rating                  object
dtype: object
```

```
In [7]: # размер набора данных
data.shape
```

```
Out[7]: (16719, 16)
```

## Обработка пропусков в данных

```
In [8]: # проверим есть ли пропущенные значения
data.isnull().sum()
```

```
Out[8]: Name                2
Platform                0
Year_of_Release        269
Genre                   2
Publisher               54
NA_Sales                0
EU_Sales                0
JP_Sales                0
Other_Sales             0
Global_Sales            0
Critic_Score           8582
Critic_Count           8582
User_Score              6704
User_Count              9129
Developer               6623
Rating                  6769
dtype: int64
```

```
In [9]: # Удаление колонок, содержащих пустые значения
data_new_1 = data.dropna(axis=1, how='any')
(data.shape, data_new_1.shape)
```

```
Out[9]: ((16719, 16), (16719, 6))
```

```
In [10]: data_new_1.columns
```

```
Out[10]: Index(['Platform', 'NA_Sales', 'EU_Sales', 'JP_Sales', 'Other_Sales',
               'Global_Sales'],
              dtype='object')
```

```
In [11]: # Удаление строк, содержащих пустые значения
```

```
data_new_2 = data.dropna(axis=0, how='any')
(data.shape, data_new_2.shape)
```

Out[11]: ((16719, 16), (6825, 16))

```
In [12]: # Найдем пропуски в данных в процентном соотношении
for col in data.columns:
    pct_missing = np.mean(data[col].isnull())
    print('{} - {}'.format(col, round(pct_missing*100)))
```

```
Name - 0%
Platform - 0%
Year_of_Release - 2%
Genre - 0%
Publisher - 0%
NA_Sales - 0%
EU_Sales - 0%
JP_Sales - 0%
Other_Sales - 0%
Global_Sales - 0%
Critic_Score - 51%
Critic_Count - 51%
User_Score - 40%
User_Count - 55%
Developer - 40%
Rating - 40%
```

```
In [13]: data[data.columns].isnull()
```

```
Out[13]:
```


	Name	Platform	Year_of_Release	Genre	Publisher	NA_Sales	EU_Sales	JP_Sales	Other
0	False	False	False	False	False	False	False	False	
1	False	False	False	False	False	False	False	False	
2	False	False	False	False	False	False	False	False	
3	False	False	False	False	False	False	False	False	
4	False	False	False	False	False	False	False	False	
...	...	...	...	...	...	...	...	...	
16714	False	False	False	False	False	False	False	False	
16715	False	False	False	False	False	False	False	False	
16716	False	False	False	False	False	False	False	False	
16717	False	False	False	False	False	False	False	False	
16718	False	False	False	False	False	False	False	False	

16719 rows × 16 columns



```
In [14]: # Поработаем с заполнение пропусков в колонке "Year of release"
colors = ['#FF0F5', '#008B8B']
sns.heatmap(data[data.columns].isnull(), cmap=sns.color_palette(colors))
```

Out[14]: <AxesSubplot:>




```
In [15]: # Заполним пропуски в колонке нулями
sns.distplot(data['Year_of_Release'].fillna(0))
```

/home/zeus/anaconda3/envs/tml\_env/lib/python3.9/site-packages/seaborn/distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).

warnings.warn(msg, FutureWarning)

```
Out[15]: <AxesSubplot:xlabel='Year_of_Release', ylabel='Density'>
```




```
In [16]: # Получаем совершенно не то, что нам нужно
# С помощью класса SimpleImputer можно проводить импьютацию различными показ
# Применим заполнение средними значениями
mean=sklearn.impute.SimpleImputer(strategy="mean") # Среднее значение
mean_rate=mean.fit_transform(data[['Year_of_Release']])
sns.distplot(mean_rate)
```

/home/zeus/anaconda3/envs/tml\_env/lib/python3.9/site-packages/seaborn/distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).

```
el function for histograms).
warnings.warn(msg, FutureWarning)
```

Out[16]: <AxesSubplot:ylabel='Density'>




```
In [17]: med=sklearn.impute.SimpleImputer(strategy="median") # Половина элементов бол
med_rate=med.fit_transform(data[['Year_of_Release']])
sns.distplot(med_rate)
```

```
/home/zeus/anaconda3/envs/tml_env/lib/python3.9/site-packages/seaborn/distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).
```

```
warnings.warn(msg, FutureWarning)
```

Out[17]: <AxesSubplot:ylabel='Density'>




```
In [18]: freq=sklearn.impute.SimpleImputer(strategy="most_frequent")
freq_rate=freq.fit_transform(data[['Year_of_Release']])
sns.distplot(freq_rate)
```

```
/home/zeus/anaconda3/envs/tml_env/lib/python3.9/site-packages/seaborn/distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).
```

```
warnings.warn(msg, FutureWarning)
```

Out[18]: <AxesSubplot:ylabel='Density'>



```
In [19]: # Остановим выбор на средних значениях
data['Year_of_Release'] = mean_rate
```

### Обработка пропусков в категориальных данных

```
In [20]: # Выберем категориальные колонки с пропущенными значениями
# Цикл по колонкам датасета
cat_cols = []
for col in data.columns:
    # Количество пустых значений
    temp_null_count = data[data[col].isnull()].shape[0]
    dt = str(data[col].dtype)
    if temp_null_count > 0 and (dt == 'object'):
        cat_cols.append(col)
        temp_perc = round((temp_null_count / total_count) * 100.0, 2)
        print('Колонка {}. Тип данных {}. Количество пустых значений {}, {}%.'
```

Колонка Name. Тип данных object. Количество пустых значений 2, 0.01%.  
 Колонка Genre. Тип данных object. Количество пустых значений 2, 0.01%.  
 Колонка Publisher. Тип данных object. Количество пустых значений 54, 0.32%.  
 Колонка User\_Score. Тип данных object. Количество пустых значений 6704, 40.1%.  
 Колонка Developer. Тип данных object. Количество пустых значений 6623, 39.61%.  
 Колонка Rating. Тип данных object. Количество пустых значений 6769, 40.49%.

```
In [21]: cat_temp_data = data[['Genre']]
cat_temp_data.head()
```

```
Out[21]:
```

	Genre
0	Sports
1	Platform
2	Racing
3	Sports
4	Role-Playing

```
In [22]: cat_temp_data['Genre'].unique()
```

```
Out[22]: array(['Sports', 'Platform', 'Racing', 'Role-Playing', 'Puzzle', 'Misc',
```

```
    'Shooter', 'Simulation', 'Action', 'Fighting', 'Adventure', 'Strategy',
    nan], dtype=object)
```

```
In [23]: cat_temp_data[cat_temp_data['Genre'].isnull()]
```

```
Out[23]:
```

	Genre
659	NaN
14246	NaN

```
In [24]: # Импьютация наиболее частыми значениями
imp2 = sklearn.impute.SimpleImputer(missing_values=np.nan, strategy='most_fre
data_imp2 = imp2.fit_transform(cat_temp_data)
data_imp2
```

```
Out[24]: array(['Sports'],
               ['Platform'],
               ['Racing'],
               ...,
               ['Adventure'],
               ['Platform'],
               ['Simulation']], dtype=object)
```

```
In [25]: # Пустые значения отсутствуют
np.unique(data_imp2)
```

```
Out[25]: array(['Action', 'Adventure', 'Fighting', 'Misc', 'Platform', 'Puzzle',
               'Racing', 'Role-Playing', 'Shooter', 'Simulation', 'Sports',
               'Strategy'], dtype=object)
```

```
In [26]: # Импьютация константой
imp3 = sklearn.impute.SimpleImputer(missing_values=np.nan, strategy='constant
data_imp3 = imp3.fit_transform(cat_temp_data)
data_imp3
```

```
Out[26]: array(['Sports'],
               ['Platform'],
               ['Racing'],
               ...,
               ['Adventure'],
               ['Platform'],
               ['Simulation']], dtype=object)
```

```
In [27]: np.unique(data_imp3)
```

```
Out[27]: array(['Action', 'Adventure', 'Fighting', 'Misc', 'NA', 'Platform',
               'Puzzle', 'Racing', 'Role-Playing', 'Shooter', 'Simulation',
               'Sports', 'Strategy'], dtype=object)
```

```
In [28]: data_imp3[data_imp3=='NA'].size
```

```
Out[28]: 2
```

```
In [29]: data['Genre'] = data_imp2
```

```
In [30]: data['Genre'].unique()
```



```
Out[30]: array(['Sports', 'Platform', 'Racing', 'Role-Playing', 'Puzzle', 'Misc',
               'Shooter', 'Simulation', 'Action', 'Fighting', 'Adventure',
               'Strategy'], dtype=object)
```

## Кодирование категориальных признаков

```
In [31]: types=data["Genre"]
         types.value_counts()
```

```
Out[31]: Action      3372
         Sports      2348
         Misc        1750
         Role-Playing 1500
         Shooter     1323
         Adventure    1303
         Racing      1249
         Platform     888
         Simulation   874
         Fighting     849
         Strategy     683
         Puzzle       580
         Name: Genre, dtype: int64
```

### Кодирование категорий целочисленными значениями - label encoding

```
In [32]: le=sklearn.preprocessing.LabelEncoder()
         type_le=le.fit_transform(types)
         print(np.unique(type_le))
         le.inverse_transform(np.unique(type_le))
```

```
[ 0  1  2  3  4  5  6  7  8  9 10 11]
```

```
Out[32]: array(['Action', 'Adventure', 'Fighting', 'Misc', 'Platform', 'Puzzle',
               'Racing', 'Role-Playing', 'Shooter', 'Simulation', 'Sports',
               'Strategy'], dtype=object)
```

### Pandas get\_dummies - быстрый вариант one-hot кодирования

```
In [33]: type_s=pd.get_dummies(types)
         type_s.head(25)
```

```
Out[33]:
```

	Action	Adventure	Fighting	Misc	Platform	Puzzle	Racing	Role-Playing	Shooter	Simulation	S
0	0	0	0	0	0	0	0	0	0	0	
1	0	0	0	0	1	0	0	0	0	0	
2	0	0	0	0	0	0	1	0	0	0	
3	0	0	0	0	0	0	0	0	0	0	
4	0	0	0	0	0	0	0	1	0	0	
5	0	0	0	0	0	1	0	0	0	0	
6	0	0	0	0	1	0	0	0	0	0	
7	0	0	0	1	0	0	0	0	0	0	
8	0	0	0	0	1	0	0	0	0	0	
9	0	0	0	0	0	0	0	0	1	0	

	Action	Adventure	Fighting	Misc	Platform	Puzzle	Racing	Role-Playing	Shooter	Simulation	S
10	0	0	0	0	0	0	0	0	0	1	
11	0	0	0	0	0	0	1	0	0	0	
12	0	0	0	0	0	0	0	1	0	0	
13	0	0	0	0	0	0	0	0	0	0	
14	0	0	0	1	0	0	0	0	0	0	
15	0	0	0	0	0	0	0	0	0	0	
16	1	0	0	0	0	0	0	0	0	0	
17	1	0	0	0	0	0	0	0	0	0	
18	0	0	0	0	1	0	0	0	0	0	
19	0	0	0	1	0	0	0	0	0	0	
20	0	0	0	0	0	0	0	1	0	0	
21	0	0	0	0	1	0	0	0	0	0	
22	0	0	0	0	1	0	0	0	0	0	
23	1	0	0	0	0	0	0	0	0	0	
24	1	0	0	0	0	0	0	0	0	0	

Переходим к масштабированию данных.

Масштабирование предполагает изменение диапазона измерения величины, анормализация - изменение распределения этой величины.


Если признаки лежат в различных диапазонах, то необходимо их нормализовать. Как правило, применяют два следующих подхода:

## MinMax масштабирование


```
In [34]: from sklearn.preprocessing import MinMaxScaler, StandardScaler
```

```
In [35]: sc1 = MinMaxScaler()
sc1_data = sc1.fit_transform(data[['Year_of_Release']])
```

```
In [36]: plt.hist(data['Year_of_Release'], 80)
plt.show()
```



```
In [37]: plt.hist(sc1_data, 80)
plt.show()
```



## Масштабирование данных на основе Z-оценки - StandardScaler

```
In [38]: sc2 = StandardScaler()
sc2_data = sc2.fit_transform(data[['Year_of_Release']])
```

```
In [39]: plt.hist(sc2_data, 50)
plt.show()
```

