

KUMARI NEHA
SECTION - AI & DS
ROLL NO:- 27
UNIVERSITY ROLL-2017650

Tutorial - 1 (DAA)

Q1) Solution:- Asymptotic Notation: Asymptotic Notation are the mathematical notations used to describe the running time of an algorithm.

Different types of Asymptotic Notations:

1. Big-O Notation (O): It represents upper Bound of algorithm.
 $f(n) = O(g(n))$ if $f(n) \leq C * g(n)$.

2. Omega Notation (Ω): It represents lower bound of algorithm.
 $f(n) = \Omega(g(n))$ if $f(n) \geq C * g(n)$.

3. Theta Notation (Θ): It represents upper and lower bound of algorithm.

$$f(n) = \Theta(g(n)) \text{ if } C_1 g(n) \leq f(n) \leq C_2 g(n)$$

Q2) Solution:- for ($i=1$ to n)
 { $i = i * 2$
 }

$i=1$
 $i=2$
 $i=4$
 $i=8$
 $i=16$
 $i=n$

It is forming G.P

$$a_n = ar^{n-1}$$

$$n = ar^{k-1}$$

$$n = 1 \times (2)^{k-1}$$

$$\log n = \log 2^{k-1}$$

$$\log n = (k-1) \log 2$$

$$\boxed{k = \log n + 1}$$

$$O(\log n)$$

$$\begin{pmatrix} a_n = n \\ r = 2 \\ a = 1 \end{pmatrix}$$

Q3 Solution :- $T(n) = 3T(n-1)$ if $n > 0$, otherwise 1
 $T(1) = 3T(0)$ [$T(0) = 1$]
 $T(1) = 3 \times 1$
 $T(2) = 3T(1) = 3 \times 3 \times 1$
 $T(3) = 3 \times T(2) = 3 \times 3 \times 3$
 \vdots
 $T(n) = 3 \times 3 \times 3 \dots$
 $= 3^n = O(3^n)$

Q4 Solution :- $T(n) = 2T(n-1) - 1$ if $n > 0$, otherwise 1
 $T(0) = 1$
 $T(1) = 2T(0) - 1$
 $T(1) = 2 - 1 = 1$
 $T(2) = 2T(1) - 1$
 $T(2) = 2 - 1 = 1$
 $T(3) = 2T(2) - 1$
 $= 2 - 1 = 1$
 \vdots
 $T(n) = 1 \quad O(1)$

Q5 Solution:-

```

int i=1, s=1
while (s <= n)
{
    i++;
    s = s+i;
    printf("#");
}

```

$i=1$	$s=1$
$i=2$	$s=1+2$
$i=3$	$s=1+2+3$
$i=4$	$s=1+2+3+4$
\vdots	\vdots
Loop Ends	When $s > n$
	$1+2+3+4+\dots+k > n$
	$\frac{k(k+1)}{2} > n$
	$k^2 > n$
	$k > \sqrt{n}$
	$\therefore O(\sqrt{n})$

Q6 > Solution :- Void function (int n)
 { int i, Count = 0;
 for (int i = 1; i + 1 <= n; i++)
 Count++
 }

i = 1
 i = 2
 i = 3
 i = 4
 ⋮
 i = K

Loop Ends when $i * i > n$
 $K * K > n$
 $K^2 > n$
 $K > \sqrt{n}$
 $O(n) = \sqrt{n}$

Q7 > Solution :- Void function (int n)
 { int i, j, k, Count = 0;
 for (i = n/2; k = n; i++)
 for (j = 1; j <= n; j = j * 2)
 for (k = 1; k <= n; k = k * 2)
 Count++;
 }

1st loop: $i = n/2$ to n , $i++$
 $= O(n/2) = O(n)$

2nd ^{nested} loop: $j = 1$ to n , $j = j * 2$
 $j = 1$
 $j = 2$
 $j = 4$
 \vdots
 $j = n$
 $= O(\log n)$

3rd loop: $k = 1$ to n , $k = k * 2$
 $k = 1$
 $k = 2$
 $k = 4$
 $= O(\log n)$

Total Complexity = $O(n * \log n * \log n) = O(n \log^2 n)$

Q8 > Solution :- fun(int n)
 { if (n == 1) return; — 1
 for (int i = 1; i <= n; i++) — n^2
 Print("x");
 fun(n-3) — $T(n-3)$
 }

$$T(n) = T(n-3) + n^2 \quad \because T(1) = 1$$

$$\rightarrow T(4) = T(4-3) + 4^2 = T(1) + 16 = 1 + 16 = 17$$

$$\rightarrow T(7) = T(7-3) + 7^2 = 17 + 49 = 66$$

$$\rightarrow T(10) = T(10-3) + 10^2 = 66 + 100 = 166$$

$$\text{So, } T(n) = 1^2 + 4^2 + 7^2 + 10^2 + \dots + n^2 = \frac{n(n+1)(2n+1)}{6} = O(n^3)$$

also for terms like $T(2), T(3), T(5)$
 So, $T(n) = O(n^3)$

Q9) Solution:-

Void function (int n)

```
{
  for (int i=1 to n) — n
    for (j=1 ; j<=n ; i=j+1) — n
      Print ("* ") ;
}
```

$i=1 \rightarrow j=1 \text{ to } n$
 $i=2 \rightarrow j=1 \text{ to } n$
 $i=3 \rightarrow j=1 \text{ to } n$
 $i=4 \rightarrow j=1 \text{ to } n$

}
 So, for i upto n it will take
 n^2

$$\text{So, } T(n) = O(n^2)$$

Q10) Solution:- $f_1(n) = n^k$

$$f_2(n) = c^n$$

Asymptotic relationship between f_1 & f_2

$$k \geq 1, c > 1$$

is Big O i.e. $f_1(n) = O(f_2(n)) = O(c^n)$

$$\text{is } n^k \leq G * c^n$$

[n is some constant]