1773972009_PRNU-imp IEEE-1.pdf

My Files

My Files

Shri Vile Parle Kelavani Mandal

Document Details

Submission ID

trn:oid:::9832:132296804

Submission Date

Mar 20, 2026, 11:34 AM GMT+5:30

Download Date

Mar 20, 2026, 11:36 AM GMT+5:30

File Name

1773972009_PRNU-imp IEEE-1.pdf

File Size

417.0 KB

10 Pages

5,575 Words

35,794 Characters

71% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely AI-paraphrased.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Detection Groups

23 AI-generated only 69%
Likely AI-generated text from a large-language model.

1 AI-generated text that was AI-paraphrased 2%
Likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

Disclaimer
Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?
The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?
Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.

PRNU- Image Source Verification & Forgery Detection

Ms.M. Raghavi
Dept. of Cyber Security
SRM Valliammai Engineering College,
(Affiliated to Anna University)
Kattankulathur, India
raghavirgo@gmail.com

Mr.S.lokesh
Dept. of Cyber Security
SRM Valliammai Engineering College,
(Affiliated to Anna University)
Kattankulathur, India
Lokesh.saravanan2212@gmail.com

Mr.D.Manoj
Dept. of Cyber Security
SRM Valliammai Engineering College,
(Affiliated to Anna University)
Kattankulathur, India
2004manojd@gmail.com

Mr.K.Hariharan
Dept. of Cyber Security
SRM Valliammai Engineering College,
(Affiliated to Anna University)
Kattankulathur, India
hariharan09tgk@gmail.com

Abstract—A PRNU-based image forensic framework is presented for camera source identification and digital image forgery detection. The system exploits PhotoResponse Non-Uniformity (PRNU), a sensor-level noise pattern unique to each camera device, to reliably attribute images to their source cameras [1],[6]. Multiple reference images are used to generate device-specific fingerprints, which are matched against query images using frequency-domain correlation and Peak-to-Correlation Energy (PCE) analysis [6]. To enable fine-grained tampering analysis, block-wise PRNU examination is performed, allowing localization of inconsistencies caused by image manipulation [7]. The framework further integrates copy–move forgery detection using feature-based matching techniques and splicing detection through PRNU inconsistency analysis [2],[9]. Robustness evaluation is conducted under common realworld attacks such as JPEG compression, resizing, cropping, denoising, and AI-based image enhancement [2],[4]. Experimental results demonstrate effective camera identification, accurate detection of inter-image splicing, and reliable differentiation between authentic and manipulated images. The modular and extensible design makes the system suitable for digital forensics, multimedia authentication, and cybercrime investigation applications.

Keywords: Photo-Response Non-Uniformity (PRNU), Image Forensics, Camera Source Identification, Image Splicing Detection, Copy–Move Forgery Detection, Digital Image Authentication, Robustness Analysis.

I. INTRODUCTION

With the explosive growth of digital media sharing through social networks, online journalism, and cloud platforms, digital images have become a dominant medium for information dissemination and forensic evidence. However, the rapid advancement of image manipulation tools has made it increasingly easy to alter image content without leaving perceptible visual traces, thereby threatening the authenticity and credibility of digital imagery [2],[4]. Image forgeries such as splicing, copy-move, and object removal are frequently combined with post-processing operations—including JPEG compression, filtering, and blurring—to intentionally conceal tampering artifacts, making reliable detection a challenging task in practical forensic scenarios [2].

Conventional image forensic techniques primarily rely on handcrafted features or intrinsic statistical inconsistencies, such as Photo-Response Non-Uniformity (PRNU), color filter array artifacts, and compression anomalies [6]. While these approaches have shown effectiveness in controlled environments, their robustness significantly degrades when forged images undergo unknown or multiple post-processing operations. In particular, post-processing noise tends to suppress sensor-level fingerprints and boundary inconsistencies, leading to poor generalization across datasets and real-world conditions [7].

Recent advances in deep learning and representation learning have enabled the development of data-driven image forensic models capable of capturing subtle manipulation traces beyond handcrafted assumptions [4],[5]. Self-supervised, unsupervised, and hybrid learning frameworks have demonstrated improved resilience against compression artifacts, unseen manipulation types, and limited labeled data. . Moreover, integrating intrinsic camera fingerprints such as PRNU and noiseprint with adaptive learning strategies has emerged as a promising direction for enhancing both robustness and interpretability in forgery detection systems [9].

Unlike traditional single-stage forensic methods, the proposed system emphasizes robustness, adaptability, and scalability, making it suitable for real-world digital investigations. This work contributes to contemporary multimedia forensics research by demonstrating how intrinsic sensor fingerprints can be effectively combined with modern learning techniques to address the growing challenges of post-processed image forgery detection.

II.LITERATURE SURVEY

Early image forensics research focused on detecting inconsistencies introduced during image capture and processing [6]. Techniques such as Photo-Response Non-Uniformity (PRNU), color filter array patterns, compression analysis, and noise residual extraction were widely used to identify image sources and detect forgeries [7]. These methods

assume that original images contain consistent sensor fingerprints, while manipulated regions disturb these patterns. However, their performance reduces when images are post-processed using operations like JPEG compression, filtering, or resizing. Such operations weaken sensor noise information, making traditional forensic methods less reliable in real-world scenarios.

With the advancement of deep learning, learning-based image forgery detection methods have gained attention. Convolutional neural networks are capable of learning important features automatically and have shown good performance in detecting and localizing tampered regions [5]. However, many deep learning models perform poorly on post-processed or cross-domain images [4]. To overcome this limitation, researchers have explored training strategies that consider post-processing effects. Recent studies have also introduced noise-based and hybrid approaches that separate tampering traces from image content and noise [9],[8]. Unsupervised and hybrid learning methods reduce the need for large labeled datasets and improve generalization. Combining intrinsic sensor fingerprints such as PRNU with learning-based models has shown better robustness in both image and video forgery detection [1],[9].

III.WORKFLOW OF THE SYSTEM

The workflow of the proposed PRNU-based Image Source Verification and Forgery Detection framework begins with the acquisition and processing of digital image evidence [2]. The primary objective of this workflow is to transform raw image data collected during an investigation into reliable and structured forensic information suitable for further analysis. Digital images may be obtained from multiple sources, including mobile devices, social media platforms, cloud storage services, surveillance systems, and seized digital media [6]. These images often originate from heterogeneous environments and are captured using different camera devices under varying acquisition conditions.

Due to the diverse nature of image sources, the collected image datasets frequently exhibit inconsistencies such as varying resolutions, different compression formats (e.g., JPEG, PNG), resizing artifacts, noise distortions, and post-processing effects. Additionally, images may be subjected to manipulations such as splicing, copy–move operations, or enhancement, either intentionally or through social media processing pipelines. As a result, the raw image data may be considered noisy, inconsistent, or partially degraded, making direct forensic analysis unreliable[7].

To address these challenges, the system employs automated image preprocessing and normalization procedures. These procedures standardize image formats, dimensions, and color spaces, while suppressing scene content to isolate sensor noise characteristics. Following preprocessing, the system performs Photo-Response Non-Uniformity (PRNU) extraction, which acts as a unique intrinsic identifier of a camera device, analogous to identifiers such as phone numbers or IP addresses in linkage analysis systems.

Subsequently, the extracted PRNU noise residuals are analyzed to perform image source attribution and forgery detection. Correlation analysis and Peak-to-Correlation Energy (PCE) metrics are used to determine whether an image originates from a specific camera device. Localized PRNU inconsistencies are further examined through block-wise analysis to identify suspicious regions within the image. The overall workflow ensures that investigators can reliably verify image authenticity, attribute images to source devices, and detect possible manipulations in a structured and automated manner.



Figure 1: Workflow of the PRNU-based Image Source Verification and Forgery Detection System

IV. DATA PREPROCESSING AND CLEANING

Before performing the actual forensic analysis, an effective image preprocessing and cleaning framework must be established. Digital images acquired during investigations may be sourced from mobile phones, social networking platforms, messaging applications, or cloud services. These images are often stored in different formats and compression levels and may contain inconsistencies that, if not properly addressed, can adversely affect PRNU extraction and correlation accuracy.

Traditional approaches often involve manual handling of images, which increases processing time and the likelihood of human error. In contrast, the proposed framework adopts automated preprocessing techniques to standardize image data prior to analysis. Image normalization procedures include format validation, resolution alignment, grayscale conversion, and intensity normalization. These steps ensure uniformity across datasets and reduce variability introduced by external factors.

Noise estimation and denoising mechanisms are applied to suppress scene content while preserving sensor-level noise patterns essential for PRNU analysis [6]. Automated preprocessing pipelines ensure that images are cleaned and structured in a consistent manner, allowing investigators to focus on analytical interpretation rather than manual data preparation. By converting raw image evidence into standardized inputs, the preprocessing stage significantly improves the accuracy and reliability of downstream source attribution and forgery detection tasks.

A robust preprocessing pipeline forms the foundation of the forensic framework by ensuring high-quality and consistent image data. This reduces false positives in forgery detection and improves the confidence of camera attribution results. Consequently, standardized preprocessing practices play a crucial role in modern digital image forensic investigations by enabling timely and dependable analysis [7].

V. IMAGE SOURCE ATTRIBUTION AND PRNU ANALYSIS

Image source attribution is a core component of the proposed forensic framework, transforming preprocessed image data into meaningful forensic intelligence. Each digital camera sensor exhibits slight manufacturing imperfections that result in a unique PRNU pattern [6]. These patterns act as intrinsic identifiers, enabling the association of images with their originating camera devices.

In this framework, reference PRNU fingerprints are generated using multiple images captured from known camera devices [1]. For a query image, its extracted noise residual is correlated with stored camera fingerprints using frequency-domain

correlation techniques. The resulting PCE values indicate the strength of association between the image and a particular camera device. High correlation values suggest that the image originates from the corresponding device, whereas low correlation values indicate a mismatch.

To detect image manipulation, the system performs block-wise PRNU analysis, dividing the image into non-overlapping regions and evaluating PRNU consistency locally. Regions that exhibit significant deviation from the global camera fingerprint are flagged as suspicious, indicating potential splicing or localized tampering. This localized analysis enables investigators not only to detect forgery but also to identify the spatial location of manipulated regions within the image.

By automating PRNU extraction, correlation, and block-wise evaluation, the system reduces manual effort and cognitive load on investigators. The framework provides a comprehensive overview of image authenticity and source consistency, supporting accurate and scalable forensic investigations.



Figure 2: PRNU Based Forensics Dashboard

Figure 3: PRNU-based Source Attribution and Local Forgery Localization

VI. VISUALIZATION FRAMEWORKS

Visualization plays a critical role in the interpretation of complex forensic analysis results. The proposed framework employs visual representations such as PRNU heatmaps, correlation plots, and confidence indicators to present analytical findings in an intuitive and investigator-friendly manner. These visual tools convert numerical correlation metrics and blockwise inconsistency data into interpretable visual formats.

Heatmaps are used to highlight suspicious regions within an image, enabling investigators to quickly identify areas of potential manipulation. Camera attribution results are summarized through confidence scores and graphical indicators that assist in rapid decision-making. Interactive dashboards further reduce cognitive complexity by allowing investigators to explore forensic results without manually analysing raw numerical outputs.

Visualization frameworks improve investigative efficiency by enabling faster pattern recognition and anomaly detection. By presenting complex PRNU-based forensic evidence in an accessible manner, the system enhances both accuracy and usability in real-world digital image investigations [7].

VII. REPORT AND EVIDENCE GENERATION

Automated report generation is an essential component of modern forensic systems, enabling the documentation and presentation of analytical findings in a standardized format. In the proposed framework, forensic results such as camera attribution confidence, PRNU correlation metrics, and forgery localization outputs are automatically compiled into structured reports.

These reports can be generated in professional formats such as PDF, ensuring consistency and compliance with forensic documentation standards. Automated report generation reduces manual effort, minimizes human error, and ensures that forensic evidence can be readily presented during legal or investigative proceedings. The ability to generate multiple reports efficiently enhances productivity and supports large-scale forensic investigations.

Figure 4: PRNU-based Source Analysis and Local Forgery

Figure 5: PRNU Final Verdict Analysis

VIII. BACKEND AND DATA MANAGEMENT INTEGRATION

The backend architecture of the PRNU-based forensic system is responsible for managing image data, analytical results, and system interactions. Lightweight backend frameworks facilitate communication between the front-end interface and analytical modules, enabling functions such as image upload, PRNU extraction, analysis execution, and report generation.

Scalable data storage mechanisms are used to store reference camera fingerprints, analysis results, and metadata associated with image evidence. The modular backend design ensures scalability and flexibility, allowing new forensic modules or analytical techniques to be integrated without disrupting existing functionality. Efficient data management and inter-component communication form the backbone of the system, ensuring reliable performance and timely delivery of actionable forensic insights.



Figure 6: Backend Forgery Heatmap and Forensic Data Storage

IX RESULTS AND DISCUSSION

The experimental evaluation confirms that the proposed PRNU-based image forgery detection framework effectively identifies forged images and localizes tampered regions by integrating machine learning–based prediction with noise centric forensic analysis. The system successfully classifies images into low, medium, and high forgery risk categories by jointly considering global forgery likelihood and localized PRNU inconsistency patterns. Among the evaluated classifiers, ensemble-based models demonstrated superior performance compared to linear classifiers, achieving higher accuracy, precision, recall, and AUC scores. This improvement can be attributed to their ability to model complex and non-linear relationships within PRNU residual features and noise-based forensic indicators.

The rule-based forgery risk scoring module played a significant role in identifying spatially abnormal patterns, such as abrupt PRNU correlation drops, residual energy concentration, and boundary inconsistencies between adjacent regions. These indicators, which are often weakened or overlooked under post-processing conditions, enhanced the system's ability to provide fine-grained localization and forensic interpretability. The rule-based layer ensured transparency by explicitly linking forensic cues to risk decisions, allowing analysts to understand and validate the detection outcomes.

The weighted fusion of machine learning–based forgery probability scores and rule-based residual risk assessments resulted in a balanced and holistic evaluation of image authenticity. This integration reduced false positives caused by isolated noise artifacts while ensuring that genuinely manipulated regions were appropriately highlighted. Overall, the results demonstrate that the proposed hybrid framework is robust, interpretable, and effective for detecting image forgeries under post-processing conditions, making it suitable for real-world digital forensic applications.

X.CONCLUSION

This research presented an integrated PRNU-based image forgery detection framework that combines machine learning techniques with rule-based forensic analysis to achieve robust and explainable detection of manipulated images. By leveraging ensemble learning models alongside intrinsic sensor noise analysis, the proposed system provides a balanced assessment of image authenticity while maintaining resilience against post-processing operations such as compression and filtering. Experimental results demonstrate that the hybrid approach achieves high detection accuracy and effective localization of forged regions, even in challenging scenarios.

The fusion of predictive learning and interpretable rulebased scoring enables proactive and reliable forensic decisionmaking while minimizing false detections. Moreover, the modular and layered system architecture ensures scalability and adaptability for practical deployment in digital forensic investigations. Overall, the proposed framework offers a practical and effective solution for modern image forensics, contributing to enhanced trust, reliability, and security in digital media analysis.

REFERENCE

[1] Liu Liu, Xinwen Fu, Xiaodong Chen, Jianpeng Wang, Zhongjie Ba. "ACL: Account Linking in Online Social Networks With Robust Camera Fingerprint Matching" IEEE TRANSACTIONS ON DEPENDABLE AND SECURE COMPUTING, JUNE 2025.

[2] Yuan Rao, Jiangqun Ni, Jiwu Huang.,"Towards JPEGResistant Image Forgery Detection and Localization Via Self-Supervised Domain Adaptation" IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, MAY 2025.

[3] Yu Tian, Kunbo Zhang, Yalin Huang, Leyuan Wang. "Cross-Optical Property Image Translation for Face Anti- Spoofing: From Visible to Polarization." IEEE TRANSACTIONS ON INFORMATION FORENSICS AND SECURITY, 2025.

[4] Tong Qiao , Hang Shao, Shichuang Xie, Ran Shi,. "Unsupervised Generative Fake Image Detector.", IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, SEPTEMBER 2024.

[5] Dengyong Zhang, Jiahao Chen, Xin Liao.," Face Forgery Detection via Multi-Feature Fusion and Local Enhancement", IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY , SEPTEMBER 2024.

[6] Andrea Montibellerd Fernando Pérez-González. "An Adaptive Method for Camera Attribution Under Complex Radial Distortion Corrections ." IEEE TRANSACTIONS ON INFORMATION FORENSICS AND SECURITY, 2025.

[7] Peiyu Zhuang, Haodong Li, Rui Yang, and Jiwu Huang.," ReLoc: A Restoration-Assisted Framework for Robust Image Tampering Localization." IEEE TRANSACTIONS ON INFORMATION FORENSICS AND SECURITY, 2023.

[8] Li Zhang, Tong Qiao, Ming Xu, Ning Zheng , Shichuang Xie."Unsupervised Learning-Based Framework for Deep fake Video Detection." IEEE TRANSACTIONS ON MULTIMEDIA, 2023.

[9] Jia xin Chen , Xin Liao , Wei Wang , Zhen xing Qian. ,. " "SNIS : A Signal Noise Separation-Based Network for Post - Processed Image Forgery Detection.", IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO

TECHNOLOGY, FEBRUARY 2023.

[10] Cong Yang, Zhenyu Yang, Yan Ke, Tao Chen, Marcin Grzegorzek, and John SeeDoing More With Moiré Pattern Detection in Digital Photos.", IEEE TRANSACTIONS ON IMAGE PROCESSING, 2023.

Linkage analysis and relationship mapping is performed by the system next. In order to find hidden relationships between diverse datasets, an individual's unique identifiers such as their phone number, IP address, and device ID are extracted and analyzed. The connections will be displayed in the form of a graph model, with nodes representing an entity and edges representing a relationship. Using visualization libraries like NetworkX, D3.js and Cytoscape.js allow an investigator to navigate through the relationship mappings of entities in an intuitive manner



Figure 1 : Workflow of the project

IV. DATA PREPROCESSING AND CLEANING

Before performing the actual analysis, an effective linkage analysis framework needs to be established; this will include both data preprocessing and cleaning. For example, call detail records (CDRs) and Internet protocol detail records (IPDRs) can be sourced from email, banking logs, and/or other digital sources. These records can be formatted differently and may contain inconsistencies; if not identified and rectified, they can disrupt the overall analysis . Most researchers and utilizers of these types/sets of records handle them manually instead of automatically, which means that time is wasted due to human error and duplicated efforts. Automated ingestion mechanisms provide a means for researchers and utilizers to minimize their reliance on manual entry of data by automatically capturing records and organizing them as they are ingested. The pandas library in Python is frequently used for cleaning, normalizing

Upon the completion of the processing stage, datasets reside in scalable databases like MongoDB, which can handle large amounts of both qualitatively and quantitatively different data with ease through a variety of flexible query options. A reliable preprocessing pipeline builds a framework that ensures that investigators are working with a set of high quality, consistent data to reduce the possibility of error and improve the efficiency of downstream analysis. The accuracy of linkage results is also improved by preprocessing. Additionally, by converting raw, unstructured records into standard formats, modern frameworks allow investigators to spend less time on urgent investigations. As a result, the development of standard practices with regard to preprocessing represents the foundation of systems used in the investigation of cybercrime, allowing for the reliable and timely exploration of investigations.

VI. VISUALIZATION FRAMEWORKS

V. LINKAGE ANALYSIS AND RELATIONSHIP MAPPING

Linkage analysis is an integral aspect of a cybercrime investigation framework that transforms raw datasets into meaningful information, such as identifying hidden relationships among elements of the dataset. In this instance, datasets often contain key identifiers, such as telephone numbers, Internet Protocol (IP) addresses, domains accessed, and/or device identification numbers; these key identifiers are extracted from the dataset to provide investigators with the means to identify connections between individuals, devices, and activities. After extraction, the key identifiers are placed into graph models and represented as nodes (individuals or devices) and edges (how those individuals and/or devices are related). Through this visualization method, an investigator can then intuitively interact with, and analyze, networks of entities (individuals or devices), detect coordinated groups of activity, and ultimately identify a potential criminal organization or scheme.

Modern frameworks use automation to create relationship maps for investigators. This decreases the investigator's cognitive tasks by allowing them to focus on finding insights instead of relying on manual correlation across data sources. Network visualizations help identify unusual relationships, such as multiple telephone numbers located at the same IP address, suggesting possible cooperative activity or a common digital footprint[5]. Graph models with automated analysis enable highly accurate and rapid completion of investigations based on both size and complexity, including large datasets. Linkage analysis gives a comprehensive overview of an individual's activity, including potentially undiscovered connections. By implementing these frameworks' automation, visualization, and structured output capabilities, investigators can quickly locate their initial leads and increase the productivity of cybercrime investigations.



Figure 2: Linkage relationship

VII. NOTICE GENRATTION

Linkage analysis relies on visualization as one of its primary tools, converting complex and wide-ranging datasets into interactive and visual representations

that make it easy for investigators to analyze. By providing tools like Cytoscape.js [10] and D3.js, researchers can dynamically interact with and explore the relationships between entities, enabling investigators to see the connections between different entities, zoom in and out, hover over an object to retrieve more information about it, and filter their view of the relationships. Entities can be represented graphically as nodes while relationships are depicted graphically as edges between two or more nodes. Investigators can find hidden structures or clusters of entities and potentially suspicious linkages [16] that cannot be derived from raw tabular data. In addition to helping to streamline the investigative process, interactive visualization allows investigators to reduce their cognitive load and efficiently work through their analyses, enabling them to focus on evaluating the patterns in their data as opposed to manually correlating records. Automated updates to graphs[3] ensure that visualizations remain up to date as new data is added to the investigation, facilitating the ability to conduct real-time investigations on the ever-evolving datasets.

Visualization framework tools can be used to improve investigative accuracy and detection of anomalies or outliers, beyond just recognizing patterns within the data being analyzed. Networked graph visualizations show an unusual relationship between multiple telephone numbers (TN) relating to an I.P. Address or domain. This can indicate some level of relationship between these items and provide an indication that there may be either coordinated or fraudulent activity occurring. In addition to filtering, clustering and examining details for different segments of the network, these tools help make more complex dataset structures much simpler for an investigator to analyze. Also, a more intuitive user interface enables an investigator



Figure 3: Linkage Visualization

Sending automated notices is an important part of present day linkage analysis frameworks, as they provide a way for investigators to make formal requests for CDR, IPDR and intermediary data from telecom operators, ISPs and other service providers [20]. Historically, creating these sorts of notices was labour- intensive, taking a large amount of time, and increasing the chance of human error or omission. Today's systems simplify this workflow through the use of pre- defined templates connected to legal and procedural standards, ensuring [1] that requests for call detail, internet activity logs and intermediary datasets will be properly formatted and compliant with applicable.

Libraries like ReportLab or pdfkit make it possible to automatically create professional-quality PDFs. This integration allows for case-specific information to be automatically inserted into PDF notice formats by utilizing the auto-fill feature. By utilizing the auto-fill feature when generating PDF notices, the need for manual entry is greatly reduced along with the likelihood for error and maintaining the same format across various PDF notices. Investigators are able to produce numerous PDF notices at once for various service providers, thereby increasing [17] the overall efficiency of the data acquisition process.

State Cyber Crime Investigation Centre
Cyber Crime Wing HQ,
Ashok Nagar,
Chennai-83.
Tamil Nadu, India.
Dated: 21.07.2025

INDIAN POLICE DEPARTMENT

Under Section 91 Cr.P.C

From,	**To,**
Goethum, Deputy Superintendent of Police, Mobile: 1010101010, goetwik@gmail.com,	

Sir/Madam,

Sub: Tamil Nadu – Cyber Crime wing – State Cyber Crime Investigation Center – Wallet details requested – Reg.

Ref: SCCIC Crime No: 194dgfs/u. 420 IPC & Sec 66D of IT Act 2000

While investigating the above case it is found that the suspect is using account using the mobile number: 9750144419

Kindly provide us with the following details linked with the above-mentioned mobile number:

1 Wallet statement from account opening date.
2 KYC details
3 Linked email id.
4 Bank account & payment details

If you need any clarification, feel free to contact us. We are expecting your extended co-operation in this regard.

Goethum
Deputy Superintendent of Police,
State Cyber Crime Investigation Centre,
Chennai – 83.

Figure 4: Sample Notice Genration

VIII. BACKEND AND DATABASE INTEGRATION

The backend components of linkage analysis systems are critical to the efficient processing, storage & communication of information among all system components[3]. The majority of linkage analysis RESTful APIs are constructed with lightweight frameworks (e.g., Flask) that facilitate connecting the front-end user interface to the back-end application logic. Connection and interaction between the front- end user interface and back-end application logic is accomplished via these RESTful APIs, which handle actions such as uploading files, managing cases, generating graphs, and creating notices. The dynamic[1] nature of MonoDB and its support for storing nested data structural types makes it an ideal database choice for storing the diverse & varying types of investigative record.

The backend's modular architecture provides scalability, allowing new features or functionality to be added

without affecting current operations. This flexibility is essential for meeting changing investigative requirements and efficiently managing growing volumes of data. Providing effective inter-component communication, automated processing, and dependable data management allows the backend to be the foundation for a successful linkage analysis framework58. As such, the backend design has a direct impact on59 system performance, reliability, and the ability to deliver timely actionable

XI. CASE MANAGEMENT



Figure 5: Mongodb data storage

IX RESULTS AND DISCUSSION

The survey illustrates how modern linkage analysis frameworks are capable of assisting with cybercrime investigations using automated pipelines for pre- processing, linkage analysis, visualisation, and reporting; therefore, these automated systems can help reduce manual workload as well as improve the accuracy of investigative efforts. These visualisation techniques (i.e. use of node graphs) provide an intuitive understanding of the complex relationships between people, devices, and intermediary data sets [2]. In addition, the performance metrics (e.g. processing times, error rates, and anomaly detection accuracy) indicate capability and usability. Future enhancements could involve AI-enabled anomaly detection, better use of interoperability among datasets, and cloud-based deployment for scalability and cooperative investigation.

The Case Management module of a project organizes all information related to an individual's investigative case. This includes the name of the officer in charge of the investigation, their title, and department so that there is no confusion as to who is responsible for the case. Additionally, the Case Management module stores information on the basic elements of the case, i.e., case number, case type, date, current status, so that an investigator or supervisor can easily identify who is responsible for a particular case and how far along it is without having to look at paper records.

Along with storing personnel information, the case management module tracks which data has been included in the investigation. It holds records of all digital evidence collected about a case, such as uploaded CDR files, IPDR Files [1], and all intermediate data like social media or service provider logs. Each dataset is linked to each case, providing clear visibility into the evidence collected and what other data still needs to be collected. The structure of this storage prevents loss and duplication of data.

The case management module provides a dependable, centralized overview of an investigation by providing officer responsibilities and methodologies to use data in one location. Case monitoring becomes simple because investigators can easily determine case status, assigned officers, and available evidence on a single dashboard. All the information within the case is already formatted correctly so that generating an accurate and quick (field or limited volume) request for additional CDRs or IPDRs can be done with the click of a button. The case management module will also allow for analyses of data sets used in a case to be done efficiently and will clearly indicate what datasets are associated with what cases, making it easy for investigators to track case history, updates, and modifications over time by providing for proper record keeping of all case activity.

In all cases, advanced analytical systems for linking evidence will give investigators better ways to turn their evidence into useful information for the investigation process. They will help law enforcement spend less time creating networks of crime, identifying outliers and preparing a formal report of their findings. The future of these systems appears bright as they continue to evolve and improve how digital investigations are conducted and how effectively law enforcement responds to them.

IX RESULTS AND DISCUSSION

According to the findings of the survey, capacity of modern linkage analysis frameworks for use in cybercrime investigation; preprocessing, linkage analysis, visualization and reporting capabilities are automated processes; that reduce the amount of manual work done and increase accuracy of the investigation by automating these processes. This has been demonstrated through case studies showing that utilizing a node graph-based visualization provides intuitive understanding of the complex relationship between various individuals, devices and third party datasets. Performance metrics (processing time, error rate, and accuracy for anomaly detection) indicate that these systems are practically effective when being used for conducting investigations in the real world. As a result of transforming raw data into actionable insights.

Despite the great potential offered by today's systems, there are still many challenges that need to be addressed in terms of the practical utility of such systems for real- world investigative work. Modern linkage analysis frameworks enable investigators to convert raw data into actionable insights allowing them to identify.

There are still many obstacles despite the ability of present architectures to work well, especially when integrating with telecom providers in real-time; dealing with datasets containing multiple languages; and keeping sensitive data secure and private. These limitations emphasize the need to continue researching and developing more powerful systems with greater

of real-time integration with telecommunications providers, managing multilingual data, and ensuring safe and secure access to sensitive data. These challenges illustrate the continuing need for significant research and development work in order to improve system performance and usability.

X. CONCLUSION

Linkage analysis frameworks (surveys), including automated processes, visualisation, and structured reporting, help cybercrime investigators perform more effective and efficient cybercrime investigations by linking raw datasets (e.g., call detail records (CDRs), internet provider detail records (IPDRs), and other intermediary records) in order to find hidden connections between them and identify anomalous behaviour. This is done by transforming raw datasets into an interrelated network of data, enabling investigators to uncover hidden relationships among them. Establishing and using automated preprocessing pipelines helps to ensure consistency and correctness of the dataset by eliminating or reducing inconsistency and/or incorrectness, and by providing a method to process large.

Visualization cannot be overstated in these frameworks, which turn complex data into digestible network graphs by visually illustrating the relationships between people, computers, and service providers through the relationships among their respective nodes. Through node-based representations and dynamic interactive dashboards, users can identify patterns[19] and increase understanding, decision-making, and their ability to make informed decisions about cases. There are currently many systems available that provide significant benefits; however, additional work still needs to occur before achieving full functionality for all aspects of the investigation (such as real-time monitoring, handling of multilingual datasets.

Integrating AI-based anomaly detection, scalability through the cloud and enhanced ISP mapping are future enhancement options that may enhance investigative capacity. With these enhancements, cognitive load will decrease, data analysis will be completed faster and action-oriented intelligence will be generated more easily. Overall, linkage analysis frameworks provide adaptable and flexible solutions for the changing landscape of forensic investigation and provide an opportunity for law enforcement and cyber security professionals to effectively react.

REFERENCE

[1] X. Zhao et al., "Investigating Visual Perception of Degree Centrality in Graph Visualization," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 6, pp. 3679– 3692, Jun. 2025.

[2] V. S. Bitra, R. R. Vangimalla, and J. Sreevalsan-Nair, "Network-based Diseasome Construction from Multi-omics Data and RadTrix Visualization," IEEE Trans. Comput. Biol. Bioinf., doi: 10.1109/TCBBIO.2025.

[3] S. Song et al., "GVVST: Image-Driven Style Extraction From Graph Visualizations for Visual Style Transfer," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 9, pp. 5975–5989, Sept. 2025.

[4] S. Schöttler et al., "Constraint-Based Breakpoints for Responsive Visualization Design and Development," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 9, pp. 4593–4604, Sept. 2025.

[5] N. Al-Naami et al., "Improved Visual Saliency of Graph Clusters with Orderable Node-Link Layouts," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 1, pp. 1028–1038, Jan. 2025.

[6] S. S. Bae et al., "Bridging Network Science and Vision Science: Mapping Perceptual Mechanisms to Network Visualization Tasks," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 10, pp. 7137–7152, Oct. 2025.

[7] H. Li et al., "Knowledge Graphs in Practice: Characterizing their Users, Challenges, and Visualization Opportunities," IEEE Trans. Vis. Comput. Graphics, vol. 30, no. 1, pp. 584–594, Jan. 2024.

[8] J. Fuchs et al., "Quality Metrics and Reordering Strategies for Revealing Patterns in BioFabric Visualizations," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 1, pp. 1039–1049, Jan. 2025.

[9] M. Li et al., "Anonymous, Secure, Traceable, and Efficient Decentralized Digital Forensics," IEEE Trans. Knowl. Data Eng., vol. 36, no. 5, pp. 1874–1888, May 2024

[10] Z. Liu et al., "Locality-Aware Tail Node Embeddings on Homogeneous and Heterogeneous Networks," IEEE Trans. Knowl. Data Eng., vol. 36, no. 6, pp. 2517–2532, Jun. 2024.

[11] X. Zhao et al., "An Open Dataset of Cyber Asset Graphs for Cybercrime Research," IEEE Trans. Big Data, vol. 11, no. 2, pp. 438–446, Apr. 2025.

[12] Z. Aziz and R. Bestak, "Modeling Voice Traffic Patterns for Anomaly Detection and Prediction in Cellular Networks Based on CDR Data," IEEE Trans. Mobile Comput., vol. 23, no. 12, pp. 13131–13143, Dec. 2024.

[13] C. Zheng, L. Pan, and P. Wu, "JORA: Weakly Supervised User Identity Linkage via Jointly Learning to Represent and Align," IEEE Trans. Neural Netw. Learn. Syst., vol. 35, no. 3, pp. 3900–3911, Mar. 2024.

[14] W. Yin et al., "Differential Cryptanalysis of Bloom Filters for Privacy-Preserving Record Linkage," IEEE Trans. Inf. Forensics Security, vol. 19, pp. 6665–6678, 2024.

[15] Q. Chen, S. Cao, J. Wang, and N. Cao, "How Does Automation Shape the Process of Narrative Visualization: A Survey of Tools," IEEE Trans. Vis. Comput. Graphics, vol. 30, no. 8, pp. 4429–4448, Aug. 2024.

[16] Q. Chen et al., "Chart2Vec: A Universal Embedding of Context-Aware Visualizations," IEEE Trans.

Vis. Comput. Graphics, vol. 31, no. 4, pp. 2167– 2181, Apr. 2025.

[17] Y. He et al., "Leveraging Foundation Models for Crafting Narrative Visualization: A Survey," IEEE Trans. Vis. Comput. Graphics, vol. 31, no. 10, pp. 9303–9323, Oct. 2025.

[18] S. Li et al., "MFLink: User Identity Linkage Across Online Social Networks via Multimodal Fusion and Adversarial Learning," IEEE Trans. Emerg. Topics Comput. Intell., vol. 8, no. 5, pp. 3716–3725, Oct. 2024.

[19] H. Huang et al., "EgoMUIL: Enhancing Spatio-Temporal User Identity Linkage in Location-Based Social Networks With Ego-Mo Hypergraph," IEEE Trans. Mobile Comput., vol. 23, no. 8, pp. 8341–8354, Aug. 2024.

[20] B. Singh, A. R. Rajagopalan, and S. Bhashyam, "Exponentially Consistent Nonparametric Linkage Clustering for Dynamic User Identity Resolution," IEEE Trans. Knowl. Data Eng., vol. 36, no. 7, pp. 3120– 3134, Jul. 2024.