1. Which keyword is used to define an anonymous function in Python?
    a. def
    b. func
    c. anonymous
    d. lambda

2. What does a module in Python represent?
    a. A function
    b. A directory of files
    c. A python file with .py extension
    d. Combination of many python files

3. Which keyword is used to use modules in Python?
    a. load
    b. include
    c. module
    d. import

4. Which syntax imports only the sqrt() function from math module?
    a. import sqrt from math
    b. import sqrt
    c. from sqrt import math
    d. from math import sqrt
5. What error occurs if blocks of code are not properly aligned in Python?
    a. IndentationError
    b. SyntaxError
    c. TypeError
    d. ValueError

6. What is the parent of all exceptions?
    a. AllError
    b. Error
    c. Exception
    d. ValueError

7. Which block is used to handle exceptions in Python?
    a. except
    b. catch
    c. try
    d. else

8. WAP to create a function named ‘introduce’ that takes 2 arguments:
    a. name – positional argument
    b. age – default argument with a default value of None.

    If age is provided while calling the function, introduce(“John”, 20), print =>
    My name is John. I am 20 years old.

If age is not provided while calling the function, introduce("John"), print =>
My name is John. My age is secret.

9. WAP to create a function drop_minimum that takes variable length arguments (*args). The function takes integers and returns a list of these integers after removing the minimum value from the arguments.
   Example: drop_minimum(5, -2, 8, 4, -5, 7, 10), output => [5, -2, 8, 4, 7, 10]

10. A function find_max(a, b, c) that returns the largest of its three arguments by calling the built-in max() function. Create another function called main() that reads three user inputs x, y & z from the user (integers) and calls find_max() function. The main() function should print only the resulting maximum value.

11. Write a lambda function to add two numbers.

12. WAP to filter the elements of a list that starts with 'p'. Use lambda and filter().
    Words = ['python', 'fun', 'java', 'awesome', 'data analysis', 'practice', 'patience', 'burger', 'pizza']
    Output = ['python', 'practice', 'patience', 'pizza']

13. Write a lambda function that accepts a temperature in Celsius (a float number), converts it to the Fahrenheit scale using the formula: Fahrenheit = Celsius * 9 / 5 + 32

14. Write a Python program to create a file called student.txt. Write the following three lines into it:
    Python is easy to learn.
    File handling is important.
    Practice makes perfect.
    Use exception/error handing to catch FileExists error and all errors (Exception).

15. Write a program to read the contents of student.txt and
    a. Print all content
       Output:
       Python is easy to learn.
       File handling is important.
       Practice makes perfect.
    b. Print line-by-line.
       Output:
       Line 1: Python is easy to learn.
       Line 2: File handling is important.
       Line 3: Practice makes perfect.

16. Write a Python program to count how many words are present in student.txt.
    Output:
    Total words: 12

17. Write a Python program to add the below line to the file:
    Python file handling becomes simple with practice.

18. WAP to take a filename from the user and check whether the file exists or not using the os module. If it exists, print "File exists.", Else, print "File not found."
    Sample Output 1:
    Enter the filename: student.txt
    File exists
    Sample Output 2:
    Enter the filename: abc.txt
    File not found

19. Create a list, numbers = [7, 4, 0, -2, 3]. Print this list. Then ask the user to provide an index for which they want to value. Use exception handling to handle IndexError.

20. Create a python module named calculator.py. Define the following functions inside it:
    add(a, b)
    subtract(a, b)
    multiply(a, b)
    divide(a, b)
    Create another file main.py where you import the module and call all functions by passing the values to the arguments.

21. Create a function employee(**salary) that takes the name as the keyword argument and salary as the value. The function returns 2 values:
    a. Average salary
    b. Name of the person with highest salary

    Call the function and stored the returned values in 2 variables. The print the output like this:
    Example: employee(john=50000, jill=70000, mark=60000)
    Average salary is 60000
    Jill gets highest salary