

Fibonacci Numbers with Matrices

Rushi Shah

11 September 2015

Ahh, the Fibonacci numbers. What mathematician doesn't love them?

Well, in Week 06 of CIS194, some interesting implementations were discussed. My favorite (that I never actually had encountered before), was in order to get the n 'th number, you raise a two by two matrix to the n 'th power.

Let's take a look at my implementation:

0.1 The Matrix

First off, you need to be able to represent matrices. I decided to use a tuple of tuples for the two by two matrix.

```
data Matrix =      Matrix ((Integer, Integer),
                             (Integer, Integer))
```

I also wanted to be able to print them nicely in the terminal, so I whipped up a quick show function. I could have derived it, but in my opinion, this makes it look slightly nicer (sorry, the function is a bit long, so the text wraps).

```
instance Show Matrix where
    show (Matrix ((a, b), (c, d))) =
        " [ " ++ show a ++ " , " ++ show b ++ " ] "
        " [ " ++ show c ++ " , " ++ show d ++ " ] "
```

And now let's instantiate a matrix!

```
m :: Matrix
m = Matrix ((1, 1), (1, 0))
```

To check that it works, let's print out the matrix in `ghci`:

```
> m
[1, 1]
[1, 0]
```

0.2 Multiplying Matrices

So that's great, but these matrices don't really do much. We need to be able to raise each matrix to a specific power, but who knows how to do that? I sure don't. With that being

said, I do know how to multiply two 2x2 matrices together! Let's define a function `(*)` that takes two 2x2 matrices and returns a matrix representing the multiplication of the two arguments. This multiplication function is a part of the `Num` typeclass, so in essence, we are making `Matrix` an instance of `Num`.

```
instance Num Matrix where
    (*) (Matrix ((a, b), (c, d))) (Matrix ((e, f), (g, h))) = Matrix (
        ((a*e + b*g), (a*f + b*h)),
        ((c*e + d*g), (c*f + d*h))
    )
```

You can raise any instance of `Num` to a power after defining the multiplication operator, so Haskell will take care of the rest.

0.3 Quick helper function

The last element of a matrix will represent the Fibonacci number you're looking for. So let's whip up a quick function to get that element.

```
l :: Matrix -> Integer
l (Matrix m) = (snd . snd) m
```

0.4 Finally, the Fibonacci Function!

In CIS194, this is the fourth version of the function, so it is named `fib4`. Essentially, you take a number `n` and return the `n`th Fibonacci number by raising a 2x2 matrix to the `n`th power. Note that raising the matrix to the 0th power won't work, so we'll use pattern-matching to account for that special case.

```
fib4 :: Integer -> Integer
fib4 0 = 0
fib4 n = l (f^n)
```

0.5 Conclusion

To conclude, let's try it out!

What's an insanely large Fibonacci number? Well my birthday is April 13th, 1998, so how about we calculate the 41398th Fibonacci? That'll take a while, right? Wrong.

...

That's right, the answer is a 8652 digit number, and was calculated in about .009 seconds. If you want to see the answer, check out this `.txt` file.