제5강
지연시간, 손실, 처리율

Computer Networking: A Top Down Approach

컴퓨터 네트워크
(2019년 1학기)

박승철교수

한국기술교육대학교
컴퓨터공학부



Pre-study Test :

1) 다음 중 가변적인 지연시간은 어느 것인가?
① 처리 지연시간(processing delay)
② 큐잉 지연시간(gueueing delay)
③ 전송 지연시간(transmission delay)
④ 전달 지연시간(propagation delay)

2) 다음 중 패킷이 손실될 수 있는 곳이 아닌 곳은?
① 송신자
② 수신자
③ 경로상의 스위치
④ 경로상의 라우터

3) 다음 중 라우터에서 혼잡 상황이 발생하지 않는 경우는 어떤 경우인가?
L은 패킷의 길이, a은 패킷 도착율, R은 링크의 전송속도이다.
① La/R -> 0
② La/R -> 1
③ La/R = 1
④ La/R > 1

4) 전송속도가 각각 Ra, Rb, Rc, Rd이고, Ra > Rb > Rc > Rd 관계를 가지는 링크가 연결된 전송 경로가 있다. 해당 경로의 총 전송속도는 얼마인가?
① Ra
② Rd
③ Ra + Rb + Rc + Rd
④ Ra * Rb * Rc * Rd

5) 다음 중 최종 전송속도를 결정하는 링크는?
① Client link
② Server link
③ Backbone link
④ Bottleneck link

6) 라우터에서 혼잡 상황이 발생하지 않게 하려면 어떻게 하면 될까?
① 입력 링크의 전송속도를 높인다.
② 패킷 버퍼의 크기를 키운다.
③ 라우터의 CPU 처리속도를 높인다.
④ 출력 링크의 전송속도를 높인다.

Chapter 1: roadmap

1.1 what *is* the Internet?

1.2 network edge

- end systems, access networks, links

1.3 network core

- packet switching, circuit switching, network structure

1.4 delay, loss, throughput in networks

1.5 protocol layers, service models

1.6 networks under attack: security

1.7 history

How do loss and delay occur?

packets *queue* in router buffers

- packet arrival rate to link (temporarily) exceeds output link capacity
- packets queue, wait for turn



Four sources of packet delay



$$d_{nodal} = d_{proc} + d_{queue} + d_{trans} + d_{prop}$$

d_{proc}: nodal processing
- check bit errors
- determine output link
- typically < msec

d_{queue}: queueing delay
- time waiting at output link for transmission
- depends on congestion level of router

Four sources of packet delay



$$\boxed{d_{nodal} = d_{proc} + d_{queue} + d_{trans} + d_{prop}}$$

가변

d_{trans}: transmission delay:
- L: packet length (bits)
- R: link *bandwidth (bps)*
- $d_{trans} = L/R$

d_{trans} and d_{prop} *very* different

d_{prop}: propagation delay:
- d: length of physical link
- s: propagation speed (~2×10^8 m/sec)
- $d_{prop} = d/s$

Caravan analogy



- cars "propagate" at 100 km/hr
- toll booth takes 12 sec to service car (bit transmission time)
- car ~ bit; caravan ~ packet
- *Q:* How long until caravan is lined up before 2nd toll booth?

- time to "push" entire caravan through toll booth onto highway = 12*10 = 120 sec
- time for last car to propagate from 1st to 2nd toll both: 100km/(100km/hr)= 1 hr
- *A:* 62 minutes

Caravan analogy (more)



- suppose cars now "propagate" at 1000 km/hr
- and suppose toll booth now takes one min to service a car
- *Q:* Will cars arrive to 2nd booth before all cars serviced at first booth?
  - *A: Yes!* after 7 min, first car arrives at second booth; three cars still at first booth

Queueing delay (revisited)

- *R:* link bandwidth (bps)
- *L:* packet length (bits)
- a: average packet arrival rate



트래픽 강도 :

- *La/R* ~ 0: avg. queueing delay small
- *La/R* -> 1: avg. queueing delay large
- *La/R* > 1: more "work" arriving than can be serviced, average delay infinite!


La/R ~ 0


La/R -> 1

* Check online interactive animation on queuing and loss

"Real" Internet delays and routes

- what do "real" Internet delay & loss look like?
- **`traceroute`** program: provides delay measurement from source to router along end-end Internet path towards destination. For all *i:*
  - sends three packets that will reach router *i* on path towards destination
  - router *i* will return packets to sender(w/ router name & address)
  - sender times interval between transmission and reply.



"Real" Internet delays, routes

traceroute: gaia.cs.umass.edu to www.eurecom.fr

3 delay measurements from gaia.cs.umass.edu to cs-gw.cs.umass.edu

```
1  cs-gw (128.119.240.254)  1 ms  1 ms  2 ms
2  border1-rt-fa5-1-0.gw.umass.edu (128.119.3.145)  1 ms  1 ms  2 ms
3  cht-vbns.gw.umass.edu (128.119.3.130)  6 ms 5 ms 5 ms
4  jn1-at1-0-0-19.wor.vbns.net (204.147.132.129)  16 ms 11 ms 13 ms
5  jn1-so7-0-0-0.wae.vbns.net (204.147.136.136)  21 ms 18 ms 18 ms
6  abilene-vbns.abilene.ucaid.edu (198.32.11.9)  22 ms  18 ms  22 ms
7  nycm-wash.abilene.ucaid.edu (198.32.8.46)  22 ms  22 ms  22 ms
8  62.40.103.253 (62.40.103.253)  104 ms 109 ms 106 ms
9  de2-1.de1.de.geant.net (62.40.96.129)  109 ms 102 ms 104 ms
10  de.fr1.fr.geant.net (62.40.96.50)  113 ms 121 ms 114 ms
11  renater-gw.fr1.fr.geant.net (62.40.103.54)  112 ms  114 ms  112 ms
12  nio-n2.cssi.renater.fr (193.51.206.13)  111 ms  114 ms  116 ms
13  nice.cssi.renater.fr (195.220.98.102)  123 ms  125 ms  124 ms
14  r3t2-nice.cssi.renater.fr (195.220.98.110)  126 ms  126 ms  124 ms
15  eurecom-valbonne.r3t2.ft.net (193.48.50.54)  135 ms  128 ms  133 ms
16  194.214.211.25 (194.214.211.25)  126 ms  128 ms  126 ms
17  * * *
18  * * *
19  fantasia.eurecom.fr (193.55.113.142)  132 ms  128 ms  136 ms
```

trans-oceanic link

* means no response (probe lost, router not replying)

* Do some traceroutes from exotic countries at www.traceroute.org

Packet loss

- queue (aka buffer) preceding link in buffer has finite capacity
- packet arriving to full queue dropped (aka lost)
- lost packet may be retransmitted by previous node, by source end system, or not at all

* aka : also known as



Throughput

- *throughput:* rate (bits/time unit) at which bits transferred between sender/receiver
  - *instantaneous:* rate at given point in time
  - *average:* rate over longer period of time



Throughput (more)

- $R_s < R_c$ What is average end-end throughput?



- $R_s > R_c$ What is average end-end throughput?



bottleneck link

link on end-end path that constrains end-end throughput

Throughput: Internet scenario

- per-connection end-end throughput: *min(R_c,R_s,R/10)*
- in practice: R_c or R_s is often bottleneck



10 connections (fairly) share backbone bottleneck link *R* bits/sec

Pre-study Test :

1) 다음 중 가변적인 지연시간은 어느 것인가?
① 처리 지연시간(processing delay)
② 큐잉 지연시간(gueueing delay)
③ 전송 지연시간(transmission delay)
④ 전달 지연시간(propagation delay)

2) 다음 중 패킷이 손실될 수 있는 곳이 아닌 곳은?
① 송신자
② 수신자
③ 경로상의 스위치
④ 경로상의 라우터

3) 다음 중 라우터에서 혼잡 상황이 발생하지 않는 경우는 어떤 경우인가?
L은 패킷의 길이, a은 패킷 도착율, R은 링크의 전송속도이다.
① La/R -> 0
② La/R -> 1
③ La/R = 1
④ La/R > 1

Pre-study Test :

1) 다음 중 가변적인 지연시간은 어느 것인가?
① 처리 지연시간(processing delay)
② 큐잉 지연시간(gueueing delay)
③ 전송 지연시간(transmission delay)
④ 전달 지연시간(propagation delay)

2) 다음 중 패킷이 손실될 수 있는 곳이 아닌 곳은?
① 송신자
② 수신자
③ 경로상의 스위치
④ 경로상의 라우터

3) 다음 중 라우터에서 혼잡 상황이 발생하지 않는 경우는 어떤 경우인가?
L은 패킷의 길이, a은 패킷 도착율, R은 링크의 전송속도이다.
① La/R -> 0
② La/R -> 1
③ La/R = 1
④ La/R > 1