

Fundamentals of Deep Learning

ELL 881 Lec 06A: Recurrent Neural Networks

Vineet Kumar

September 12, 2018

Sequential Data

Recurrent Neural Network (RNN) is a family of neural networks for processing **sequential data**

Sequential Data

Recurrent Neural Network (RNN) is a family of neural networks for processing **sequential data**


$$\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(\tau)}$$

Sequential Data

Recurrent Neural Network (RNN) is a family of neural networks for processing **sequential data**

$$\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(\tau)}$$

Examples of sequential data?¹

¹Borrowed from <https://www.cs.toronto.edu/~hinton/csc2515/notes/lec9timeseries.pdf> 

Sequential Data

Recurrent Neural Network (RNN) is a family of neural networks for processing **sequential data**

$$\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(\tau)}$$

Examples of sequential data?¹

- ▶ **Ordered Sequence:** Words/Characters in a sentence, Gene sequence
- ▶ **Time-series:** Stock Market, Speech, Video analysis

¹Borrowed from <https://www.cs.toronto.edu/~hinton/csc2515/notes/lec9timeseries.pdf>

Parameter Sharing

Key Idea **Parameter Sharing**: Share parameters across different parts of the model.

Parameter Sharing

Key Idea **Parameter Sharing**: Share parameters across different parts of the model.

Parameter sharing allows to extend and apply the model to examples of **different lengths**, and generalize!

Parameter Sharing

Key Idea **Parameter Sharing**: Share parameters across different parts of the model.

Parameter sharing allows to extend and apply the model to examples of **different lengths**, and generalize!

Without parameter sharing, we would require separate parameters across each time step!

Parameter Sharing

Key Idea Parameter Sharing: Share parameters across different parts of the model.

Parameter sharing allows to extend and apply the model to examples of **different lengths**, and generalize!

Without parameter sharing, we would require separate parameters across each time step!

In **2009**, I went to Nepal

Parameter Sharing

Key Idea Parameter Sharing: Share parameters across different parts of the model.

Parameter sharing allows to extend and apply the model to examples of **different lengths**, and generalize!

Without parameter sharing, we would require separate parameters across each time step!

In **2009**, I went to Nepal
I went to Nepal in **2009**

Parameter Sharing

Key Idea Parameter Sharing: Share parameters across different parts of the model.

Parameter sharing allows to extend and apply the model to examples of **different lengths**, and generalize!

Without parameter sharing, we would require separate parameters across each time step!

In **2009**, I went to Nepal
I went to Nepal in **2009**

Dynamical System and Recurrence

Consider the following network:

$$s^{(t)} = f(s^{(t-1)}; \theta)$$

This network is **recurrent** as computing $s^{(t)}$ requires $s^{(t-1)}$

Question: How would you unfold this graph for $\tau = 3$ time steps, i.e compute $s^{(3)}$?

Dynamical System and Recurrence

Consider the following network:

$$s^{(t)} = f(s^{(t-1)}; \theta)$$

This network is **recurrent** as computing $s^{(t)}$ requires $s^{(t-1)}$

Question: How would you unfold this graph for $\tau = 3$ time steps, i.e compute $s^{(3)}$?

$$\begin{aligned} s^{(3)} &= f(s^{(2)}; \theta) \\ &= f(f(s^{(1)}; \theta); \theta) \end{aligned}$$

Dynamical System and Recurrence

Consider the following network:

$$s^{(t)} = f(s^{(t-1)}; \theta)$$

This network is **recurrent** as computing $s^{(t)}$ requires $s^{(t-1)}$

Question: How would you unfold this graph for $\tau = 3$ time steps, i.e compute $s^{(3)}$?

$$\begin{aligned} s^{(3)} &= f(s^{(2)}; \theta) \\ &= f(f(s^{(1)}; \theta); \theta) \end{aligned}$$

Same parameters θ are used across all time steps!




Figure 10.1

Input Signal Summary

The following system computes $\mathbf{h}^{(t)}$, updated by an external signal $\mathbf{x}^{(t)}$:

$$\mathbf{h}^{(t)} = f(\mathbf{h}^{(t-1)}, \mathbf{x}^{(t)}; \theta)$$

Input Signal Summary

The following system computes $\mathbf{h}^{(t)}$, updated by an external signal $\mathbf{x}^{(t)}$:

$$\mathbf{h}^{(t)} = f(\mathbf{h}^{(t-1)}, \mathbf{x}^{(t)}; \theta)$$




Figure 10.2

Input Signal Summary

$h^{(t)}$ can be thought of as a **lossy summary** of input seen so far, that is $\mathbf{x}^1, \dots, \mathbf{x}^t$




Figure 10.2