

🎉 축하합니다! 통과하셨습니다!

받은 학점 100% 최신 제출물 학점 100% 통과 점수: 80% 이상

다음 항목으로 이동

1. Which of the following are true about hyperparameter search?

1/1점

- ☐ When sampling from a grid, the number of values for each hyperparameter is larger than when using random values.
- ☐ When using random values for the hyperparameters they must be always uniformly distributed.
- ☐ Choosing values in a grid for the hyperparameters is better when the number of hyperparameters to tune is high since it provides a more ordered way to search.
- ☒ Choosing random values for the hyperparameters is convenient since we might not know in advance which hyperparameters are more important for the problem at hand.

👁️ 더 보기

👏 맞습니다

Correct. Different problems might be more sensitive to different hyperparameters.

2. If it is only possible to tune two parameters from the following due to limited computational resources. Which two would you choose?

1/1점

- ☐ β_1, β_2 in Adam.
- ☐ ϵ in Adam.
- ☒ The β parameter of the momentum in gradient descent.

👏 Correct

Correct. This hyperparameter can increase the speed of convergence of the training, thus is worth tuning.

☒ α

👏 Correct

Correct. This might be the hyperparameter that most impacts the results of a model.

👁️ 더 보기

👏 맞습니다

Great, you got all the right answers.

3. Using the "Panda" strategy, it is possible to create several models. True/False?

1/1점

- ☐ False
- ☒ True

👁️ 더 보기

👏 맞습니다

Correct. Following the "Panda" analogy, it is possible to babysit a model until a certain point and then start again to produce a different one.

4. If you think β (hyperparameter for momentum) is between 0.9 and 0.99, which of the following is the recommended way to sample a value for beta?

1/1점

- ☒ $r = \text{np.random.rand}()$
 $\text{beta} = 1 - 10^{(r - 1)}$
- ☐ $r = \text{np.random.rand}()$
 $\text{beta} = 1 - 10^{(r + 1)}$
- ☐ $r = \text{np.random.rand}()$
 $\text{beta} = r * 0.09 + 0.9$
- ☐ $r = \text{np.random.rand}()$
 $\text{beta} = r * 0.9 + 0.09$

👁️ 더 보기

👏 맞습니다

5. Once good values of hyperparameters have been found, those values should be changed if new data is added or a change in computational power occurs. True/False?

1/1점

- ☒ True
- ☐ False

👁️ 더 보기

👏 맞습니다

Correct. The choice of some hyperparameters such as the batch size depends on conditions such as hardware and quantity of data.

6. When using batch normalization it is OK to drop the parameter $\hat{W}^{[l]}$ from the forward propagation since it will be subtracted out when we compute $\hat{z}_{\text{normalize}}^{[l]} = \beta^{[l]} \hat{z}^{[l]} + \gamma^{[l]}$. True/False?

1/1점

- ☐ True
- ☒ False

👁️ 더 보기

👏 맞습니다

Correct. The parameter $\hat{W}^{[l]}$ doesn't get subtracted during the batch normalization process, although it gets re-scaled.

7. Which of the following are true about batch normalization?

1 / 18

- ☒ One intuition behind why batch normalization works is that it helps reduce the internal covariance.
- ☐ The parameter ϵ in the batch normalization formula is used to accelerate the convergence of the model.
- ☐ There is a global value of γ and β that is used for all the hidden layers where batch normalization is used.
- ☐ The parameters β and γ of batch normalization can't be trained using Adam or RMS prop.

👉 더 보기

👉 맞습니다

Yes, internal covariance is a name to express that there has been a change in the distribution of the activations. Since after each iteration of gradient descent the parameters of a layer change, we might think that the activations suffer from covariance shift.

8. Which of the following are true about batch normalization?

1 / 18

- ☒ When using batch normalization we introduce two new parameters γ^l, β^l that must be "learned" or trained.

👉 Correct

Correct. Batch normalization uses two parameters β and γ to compute $z^{(l)} = \beta_{\text{norm}}^{(l)} + \gamma$.

☐ $\mu_{\text{norm}}^{(l)} = \frac{z^{(l)} - \mu}{\sqrt{\sigma^2}}$.

- ☐ β^l and γ^l are hyperparameters that must be tuned by random sampling in a logarithmic scale.

- ☒ The parameters γ^l and β^l set the mean and variance of z^l .

👉 Correct

Correct. When applying the linear transformation $z^{(l)} = \beta_{\text{norm}}^{(l)} + \gamma^l$ we set the mean and variance of z^l .

👉 더 보기

👉 맞습니다

Great, you got all the right answers.

9. After training a neural network with Batch Norm, at test time, to evaluate the neural network on a new example you should:

1 / 18

- ☐ Skip the step where you normalize using μ and σ^2 since a single test example cannot be normalized.
- ☒ Perform the needed normalizations, use μ and σ^2 estimated using an exponentially weighted average across mini-batches seen during training.
- ☐ If you implemented Batch Norm on mini-batches of (say) 256 examples, then to evaluate on one test example, duplicate that example 256 times so that you're working with a mini-batch the same size as during training.
- ☐ Use the most recent mini-batch's value of μ and σ^2 to perform the needed normalizations.

👉 더 보기

👉 맞습니다

10. If a project is open-source, it is a guarantee that it will remain open source in the long run and will never be modified to benefit only one company. True/False?

1 / 18

- ☐ True
- ☒ False

👉 더 보기

👉 맞습니다

Correct. To ensure that a project will remain open source in the long run it must have a good governance body too.