

Ontology-based Data Access: Theory and Practice

Guohui Xiao

KRDB Research Centre

Free University of Bozen-Bolzano

Roman Kontchakov

Department of Computer Science & Inf. Systems

Birkbeck, University of London

<http://ontop.inf.unibz.it/ijcai-2018-tutorial>

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Π_2 -PE have matrix of the form $\wedge \vee$

= semiconjunctive queries (SCQs)

for ontologies without $\exists y$ on RHS, the size is $|q| \cdot |\mathcal{T}|$

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Π_2 -PE have matrix of the form $\wedge \vee$

= semiconjunctive queries (SCQs)

for ontologies without $\exists y$ on RHS, the size is $|q| \cdot |\mathcal{T}|$

Σ_3 -PE have matrix of the form $\vee \wedge \vee$

= unions of SCQs

e.g., tree-witness rewriting

size $O(2^{|\Theta_Q|} \cdot |Q|^2)$ with $\underbrace{|\Theta_Q| \leq 3^{|q|}}_{\text{number of tree witnesses}}$

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Π_2 -PE have matrix of the form $\wedge \vee$

= semiconjunctive queries (SCQs)

for ontologies without $\exists y$ on RHS, the size is $|q| \cdot |\mathcal{T}|$

Σ_3 -PE have matrix of the form $\vee \wedge \vee$

= unions of SCQs

e.g., tree-witness rewriting

size $O(2^{|\Theta_Q|} \cdot |Q|^2)$ with

$\underbrace{|\Theta_Q| \leq 3^{|q|}}_{\text{number of tree witnesses}}$

Π_4 -PE have matrix of the form $\wedge \vee \wedge \vee$

e.g., modified tree-witness rewriting without conflicts has size $O(|\Theta_Q| \cdot |Q|^2)$

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Π_2 -PE have matrix of the form $\wedge \vee$

= semiconjunctive queries (SCQs)

for ontologies without $\exists y$ on RHS, the size is $|q| \cdot |\mathcal{T}|$

Σ_3 -PE have matrix of the form $\vee \wedge \vee$

= unions of SCQs

e.g., tree-witness rewriting size $O(2^{|\Theta_Q|} \cdot |Q|^2)$ with $\underbrace{|\Theta_Q| \leq 3^{|q|}}_{\text{number of tree witnesses}}$

Π_4 -PE have matrix of the form $\wedge \vee \wedge \vee$

e.g., modified tree-witness rewriting without conflicts has size $O(|\Theta_Q| \cdot |Q|^2)$

NDL (non-recursive datalog)

= PE + shared subformulas = SPJU + views

e.g., Presto produced rewritings of size $|\mathcal{T}|^{O(1)} \cdot 2^{|q|}$

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Π_2 -PE have matrix of the form $\wedge \vee$

= semiconjunctive queries (SCQs)

for ontologies without $\exists y$ on RHS, the size is $|q| \cdot |\mathcal{T}|$

Σ_3 -PE have matrix of the form $\vee \wedge \vee$

= unions of SCQs

e.g., tree-witness rewriting

size $O(2^{|\Theta_Q|} \cdot |Q|^2)$ with

$\underbrace{|\Theta_Q| \leq 3^{|q|}}_{\text{number of tree witnesses}}$

Π_4 -PE have matrix of the form $\wedge \vee \wedge \vee$

e.g., modified tree-witness rewriting without conflicts has size $O(|\Theta_Q| \cdot |Q|^2)$

NDL (non-recursive datalog)

= PE + shared subformulas = SPJU + views

e.g., Presto produced rewritings of size $|\mathcal{T}|^{O(1)} \cdot 2^{|q|}$

FO (first-order formulas)

= PE + negation \approx RA

Size of OMQ Rewritings: Target Languages

UCQ

as produced, e.g., by PerfectRef

= unions of SPJ queries
size $|q|^{|\mathcal{T}|} \cdot 2^{O(|q|^2)}$

PE (positive existential formulas)

= SPJU queries

Π_2 -PE have matrix of the form $\wedge \vee$

= semiconjunctive queries (SCQs)

for ontologies without $\exists y$ on RHS, the size is $|q| \cdot |\mathcal{T}|$

Σ_3 -PE have matrix of the form $\vee \wedge \vee$

= unions of SCQs

e.g., tree-witness rewriting

size $O(2^{|\Theta_Q|} \cdot |Q|^2)$ with $\underbrace{|\Theta_Q| \leq 3^{|q|}}_{\text{number of tree witnesses}}$

Π_4 -PE have matrix of the form $\wedge \vee \wedge \vee$

e.g., modified tree-witness rewriting without conflicts has size $O(|\Theta_Q| \cdot |Q|^2)$

NDL (non-recursive datalog)

= PE + shared subformulas = SPJU + views

e.g., Presto produced rewritings of size $|\mathcal{T}|^{O(1)} \cdot 2^{|q|}$

FO (first-order formulas)

= PE + negation \approx RA

no combined approach (no additional constants, no assumptions on data)

Tree-Witness Rewriting: Recap

$$\begin{array}{lll} A_1(x) \rightarrow \exists y P(x, y) & P(x, y) \rightarrow R(x, y) & P(x, y) \rightarrow Q(y, x) \\ A_2(x) \rightarrow \exists y S_1(x, y) & S_1(x, y) \rightarrow S_2(x, y) & \\ A_3(x) \rightarrow \exists y Q(x, y) & \exists y Q(y, x) \rightarrow \exists y S_1(x, y) & \end{array}$$

Tree-Witness Rewriting: Recap

$$A_1(x) \rightarrow \exists y P(x, y)$$


$$P(x, y) \rightarrow R(x, y)$$

$$P(x, y) \rightarrow Q(y, x)$$

$$A_2(x) \rightarrow \exists y S_1(x, y)$$


$$S_1(x, y) \rightarrow S_2(x, y)$$

$$A_3(x) \rightarrow \exists y Q(x, y) \quad \exists y Q(y, x) \rightarrow \exists y S_1(x, y)$$



Tree-Witness Rewriting: Recap


$$\begin{array}{lll}
 A_1(x) \rightarrow \exists y P(x, y) & P(x, y) \rightarrow R(x, y) & P(x, y) \rightarrow Q(y, x) \\
 A_2(x) \rightarrow \exists y S_1(x, y) & S_1(x, y) \rightarrow S_2(x, y) & \\
 A_3(x) \rightarrow \exists y Q(x, y) & \exists y Q(y, x) \rightarrow \exists y S_1(x, y) &
 \end{array}$$



$$q' = \bigvee_{\Theta \subseteq \Theta_Q \text{ compatible}} \left(\bigwedge_{S(z) \in q \setminus q_\Theta} S(z) \wedge \bigwedge_{t \in \Theta} \text{tw}_t \right)$$

Tree-Witness Rewriting: Recap

$$\begin{array}{lll}
 A_1(x) \rightarrow \exists y P(x, y) & P(x, y) \rightarrow R(x, y) & P(x, y) \rightarrow Q(y, x) \\
 A_2(x) \rightarrow \exists y S_1(x, y) & S_1(x, y) \rightarrow S_2(x, y) & \\
 A_3(x) \rightarrow \exists y Q(x, y) & \exists y Q(y, x) \rightarrow \exists y S_1(x, y) &
 \end{array}$$




$$q' = \bigvee_{\Theta \subseteq \Theta_Q \text{ compatible}} \left(\bigwedge_{S(z) \in q \setminus q_\Theta} S(z) \wedge \bigwedge_{t \in \Theta} \text{tw}_t \right)$$

5 **compatible** subsets:
 $\emptyset, \{t_1\}, \{t_2\}, \{t_3\}$ and $\{t_1, t_2\}$
 (exponentially many in general)

Tree-Witness Rewriting: Recap

$$\begin{array}{lll}
 A_1(x) \rightarrow \exists y P(x, y) & P(x, y) \rightarrow R(x, y) & P(x, y) \rightarrow Q(y, x) \\
 A_2(x) \rightarrow \exists y S_1(x, y) & S_1(x, y) \rightarrow S_2(x, y) & \\
 A_3(x) \rightarrow \exists y Q(x, y) & \exists y Q(y, x) \rightarrow \exists y S_1(x, y) &
 \end{array}$$




$$q' = \bigvee_{\Theta \subseteq \Theta_Q \text{ compatible}} \left(\bigwedge_{S(z) \in q \setminus q_\Theta} S(z) \wedge \bigwedge_{t \in \Theta} \text{tw}_t \right)$$

5 **compatible** subsets:
 $\emptyset, \{t_1\}, \{t_2\}, \{t_3\}$ and $\{t_1, t_2\}$
 (exponentially many in general)


a **homomorphism** $q \rightarrow \mathfrak{C}_{\mathcal{O}}(\mathcal{D})$ = a map from variables of q to $\text{ind}(\mathcal{A})$ + an **compatible subset** of Θ_Q such that

1. each tree witness is 'generated' by the data
2. each atom outside tree witnesses is 'present' in the data

Tree Witness Rewritings as Hypergraphs




Tree Witness Rewritings as Hypergraphs




OMQ hypergraph

vertices = query atoms

hyperedges = sets of query atoms that can be mapped to trees




Tree Witness Rewritings as Hypergraphs



OMQ hypergraph

vertices = query atoms

hyperedges = sets of query atoms that can be mapped to trees



$$f_H = \bigvee_{E' \text{ independent}} \left(\bigwedge_{v \in V \setminus V_{E'}} p_v \wedge \bigwedge_{e \in E'} p_e \right)$$

hypergraph function f_H

From OMQs to Hypergraph Programs (HGP)


- a **HGP** P is a hypergraph H whose vertices are labelled by
0, 1, or a literal over p_1, \dots, p_n
- P returns 1 on an assignment $\alpha: \{p_1, \dots, p_n\} \rightarrow \{0, 1\}$
if there is an independent subset in H that covers all zeroes under α

From OMQs to Hypergraph Programs (HGP)

- a **HGP** P is a hypergraph H whose vertices are labelled by
 $0, 1$, or a literal over p_1, \dots, p_n
 P returns 1 on an assignment $\alpha: \{p_1, \dots, p_n\} \rightarrow \{0, 1\}$
if there is an independent subset in H that covers all zeroes under α
- a HGP is **monotone** if none of the labels is negative
- degree of a hypergraph = the maximum number of hyperedges that contain a vertex

From OMQs to Hypergraph Programs (HGP)


- a **HGP** P is a hypergraph H whose vertices are labelled by
 $0, 1$, or a literal over p_1, \dots, p_n
- P returns 1 on an assignment $\alpha: \{p_1, \dots, p_n\} \rightarrow \{0, 1\}$
 if there is an independent subset in H that covers all zeroes under α
- a HGP is **monotone** if none of the labels is negative
- degree of a hypergraph = the maximum number of hyperedges that contain a vertex



$$\text{m}\Pi_3 \subsetneq \text{mAC}^0 \subsetneq \text{mNC}^1 \subsetneq \text{mNL/poly} \subseteq \text{mLogCFL/poly} \subsetneq \text{mP/poly} \subsetneq \text{mNP/poly}$$

monotone Boolean formulas (PE)
monotone circuits (NDL)
nondeterministic Boolean circuits (FO)

Roadmap for Succinctness Proofs




ontology depth


0 = no axioms with $\exists y$ on the right-hand side

$d \approx$ trees $\mathfrak{C}_O^{\tau(a)}$ of labelled nulls are of depth at most d


Succinctness Landscape



OMQ Answering Combined Complexity




OMQ Answering Combined Complexity



NB: polynomial-size NDL rewritings exist in all cases
when OMQ answering is in LogCFL

OMQ Answering Combined Complexity



NB: polynomial-size NDL rewritings exist in all cases
when OMQ answering is in LogCFL

constructed polynomial-size NDL rewritings that can be evaluated in LogCFL/NL

LogCFL means that they are **highly parallelisable**

References

1. M. Bienvenu, S. Kikot, R. Kontchakov, V. V. Podolskii & M. Zakharyashev. “Ontology-mediated queries: combined complexity and succinctness of rewritings via circuit complexity”. In: *JACM*, 2018.
2. M. Bienvenu, S. Kikot, R. Kontchakov, V. V. Podolskii, V. Ryzhikov & M. Zakharyashev. “The complexity of ontology-based data access with OWL 2 QL and bounded treewidth queries”. In: *Proc. of the 36th ACM Symposium on Principles of Database Systems, PODS 2017*, 2017.
3. G. Gottlob, S. Kikot, R. Kontchakov, V. V. Podolskii, T. Schwentick & M. Zakharyashev. “The Price of Query Rewriting in Ontology-Based Data Access”. In: *Artificial Intelligence*, 213:42–59, 2014.
4. R. Rosati & A. Almatelli. “Improving query answering over DL-Lite ontologies”. In: *Proc. of the 12th Int. Conf. on Principles of Knowledge Representation & Reasoning, KR’10*, pp. 290–300. AAAI, 2010.
5. M. Thomazo. “Compact rewritings for existential rules”. In: *Proc. of the 23rd Int. Joint Conf. on Artificial Intelligence IJCAI 2013*, pp. 1125–1131. IJCAI/AAAI, 2013.