

Ontology-based Data Access: Theory and Practice

Guohui Xiao

KRDB Research Centre

Free University of Bozen-Bolzano

Roman Kontchakov

Department of Computer Science & Inf. Systems

Birkbeck, University of London

<http://ontop.inf.unibz.it/ijcai-2018-tutorial>

The “simple” axiom

$$\text{CheckingAccount} \sqcap \exists \text{name}. \text{Person} \sqsubseteq \text{SimpleAccount}$$

is NOT in OWL 2 QL.

Recall that OWL 2 QL does not contain:

- **existential quantification** (`ObjectSomeValuesFrom`) **on the left**
- **conjunction** (`intersectionOf`) **on the left**
- **universal quantification** (`ObjectAllValuesFrom`, `DataAllValuesFrom`)
- **enumeration** of individuals and literals (`ObjectOneOf`, `DataOneOf`)
- **disjunction** (`ObjectUnionOf`, `DisjointUnion` and `DataUnionOf`)
- individual equality assertions (**sameAs**) (`SameIndividual`)
- ...


The “simple” axiom

$$\text{CheckingAccount} \sqcap \exists \text{name}. \text{Person} \sqsubseteq \text{SimpleAccount}$$

is NOT in OWL 2 QL.

Recall that OWL 2 QL does not contain:


- **existential quantification** (ObjectSomeValuesFrom) **on the left**
- **conjunction** (intersectionOf) **on the left**
- **universal quantification** (ObjectAllValuesFrom, DataAllValuesFrom)
- **enumeration** of individuals and literals (ObjectOneOf, DataOneOf)
- **disjunction** (ObjectUnionOf, DisjointUnion and DataUnionOf)
- individual equality assertions (**sameAs**) (SameIndividual)
- ...



Rewriting The new specification is equivalent to the original one w.r.t. query answering (**query-inseparable**).

Approximation The new specification is a sound approximation of the original one w.r.t. query answering.

NB: This idea is inspired by the mapping saturation technique



Rewriting The new specification is equivalent to the original one w.r.t. query answering (**query-inseparable**).

Approximation The new specification is a sound approximation of the original one w.r.t. query answering.

NB: This idea is inspired by the mapping saturation technique

Example

$$\begin{array}{l} \mathcal{T} = \{ A \sqcap B \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x), \\ \quad \text{SQL}_A(x) \wedge \text{SQL}_B(x) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ \exists R.A \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y), \\ \quad \text{SQL}_R(x, y) \wedge \text{SQL}_A(y) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ A \sqcap B \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x), \\ \quad \text{SQL}_A(x) \wedge \text{SQL}_B(x) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ \exists R.A \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y), \\ \quad \text{SQL}_R(x, y) \wedge \text{SQL}_A(y) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ A \sqcap B \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x), \\ \quad \text{SQL}_A(x) \wedge \text{SQL}_B(x) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ \exists R.A \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y), \\ \quad \text{SQL}_R(x, y) \wedge \text{SQL}_A(y) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ A \sqcap B \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_B(x) \leadsto B(x), \\ \quad \text{SQL}_A(x) \wedge \text{SQL}_B(x) \leadsto C(x) \} \end{array}$$

Example

$$\begin{array}{l} \mathcal{T} = \{ \exists R. A \sqsubseteq C \} \\ \mathcal{M} = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y) \} \end{array} \Rightarrow \begin{array}{l} \mathcal{T}' = \{ \} \\ \mathcal{M}' = \{ \text{SQL}_A(x) \leadsto A(x), \\ \quad \text{SQL}_R(x, y) \leadsto R(x, y), \\ \quad \text{SQL}_R(x, y) \wedge \text{SQL}_A(y) \leadsto C(x) \} \end{array}$$

Recursion cannot be fully captured via the mapping.


\leadsto We use approximation, by setting **a bound on the depth** of the Datalog expansion of queries.

Example

$$\begin{aligned}\mathcal{T} &= \{ \exists R. A \sqsubseteq A \} \\ \mathcal{M} &= \{ \text{SQL}_A(x) \leadsto A(x), \\ &\quad \text{SQL}_R(x, y) \leadsto R(x, y) \}\end{aligned}$$

\Rightarrow

$$\begin{aligned}\mathcal{T}' &= \{ \} \\ \mathcal{M}' &= \{ \text{SQL}_A(x) \leadsto A(x), \\ &\quad \text{SQL}_R(x, y) \leadsto R(x, y), \\ &\quad \text{SQL}_R(x, y) \wedge \text{SQL}_A(y) \leadsto A(x) \\ &\quad \text{SQL}_R(x, y) \wedge \text{SQL}_R(y, z) \wedge \text{SQL}_A(z) \leadsto A(x) \\ &\quad \text{SQL}_R(x, y) \wedge \text{SQL}_R(y, z) \wedge \text{SQL}_R(z, w) \wedge \text{SQL}_A(w) \leadsto A(x) \\ &\quad \dots \}\end{aligned}$$



Ontoprox: $\langle \mathcal{T}, \mathcal{M}, \mathcal{S} \rangle, k \rightarrow \langle \mathcal{T}', \mathcal{M}', \mathcal{S} \rangle$

where \mathcal{T} is a Horn-*SHIQ* ontology and \mathcal{T}' is a OWL 2 QL ontology.

<https://github.com/ontop/ontoprox>

- [1] E. Botoeva et al. "Beyond OWL 2 QL in OBDA: Rewritings and Approximations". In: *Proc. of AAAI*. 2016, pp. 921–928.