

Ontology-based Data Access: Theory and Practice

Guohui Xiao

KRDB Research Centre

Free University of Bozen-Bolzano

Roman Kontchakov

Department of Computer Science & Inf. Systems

Birkbeck, University of London

<http://ontop.inf.unibz.it/ijcai-2018-tutorial>

Motivation: Geologists at Statoil (Equinor)


900 geologists & geophysicists in Statoil Exploration develop **stratigraphic models** of unexplored areas on the basis of data acquired from previous operations at nearby locations

Motivation: Geologists at Statoil (Equinor)

900 geologists & geophysicists in Statoil Exploration develop **stratigraphic models** of unexplored areas on the basis of data acquired from previous operations at nearby locations

G&G's **information need (009)**

In my area of interest, return all pressure data tagged with key stratigraphy information with understandable QC attributes (and suitable for further filtering).




Motivation: Geologists at Statoil (Equinor)

900 geologists & geophysicists in Statoil Exploration develop **stratigraphic models** of unexplored areas on the basis of data acquired from previous operations at nearby locations

G&G's **information need (009)**

In my area of interest, return all pressure data tagged with key stratigraphy information with understandable QC attributes (and suitable for further filtering).



Slegge database contains **1545** tables and 1727 views

table WELLBORE has 38 columns

formation pressure: a join of PTY_PRESSURE, ACTIVITY, ACTIVITY_CLASS and WELLBORE

stratigraphic information: a join of PICKED_STRATIGRAPHIC_ZONES, PTY_LOCATION_1D, PTY_PRESSURE, ACTIVITY, ACTIVITY_CLASS and WELLBORE

Data Gathering at Statoil (1)

data gathering is a huge problem in industry:

search for data and quality assessment,

e.g., in oil&gas takes **30–70%** of engineers' time

(Crompton, 2008)

Data Gathering at Statoil (1)

data gathering is a huge problem in industry:

search for data and quality assessment,

e.g., in oil&gas takes **30–70%** of engineers' time

(Crompton, 2008)

solution 1

use **predefined SQL queries** of the in-house system to retrieve information about

(a) pressure measurements,

(b) lithostratigraphy of wellbores, etc.

and integrate the results using a **spreadsheet**

Data Gathering at Statoil (1)

data gathering is a huge problem in industry:

search for data and quality assessment,

e.g., in oil&gas takes **30–70%** of engineers' time

(Crompton, 2008)

solution 1

use **predefined SQL queries** of the in-house system to retrieve information about

(a) pressure measurements,

(b) lithostratigraphy of wellbores, etc.

and integrate the results using a **spreadsheet**

time-consuming, error-prone (e.g., different units of measurement), **difficult to repeat**

Data Gathering at Statoil (2)

solution 2

ask an **IT expert** to translate the information need into SQL

Data Gathering at Statoil (2)

solution 2

ask an **IT expert** to translate the information need into SQL

```
SELECT
    WELLBORE.IDENTIFIER,
    PTY_PRESSURE.PTY_PRESSURE_S,
    STRATIGRAPHIC_ZONE.STRAT_COLUMN.IDENTIFIER,
    STRATIGRAPHIC_ZONE.STRAT_UNIT.IDENTIFIER
FROM WELLBORE,
    PTY_PRESSURE,
    ACTIVITY FP_DEPTH_DATA
    LEFT JOIN (PTY_LOCATION_1D FP_DEPTH_PT1_LOC
        INNER JOIN PICKED_STRATIGRAPHIC_ZONES ZS
            ON ZS.STRAT_ZONE_ENTRY_MD <= FP_DEPTH_PT1_LOC.DATA_VALUE_1_O AND
               ZS.STRAT_ZONE_EXIT_MD >= FP_DEPTH_PT1_LOC.DATA_VALUE_1_O AND
               ZS.STRAT_ZONE_DEPTH_UOM = FP_DEPTH_PT1_LOC.DATA_VALUE_1_OU
        INNER JOIN STRATIGRAPHIC_ZONE
            ON ZS.WELLBORE = STRATIGRAPHIC_ZONE.WELLBORE AND
               ZS.STRAT_COLUMN.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_COLUMN.IDENTIFIER AND
               ZS.STRAT_INTERP_VERSION = STRATIGRAPHIC_ZONE.STRAT_INTERP_VERSION AND
               ZS.STRAT_ZONE.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_ZONE.IDENTIFIER)
    ON FP_DEPTH_DATA.FACILITY_S = ZS.WELLBORE AND
       FP_DEPTH_DATA.ACTIVITY_S = FP_DEPTH_PT1_LOC.ACTIVITY_S,
    ACTIVITY_CLASS FORM_PRESSURE_CLASS
WHERE WELLBORE.WELLBORE_S = FP_DEPTH_DATA.FACILITY_S AND
    FP_DEPTH_DATA.ACTIVITY_S = PTY_PRESSURE.ACTIVITY_S AND
    FP_DEPTH_DATA.KIND_S = FORM_PRESSURE_CLASS.ACTIVITY_CLASS_S AND
    WELLBORE.REF.EXISTENCE_KIND = 'actual' AND
    FORM_PRESSURE_CLASS.NAME = 'formation pressure depth data'
```

Data Gathering at Statoil (2)

solution 2

ask an **IT expert** to translate the information need into SQL

```
SELECT
  WELLBORE.IDENTIFIER,
  PTY_PRESSURE.PTY_PRESSURE_S,
  STRATIGRAPHIC_ZONE.STRAT_COLUMN.IDENTIFIER,
  STRATIGRAPHIC_ZONE.STRAT_UNIT.IDENTIFIER
FROM WELLBORE,
  PTY_PRESSURE,
  ACTIVITY FP_DEPTH_DATA
  LEFT JOIN (PTY_LOCATION_1D FP_DEPTH_PT1_LOC
    INNER JOIN PICKED_STRATIGRAPHIC_ZONES ZS
      ON ZS.STRAT_ZONE_ENTRY_MD <= FP_DEPTH_PT1_LOC.DATA_VALUE_1_O AND
      ZS.STRAT_ZONE_EXIT_MD >= FP_DEPTH_PT1_LOC.DATA_VALUE_1_O AND
      ZS.STRAT_ZONE_DEPTH_UOM = FP_DEPTH_PT1_LOC.DATA_VALUE_1_OU
    INNER JOIN STRATIGRAPHIC_ZONE
      ON ZS.WELLBORE = STRATIGRAPHIC_ZONE.WELLBORE AND
      ZS.STRAT_COLUMN.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_COLUMN.IDENTIFIER AND
      ZS.STRAT_INTERP_VERSION = STRATIGRAPHIC_ZONE.STRAT_INTERP_VERSION AND
      ZS.STRAT_ZONE.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_ZONE.IDENTIFIER)
  ON FP_DEPTH_DATA.FACILITY_S = ZS.WELLBORE AND
  FP_DEPTH_DATA.ACTIVITY_S = FP_DEPTH_PT1_LOC.ACTIVITY_S,
  ACTIVITY_CLASS FORM_PRESSURE_CLASS
WHERE WELLBORE.WELLBORE_S = FP_DEPTH_DATA.FACILITY_S AND
  FP_DEPTH_DATA.ACTIVITY_S = PTY_PRESSURE.ACTIVITY_S AND
  FP_DEPTH_DATA.KIND_S = FORM_PRESSURE_CLASS.ACTIVITY_CLASS
  WELLBORE.REF_EXISTENCE_KIND = 'actual' AND
  FORM_PRESSURE_CLASS.NAME = 'formation pressure depth data'
```

takes **4 days**
on average (with Slegge only)

Data Gathering at Statoil (2)

solution 2

ask an **IT expert** to translate the information need into SQL

```
SELECT
  WELLBORE.IDENTIFIER,
  PTY.PRESSURE.PTY.PRESSURE_S,
  STRATIGRAPHIC_ZONE.STRAT.COLUMN.IDENTIFIER
```

knowledge of the **geological domain** and **database structure**
(1545 tables and 1727 views, magic values, extensive denormalisation)

```
ON ZS.STRAT_ZONE_ENTRY.MD <= FP.DEPTH_PT1.LOC.DATA.VALUE_1_O AND
  ZS.STRAT_ZONE_EXIT.MD >= FP.DEPTH_PT1.LOC.DATA.VALUE_1_O AND
  ZS.STRAT_ZONE.DEPTH.UOM = FP.DEPTH_PT1.LOC.DATA.VALUE_1_OU
INNER JOIN STRATIGRAPHIC_ZONE
  ON ZS.WELLBORE = STRATIGRAPHIC_ZONE.WELLBORE AND
  ZS.STRAT_COLUMN.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_COLUMN.IDENTIFIER AND
  ZS.STRAT_INTERP_VERSION = STRATIGRAPHIC_ZONE.STRAT_INTERP_VERSION AND
  ZS.STRAT_ZONE.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_ZONE.IDENTIFIER)
ON FP.DEPTH_DATA.FACILITY_S = ZS.WELLBORE AND
  FP.DEPTH_DATA.ACTIVITY_S = FP.DEPTH_PT1.LOC.ACTIVITY_S,
  ACTIVITY_CLASS.FORM.PRESSURE_CLASS
WHERE WELLBORE.WELLBORE_S = FP.DEPTH_DATA.FACILITY_S AND
  FP.DEPTH_DATA.ACTIVITY_S = PTY.PRESSURE.ACTIVITY_S AND
  FP.DEPTH_DATA.KIND_S = FORM.PRESSURE.CLASS.ACTIVITY_CLA
  WELLBORE.REF.EXISTENCE_KIND = 'actual' AND
  FORM.PRESSURE.CLASS.NAME = 'formation pressure depth data'
```

takes **4 days**
on average (with Slegge only)

Data Gathering at Statoil (2)

solution 2

ask an **IT expert** to translate the information need into SQL

```
SELECT  
  WELLBORE.IDENTIFIER,  
  PTY.PRESSURE.PTY.PRESSURE_S,  
  STRATIGRAPHIC_ZONE.STRAT.COLUMN.IDENTIFIER
```

knowledge of the **geological domain** and **database structure**
(1545 tables and 1727 views, magic values, extensive denormalisation)

```
ON ZS.STRAT_ZONE_ENTRY.MD <= FP.DEPTH_PT1.LOC.DATA.VALUE_1_O AND  
  ZS.STRAT_ZONE_EXIT.MD >= FP.DEPTH_PT1.LOC.DATA.VALUE_1_O AND  
  ZS.STRAT_ZONE_DEPTH.LOC.MD = FP.DEPTH_PT1.LOC.DATA.VALUE_1_O
```

encode the domain knowledge in an ontology

```
  ZS.STRAT_COLUMN.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_COLUMN.IDENTIFIER AND  
  ZS.STRAT_INTERP_VERSION = STRATIGRAPHIC_ZONE.STRAT_INTERP_VERSION AND  
  ZS.STRAT_ZONE.IDENTIFIER = STRATIGRAPHIC_ZONE.STRAT_ZONE.IDENTIFIER)  
ON FP.DEPTH_DATA.FACILITY_S = ZS.WELLBORE AND  
  FP.DEPTH_DATA.ACTIVITY_S = FP.DEPTH_PT1.LOC.ACTIVITY_S,  
  ACTIVITY_CLASS.FORM.PRESSURE_CLASS  
WHERE WELLBORE.WELLBORE_S = FP.DEPTH_DATA.FACILITY_S AND  
  FP.DEPTH_DATA.ACTIVITY_S = PTY.PRESSURE.ACTIVITY_S AND  
  FP.DEPTH_DATA.KIND_S = FORM.PRESSURE_CLASS.ACTIVITY_CLASS  
  WELLBORE.REF.EXISTENCE_KIND = 'actual' AND  
  FORM.PRESSURE_CLASS.NAME = 'formation pressure depth data'
```

takes **4 days**
on average (with Slegge only)

Data Gathering at Statoil (2)

solution 2

ask an **IT expert** to translate the information need into SQL

```
SELECT  
  WELLBORE.IDENTIFIER,  
  PTY_PRESSURE.PTY_PRESSURE_S,  
  STRATIGRAPHIC_ZONE_STRAT_COLUMN IDENTIFIED
```

knowledge of the **geological domain** and **database structure**
(1545 tables and 1727 views, magic values, extensive denormalisation)

```
ON ZS.STRAT_ZONE_ENTRY_MD <= FP_DEPTH_PT1_LOC.DATA_VALUE_1_O AND  
  ZS.STRAT_ZONE_EXIT_MD >= FP_DEPTH_PT1_LOC.DATA_VALUE_1_O AND  
  ZS.STRAT_ZONE_DEPTH_UOM = FP_DEPTH_PT1_LOC.DATA_VALUE_1_O
```


encode the domain knowledge in an ontology

and database structure in mappings

```
ON  
  FP_DEPTH_DATA.ACTIVITY_S = FP_DEPTH_PT1_LOC.ACTIVITY_S,  
  ACTIVITY_CLASS FORM_PRESSURE_CLASS  
WHERE WELLBORE.WELLBORE_S = FP_DEPTH_DATA.FACILITY_S AND  
  FP_DEPTH_DATA.ACTIVITY_S = PTY_PRESSURE.ACTIVITY_S AND  
  FP_DEPTH_DATA.KIND_S = FORM_PRESSURE_CLASS.ACTIVITY_CLA  
  WELLBORE.REF_EXISTENCE_KIND = 'actual' AND  
  FORM_PRESSURE_CLASS.NAME = 'formation pressure depth data
```

takes **4 days**
on average (with Slegge only)

Ontology-Based Data Access




```
CREATE TABLE WELLBORE (  
  WELLBORE_S VARCHAR2(19) NOT NULL,  
  WELLBORE_ID VARCHAR2(50) NOT NULL,  
  R_EXISTENCE_KD_NM VARCHAR2(40) NOT NULL,  
  ...  
)
```

```
CREATE TABLE WELLBORE.INTV (  
  WELLBORE.INTV_S VARCHAR2(19) NOT NULL,  
  ACTIVITY_S VARCHAR2(19),  
  EMODEL_OBJECT_ID VARCHAR2(40),  
  ...  
)
```

data source

Ontology-Based Data Access



```
CREATE TABLE WELLBORE (  
  WELLBORE_S VARCHAR2(19) NOT NULL,  
  WELLBORE_ID VARCHAR2(50) NOT NULL,  
  R_EXISTENCE_KD_NM VARCHAR2(40) NOT NULL,  
  ...  
)
```


```
CREATE TABLE WELLBORE.INTV (  
  WELLBORE.INTV_S VARCHAR2(19) NOT NULL,  
  ACTIVITY_S VARCHAR2(19),  
  EMODEL.OBJECT_ID VARCHAR2(40),  
  ...  
)
```

data source

Ontology-Based Data Access

```
SELECT ?w ?depth ?strat_unit
WHERE {
  ?w a :Wellbore . ?w :hasMeasurement ?p .
  ?p a :Pressure . ?p :hasDepth ?depth
  OPTIONAL {
    ?depth :inWellboreInterval ?strat_zone .
    ?strat_zone :hasUnit ?strat_unit
  }
}
```

SPARQL query



```
CREATE TABLE WELLBORE (
  WELLBORE_S VARCHAR2(19) NOT NULL,
  WELLBORE_ID VARCHAR2(50) NOT NULL,
  R_EXISTENCE_KD_NM VARCHAR2(40) NOT NULL,
  ...
)
```

```
CREATE TABLE WELLBORE_INTV (
  WELLBORE_INTV_S VARCHAR2(19) NOT NULL,
  ACTIVITY_S VARCHAR2(19),
  EMODEL_OBJECT_ID VARCHAR2(40),
  ...
)
```

data source


Ontology-Based Data Access

```
SELECT ?w ?depth ?strat_unit
WHERE {
  ?w a :Wellbore . ?w :hasMeasurement ?p .
  ?p a :Pressure . ?p :hasDepth ?depth
  OPTIONAL {
    ?depth :inWellboreInterval ?strat_zone .
    ?strat_zone :hasUnit ?strat_unit
  }
}
```

SPARQL query

```
map:m-00008 a rr:TriplesMap ;
rr:logicalTable [ rr:tableName "STRATIGRAPHIC_ZONE" ] ;
rr:predicateObjectMap [
  rr:predicate expl:hasUnit ;
  rr:objectMap [ rr:termType rr:IRI ;
    rr:template "StratigraphicUnit-{STRAT_COLUMN_ID}-{...}" ]
  ...
]
```

mappings




```
CREATE TABLE WELLBORE (
  WELLBORE_S VARCHAR2(19) NOT NULL,
  WELLBORE_ID VARCHAR2(50) NOT NULL,
  R_EXISTENCE_KD_NM VARCHAR2(40) NOT NULL,
  ...
)
```

```
CREATE TABLE WELLBORE_INTV (
  WELLBORE_INTV_S VARCHAR2(19) NOT NULL,
  ACTIVITY_S VARCHAR2(19),
  EMODEL_OBJECT_ID VARCHAR2(40),
  ...
)
```

data source

Ontology-Based Data Access



reduced time for translating information needs into (SPARQL) queries


days → minutes

Tutorial Plan

- Semantic Web standards
 - RDF (Data Model)
 - OWL 2 QL (Ontology Language)
 - SPARQL (Query Language)
 - R2RML (Mapping Language)
- Tutorial with Ontop
- coffee break
- Using OBDA in Practice
- Basics: Query Rewriting and Optimisation
- Extending the Foundations
 - Approximating Expressive Ontologies
 - Dealing with Identity: SameAs
 - Ontology-Mediated Query Answering and Circuit Complexity
- Recent Advances / Challenges

RDF: Resource Description Framework (RDF in 2004, RDF 1.1 in 2014)


IRIs are identifiers:

`slegge:Wellbore-16/1-29_S`

prefix `http://slegger.gitlab.io/data#`

RDF: Resource Description Framework (RDF in 2004, RDF 1.1 in 2014)

IRIs are identifiers:

`slegge:Wellbore-16/1-29_S`
prefix `http://slegger.gitlab.io/data#`




an **RDF graph**
is a set of triples of the form
subject-predicate-object

RDF: Resource Description Framework (RDF in 2004, RDF 1.1 in 2014)

IRIs are identifiers:

`slegge:Wellbore-16/1-29_S`
prefix `http://slegger.gitlab.io/data#`



an **RDF graph**
is a set of triples of the form
subject-predicate-object

```
@prefix : <http://slegger.gitlab.io/data#> .
@prefix expl: <http://slegger.gitlab.io/slegge-obda/ontology/subsurface-exploration#> .

:Wellbore-16/1-29_S rdf:type expl:Wellbore .
:Wellbore-16/1-29_S expl:name "16/1-29 S" .
:Wellbore-16/1-29_S expl:completionDate "2018-06-03T00:00:00"^^xsd:dateTime .
:Wellbore-16/1-29_S expl:hasFormationPressure :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 rdf:type expl:FormationPressure .
```


Turtle syntax

OWL 2 QL

OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER


OWL 2 QL

OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER



OWL 2 QL


OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER



$\text{FormationPressure} \sqsubseteq \text{Pressure}$ (subclass)

OWL 2 QL

OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER




$\text{FormationPressure} \sqsubseteq \text{Pressure}$ (**subclass**)

$\text{FormationPressure} \sqcap \text{HydrostaticPressure} \sqsubseteq \perp$ (**disjointness**)

OWL 2 QL

OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER




$\text{FormationPressure} \sqsubseteq \text{Pressure}$ (**subclass**)

$\text{FormationPressure} \sqcap \text{HydrostaticPressure} \sqsubseteq \perp$ (**disjointness**)

$\text{hasFormationPressure} \sqsubseteq \text{hasMeasurement}$ (**sub-association**)

OWL 2 QL

OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER



$\text{FormationPressure} \sqsubseteq \text{Pressure}$ (**subclass**)


$\text{FormationPressure} \sqcap \text{HydrostaticPressure} \sqsubseteq \perp$ (**disjointness**)

$\text{hasFormationPressure} \sqsubseteq \text{hasMeasurement}$ (**sub-association**)

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$ (**range/domain**)

OWL 2 QL

OWL 2 QL is based on
the DL-Lite family of descriptions logics
inspired by the **conceptual modelling formalisms**
like UML class diagrams and ER



$\text{FormationPressure} \sqsubseteq \text{Pressure}$ (**subclass**)

$\text{FormationPressure} \sqcap \text{HydrostaticPressure} \sqsubseteq \perp$ (**disjointness**)

$\text{hasFormationPressure} \sqsubseteq \text{hasMeasurement}$ (**sub-association**)

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$ (**range/domain**)

$\text{FormationPressure} \sqsubseteq \exists \text{hasDepth}.\text{Depth}$ (**mandatory participation/multiplicity**)

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

$$\forall x y (\text{hasFormationPressure}(x, y) \rightarrow \text{hasMeasurement}(x, y))$$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

$$\forall xy (\text{hasFormationPressure}(x, y) \rightarrow \text{hasMeasurement}(x, y))$$

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

$$\forall xy (\text{hasFormationPressure}(x, y) \rightarrow \text{hasMeasurement}(x, y))$$

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$

$$\forall xy (\text{hasFormationPressure}(x, y) \rightarrow \text{FormationPressure}(y))$$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

$$\forall xy (\text{hasFormationPressure}(x, y) \rightarrow \text{hasMeasurement}(x, y))$$

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$

$$\forall xy (\text{hasFormationPressure}(x, y) \rightarrow \text{FormationPressure}(y))$$

FormationPressure $\sqsubseteq \exists \text{hasDepth}.\text{Depth}$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

$$\forall x y (\text{hasFormationPressure}(x, y) \rightarrow \text{hasMeasurement}(x, y))$$

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$

$$\forall x y (\text{hasFormationPressure}(x, y) \rightarrow \text{FormationPressure}(y))$$

FormationPressure $\sqsubseteq \exists \text{hasDepth}.\text{Depth}$

$$\forall x (\text{FormationPressure}(x) \rightarrow \exists y (\text{hasDepth}(x, y) \wedge \text{Depth}(y)))$$

Semantics of OWL 2 QL

DLs are **fragments of First-Order Logic**:

classes are **unary predicates** / properties are **binary predicates**

FormationPressure \sqsubseteq Pressure

$$\forall x (\text{FormationPressure}(x) \rightarrow \text{Pressure}(x))$$

FormationPressure \sqcap HydrostaticPressure $\sqsubseteq \perp$

$$\forall x (\text{FormationPressure}(x) \wedge \text{HydrostaticPressure}(x) \rightarrow \perp)$$

hasFormationPressure \sqsubseteq hasMeasurement

$$\forall x y (\text{hasFormationPressure}(x, y) \rightarrow \text{hasMeasurement}(x, y))$$

$\exists \text{hasFormationPressure}^- \sqsubseteq \text{FormationPressure}$

$$\forall x y (\text{hasFormationPressure}(x, y) \rightarrow \text{FormationPressure}(y))$$

FormationPressure $\sqsubseteq \exists \text{hasDepth}.\text{Depth}$

$$\forall x (\text{FormationPressure}(x) \rightarrow \exists y (\text{hasDepth}(x, y) \wedge \text{Depth}(y)))$$

tuple-generating dependencies / existential rules

OWL

Web Ontology Language (OWL) was standardised in 2004; OWL 2 in 2012

OWL 2 QL is one of the three **profiles** of OWL 2

(fragments tailored for specific applications)

OWL 2 QL contains

- subclass axioms, where

existential quantification (ObjectSomeValuesFrom) is limited to **owl:Thing**

OWL

Web Ontology Language (OWL) was standardised in 2004; OWL 2 in 2012

OWL 2 QL is one of the three **profiles** of OWL 2

(fragments tailored for specific applications)

OWL 2 QL contains

- subclass axioms, where **existential quantification** (ObjectSomeValuesFrom) is limited to **owl:Thing**
- **inverse** object properties (InverseObjectProperties)

OWL

Web Ontology Language (OWL) was standardised in 2004; OWL 2 in 2012

OWL 2 QL is one of the three **profiles** of OWL 2

(fragments tailored for specific applications)

OWL 2 QL contains

- subclass axioms, where **existential quantification** (ObjectSomeValuesFrom) is limited to **owl:Thing**
- **inverse** object properties (InverseObjectProperties)
- property domain axioms (ObjectPropertyDomain and DataPropertyDomain)
- property range axioms (ObjectPropertyRange and DataPropertyRange)

OWL

Web Ontology Language (OWL) was standardised in 2004; OWL 2 in 2012

OWL 2 QL is one of the three **profiles** of OWL 2

(fragments tailored for specific applications)

OWL 2 QL contains

- subclass axioms, where **existential quantification** (ObjectSomeValuesFrom) is limited to **owl:Thing**
- **inverse** object properties (InverseObjectProperties)
- property domain axioms (ObjectPropertyDomain and DataPropertyDomain)
- property range axioms (ObjectPropertyRange and DataPropertyRange)
- **property inclusions** (SubObjectPropertyOf but no property chains)

OWL

Web Ontology Language (OWL) was standardised in 2004; OWL 2 in 2012

OWL 2 QL is one of the three **profiles** of OWL 2

(fragments tailored for specific applications)

OWL 2 QL contains

- subclass axioms, where **existential quantification** (ObjectSomeValuesFrom) is limited to **owl:Thing**
- **inverse** object properties (InverseObjectProperties)
- property domain axioms (ObjectPropertyDomain and DataPropertyDomain)
- property range axioms (ObjectPropertyRange and DataPropertyRange)
- **property inclusions** (SubObjectPropertyOf but no property chains)

does not contain

- **universal quantification** (ObjectAllValuesFrom, DataAllValuesFrom)
- **enumeration** of individuals and literals (ObjectOneOf, DataOneOf)
- **disjunction** (ObjectUnionOf, DisjointUnion and DataUnionOf)
- individual equality assertions (**sameAs**) (SameIndividual)

SPARQL: Basic Graph Patterns

SPARQL is the query language for RDF

(SPARQL 1.0 in 2008, SPARQL 1.1 in 2013)

```
SELECT ?w ?d
WHERE {
    ?w a expl:Wellbore .
    ?w expl:hasMeasurement ?p .
    ?p a expl:Pressure .
    ?p expl:hasDepth ?d
}
```

SPARQL: Basic Graph Patterns

SPARQL is the query language for RDF

(SPARQL 1.0 in 2008, SPARQL 1.1 in 2013)

```
SELECT ?w ?d
```

variables to appear in the **query results**

```
WHERE {
```

```
  ?w a expl:Wellbore .
```

```
  ?w expl:hasMeasurement ?p .
```

```
  ?p a expl:Pressure .
```

```
  ?p expl:hasDepth ?d
```

```
}
```

triple patterns separated by .

a abbreviates **rdf:type**

'find all depths of pressure measurements for all wellbores'

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 a expl:Pressure .
:FormationPressure-FP-1249 expl:hasDepth :TVD-FP-1249 .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1377 .
:FormationPressure-FP-1377 a expl:Pressure .
:FormationPressure-FP-1377 expl:hasDepth :TVD-FP-1377 .
```


SPARQL: Basic Graph Patterns

SPARQL is the query language for RDF

(SPARQL 1.0 in 2008, SPARQL 1.1 in 2013)

```
SELECT ?w ?d
```

variables to appear in the **query results**

```
WHERE {
```

```
  ?w a expl:Wellbore .
```

```
  ?w expl:hasMeasurement ?p .
```

```
  ?p a expl:Pressure .
```

```
  ?p expl:hasDepth ?d
```

```
}
```

triple patterns separated by .

a abbreviates **rdf:type**

'find all depths of pressure measurements for all wellbores'

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 a expl:Pressure .
:FormationPressure-FP-1249 expl:hasDepth :TVD-FP-1249 .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1377 .
:FormationPressure-FP-1377 a expl:Pressure .
:FormationPressure-FP-1377 expl:hasDepth :TVD-FP-1377 .
```

answer:

?w	?d
:Wellbore-16/1-29_S	:TVD-FP-1249
:Wellbore-16/1-29_S	:TVD-FP-1377

SPARQL: Basic Graph Patterns

SPARQL is the query language for RDF

(SPARQL 1.0 in 2008, SPARQL 1.1 in 2013)

```
SELECT ?w ?d
```

```
WHERE {
```

```
  ?w a expl:Wellbore .
```

```
  ?w expl:hasMeasurement ?p .
```

```
  ?p a expl:Pressure .
```

```
  ?p expl:hasDepth ?d
```

```
}
```

variables to appear in the **query results**

triple patterns separated by .

a abbreviates **rdf:type**


'find all depths of pressure measurements for all wellbores'

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 a expl:Pressure .
:FormationPressure-FP-1249 expl:hasDepth :TVD-FP-1249 .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1377 .
:FormationPressure-FP-1377 a expl:Pressure .
:FormationPressure-FP-1377 expl:hasDepth :TVD-FP-1377 .
```

answer:

?w	?d
:Wellbore-16/1-29_S	:TVD-FP-1249
:Wellbore-16/1-29_S	:TVD-FP-1377

graph matching



SPARQL: Union

```
SELECT ?w
WHERE {
  { ?w a expl:Wellbore }
  UNION
  { ?w a expl:ExplorationWellbore }
}
```

SPARQL: Union

```
SELECT ?w
```

```
WHERE {
```

```
  { ?w a expl:Wellbore }
```

```
  UNION
```

```
  { ?w a expl:ExplorationWellbore }
```

```
}
```

matches one of **alternative** graph patterns

SPARQL: Union

```
SELECT ?w
```

```
WHERE {
```

```
  { ?w a expl:Wellbore }
```

```
  UNION
```

```
  { ?w a expl:ExplorationWellbore }
```

```
}
```

matches one of **alternative** graph patterns

```
:Wellbore-16/1-29_S a expl:ExplorationWellbore .
```

```
:Wellbore-1/2-U-3 a expl:Wellbore .
```

SPARQL: Union

```
SELECT ?w
```

```
WHERE {
```

```
  { ?w a expl:Wellbore }
```

```
  UNION
```

```
  { ?w a expl:ExplorationWellbore }
```

```
}
```

matches one of **alternative** graph patterns

```
:Wellbore-16/1-29_S a expl:ExplorationWellbore .
```

```
:Wellbore-1/2-U-3 a expl:Wellbore .
```

answer:

?w
:Wellbore-16/1-29_S
:Wellbore-1/2-U-3

SPARQL: Union

```
SELECT ?w
```

```
WHERE {
```

```
  { ?w a expl:Wellbore }
```

```
  UNION
```

```
  { ?w a expl:ExplorationWellbore }
```

```
}
```

matches one of **alternative** graph patterns

```
:Wellbore-16/1-29_S a expl:ExplorationWellbore .
```

```
:Wellbore-1/2-U-3 a expl:Wellbore .
```

answer:

?w
:Wellbore-16/1-29_S
:Wellbore-1/2-U-3

SELECT with Basic Graph Patterns = Conjunctive Queries (CQs)

$\exists p \text{ [Wellbore}(w) \wedge \text{hasMeasurement}(w, p) \wedge \text{Pressure}(p) \wedge \text{hasDepth}(p, d)]$

SELECT with Basic Graph Patterns + UNION \approx Unions of Conjunctive Queries
(UCQs)

$\text{ExplorationWellbore}(w) \vee \text{Wellbore}(w)$

SPARQL: Union

```
SELECT ?w
```

```
WHERE {
```

```
  { ?w a expl:Wellbore }
```

```
  UNION
```

```
  { ?w a expl:ExplorationWellbore }
```

```
}
```

matches one of **alternative** graph patterns

```
:Wellbore-16/1-29_S a expl:ExplorationWellbore .
```

```
:Wellbore-1/2-U-3 a expl:Wellbore .
```

answer:

```
?w
```

```
:Wellbore-16/1-29_S
```

```
:Wellbore-1/2-U-3
```

SELECT with Basic Graph Patterns = Conjunctive Queries (CQs)

$$\exists p \text{ [Wellbore}(w) \wedge \text{hasMeasurement}(w, p) \wedge \text{Pressure}(p) \wedge \text{hasDepth}(p, d)]$$

SELECT with Basic Graph Patterns + UNION \approx Unions of Conjunctive Queries

(UCQs)

$$\text{ExplorationWellbore}(w) \vee \text{Wellbore}(w)$$

observe that `expl:ExplorationWellbore` is naturally a **subclass** of `expl:Wellbore`

why do we need the UNION above then?

Entailment Regime

OWL 2 Direct Semantics Entailment Regime is part of SPARQL 1.1 recommendation
it allows to take account of the **ontology** (subclass & subproperty axioms, etc.)
when **answering** SPARQL queries

Entailment Regime

OWL 2 Direct Semantics Entailment Regime is part of SPARQL 1.1 recommendation
it allows to take account of the **ontology** (subclass & subproperty axioms, etc.)
when **answering** SPARQL queries

if `expl:ExplorationWellbore \sqsubseteq expl:Wellbore`, then

```
SELECT DISTINCT ?w
WHERE {
    ?w a expl:Wellbore
}
```

is equivalent
(under the
entailment
regime)
to

```
SELECT DISTINCT ?w
WHERE {
    { ?w a expl:Wellbore }
    UNION
    { ?w a expl:ExplorationWellbore }
}
```

Entailment Regime

OWL 2 Direct Semantics Entailment Regime is part of SPARQL 1.1 recommendation
it allows to take account of the **ontology** (subclass & subproperty axioms, etc.)
when **answering** SPARQL queries

if `expl:ExplorationWellbore \sqsubseteq expl:Wellbore`, then

```
SELECT DISTINCT ?w
WHERE {
    ?w a expl:Wellbore
}
```

is equivalent
(under the
entailment
regime)
to

```
SELECT DISTINCT ?w
WHERE {
    { ?w a expl:Wellbore }
    UNION
    { ?w a expl:ExplorationWellbore }
}
```

more precisely, when evaluating basic graph patterns (BGPs),
graph matching is replaced by **'entailed by the ontology'**

the semantics of all other constructs of SPARQL is the same

SPARQL: Optional Matching

```
SELECT ?w ?d ?u
WHERE {
    ?w a expl:Wellbore . ?w expl:hasMeasurement ?p .
    ?p a expl:Pressure . ?p expl:hasDepth ?d
    OPTIONAL {
        ?d expl:inWellboreInterval ?z .
        ?z expl:hasUnit ?u
    }
}
```

SPARQL: Optional Matching

```
SELECT ?w ?d ?u
WHERE {
  ?w a expl:Wellbore . ?w expl:hasMeasurement ?p .
  ?p a expl:Pressure . ?p expl:hasDepth ?d
  OPTIONAL {
    ?d expl:inWellboreInterval ?z .
    ?z expl:hasUnit ?u
  }
}
```

if the optional part does not match,
it creates **no bindings**
but **does not eliminate** the solution

SPARQL: Optional Matching

```
SELECT ?w ?d ?u
```

```
WHERE {
```

```
    ?w a expl:Wellbore . ?w expl:hasMeasurement ?p .
```

```
    ?p a expl:Pressure . ?p expl:hasDepth ?d
```

```
    OPTIONAL {
```

```
        ?d expl:inWellboreInterval ?z .
```

```
        ?z expl:hasUnit ?u
```

```
    }
```

```
}
```

if the optional part does not match,
it creates **no bindings**
but **does not eliminate** the solution

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 a expl:Pressure .
:FormationPressure-FP-1249 expl:hasDepth :TVD-FP-1249 .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1377 .
:FormationPressure-FP-1377 a expl:Pressure .
:FormationPressure-FP-1377 expl:hasDepth :TVD-FP-1377 .
:TVD-FP-1377 expl:inWellboreInterval :SZ-4 .
:SZ-4 expl:hasUnit :Stratigraphic-Unit-ROGALAND .
```

SPARQL: Optional Matching

```
SELECT ?w ?d ?u
```

```
WHERE {
```

```
  ?w a expl:Wellbore . ?w expl:hasMeasurement ?p .
```

```
  ?p a expl:Pressure . ?p expl:hasDepth ?d
```

```
  OPTIONAL {
```

```
    ?d expl:inWellboreInterval ?z .
```

```
    ?z expl:hasUnit ?u
```

```
  }
```

```
}
```

if the optional part does not match,
it creates **no bindings**
but **does not eliminate** the solution

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 a expl:Pressure .
:FormationPressure-FP-1249 expl:hasDepth :TVD-FP-1249 .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1377 .
:FormationPressure-FP-1377 a expl:Pressure .
:FormationPressure-FP-1377 expl:hasDepth :TVD-FP-1377 .
:TVD-FP-1377 expl:inWellboreInterval :SZ-4 .
:SZ-4 expl:hasUnit :Stratigraphic-Unit-ROGALAND .
```

answer:

?w	?d	?u
:Wellbore-16/1-29_S	:TVD-FP-1249	—
:Wellbore-16/1-29_S	:TVD-FP-1377	:Stratigraphic-Unit-ROGALAND

SPARQL: Optional Matching

```
SELECT ?w ?d ?u
```

```
WHERE {
```

```
  ?w a expl:Wellbore . ?w expl:hasMeasurement ?p .
```

```
  ?p a expl:Pressure . ?p expl:hasDepth ?d
```

```
  OPTIONAL {
```

```
    ?d expl:inWellboreInterval ?z .
```

```
    ?z expl:hasUnit ?u
```

```
  }
```

```
}
```

if the optional part does not match,
it creates **no bindings**
but **does not eliminate** the solution

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1249 .
:FormationPressure-FP-1249 a expl:Pressure .
:FormationPressure-FP-1249 expl:hasDepth :TVD-FP-1249 .
:Wellbore-16/1-29_S expl:hasMeasurement :FormationPressure-FP-1377 .
:FormationPressure-FP-1377 a expl:Pressure .
:FormationPressure-FP-1377 expl:hasDepth :TVD-FP-1377 .
:TVD-FP-1377 expl:inWellboreInterval :SZ-4 .
:SZ-4 expl:hasUnit :Stratigraphic-Unit-ROGALAND .
```

answer:

?w	?d	?u
:Wellbore-16/1-29_S	:TVD-FP-1249	—
:Wellbore-16/1-29_S	:TVD-FP-1377	:Stratigraphic-Unit-ROGALAND

NB: similar to LEFT JOIN in SQL

Remarks on SPARQL 1.1

we have seen the following features of SPARQL:

- Basic Graph Patterns
- UNION
- OPTIONAL

Remarks on SPARQL 1.1

we have seen the following features of SPARQL:

- Basic Graph Patterns
- UNION
- OPTIONAL

SPARQL 1.1 has many additional features:

- complex FILTER conditions
- GROUP BY, to express aggregations and support aggregation operators
- MINUS, to remove possible solutions
- FILTER NOT EXISTS, to test for the absence of a pattern
- property paths (regular expressions)
- solution modifiers (LIMIT, ORDER BY)
- CONSTRUCT / ASK / DESCRIBE queries
- ...

Mappings Relational Data to RDF

```
SELECT IDENTIFIER FROM WELLBORE  
WHERE REF_EXISTENCE_KIND = 'actual'  
  ~→ Wellbore(iri("Wellbore-", IDENTIFIER))
```

Mappings Relational Data to RDF

```
SELECT IDENTIFIER FROM WELLBORE  
WHERE REF_EXISTENCE_KIND = 'actual'  
  ~> Wellbore(iri("Wellbore-", IDENTIFIER))
```

source query

(in SQL for relational databases)

target query

(atoms in the ontology vocabulary)

Mappings Relational Data to RDF

```
SELECT IDENTIFIER FROM WELLBORE
WHERE REF_EXISTENCE_KIND = 'actual'
  ~> Wellbore(iri("Wellbore-", IDENTIFIER))
```

source query

(in SQL for relational databases)

target query

(atoms in the ontology vocabulary)

the `iri` function constructs IRIs by concatenating any number of strings

WELLBORE table

IDENTIFIER	REF_EXISTENCE_KIND	...
16/1-29_S	actual	...
30/8-5	actual	...
33/10-12	planned	...

Mappings Relational Data to RDF

```
SELECT IDENTIFIER FROM WELLBORE
WHERE REF_EXISTENCE_KIND = 'actual'
  ~> Wellbore(iri("Wellbore-", IDENTIFIER))
```

source query

(in SQL for relational databases)

target query

(atoms in the ontology vocabulary)

the `iri` function constructs IRIs by concatenating any number of strings

WELLBORE table

IDENTIFIER	REF_EXISTENCE_KIND	...
16/1-29_S	actual	...
30/8-5	actual	...
33/10-12	planned	...

result:

```
Wellbore(Wellbore-16/1-29_S)
Wellbore(Wellbore-30/8-5)
      ↑ IRIs
```

R2RML

a language for expressing
customised mappings
from relational databases
to RDF datasets
(W3C recommendation 2012)

```
map:m-00001
  a rr:TriplesMap ;
  rr:logicalTable [
    a rr:R2RMLView ;
    rr:sqlQuery " SELECT * FROM WELLBORE WHERE REF_EXISTENCE_KIND = 'actual' "
  ] ;
  rr:predicateObjectMap [
    a rr:PredicateObjectMap ;
    rr:objectMap [
      a rr:ObjectMap, rr:TermMap ;
      rr:template "http://slegger.gitlab.io/data#TotalCoreLength-{"IDENTIFIER"}" ;
      rr:termType rr:IRI
    ] ;
    rr:predicate expl:hasTotalCoreLength
  ] ;
  rr:subjectMap [
    a rr:SubjectMap, rr:TermMap ;
    rr:class expl:Wellbore ;
    rr:template " http://slegger.gitlab.io/data#Wellbore-{"IDENTIFIER"} " ;
    rr:termType rr:IRI
  ] .
```

R2RML

```
map:m-00001
  a rr:TriplesMap ;
  rr:logicalTable [
    a rr:R2RMLView ;
    rr:sqlQuery " SELECT * FROM WELLBORE WHERE REF_EXISTENCE_KIND = 'actual' "
  ] ;
  rr:predicateObjectMap [
    a rr:PredicateObjectMap ;
    rr:objectMap [
      a rr:ObjectMap, rr:TermMap ;
      rr:template "http://slegger.gitlab.io/data#TotalCoreLength-{IDENTIFIER}" ;
      rr:termType rr:IRI
    ] ;
    rr:predicate expl:hasTotalCoreLength
  ] ;
  rr:subjectMap [
    a rr:SubjectMap, rr:TermMap ;
    rr:class expl:Wellbore ;
    rr:template " http://slegger.gitlab.io/data#Wellbore-{IDENTIFIER} " ;
    rr:termType rr:IRI
  ] .
```

a language for expressing
customised mappings
from relational databases
to RDF datasets
(W3C recommendation 2012)

produces RDF graph

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
```


R2RML

```
map:m-00001
  a rr:TriplesMap ;
  rr:logicalTable [
    a rr:R2RMLView ;
    rr:sqlQuery " SELECT * FROM WELLBORE WHERE REF_EXISTENCE_KIND = 'actual' "
  ] ;
  rr:predicateObjectMap [
    a rr:PredicateObjectMap ;
    rr:objectMap [
      a rr:ObjectMap, rr:TermMap ;
      rr:template "http://slegger.gitlab.io/data#TotalCoreLength-{IDENTIFIER}" ;
      rr:termType rr:IRI
    ] ;
    rr:predicate expl:hasTotalCoreLength
  ] ;
  rr:subjectMap [
    a rr:SubjectMap, rr:TermMap ;
    rr:class expl:Wellbore ;
    rr:template " http://slegger.gitlab.io/data#Wellbore-{IDENTIFIER} " ;
    rr:termType rr:IRI
  ] .
```

a language for expressing
customised mappings
from relational databases
to RDF datasets
(W3C recommendation 2012)

produces RDF graph

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
```

NB: is this a GAV (Global-As-View) mapping?

R2RML

```
map:m-00001
  a rr:TriplesMap ;
  rr:logicalTable [
    a rr:R2RMLView ;
    rr:sqlQuery " SELECT * FROM WELLBORE WHERE REF_EXISTENCE_KIND = 'actual' "
  ] ;
  rr:predicateObjectMap [
    a rr:PredicateObjectMap ;
    rr:objectMap [
      a rr:ObjectMap, rr:TermMap ;
      rr:template "http://slegger.gitlab.io/data#TotalCoreLength-{IDENTIFIER}" ;
      rr:termType rr:IRI
    ] ;
    rr:predicate expl:hasTotalCoreLength
  ] ;
  rr:subjectMap [
    a rr:SubjectMap, rr:TermMap ;
    rr:class expl:Wellbore ;
    rr:template " http://slegger.gitlab.io/data#Wellbore-{IDENTIFIER} " ;
    rr:termType rr:IRI
  ] .
```

a language for expressing
customised mappings
from relational databases
to RDF datasets
(W3C recommendation 2012)

produces RDF graph

```
:Wellbore-16/1-29_S a expl:Wellbore .
:Wellbore-30/8-5 a expl:Wellbore .
```

NB: is this a GAV (Global-As-View) mapping?

not quite — the IRI function can simulate GLAV (more in part 2. ...)

References

1. G. Xiao, D. Calvanese, R. Kontchakov, D. Lembo, A. Poggi, R. Rosati & M. Zakharyashev. "Ontology-Based Data Access: A Survey". In: Proc. of the 27th Int. Joint Conf. on Artificial Intelligence, IJCAI-ECAI 2018, 5511–5519. ijcai.org, 2018.
2. D. Calvanese, G. De Giacomo, D. Lembo, M. Lenzerini & R. Rosati. "Tractable reasoning and efficient query answering in description logics: The DL-Lite family." In: JAR, 39(3):385–429, 2007.
3. "RDF 1.1 Concepts and Abstract Syntax" R. Cyganiak, D. Wood, M. Lanthaler, editors. W3C, 2014.
<https://www.w3.org/TR/rdf11-concepts>
4. "OWL 2 Web Ontology Language Profiles (Second Edition)" B. Motik, B. Cuenca Grau, I. Horrocks, Z. Wu, A. Fokoue, C. Lutz, editors. W3C, 2012.
<https://www.w3.org/TR/owl2-profiles>
5. "SPARQL 1.1 Query Language" S. Harris & A. Seaborne, editors. W3C, 2013.
<https://www.w3.org/TR/sparql11-query>
6. "R2RML: RDB to RDF Mapping Language" S. Das, S. Sundara, R. Cyganiak, editors. W3C, 2012.
<https://www.w3.org/TR/r2rml>