

ONLINE ACTIVITY #2
10 BASIC LINUX COMMANDS

Commands	Syntax	Sample Usage
ls	ls [options] [directory]	Listing directories and files available in the current working directory.
pwd	pwd	Show the current full path directory.
mkdir	mkdir directory_name	Create a new folders or directories.
cd	cd directory_name	Change the current directory working.
rmdir	rmdir directory_name	Remove or delete directories empty.
cat	cat file_name	Display the content of the file and merge many files.
cp	cp source destination	Used to copy files and directories.
mv	mv old_name new_name	Used to rename or move directories and files.
rm	rm file_name	Remove or delete permanently the files.
uname	uname [options]	Used to show the information of the system.

BASIC GIT COMMANDS

Git Commands	Sample Usage	Description	Common Oprion/Flag
git init	git init	Create and start new git repository.	-q (quiet mode)
git status	git status	View the current state of git repository.	- s (show branch info)
git add	git add {filename}/ git add .	Starts to add track changes in the staging area.	. – (stage all changes)
git commit	git commit –m “message”	Display the message committed and save changes in local repository.	-m – add commit message -a – stage modified/deleted files
git log	git log	Show the history of changes commit in repository	-all – show all branches
git diff	git diff	Show differences two set of changes	--stat – display summary
git restore	git restore <filename>	Restore changes that not committed	--source <branch> - restore another source
git branch	git branch	Creates, delete and rename branch	-a – show local branches -d – delete branch -m – rename branch
git checkout / git switch	git checkout main	Switch different branches	-b <name> - create and switch new branch
git merge	git merge <feature/branch>	Combines changes in different branches	--no-ff – create a merge commit
git tag	git tag <name>	Create a annotated to a specific commit history.	-a – annotated tag -d – delete tag -l – list tags
git clone	git clone <url>	Creates a local copy of remote repository	-b <branch> - clone a specific branch --depth 1 – shallow clone

THE THREE-TREE ARCHITECTURE OF GIT

Working Directory	- It is also called working tree. Basically, this is the area wherein the programmers start to develop create and edit changes in their code by using IDE. It tracks the states of developer's changes of code and creation of files.
Staging Area	- This is where the files prepare to stage between working directory and repository. It prepare the changes before committed it in the repository and the developers can choose where to commit it before adding them in staging area.
Repository (git directory)	- It is the .git directory of your working directory. It stores the history of changes made in the code base. It displays all the versions made by the developers including the previous and current versions. When the developers commit, the git automatically take a snapshot of the code create by the developer then store it in the git repository.

*“The author used **GeeksforGeeks- “Basic Linux Commands”, InflectraCorporation- “Basic Git Command Cheat Sheat”** and **hashnode.dev-“git three-stage architecture”** to list 10 basic linux commands, know the git commands and to know the stages of three-tree architecture of git during assignment preparation. The author reviewed and edited the content as needed and takes full responsibility for the final content of the work.”*