## 自動構築前

ifcfg-eno1

TYPE="Ethernet"

PROXY METHOD="none"

BROWSER ONLY="no"

BOOTPROTO="none"

DEFROUTE="yes"

IPV4\_FAILURE\_FATAL="no"

IPV6INIT="yes"

IPV6\_AUTOCONF="yes"

IPV6 DEFROUTE="yes"

IPV6\_FAILURE\_FATAL="no"

IPV6\_ADDR\_GEN\_MODE="stable-privacy"

NAME="eno1"

UUID="cdc9f1c5-667b-41f8-9c99-c1672e0d3a13"

DEVICE="eno1"

ONBOOT="yes"

IPADDR="172.19.78.112"

PREFIX="24"

GATEWAY="172.19.78.1"

DNS1="172.19.78.1"

IPV6 PRIVACY="no"

NETBOOT=yes

IPV6\_PEERDNS=yes

IPV6\_PEERROUTES=yes

## 自動構築後

ifcfg-eno1

DEVICE=eno1 NAME=eno1

DEVICETYPE=ovs

TYPE=OVSPort

OVS\_BRIDGE=br-ex

ifcfg-br-ex

PROXY\_METHOD="none" BROWSER\_ONLY="no" DEFROUTE="yes"

DLI ROUTE - yes

 ${\tt UUID = "cdc9f1c5-667b-41f8-9c99-c1672e0d3a13"}$ 

ONBOOT="yes"

ONBOOT=yes BOOTPROTO=none IPADDR="172.19.78.112"

PREFIX="24"

GATEWAY="172.19.78.1"

DEVICE=br-ex

NAME=br-ex

DEVICETYPE=ovs

OVSBOOTPROTO="none"

TYPE=OVSBridge

OVS\_EXTRA="set bridge br-ex fail\_mode=standalone"