

Football Analytics & Community API

API Documentation

Module

COMP3011 – Web Services and Web Data

Project

Football Analytics & Community REST API

Student

202049082 Hany Song

Version

1.0

1. Overview

This document describes the REST API developed for the COMP3011 coursework project.

The API provides two main domains of functionality:

1. **Football analytics data**
2. **Community discussion features**

The football component allows users to explore teams, players, matches, and statistical analytics such as top scorers, assists, and league standings. The community component enables registered users to create posts, comment on discussions, and interact through a like system.

The system is implemented using **Django REST Framework** and exposes a RESTful API designed to support both analytical queries and community interaction.

The API supports:

- browsing football teams, players, and matches
- player and team analytics
- league standings computation
- community posts and comments
- user authentication and profile management
- like functionality for posts and comments
- pagination and filtering

The detailed endpoint specification included in this document is automatically generated from the OpenAPI schema.

2. Base URL

All API endpoints are accessible under the following base URL:

```
http://16.171.63.159/api/
```

Example endpoint:

```
GET /api/players/
```

Full request example:

```
http://16.171.63.159/api/players/
```

3. Authentication

Authentication is implemented using **Token Authentication**.

Users must first register an account and then obtain a token via the login endpoint.

Register

```
POST /api/auth/register/
```

Example request:

```
{
  "username": "user1",
  "email": "user@example.com",
  "password": "password123",
  "display_name": "User One",
  "bio": "Football fan",
  "favourite_team": 1
}
```

Successful response:

```
{
  "message": "User registered successfully",
  "token": "abc123...",
  "user": {
    "id": 1,
    "username": "user1"
  }
}
```

Login

```
POST /api/auth/login/
```

Example request:

```
{
  "username": "user1",
  "password": "password123"
}
```

Example response:

```
{
  "message": "Login successful",
  "token": "abc123...",
  "user": {
    "id": 1,
    "username": "user1",
    "email": "user@example.com"
  }
}
```

Using the token

Protected endpoints require the following header:

```
Authorization: Token <your_token>
```

Example:

```
Authorization: Token 9c8a1c3f2c...
```

Endpoints requiring authentication include:

- creating posts
- editing posts
- creating comments
- liking posts or comments
- deleting content
- deleting user accounts

4. Pagination

Many list endpoints use **pagination** to limit response size.

Example request:

```
GET /api/players/?page=2
```

Typical paginated response:

```
{
  "count": 100,
  "next": "http://example/api/players/?page=3",
  "previous": "http://example/api/players/?page=1",
  "results": [ ... ]
}
```

5. Filtering and Query Parameters

Several endpoints support filtering using query parameters.

Examples include:

Search players by name

```
GET /api/players/?name=Saka
```

Filter players by team

```
GET /api/players/?team_id=1
```

Filter matches by season

```
GET /api/matches/?season=2023
```

Analytics query

```
GET /api/analytics/top-scorers/?season=2023&limit=10
```

These query parameters allow flexible filtering of football statistics and analytics.

6. Error Handling

The API uses standard HTTP status codes to indicate success or failure.

Code	Meaning
200	OK
201	Created
204	No Content
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
429	Rate limit exceeded

Example Error Responses

400 – Bad Request

Returned when the request payload is invalid or missing required fields.

Example:

```
{
  "error": "Invalid request data"
}
```

Another possible example (validation error):

```
{
  "username": [
    "This field is required."
  ]
}
```

401 – Unauthorized

Returned when authentication credentials are missing or invalid.

Example:

```
{
  "detail": "Authentication credentials were not provided."
}
```

or

```
{
  "detail": "Invalid token."
}
```

404 – Not Found

Returned when a requested resource does not exist.

Example:

```
{
  "detail": "Not found."
}
```

7. API Specification

The following pages contain the **automatically generated OpenAPI specification** for the REST API.

This specification includes:

- endpoint definitions
- request parameters
- request body schemas
- response schemas
- example responses
- authentication requirements

The specification is generated directly from the Django REST Framework OpenAPI schema to ensure that the documentation accurately reflects the implemented API.

COMP3011-1 API (1.0.0)

Download OpenAPI specification: [Download](#)

REST API for football teams, players, matches, analytics, and community discussion features.

Authentication

User registration, login, and current user profile

Delete current user account

Deletes the authenticated user's account and profile.

AUTHORIZATIONS: > *tokenAuth*

Responses

> 200

> 401

DELETE /api/auth/delete/

Response samples

200

401

Content type
application/json

Copy

```
{  
  "message": "string"  
}
```

Login and get auth token

AUTHORIZATIONS: > *tokenAuth* or None

REQUEST BODY SCHEMA: application/json ▼

┌	username	string
	required	
└	password	string
	required	

Responses

> 200

> 400

> 401

POST /api/auth/login/ ▼

Request samples

Payload

Content type
application/json ▼

Copy

```
{  
  "username": "string",  
}
```

```
"password": "string"
}
```

Response samples

200

400

401

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "message": "string",
  "token": "string",
  - "user": {
    "id": 0,
    "username": "string",
    "email": "user@example.com",
    - "profile": {
      "display_name": "string",
      "bio": "string",
      "favourite_team": 0,
      "favourite_team_name": "string",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  }
}
```

Logout current user

Deletes the current user's authentication token.

AUTHORIZATIONS: >

tokenAuth

Responses

> 200

> 401

POST /api/auth/logout/

Response samples

200

401

Content type
application/json

Copy

```
{  
  "message": "string"  
}
```

Get current authenticated user

AUTHORIZATIONS: > *tokenAuth*

Responses

> 200

GET /api/auth/me/

Response samples

200

Content type
application/json

```
{
  "id": 0,
  "username": "string",
  "email": "user@example.com",
  - "profile": {
    "display_name": "string",
    "bio": "string",
    "favourite_team": 0,
    "favourite_team_name": "string",
    "created_at": "2019-08-24T14:15:22Z",
    "updated_at": "2019-08-24T14:15:22Z"
  }
}
```

Register a new user

AUTHORIZATIONS: > *tokenAuth* or None

REQUEST BODY SCHEMA: application/json ▼

username required	string
email required	string <email>
password required	string
display_name required	string
bio	string
favourite_team	integer or null

Responses

> 201

> 400

POST /api/auth/register/



Request samples

Payload

Content type

application/json



Copy

```
{
  "username": "string",
  "email": "user@example.com",
  "password": "string",
  "display_name": "string",
  "bio": "string",
  "favourite_team": 0
}
```

Response samples

201

400

Content type

application/json

Copy Expand all Collapse all

```
{
  "message": "string",
  "token": "string",
}
```

```
- "user": {
  "id": 0,
  "username": "string",
  "email": "user@example.com",
  - "profile": {
    "display_name": "string",
    "bio": "string",
    "favourite_team": 0,
    "favourite_team_name": "string",
    "created_at": "2019-08-24T14:15:22Z",
    "updated_at": "2019-08-24T14:15:22Z"
  }
}
```

Teams

Team-related endpoints

List all teams

AUTHORIZATIONS: > *tokenAuth* or None

QUERY PARAMETERS

 page	integer A page number within the paginated result set.
--	---

Responses

> 200

GET /api/teams/



Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  - "results": [
    - {
      "id": 0,
      "external_id": "string",
      "name": "string",
      "short_name": "string",
      "country": "string",
      "competition": "string",
      "season": -9223372036854776000,
      "stadium": "string",
      "founded": -9223372036854776000,
      "logo_url": "http://example.com",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Retrieve team details

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ id
required integer

Responses

> 200

GET /api/teams/{id}/



Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "external_id": "string",
  "name": "string",
  "short_name": "string",
  "country": "string",
  "competition": "string",
  "season": -9223372036854776000,
  "stadium": "string",
  "founded": -9223372036854776000,
  "logo_url": "http://example.com",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

List matches for a team

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ id required	integer
QUERY PARAMETERS	
└─ page	integer A page number within the paginated result set.
└─ season	integer Filter matches by season year

Responses

> 200

GET /api/teams/{id}/matches/

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
}
```

```
- "results": [  
  - {  
    "id": 0,  
    "external_id": "string",  
    "competition": "string",  
    "season": -9223372036854776000,  
    "match_date": "2019-08-24T14:15:22Z",  
    "home_team": 0,  
    "home_team_name": "string",  
    "away_team": 0,  
    "away_team_name": "string",  
    "home_score": -9223372036854776000,  
    "away_score": -9223372036854776000,  
    "venue": "string",  
    "attendance": -9223372036854776000,  
    "created_at": "2019-08-24T14:15:22Z",  
    "updated_at": "2019-08-24T14:15:22Z"  
  }  
]  
}
```

List players in a team

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ `id`
required integer

QUERY PARAMETERS

→ `page` integer
A page number within the paginated result set.

Responses

> 200

GET /api/teams/{id}/players/



Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  - "results": [
    - {
      "id": 0,
      "external_id": "string",
      "name": "string",
      "full_name": "string",
      "nationality": "string",
      "position": "string",
      "current_team": 0,
      "current_team_name": "string",
      "market_value": -9223372036854776000,
      "height_cm": -9223372036854776000,
      "preferred_foot": "string",
      "image_url": "http://example.com",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Players

List all players

AUTHORIZATIONS: > *tokenAuth* or None

QUERY PARAMETERS

name	string Search players by name
nationality	string Filter players by nationality
ordering	string Order by one of: name, nationality, position, height_cm, market_value. Prefix with '-' for descending.
page	integer A page number within the paginated result set.
position	string Filter players by position
team_id	integer Filter players by team id

Responses

> 200

GET /api/players/

Response samples

200

Content type
application/json

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  - "results": [
    - {
      "id": 0,
      "external_id": "string",
      "name": "string",
      "full_name": "string",
      "nationality": "string",
      "position": "string",
      "current_team": 0,
      "current_team_name": "string",
      "market_value": -9223372036854776000,
      "height_cm": -9223372036854776000,
      "preferred_foot": "string",
      "image_url": "http://example.com",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Retrieve player details

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ **id**
required integer

Responses

> 200

GET /api/players/{id}/



Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "external_id": "string",
  "name": "string",
  "full_name": "string",
  "nationality": "string",
  "position": "string",
  "current_team": 0,
  "current_team_name": "string",
  "market_value": -9223372036854776000,
  "height_cm": -9223372036854776000,
  "preferred_foot": "string",
  "image_url": "http://example.com",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

List appearances for a player

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

— id
required integer

QUERY PARAMETERS

— season integer
Filter appearances by season year

Responses

> 200

GET /api/players/{id}/appearances/

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
[
  - {
    "match_id": 0,
    "season": 0,
    "match_date": "2019-08-24",
    "home_team": "string",
    "away_team": "string",
    "team": "string",
    "goals": 0,
    "assists": 0,
    "minutes_played": 0
  }
]
```

List matches played by a player

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ id
required integer

QUERY PARAMETERS

— page

integer

A page number within the paginated result set.

Responses

> 200

GET

/api/players/{id}/matches/



Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
```



```
- "results": [  
  - {  
    "id": 0,  
    "external_id": "string",  
    "competition": "string",  
    "season": -9223372036854776000,  
    "match_date": "2019-08-24T14:15:22Z",  
    "home_team": 0,  
    "home_team_name": "string",  
    "away_team": 0,  
    "away_team_name": "string",  
    "home_score": -9223372036854776000,  
    "away_score": -9223372036854776000,  
    "venue": "string",  
    "attendance": -9223372036854776000,  
    "created_at": "2019-08-24T14:15:22Z",  
    "updated_at": "2019-08-24T14:15:22Z"  
  }  
]  
}
```

Matches

Match-related endpoints

List all matches

AUTHORIZATIONS: > *tokenAuth* or None

QUERY PARAMETERS

page	integer A page number within the paginated result set.
season	integer Filter matches by season year
team_id	integer

Responses

> 200

GET /api/matches/



Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  - "results": [
    - {
      "id": 0,
      "external_id": "string",
      "competition": "string",
      "season": -9223372036854776000,
      "match_date": "2019-08-24T14:15:22Z",
      "home_team": 0,
      "home_team_name": "string",
      "away_team": 0,
      "away_team_name": "string",
      "home_score": -9223372036854776000,
      "away_score": -9223372036854776000,
      "venue": "string",
      "attendance": -9223372036854776000,
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Retrieve match details

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ id
required integer

Responses

> 200

GET /api/matches/{id}/



Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": 0,
  "external_id": "string",
  "competition": "string",
  "season": -9223372036854776000,
  "match_date": "2019-08-24T14:15:22Z",
  "home_team": 0,
  "home_team_name": "string",
  "away_team": 0,
  "away_team_name": "string",
  "home_score": -9223372036854776000,
  "away_score": -9223372036854776000,
  "venue": "string",
  "attendance": -9223372036854776000,
  - "appearances": [
    - {
      "id": 0,
      "player": 0,
      "player_name": "string",
      "team": 0,
      "team_name": "string",
      "minutes_played": -9223372036854776000,
      "goals": -9223372036854776000,
      "assists": -9223372036854776000,
      "yellow_cards": -9223372036854776000,
      "red_cards": -9223372036854776000,
      "position_played": "string",
      "rating": 0,
      "is_starter": true,
      "appearance_date": "2019-08-24"
    }
  ],
  "created_at": "2019-08-24T14:15:22Z",
```

```
"updated_at": "2019-08-24T14:15:22Z"
}
```

Analytics

Computed football statistics and leaderboards

Get players with most minutes played

AUTHORIZATIONS: > *tokenAuth* or None

QUERY PARAMETERS

limit	integer Number of results to return
season	integer Season year, e.g. 2023

Responses

> 200

GET /api/analytics/most-minutes/

Response samples

200

Content type
application/json

CopyExpand allCollapse all

```
[
  - {
    "player_id": 0,
    "player_name": "string",
    "team": "string",
    "total_minutes": 0,
    "season": 0
  }
]
```

Get Premier League standings for a season

AUTHORIZATIONS: > tokenAuth or None

QUERY PARAMETERS

season	integer
Season year, e.g. 2023. If omitted, latest season is used.	

Responses

> 200

GET /api/analytics/standings/

Response samples

200

Content type
application/json

CopyExpand allCollapse all

```
[
  - {
    "position": 0,
    "team_id": 0,
    "team": "string",
    "played": 0,
    "wins": 0,
    "draws": 0,
    "losses": 0,
    "goals_for": 0,
    "goals_against": 0,
    "goal_difference": 0,
    "points": 0,
    "season": 0
  }
]
```

Get top assists

AUTHORIZATIONS: > *tokenAuth* or None

QUERY PARAMETERS

limit	integer Number of results to return
season	integer Season year, e.g. 2023

Responses

> 200

GET /api/analytics/top-assists/



Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "player_id": 0,
    "player_name": "string",
    "team": "string",
    "total_assists": 0,
    "season": 0
  }
]
```

Get top scorers

AUTHORIZATIONS: >

tokenAuth or None

QUERY PARAMETERS

limit	integer Number of results to return
season	integer Season year, e.g. 2023

Responses

> 200

GET /api/analytics/top-scorers/



Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "player_id": 0,
    "player_name": "string",
    "team": "string",
    "total_goals": 0,
    "season": 0
  }
]
```

Get top scorers for a team

AUTHORIZATIONS: >

tokenAuth or None

PATH PARAMETERS

→ id
required integer

QUERY PARAMETERS

└ limit
integer
Number of results to return

└ season
integer
Season year, e.g. 2023

Responses

> 200

GET /api/teams/{id}/top-scorers/



Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
[
  - {
    "player_id": 0,
    "player_name": "string",
    "team": "string",
    "total_goals": 0,
    "season": 0
  }
]
```

Posts

Community discussion posts

List all community posts

AUTHORIZATIONS: > *tokenAuth* or None

QUERY PARAMETERS

ordering	string Which field to use when ordering the results.
page	integer A page number within the paginated result set.

Responses

> 200

GET /api/posts/



Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  - "results": [
    - {
      "id": 0,
      "author": 0,
      "author_username": "string",
      "title": "string",
      "content": "string",
      "related_team": 0,
      "related_player": 0,
      "comment_count": 0,
      "like_count": 0,
      "is_liked_by_me": "string",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Create a new community post

AUTHORIZATIONS: > tokenAuth

REQUEST BODY SCHEMA: application/json ▾

title	string	<= 200 characters
required		
content	string	
required		
related_team	integer or null	
related_player	integer or null	

Responses

> 201

POST /api/posts/ ▾

Request samples

Payload

Content type

application/json ▾

Copy

```
{
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0
}
```

Response samples

201

Content type

application/json

Copy

```
{
  "id": 0,
  "author": 0,
  "author_username": "string",
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0,
  "comment_count": 0,
  "like_count": 0,
  "is_liked_by_me": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

Retrieve post details

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ id
required integer

Responses

> 200

GET /api/posts/{id}/



Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "author": 0,
  "author_username": "string",
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0,
  "comment_count": 0,
  "like_count": 0,
  "is_liked_by_me": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

Update a post

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

id
required integer

REQUEST BODY SCHEMA: application/json ▼

title
required string <= 200 characters

content
required string

related_team integer or null

related_player integer or null

Responses

> 200

PUT /api/posts/{id}/



Request samples

Payload

Content type

application/json



Copy

```
{
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0
}
```

Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "author": 0,
  "author_username": "string",
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0,
  "comment_count": 0,
  "like_count": 0,
  "is_liked_by_me": "string",
}
```

```
"created_at": "2019-08-24T14:15:22Z",
"updated_at": "2019-08-24T14:15:22Z"
}
```

Partially update a post

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

id *required* integer

REQUEST BODY SCHEMA: application/json ▼

title string ≤ 200 characters

content string

related_team integer or null

related_player integer or null

Responses

> 200

PATCH /api/posts/{id}/ ▼

Request samples

Payload

Content type
application/json ▼

Copy


```
{
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0
}
```

Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "author": 0,
  "author_username": "string",
  "title": "string",
  "content": "string",
  "related_team": 0,
  "related_player": 0,
  "comment_count": 0,
  "like_count": 0,
  "is_liked_by_me": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

Delete a post

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

→ id
required integer

Responses

— 204 No response body

DELETE /api/posts/{id}/



Like a post

Adds the authenticated user's like to the specified post.

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

id
required integer

Responses

— 200 No response body

POST /api/posts/{id}/like/



Remove like from a post

Removes the authenticated user's like from the specified post.

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

→ id
required

integer

Responses

— 204 No response body

DELETE

/api/posts/{id}/like/



Comments

Community comments

List comments for a post

AUTHORIZATIONS: > tokenAuth or None

QUERY PARAMETERS

→ page

integer

A page number within the paginated result set.

→ post_id
required

integer

ID of the post whose comments should be returned

Responses

> 200

GET /api/comments/



Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  - "results": [
    - {
      "id": 0,
      "post": 0,
      "author": 0,
      "author_username": "string",
      "content": "string",
      "like_count": 0,
      "is_liked_by_me": "string",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Create a new comment

AUTHORIZATIONS: > tokenAuth

REQUEST BODY SCHEMA: application/json

post required	integer
content required	string

Responses

> 201

POST /api/comments/

Request samples

Payload

Content type

application/json

Copy

```
{
  "post": 0,
  "content": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
  "id": 0,
  "post": 0,
  "author": 0,
  "author_username": "string",
  "content": "string",
  "like_count": 0,
  "is_liked_by_me": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

Retrieve comment details

AUTHORIZATIONS: > *tokenAuth* or None

PATH PARAMETERS

→ id
required integer

Responses

> 200

GET /api/comments/{id}/

Response samples

200

Content type
application/json

Copy

```
{
  "id": 0,
```

```
"post": 0,
"author": 0,
"author_username": "string",
"content": "string",
"like_count": 0,
"is_liked_by_me": "string",
"created_at": "2019-08-24T14:15:22Z",
"updated_at": "2019-08-24T14:15:22Z"
}
```

Update a comment

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

→ id
required integer

REQUEST BODY SCHEMA: application/json ▼

post
required integer

content
required string

Responses

> 200

PUT /api/comments/{id}/ ▼

Request samples

Payload

Content type

application/json



Copy

```
{
  "post": 0,
  "content": "string"
}
```

Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "post": 0,
  "author": 0,
  "author_username": "string",
  "content": "string",
  "like_count": 0,
  "is_liked_by_me": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

Partially update a comment

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

— id
required integer

REQUEST BODY SCHEMA: application/json ▾

— post
integer

Responses

> 200

PATCH /api/comments/{id}/



Request samples

Payload

Content type

application/json



Copy

```
{
  "post": 0,
  "content": "string"
}
```

Response samples

200

Content type

application/json

Copy

```
{
  "id": 0,
  "post": 0,
  "author": 0,
  "author_username": "string",
  "content": "string",
  "like_count": 0,
  "is_liked_by_me": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "updated_at": "2019-08-24T14:15:22Z"
}
```

```
}
```

Delete a comment

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

→ *id*
required integer

Responses

— 204 No response body

DELETE /api/comments/{id}/



Like a comment

Adds the authenticated user's like to the specified comment.

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

→ *id*
required integer

Responses

— 200 No response body

POST /api/comments/{id}/like/



Remove like from a comment

Removes the authenticated user's like from the specified comment.

AUTHORIZATIONS: > *tokenAuth*

PATH PARAMETERS

id
required integer

Responses

— 204 No response body

DELETE /api/comments/{id}/like/

