Floating Point

Chapter 2.4

Eunji Lee
(ejlee@ssu.ac.kr)

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Fractional binary numbers

- What is 1011.101_2?

Fractional Binary Numbers



- Representation
  - Bits to right of "binary point" represent fractional powers of 2
  - Represents rational number:

$$\sum_{k=-j}^{i} b_k \times 2^k$$

Fractional Binary Numbers: Examples

- Value / Representation

Value	Representation
5 3/4	$\mathbf{101.11}_2$
2 7/8	$\mathbf{10.111}_2$
1 7/16	$\mathbf{1.0111}_2$

- Observations
  - Divide by 2 by shifting right (unsigned)
  - Multiply by 2 by shifting left
  - Numbers of form $0.111111\ldots_2$ are just below 1.0
    - $1/2 + 1/4 + 1/8 + \ldots + 1/2^i + \ldots \rightarrow 1.0$
    - Use notation $1.0 - \varepsilon$

Representable Numbers

- Limitation #1
  - Can only exactly represent numbers of the form $x/2^k$
    - Other rational numbers have repeating bit representations
  - Value Representation
    - 1/3 `0.0101010101[01]`…$_2$
    - 1/5 `0.001100110011[0011]`…$_2$
    - 1/10 `0.0001100110011[0011]`…$_2$

- Limitation #2
  - Just one setting of binary point within the *w* bits
    - Limited range of numbers (very small values? very large?)

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

IEEE Floating Point

- IEEE Standard 754
  - Established in 1985 as uniform standard for floating point arithmetic
    - Before that, many idiosyncratic formats
  - Supported by all major CPUs

- Driven by numerical concerns
  - Nice standards for rounding, overflow, underflow
  - Hard to make fast in hardware
    - Numerical analysts predominated over hardware designers in defining standard

Floating Point Representation

- **Numerical Form:**

$$(-1)^s\ M\ \ 2^E$$

  - Sign bit s determines whether number is negative or positive
  - Significand M normally a fractional value in range [1.0,2.0).
  - Exponent E weights value by power of two

- **Encoding**
  - MSB s is sign bit s
  - exp field encodes E (but is not equal to E)
  - frac field encodes M (but is not equal to M)

Precision options

- Single precision: 32 bits

s	exp	frac
1	8-bits	23-bits

- Double precision: 64 bits

s	exp	frac
1	11-bits	52-bits

- Extended precision: 80 bits (Intel only)

s	exp	frac
1	15-bits	63 or 64-bits

“Normalized” Values

$v = (-1)^s M 2^E$

- When: exp ≠ 000…0 and exp ≠ 111…1

- Exponent coded as a biased value: E = Exp – Bias
  - Exp: unsigned value of exp field
  - Bias = 2^{k-1} - 1, where k is number of exponent bits
    - Single precision: 127 (Exp: 1…254, E: -126…127)
    - Double precision: 1023 (Exp: 1…2046, E: -1022…1023)

- Significand coded with implied leading 1: M = $1.xxx…x_2$
  - xxx…x: bits of frac field
  - Minimum when frac=000…0 (M = 1.0)
  - Maximum when frac=111…1 (M = 2.0 – ε)
  - Get extra leading bit for “free”

Normalized Encoding Example

$v = (-1)^s M 2^E$
$E = \text{Exp} - \text{Bias}$

- **Value:** `float F = 15213.0;`
  - $15213_{10} = 11101101101101_2$
    $= 1.1101101101101_2 \times 2^{13}$

- **Significand**

  M = `1.`$\underline{\texttt{1101101101101}}_2$

  `frac=` $\underline{\texttt{1101101101101}}\texttt{0000000000}_2$

- **Exponent**

  E = 13

  $Bias$ = 127

  Exp = 140 = $\texttt{10001100}_2$

- **Result:**

s	exp	frac
0	10001100	11011011011010000000000

Denormalized Values

$v = (-1)^s M\ 2^E$
$E = 1 - \text{Bias}$

- Condition: exp = 000…0
- Exponent value: E = 1 – Bias (instead of E = 0 – Bias)
- Significand coded with implied leading 0: $M = 0.xxx…x_2$
  - **`xxx`**…**`x`**: bits of **`frac`**
- Cases
  - **`exp`** = 000…0, **`frac`** = 000…0
    - Represents zero value
    - Note distinct values: +0 and –0 (why?)
  - **`exp`** = 000…0, **`frac`** ≠ 000…0
    - Numbers closest to 0.0
    - Equispaced

Special Values

- Condition: **`exp`** = **`111…1`**

- Case: **`exp`** = **`111…1`**, **`frac`** = **`000…0`**
  - Represents value ∞ (infinity)
  - Operation that overflows
  - Both positive and negative
  - E.g., $1.0/0.0 = -1.0/-0.0 = +\infty$, $1.0/-0.0 = -\infty$

- Case: **`exp`** = **`111…1`**, **`frac`** ≠ **`000…0`**
  - Not-a-Number (NaN)
  - Represents case when no numeric value can be determined
  - E.g., sqrt(–1), $\infty - \infty$, $\infty \times 0$

Visualization: Floating Point Encodings



(Practice: Figure 2.35)

- 8-bit floating-point format
- Sign bit : 1 bit
- Exp: 4 bit
- Frac: 3 bit

- 1.125 : ____________________________________
- 0.875 : ____________________________________
- 1.5 : ____________________________________

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Tiny Floating Point Example



- 8-bit Floating Point Representation
  - the sign bit is in the most significant bit
  - the next four bits are the exponent, with a bias of 7
  - the last three bits are the **`frac`**

- Same general form as IEEE Format
  - normalized, denormalized
  - representation of 0, NaN, infinity

Distribution of Values

- 6-bit IEEE-like format
  - e = 3 exponent bits
  - f = 2 fraction bits
  - Bias is $2^{3-1}-1 = 3$



- Notice how the distribution gets denser toward zero.



Distribution of Values (close-up view)

- 6-bit IEEE-like format
  - e = 3 exponent bits
  - f = 2 fraction bits
  - Bias is 3





Special Properties of the IEEE Encoding

- FP Zero Same as Integer Zero
  - All bits = 0
- Can (Almost) Use Unsigned Integer Comparison
  - Must first compare sign bits
  - Must consider −0 = 0
  - NaNs problematic
    - Will be greater than any other values
    - What should comparison yield?
  - Otherwise OK
    - Denorm vs. normalized
    - Normalized vs. infinity

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Floating Point Operations: Basic Idea

- $\mathbf{x} +_f \mathbf{y} = \mathbf{Round}(\mathbf{x} + \mathbf{y})$

- $\mathbf{x} \times_f \mathbf{y} = \mathbf{Round}(\mathbf{x} \times \mathbf{y})$

- Basic idea
  - First compute exact result
  - Make it fit into desired precision
    - Possibly overflow if exponent too large
    - Possibly round to fit into **`frac`**

Rounding

- Rounding Modes (illustrate with $ rounding)

	$1.40	$1.60	$1.50	$2.50	–$1.50
Towards zero	$1	$1	$1	$2	–$1
Round down (–∞)	$1	$1	$1	$2	–$2
Round up (+∞)	$2	$2	$2	$3	–$1
Nearest Even (default)	$1	$2	$2	$2	–$2

Closer Look at Round-To-Even

- Default Rounding Mode
  - Hard to get any other kind without dropping into assembly
  - All others are statistically biased
    - Sum of set of positive numbers will consistently be over- or under-estimated

- Applying to Other Decimal Places / Bit Positions
  - When exactly halfway between two possible values
    - Round so that least significant digit is even
  - E.g., round to nearest hundredth

7.8949999	7.89	(Less than half way)
7.8950001	7.90	(Greater than half way)
7.8950000	7.90	(Half way—round up)
7.8850000	7.88	(Half way—round down)

Rounding Binary Numbers

- Binary Fractional Numbers
  - "Even" when least significant bit is **0**
  - "Half way" when bits to right of rounding position = $\mathbf{100}\ldots_2$

- Examples
  - Round to nearest 1/4 (2 bits right of binary point)

Value	Binary	Rounded	Action	Rounded Value
2 3/32	10.00011_2	10.00_2	(<1/2—down)	2
2 3/16	10.00110_2	10.01_2	(>1/2—up)	2 1/4
2 7/8	10.11100_2	11.00_2	(1/2—up)	3
2 5/8	10.10100_2	10.10_2	(1/2—down)	2 1/2

FP Multiplication

- $(-1)^{s1}\ M1\ \ 2^{E1}\ \ \times\ \ (-1)^{s2}\ M2\ \ 2^{E2}$
- Exact Result: $(-1)^{s}\ M\ \ 2^{E}$
  - Sign s: s1 ^ s2
  - Significand M: M1 x M2
  - Exponent E: E1 + E2
- Fixing
  - If M ≥ 2, shift M right, increment E
  - If E out of range, overflow
  - Round M to fit **`frac`** precision
- Implementation
  - Biggest chore is multiplying significands

Floating Point Addition

- $(-1)^{s1}\ M1\ \ 2^{E1}\ \ +\ \ (-1)^{s2}\ M2\ \ 2^{E2}$
  - Assume E1 > E2

Get binary points lined up



- Exact Result: $(-1)^{s}\ M\ \ 2^{E}$
  - Sign s, significand M:
    - Result of signed align & add
  - Exponent E: E1

- Fixing
  - If M ≥ 2, shift M right, increment E
  - if M < 1, shift M left k positions, decrement E by k
  - Overflow if E out of range
  - Round M to fit `frac` precision

Mathematical Properties of FP Add

- Compare to those of Abelian Group
  - Closed under addition?
    - But may generate infinity or NaN
  - Commutative?
  - Associative?
    - Overflow and inexactness of rounding
    - `(3.14+1e10)-1e10 = 0, 3.14+(1e10-1e10) = 3.14`
  - 0 is additive identity?
  - Every element has additive inverse?
    - Yes, except for infinities & NaNs
- Monotonicity
  - $a \geq b \Rightarrow a+c \geq b+c$?
    - Except for infinities & NaNs

Yes

Yes

No

Yes

Almost

Almost

Mathematical Properties of FP Mult

- Compare to Commutative Ring
  - Closed under multiplication? Yes
    - But may generate infinity or NaN
  - Multiplication Commutative? Yes
  - Multiplication is Associative? No
    - Possibility of overflow, inexactness of rounding
    - Ex: `(1e20*1e20)*1e-20= inf`, `1e20*(1e20*1e-20)= 1e20`
  - 1 is multiplicative identity? Yes
  - Multiplication distributes over addition? No
    - Possibility of overflow, inexactness of rounding
    - `1e20*(1e20-1e20)= 0.0`, `1e20*1e20 – 1e20*1e20 = NaN`
- Monotonicity
  - $a \geq b$ & $c \geq 0 \Rightarrow a * c \geq b * c$? Almost

(Back-ups) Abelian Group

- Closure
  - For all a, b in A, the result of the operation a • b is also in A.
- Associativity
  - For all a, b, and c in A, the equation (a • b) • c = a • (b • c) holds.
- Identity element
  - There exists an element e in A, such that for all elements a in A, the equation e • a = a • e = a holds.
- Inverse element
  - For each a in A, there exists an element b in A such that a • b = b • a = e, where e is the identity element.
- Commutativity
  - For all a, b in A, a • b = b • a.

(Back to Ch1) **Great Reality #1: Ints are not Integers, Floats are not Reals**

- **Example 1: Is $x^2 \geq 0$?**
  - Float's: Yes!



  - Int's:
    - 40000 * 40000 = 1600000000
    - 50000 * 50000 = ??
- **Example 2: Is (x + y) + z = x + (y + z)?**
  - Unsigned & Signed Int's: Yes!
  - Float's:
    - (1e20 + -1e20) + 3.14 --> 3.14
    - 1e20 + (-1e20 + 3.14) --> ??

Source: xkcd.com/571

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Floating Point in C

- C Guarantees Two Levels
  - **`float`** single precision
  - **`double`** double precision
- Conversions/Casting
  - Casting between **`int`**, **`float`**, and **`double`** changes bit representation
  - **`double`**/**`float`** → **`int`**
    - **Truncates fractional part**
    - Like rounding toward zero
    - Not defined when out of range or NaN
  - **`int`** → **`double`**
    - Exact conversion, as long as **`int`** has ≤ 53 bit word size
  - **`int`** → **`float`**
    - Will round according to rounding mode

Floating Point Puzzles

- For each of the following C expressions, either:
  - Argue that it is true for all argument values
  - Explain why not true

```
int x = …;
float f = …;
double d = …;
```

Assume neither **d** nor **f** is NaN

- `x == (int)(float) x`
- `x == (int)(double) x`
- `f == (float)(double) f`
- `d == (double)(float) d`
- `f == -(-f);`
- `2/3 == 2/3.0`
- `d < 0.0` ⇒ `((d*2) < 0.0)`
- `d > f` ⇒ `-f > -d`
- `d * d >= 0.0`
- `(d+f)-d == f`

Summary

- IEEE Floating Point has clear mathematical properties
- Represents numbers of form M x 2^E
- One can reason about operations independent of implementation
  - As if computed with perfect precision and then rounded
- Not the same as real arithmetic
  - Violates associativity/distributivity
  - Makes life difficult for compilers & serious numerical applications programmers

(Back-ups) Dynamic Range (Positive Only)

$v = (-1)^s M\, 2^E$

n: E = Exp – Bias

d: E = 1 – Bias

	s	exp	frac	E	Value	
Denormalized numbers	0	0000	000	-6	0	
	0	0000	001	-6	1/8*1/64 = 1/512	closest to zero
	0	0000	010	-6	2/8*1/64 = 2/512	
	…					
	0	0000	110	-6	6/8*1/64 = 6/512	
	0	0000	111	-6	7/8*1/64 = 7/512	largest denorm
Normalized numbers	0	0001	000	-6	8/8*1/64 = 8/512	smallest norm
	0	0001	001	-6	9/8*1/64 = 9/512	
	…					
	0	0110	110	-1	14/8*1/2 = 14/16	
	0	0110	111	-1	15/8*1/2 = 15/16	closest to 1 below
	0	0111	000	0	8/8*1 = 1	
	0	0111	001	0	9/8*1 = 9/8	closest to 1 above
	0	0111	010	0	10/8*1 = 10/8	
	…					
	0	1110	110	7	14/8*128 = 224	
	0	1110	111	7	15/8*128 = 240	largest norm
	0	1111	000	n/a	inf	