info		
	_postman_id	bf324ec2-98be-41bc-9fbf-6a8ab1cd3807
	name	Plataforma Hurb Para Adm
	description	StartFragment Este MVP de sistema foi desenvolvido para suporte de antecipa��es da HURB, esta nova vertical tem alto potencial de faturamento para a HURB. A plataforma de administrador possui ferramentas de visualiza��o dos dados da nova vertical para an�lise de receitas.
	schema	https://schema.getpostman.com/json/collection/v2.1.0/collection.json
	_exporter_id	21121120

item	0							
		name	partnerFilter					
		request	method	**POST**				
			header	*(Empty List)*				
			body	mode	urlencoded			
				urlencoded	0	key	partner	
						value	Inteli	
						type	text	
			url	raw	http://127.0.0.1:3031/partnerFilter			
				protocol	http			
				host	0	127		
					1	0		
					2	0		
					3	1		
				port	3031			
				path	0	partnerFilter		
			description	StartFragment Filters the ranking informations according to the selected partner EndFragment				
		response	0	name	example success			
				originalRequest	method	GET		
					header	*(Empty List)*		
					body	mode	urlencoded	
						urlencoded	0	key	partner
								value	Inteli
								type	text
					url	raw	http://127.0.0.1:3031/partnerFilter	
						protocol	http	
						host	0	127
							1	0
							2	0
							3	1
						port	3031	
						path	0	partnerFilter
				_postman_previewlanguage	json			
				header	null			
				cookie	*(Empty List)*			
				body	[{ "montante": 100, "nome": "Inteli", "regra": "D 7",			

									"estado": "RJ" }, { "montante": 121, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }, { "montante": 88, "nome": "Inteli", "regra": "D 2", "estado": "RJ" }, { "montante": 91, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }, { "montante": 194, "nome": "Inteli", "regra": "D 2", "estado": "RJ" }]

1

name	typeFilter						
request	method	POST					
	header	*(Empty List)*					
	body	mode	urlencoded				
		urlencoded	**0**	key	regra		
				value	D 7		
				type	text		
	url	raw	http://127.0.0.1:3031/typeFilter				
		protocol	http				
		host	**0**	127			
			1	0			
			2	0			
			3	1			
		port	3031				
		path	**0**	typeFilter			
	description	StartFragment Searches the ranking information according to the type of selected requests EndFragment					

response	**0**	name	typeFilter					
		originalRequest	method	POST				
			header	**0**	key	Content-Type		
					name	Content-Type		
					value	application/x-www-form-urlencoded		
					type	text		
			body	mode	urlencoded			
				urlencoded	**0**	key	regra	
						value	D 7	
						type	text	
			url	raw	http://127.0.0.1:3031/typeFilter			
				protocol	http			
				host	**0**	127		
					1	0		
					2	0		
					3	1		
				port	3031			
				path	**0**	typeFilter		
		_postman_previewlanguage	json					
		header	null					
		cookie	*(Empty List)*					
		body	[{ "montante": 100, "nome": "Inteli", "regra": "D 7",					

			"estado": "RJ" }, { "montante": 121, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }, { "montante": 91, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }]		

2

name	openStates				
request	**method**	GET			
	header	*(Empty List)*			
	url	**raw**	http://127.0.0.1:3031/openStates		
		protocol	http		
		host	**0**	127	
			1	0	
			2	0	
			3	1	
		port	3031		
		path	**0**	openStates	
	description	StartFragment Searches for states that differ from what we possess in the database EndFragment			

response	**0**	**name**		example sucess		
		originalRequest		**method**	GET	
				header	*(Empty List)*	
				url	**raw**	http://127.0.0.1:3031/openStates
					protocol	http
					host	**0** 127
						1 0
						2 0
						3 1
					port	3031
					path	**0** openStates
		status		OK		
		code		200		
		_postman_previewlanguage		json		
		header		null		
		cookie		*(Empty List)*		
		body		[{ "estado": "RJ" }, { "estado": "SP" }]		

3

name	estados				
request	**method**	GET			
	header	*(Empty List)*			
	url	**raw**	http://127.0.0.1:3031/stateFilter		
		protocol	http		
		host	**0**	127	
			1	0	
			2	0	
			3	1	
		port	3031		
		path	**0**	stateFilter	
	description	StartFragment Filters the ranking information using selected states EndFragment			

response	**0**	**name**	example success					
		originalRequest	**method**	GET				
			header	*(Empty List)*				
			url	**raw**	http://127.0.0.1:3031/stateFilter			
				protocol	http			
				host	**0**	127		
					1	0		
					2	0		
					3	1		
				port	3031			
				path	**0**	stateFilter		
		status	OK					
		code	200					
		_postman_previewlanguage	json					
		header	**0**	**key**	X-Powered-By			
				value	Express			
			1	**key**	Access-Control-Allow-Origin			
				value	*			
			2	**key**	Content-Type			
				value	application/json; charset=utf-8			
			3	**key**	Content-Length			
				value	17			
			4	**key**	ETag			
				value	W/"11-Gv2inI53OvZIyC3+8DjRqwmt9Mw"			
			5	**key**	Date			
				value	Mon, 13 Jun 2022 18:11:19 GMT			
			6	**key**	Connection			
				value	keep-alive			
			7	**key**	Keep-Alive			
				value	timeout=5			
		cookie	*(Empty List)*					
		body	[{ "estado": "SP" }]					
4	**name**	openPartner						
	request	**method**	GET					
		header	*(Empty List)*					
		url	**raw**	http://127.0.0.1:3031/openPartner				
			protocol	http				
			host	**0**	127			
				1	0			
				2	0			
				3	1			
			port	3031				
			path	**0**	openPartner			

		description		StartFragment Searches for partners that differ from what we possess in the databse EndFragment			
response	**0**	**name**		example success			
		originalRequest		**method**	GET		
				header	*(Empty List)*		
				url	**raw**	http://127.0.0.1:3031/openPartner	
					protocol	http	
					host	**0**	127
						1	0
						2	0
						3	1
					port	3031	
					path	**0**	openPartner
		_postman_previewlanguage		json			
		header		**null**			
		cookie		*(Empty List)*			
		body		[{ "nome": "Inteli", "id": 1, "code": 1, "reserva_code": 1, "hotel_id": 1 }, { "nome": "Recanto", "id": 2, "code": 2, "reserva_code": 2, "hotel_id": 2 }, { "nome": "Central", "id": 3, "code": 3, "reserva_code": 3, "hotel_id": 3 }, { "nome": "Inteli", "id": 1, "code": 1, "reserva_code": 1, "hotel_id": 1 }, { "nome": "Inteli", "id": 1, "code": 1, "reserva_code": 1, "hotel_id": 1 }, { "nome": "Inteli", "id": 1, "code": 1, "reserva_code": 1, "hotel_id": 1 }, { "nome": "Inteli", "id": 1, "code": 1, "reserva_code": 1, "hotel_id": 1 }]			

5

name	openType					
request	**method**		GET			
	header		*(Empty List)*			
	url		**raw**	http://127.0.0.1:3031/openType		
			protocol	http		
			host	**0**	127	
				1	0	
				2	0	
				3	1	
			port	3031		
			path	**0**	openType	
	description		StartFragment Searches the database for requests we don't possess EndFragment			
response	**0**	**name**		example success		
		originalRequest		**method**	GET	
				header	*(Empty List)*	
				url	**raw**	http://127.0.0.1:3031/openType
					protocol	http
					host	**0** 127
						1 0
						2 0
						3 1

					port	3031	
					path	0	openType

	_postman_previewlanguage	null
	header	null
	cookie	*(Empty List)*
	body	[{ "regra": "D 7" }, { "regra": "D 2" }, { "regra": "D 15" }]

6	**name**	antecipations					
	request	**method**	GET				
		header	*(Empty List)*				
		url	**raw**	http://127.0.0.1:3031/antecipations			
			protocol	http			
			host	0	127		
				1	0		
				2	0		
				3	1		
			port	3031			
			path	0	antecipations		
		description	StartFragment Searches the database for the antecipationxdeadline value division EndFragment				
	response	0	**name**	example success			
			originalRequest	**method**	GET		
				header	*(Empty List)*		
				url	**raw**	http://127.0.0.1:3031/antecipations	
					protocol	http	
					host	0	127
						1	0
						2	0
						3	1
					port	3031	
					path	0	antecipations
			_postman_previewlanguage	null			
			header	null			
			cookie	*(Empty List)*			
			body	[{ "COUNT (*)": 7 }]			

7	**name**	fullValue				
	request	**method**	GET			
		header	*(Empty List)*			
		url	**raw**	http://127.0.0.1:3031/fullValue		
			protocol	http		
			host	0	127	
				1	0	
				2	0	
				3	1	
			port	3031		

				path	0	fullValue

			description	StartFragment Searches the database for the paymentsxdeadline value division EndFragment

response	0	name		example success			
		originalRequest	method	GET			
			header	*(Empty List)*			
			url	raw		http://127.0.0.1:3031/fullValue	
				protocol		http	
				host	0	127	
					1	0	
					2	0	
					3	1	
				port		3031	
				path	0	fullValue	
		_postman_previewlanguage		null			
		header		null			
		cookie		*(Empty List)*			
		body		[{ "SUM (montante)": 818 }]			

8

name	profitability				
request	method	GET			
	header	*(Empty List)*			
	url	raw	http://127.0.0.1:3031/profitability		
		protocol	http		
		host	0	127	
			1	0	
			2	0	
			3	1	
		port	3031		
		path	0	profitability	
	description	StartFragment Searches the database for the avarage rentability division EndFragment			

response	0	name		example success			
		originalRequest	method	GET			
			header	*(Empty List)*			
			url	raw		http://127.0.0.1:3031/profitability	
				protocol		http	
				host	0	127	
					1	0	
					2	0	
					3	1	
				port		3031	
				path	0	profitability	
		_postman_previewlanguage		null			
		header		null			
				(Empty List)			

		cookie		
		body		[{ "SUM(montante)/SUM(valor)": 0.7264653641207816 }]
9	**name**	ranking		
	request	**method**	GET	
		header	*(Empty List)*	
		url	**raw**	http://127.0.0.1:3031/ranking
			protocol	http
			host	**0** 127
				1 0
				2 0
				3 1
			port	3031
			path	**0** ranking

	response	**0**	**name**	example success	
			originalRequest	**method**	GET
				header	*(Empty List)*
				url	**raw** http://127.0.0.1:3031/ranking
					protocol http
					host **0** 127
					1 0
					2 0
					3 1
					port 3031
					path **0** ranking
			_postman_previewlanguage	null	
			header	null	
			cookie	*(Empty List)*	
			body	[{ "montante": 29, "nome": "Central", "regra": "D 15", "estado": "SP" }, { "montante": 88, "nome": "Inteli", "regra": "D 2", "estado": "RJ" }, { "montante": 91, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }, { "montante": 100, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }, { "montante": 121, "nome": "Inteli", "regra": "D 7", "estado": "RJ" }, { "montante": 194, "nome": "Inteli", "regra": "D 2", "estado": "RJ" }, { "montante": 195, "nome": "Recanto", "regra": "D 2", "estado": "SP" }]	