CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.1.1. Calculate Momentum

02:58

Write a program that accepts the mass of an object (in kilograms) and its velocity (in meters per second), then calculates and displays the momentum of the object. The momentum p is calculated using the formula:

$$p = m \times v$$

where:
m is the mass of the object (in kilograms).
v is the velocity of the object (in meters per second).

Input Format:

- A single floating-point number representing the mass of the object in kilograms.
- A single floating-point number representing the velocity of the object in meters per second.

Output Format:

- The output will display calculated momentum with appropriate units (kgm/s) (rounded up to 2 decimal places).

Sample Test Cases +

Explorer

calculate...

Submit

```
mass=float(input())
velocity=float(input())
p=mass*velocity
print(f"{p:.2f}kgm/s")
```

Average time 0.007 s 7.25 ms

Maximum time 0.012 s 12.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 12 ms Debug

Expected output	Actual output
5.0	5.0
10.0	10.0
50.00kgm/s	50.00kgm/s

Test case 2 5 ms

Terminal Test cases

Debugger

Prev Reset Submit Next

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.1.2. Conditional Calculation Based on the Number of Digits

03:25

Write a Python program that accepts an integer n as input. Depending on the number of digits in n.

Constraints:
$1 \le n \le 999$

Input Format:
- The input consists of a single integer n.

Output Format:
- If n is a single-digit number, print its square.
- If n is a two-digit number, print its square root (rounded to two decimal places).
- If n is a three-digit number, print its cube root (rounded to two decimal places).
- Else print "Invalid".

Sample Test Cases +

Explorer

condition...

Submit

```python
import math
n = int(input())
if (n>=1 and n<=9):
    print(n*n)
elif (n>=10 and n<=99):
    print(f"{math.sqrt(n):.2f}")
elif (n>=100 and n<=999):
    print(f"{math.cbrt(n):.2f}")
else:
    print("Invalid")
```

Average time 0.004 s 3.57 ms

Maximum time 0.004 s 4.00 ms

4 out of 4 shown test case(s) passed

3 out of 3 hidden test case(s) passed

Test case 1 3 ms Debug

Expected output	Actual output
9	9
81	81

Test case 2 4 ms

Test case 3 4 ms

Terminal Test cases

Debugger

< Prev Reset Submit Next >

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.1.3. Days between Two Dates

45:28

Write a Python program to calculate number of days between two dates.

Input Format:

- The first line contains the first date in the format $YYYY - MM - DD$.
- The second line contains the second date in the format $YYYY - MM - DD$.

Output Format:

- An integer representing the number of days between the given dates.

Note:

- The first date should always be considered earlier than the second date.

Sample Test Cases +

Explorer

noOfDay...

Submit

```python
from datetime import date
def calculate_days(first_date_str, second_date_str):
# Convert the string inputs into date objects
# fromisoformat handles 'YYYY-MM-DD' automatically
    d1 = date.fromisoformat(first_date_str)
    d2 = date.fromisoformat(second_date_str)
# Calculate the difference between the dates
    delta = d2 - d1
    return delta
# Read the dates as standard input
date1_str = input().strip()
```

Debugger

Average time	Maximum time
0.007 s	0.010 s
7.50 ms	10.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 10 ms Debug

Expected output	Actual output
2014-07-02	2014-07-02
2014-11-02	2014-11-02
123	123

Test case 2 6 ms

Terminal Test cases

< Prev Reset Submit Next >

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.1.4. Reverse a Number

01:53

Write a Python program to reverse the digits of the number and print the reversed number.

Input Format:

- The input is a single integer.

Output Format:

- The output prints a single integer, which is the reversed number.

Sample Test Cases +

Explorer

reverseN...

Submit

```
num=int(input())
reversed_num=int(str(num)[::-1])
print(reversed_num)
```

Average time 0.004 s 3.60 ms

Maximum time 0.005 s 5.00 ms

2 out of 2 shown test case(s) passed

3 out of 3 hidden test case(s) passed

Test case 1 4 ms Debug

Expected output	Actual output
5367	5367
7635	7635

Test case 2 3 ms

Terminal Test cases

Debugger

< Prev Reset Submit Next >

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.1.5. Multiplication Table

01:31

Write a Python program that takes an integer as input and prints the multiplication table for that integer from 1 to 10.

Input Format:

- The first line of input contains an integer that represents the number for which the multiplication table is to be printed.

Output Format:

- Print the multiplication table for the given number in the format:

```
<number> x <multiplier> = <result>
```

Note:

- The character "x" is used in the output to represent multiplication.
- Refer to the visible test-cases for more clarity.

Sample Test Cases +

Explorer

multiplica...

Submit

```python
num=int(input())
for i in range(1,11):
    print(f"{num} x {i} = {num*i}")
```

Debugger

Average time: 0.004 s, 4.25 ms

Maximum time: 0.005 s, 5.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 4 ms Debug

Expected output	Actual output
8	8
8 x 1 = 8	8 x 1 = 8
8 x 2 = 16	8 x 2 = 16
8 x 3 = 24	8 x 3 = 24
8 x 4 = 32	8 x 4 = 32
8 x 5 = 40	8 x 5 = 40

Terminal Test cases

< Prev Reset Submit Next >

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.2.1. Pass or Fail

20:48

Write a Python program that accepts the number of courses and the marks of a student in those courses.

The grade is determined based on the aggregate percentage:

- If the aggregate percentage is greater than 75, the grade is Distinction.
- If the aggregate percentage is greater than or equal to 60 but less than 75, the grade is First Division.
- If the aggregate percentage is greater than or equal to 50 but less than 60, the grade is Second Division.
- If the aggregate percentage is greater than or equal to 40 but less than 50, the grade is Third Division.

Input Format:

- The first input will be an integer n, the number of courses.
- The second input will be n integers representing the marks of the student in each of the n courses, separated by a space.

Output Format:

If the student passes all courses:

- Print the aggregate percentage (formatted to two decimal places).
- Print the grade based on the aggregate percentage.

If the student fails any course (marks < 40 in any course), print:

- "Fail".

Note:

- Aggregate Percentage: Average performance across all courses, calculated by summing all marks and dividing by the number of courses.

Explorer

passorFa...

Submit

```python
def cal(marks, total_courses):
    if any(mark<40 for mark in marks):
        return "Fail"
    total_marks=sum(marks)
    aggregate_percentage=(total_marks/(total_courses*100))*100
    if aggregate_percentage>75:
        grade="Distinction"
    elif aggregate_percentage>=60:
        grade="First Division"
    elif aggregate_percentage>=50:
        grade="Second Division"
```

Debugger

Average time 0.007 s 7.30 ms

Maximum time 0.010 s 10.00 ms

5 out of 5 shown test case(s) passed

5 out of 5 hidden test case(s) passed

Test case 1 7 ms Debug

Expected output	Actual output
4	4
55 65 78 89	55 65 78 89
Aggregate Percentage: 71.75	Aggregate Percentage: 71.75
Grade: First Division	Grade: First Division

Test case 2 9 ms

Terminal Test cases

< Prev Reset Submit Next >

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.2.2. Fibonacci Series

01:30

Write a Python program that uses recursion to print the first n terms of the Fibonacci series.

Input Format:

- A single integer n representing the number of terms to generate.

Output Format:

- A single line containing the first n terms of the Fibonacci sequence, separated by spaces.

Sample Test Cases +

Explorer

fibonacci.... Submit

```python
def fibonacci(n):
    if n<=2:
        return n-1
    else:
        return fibonacci(n-1)+fibonacci(n-2)


n = int(input())
for i in range(1, n + 1):
    print(fibonacci(i), end=" ")
```

Debugger

Average time 0.009 s 9.25 ms

Maximum time 0.024 s 24.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 5 ms Debug

Expected output	Actual output
5	5
0 1 1 2 3	0 1 1 2 3

Test case 2 3 ms

Terminal Test cases

Prev Reset Submit Next

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.2.3. Pattern - 1

01:11

Write a Python program to print a pattern of asterisks in the form of a right-angled triangle.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format

- The output should display the pattern of asterisks (*), with each row containing an increasing number of asterisks.

Note: Refer to the displayed test cases for the sample pattern.

Sample Test Cases +

Explorer

rightangl...

Submit

```
n=int(input())
for i in range(1,n+1):
    print("* " *i)
```

Average time 0.004 s 3.50 ms

Maximum time 0.004 s 4.00 ms

2 out of 2 shown test case(s) passed

4 out of 4 hidden test case(s) passed

Test case 1 4 ms Debug

Expected output	Actual output
5	5
*	*
* *	* *
* * *	* * *
* * * *	* * * *
* * * * *	* * * * *

Terminal Test cases

Debugger

< Prev Reset Submit Next >

CODETANTRA Home Learn Anywhere 202501090050@mitaoe.ac.in Support Logout

1.2.4. Pattern - 2

01:31

Write a Python program to print a right-angled triangle pattern of numbers.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format:

- The output should display the pattern of numbers separated by space, with each row containing increasing numbers starting from 1 up to the row number.

Note:

- Refer to the displayed test cases for the sample pattern.

Sample Test Cases +

Explorer

numberP...

Submit

```python
n=int(input())
for i in range(1,n+1):
    for j in range(1,i+1):
        print(j, end=" ")
    print("")
```

Average time 0.005 s 5.00 ms

Maximum time 0.007 s 7.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 7 ms Debug

Expected output	Actual output
5	5
1	1
1 2	1 2
1 2 3	1 2 3
1 2 3 4	1 2 3 4
1 2 3 4 5	1 2 3 4 5

Terminal Test cases

Debugger

< Prev Reset Submit Next >