

4.1.1. Pandas - series creation and manipulation

05:40

Write a Python program that takes a list of numbers from the user, creates a Pandas series from it, and then calculates the mean of even and odd numbers separately using the `groupby` and `mean()` operations.

Hint: You can group the Series based on whether each number is even or odd.

Input Format:

- The user should enter a list of numbers separated by space when prompted.

Output Format:

- The program should display the mean of even and odd numbers separately.
- Each mean value should be displayed with a label indicating whether it corresponds to even or odd numbers.

Refer to the sample test cases for better understanding regarding input and output format.

Sample Test Cases

+

seriesMa...

Submit

```
1 import pandas as pd
2
3 # Take inputs from the user to create a list of numbers
4 numbers = list(map(int, input().split()))
5
6 # Create a Pandas series from the list of numbers
7 series = pd.Series(numbers)
8 # Grouping by even and odd numbers and calculating the mean
9 grouped = series.groupby(series % 2 == 0).mean()
10
11 # Display the mean of even and odd numbers with labels
12 grouped.index = ['Even' if is_even else 'Odd' for is_even in
grouped.index]
```

Average time

0.007 s

6.67 ms

Maximum time

0.015 s

15.00 ms

3 out of 3 shown test case(s) passed

3 out of 3 hidden test case(s) passed

Test case 1

15 ms

Debug

Expected output

1 2 3 4 5 6 7 8 9 10

Mean of even and odd numbers:

Odd 5.0

Even 6.0

dtype: float64

Actual output

1 2 3 4 5 6 7 8 9 10

Mean of even and odd numbers:

Odd 5.0

Even 6.0

dtype: float64

Terminal

Test cases

Prev
Reset
Submit
Next

4.1.2. Dictionary to dataframe 45.38

A dictionary of lists has been provided to you in the editor. Create a DataFrame from the dictionary of lists and perform the listed operations, then display the DataFrame before and after each manipulation.

Create the DataFrame:

- Convert the dictionary to a Pandas DataFrame.

Add a new row:

- Take inputs from the user for the new row data (name, age).
- Add the new row to the DataFrame.
- Display the DataFrame after adding the new row.

Modify a row:

- Modify a specific row by changing the age. Take the row index and new age value from the user.
- Display the DataFrame after modifying the row.

Delete a row:

- Take the row index to be deleted from the user.
- Remove the specified row.
- Display the DataFrame after deleting the row.

Add a new column:

- Add a column **Gender** with values taken from the user.
- Display the DataFrame after adding the new column.

Modify a column:

- Convert names to uppercase.
- Display the DataFrame after modifying the column.

datafram... Submit

1 import pandas as pd
2
3 # Provided dictionary of lists
4 data = {
5 'Name': ['Alice', 'Bob', 'Charlie'],
6 'Age': [25, 30, 35],
7 }
8
9 # Convert the dictionary to a DataFrame
10 df = pd.DataFrame(data)
11
12 # Display the original DataFrame
13 print("Original DataFrame:")

Average time
0.052 s
52.50 ms

Maximum time
0.059 s
59.00 ms

1 out of 1 shown test case(s) passed
1 out of 1 hidden test case(s) passed

Test case 1 59 ms Debug

Expected output	Actual output
Original DataFrame:	Original DataFrame:
.....Name..Age	Name..Age
0...Alice...25	0...Alice...25
1...Bob...30	1...Bob...30
2...Charlie...35	2...Charlie...35
New name: Susan	New name: Susan

Terminal Test cases

4.1.3. Student Information 15:43

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

- Display the first five rows of the data frame.
- Calculate the average age of the students (limit the average age up to 2 decimal places).
- Filter out the students who have a grade above a certain threshold (consider the threshold grade is 'B').

Note:
Refer to the displayed test cases for better understanding.

Sample Test Cases +

studentin... Submit

```
1 import pandas as pd
2
3 # Read the text file into a DataFrame
4 file = input()
5 data = pd.read_csv(file, sep="\s+", header=None, names=["Name", "Age",
6 "Grade"])
7
8 # write your code here..
9 print("First five rows:")
10 print(data.head())
11 average = round(data['Age'].mean(),2)
12 print("Average age:",average)
```

Average time
0.029 s
28.50 ms

Maximum time
0.042 s
42.00 ms

1 out of 1 shown test case(s) passed
1 out of 1 hidden test case(s) passed

Test case 1 42 ms Debug

Expected output

Actual output

studentdata.txt

studentdata.txt

First five rows:

First five rows:

...

...

0 John 25 A

0 John 25 A

1 Alin 22 B

1 Alin 22 B

2 Emma 24 A

2 Emma 24 A

Terminal

Test cases

00:59

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by Month and calculate the total sales for each month.
- Find the month with the highest total sales and display it.
- Also, display the total sales for the best month.

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles
```

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

+

Submit

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8
9
10 df['Sales']=df['Quantity']*df['Price']
11 df['Month']=df['Date'].str[:7]
12 monthly_sales=df.groupby('Month')['Sales'].sum()
13
```

14.67 ms

29.00 ms

2 out of 2 hidden test case(s) passed

1 29 ms



Actual output

sales_data.csv

Best month: 2025-01

Total sales: \$1210.00

Test cases

4.2.2. Best Selling Product

13.57

AA

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Find the product that sold the most in terms of quantity sold.
- Display the product that sold the most and the total quantity sold for that product.

Sample Data:

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles
```

Note:
The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

+

monthFor...

Submit

Explorer

Debugger

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8 sales_sum = df.groupby('Product')['Quantity'].sum()
9 # Find the product with the highest total quantity sold
10 best_product = sales_sum.idxmax()
11 highest_quantity = sales_sum.max()
12
13 # Display the result
```

Average time

0.013 s

13.33 ms

Maximum time

0.027 s

27.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1

27 ms

Debug

Expected output

Actual output

sales_data.csv

sales_data.csv

Best-selling product: Product A

Best-selling product: Product A

Total quantity sold: 23

Total quantity sold: 23

Terminal

Test cases

4.2.3. City that Sold the Most Products

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by City and calculate the total quantity of products sold for each city.
- Find the city that sold the most products (based on the total quantity sold).

Sample Data:

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles
```

Note:
The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...

Submit

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8
9 # write the code..
10 a = df.groupby('City')['Quantity'].sum()
11 best_city = a.idxmax()
12 # Display the result
13 print(f"City sold the most products: {best_city}")
```

Average time
0.012 s
12.33 ms

Maximum time
0.026 s
26.00 ms

1 out of 1 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 26 ms Debug

Expected output

Actual output

sales_data.csv

sales_data.csv

City sold the most products: Los Angeles

City sold the most products: Los Angeles

Terminal

Test cases

4.2.4. Most Frequently Sold Product Pairs 02:29

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the following columns: Date, Product, Quantity, Price, and City.
- For each date, find all pairs of products that were sold together (i.e., two products sold on the same date).
- Output the product pair/s that was sold most frequently.

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Explanation:

Transactions:

- 2025-01-01: Product A, Product B
- 2025-01-02: Product A, Product C
- 2025-01-03: Product B, Product A
- 2025-01-04: Product C, Product B
- 2025-01-05: Product A, Product C

Now, let's count how often the pairs of products appear together:

- **Product A and Product B:** Appear in transactions on 2025-01-01 and 2025-01-03.

Explorer

frequentl...

1 import pandas as pd
2 from itertools import combinations
3 from collections import Counter
4
5 # Prompt user to input the file name
6 file_name = input()
7
8 # Read data from the specified CSV file
9 df = pd.read_csv(file_name)
10
11 count_pairs=Counter()
12 # write the code
13

Debugger

Average time
0.013 s
13.33 ms

Maximum time
0.028 s
28.00 ms

1 out of 1 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 28 ms Debug

Expected output
sales_data.csv
Product A and Product B: 2 times
Product A and Product C: 2 times

Actual output
sales_data.csv
Product A and Product B: 2 times
Product A and Product C: 2 times

Terminal

Test cases

4.2.5. Titanic Dataset Analysis and Data Cleaning 18:19

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset. For each question, perform necessary data cleaning, transformations, and calculations as required.

- 1. Display the first 5 rows of the dataset.
- 2. Display the last 5 rows of the dataset.
- 3. Get the shape of the dataset (number of rows and columns).
- 4. Get a summary of the dataset (using .info()).
- 5. Get basic statistics (mean, standard deviation, etc.) of the dataset using .describe().
- 6. Check for missing values and display the count of missing values for each column.
- 7. Fill missing values in the 'Age' column with the median age.
- 8. Fill missing values in the 'Embarked' column with the most frequent value (mode()).
- 9. Drop the 'Cabin' column due to many missing values.
- 10. Create a new column, 'FamilySize' by adding the 'SibSp' and 'Parch' columns.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

Explorer

titanicDat...

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # 1. Display the first 5 rows of the dataset
8 print(data.head())
9
10 # 2. Display the last 5 rows of the dataset
11 print(data.tail())
12
13 # 3. Get the shape of the dataset
```

Average time0.130 s130.00 ms

Maximum time0.130 s130.00 ms

1 out of 1 shown test case(s) passed

Test case 1130 ms

Debug

Expected output

Actual output

... PassengerId ... Survived ... Pclass ... Fare ... Cabin ... Embarked ...

0 ... 1 ... 0 ... 3 ... 7.2500 ... NaN ... S ...

1 ... 2 ... 1 ... 1 ... 71.2833 ... C85 ... C ...

2 ... 3 ... 1 ... 3 ... 7.9250 ... NaN ... S ...

Terminal

Test cases

4.2.6. Titanic Dataset Analysis and Data Cleaning - 2

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Create a new column 'IsAlone' which is 1 if the passenger is alone (FamilySize = 0), otherwise 0.
2. Convert the 'Sex' column to numeric values (male: 0, female: 1).
3. One-hot encode the 'Embarked' column, dropping the first category.
4. Get the mean age of passengers.
5. Get the median fare of passengers.
6. Get the number of passengers by class.
7. Get the number of passengers by gender.
8. Get the number of passengers by survival status.
9. Calculate the survival rate of passengers.
10. Calculate the survival rate by gender.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

titanicDat...

1import pandas as pd

2import numpy as np

3

4# Load the Titanic dataset

5data = pd.read_csv('Titanic-Dataset.csv')

6data['FamilySize'] = data['SibSp'] + data['Parch']

7

8# 1. Create a new column 'IsAlone' (1 if alone, 0 otherwise)

9def familysize(size):

10 if size == 0:

11 return 1

12 else:

13 return 0

Average time0.046 s46.00 ms

Maximum time0.046 s46.00 ms

1 out of 1 shown test case(s) passed

Test case 140 ms

Debug

Expected output

Actual output

29.69911764705882

29.69911764705882

14.4542

14.4542

3...491

3...491

1...216

1...216

2...184

2...184

Name: Pclass, dtype: int64

Name: Pclass, dtype: int64

Terminal

Test cases

00:51 AA 🌙 ✍️ 🔗 —

- | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|-----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 | 52 | 53 | 54 | 55 | 56 | 57 | 58 | 59 | 60 | 61 | 62 | 63 | 64 | 65 | 66 | 67 | 68 | 69 | 70 | 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 79 | 80 | 81 | 82 | 83 | 84 | 85 | 86 | 87 | 88 | 89 | 90 | 91 | 92 | 93 | 94 | 95 | 96 | 97 | 98 | 99 | 100 |
|---|---|---|---|---|---|---|---|---|-----|

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17590,53.1,S
```

 Debugger

Average time **0.072 s** 72.00 ms  Maximum time **0.072 s** 72.00 ms  **1 out of 1 shown test case(s) passed**

 Debug

Expected output	Actual output
Pclass	Pclass
1---0.629630	1---0.629630
2---0.472825	2---0.472825
3---0.242363	3---0.242363
Name:-Survived, dtype:-float64	Name:-Survived, dtype:-float64
Embarked_S	Embarked_S
0 0.500000	0 0.500000

Terminal Test cases

4.2.8. Titanic Dataset Analysis and Data Cleaning - 4 00:27

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

- 1. Get the number of survivors by gender (Sex).
- 2. Get the number of non-survivors by gender (Sex).
- 3. Get the number of survivors by embarkation location (Embarked_S).
- 4. Get the number of non-survivors by embarkation location (Embarked_S).
- 5. Calculate the percentage of children (Age < 18) who survived.
- 6. Calculate the percentage of adults (Age >= 18) who survived.
- 7. Get the median age of survivors.
- 8. Get the median age of non-survivors.
- 9. Get the median fare of survivors.
- 10. Get the median fare of non-survivors.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Allen, Miss. Elisabeth Lucy",female,35,0,0,230363,53.1,,S
3,1,3,"Meyer, Mr. Jacob",male,27,0,0,261511,8.51,,S

Explorer

titanicDat...

1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
7
8
9 # 1. Get the number of survivors by gender
10 print(data[data['Survived']==1]['Sex'].value_counts())
11
12 # 2. Get the number of non-survivors by gender
13 print(data[data['Survived']==0]['Sex'].value_counts())

Debugger

Average time
0.050 s
50.00 ms

Maximum time
0.050 s
50.00 ms

1 out of 1 shown test case(s) passed

Test case 1 50 ms Debug

Expected output

Actual output

female...233
male...109
Name: Sex, dtype: int64
male...468
female...81
Name: Sex, dtype: int64

female...233
male...109
Name: Sex, dtype: int64
male...468
female...81
Name: Sex, dtype: int64

Terminal

Test cases