```
 GNU nano 8.7.1                                    exp4.sh
#!/bin/bash

echo "Currently working users are"
echo ""
who
echo ""

read -p "Enter username: " user

login_time=$(who | awk -v u="$user" '$1 == u {print $3, $4; exit}')

if [ -z "$login_time" ]
then
echo "User is not currently logged in."
else
echo "Login time: $login_time"

login_seconds=$(date -d "$login_time" +%s)
current_seconds=$(date +%s)

total_seconds=$((current_seconds - login_seconds))

hours=$((total_seconds / 3600))
minutes=$(((total_seconds % 3600) / 60))

echo "Total working time: $hours hours $minutes minutes"
fi
```

```
user@nandini:~$$ nano exp4.sh
user@nandini:~$$ bash exp4.sh
Currently working users are


Enter username: user@nandini
User is not currently logged in.
user@nandini:~$$ nano exp4.sh
user@nandini:~$$
```

```
 GNU nano 8.7.1
#!/bin/bash

if [ "$#" -ne 3 ]
then
echo "Usage: $0 filename start_line end_line"
fi

file="$1"
start="$2"
end="$3"

sed -n "${start},${end}p" "$file"
```

```
user@nandini:~$ nano exp4b.sh
user@nandini:~$ bash exp4b.sh numbers.txt 3 8
4
5
6
7
8
9
user@nandini:~$
```

```
  GNU nano 8.7.1
#!/bin/bash

if [ "$#" -lt 2 ]
then
echo "Need atleast two arguments"
fi

word="$1"
shift

for file in "$@"
do
if [ -f "$file" ]
then
sed -i "/$word/d" "$file"
echo "Deleted lines containing '$word' from $file"
else
echo "$file does not exist."
fi
done
```

```
user@nandini:~$ nano exp4c.sh
user@nandini:~$ bash exp4c.sh sharma name.txt
Deleted lines containing 'sharma' from name.txt
user@nandini:~$ cat name.txt
mahi mangotra
nandini chadha
user@nandini:~$
```