

```
In [1]: import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.linear_model import Ridge, RidgeCV, Lasso
from sklearn.preprocessing import StandardScaler
```

```
In [2]: data=pd.read_csv(r"C:\Users\chinta pavani\Documents\fiat500_VehicleSelectio
data
```

Out[2]:

	ID	model	engine_power	age_in_days	km	previous_owners	lat
0	1	lounge	51	882	25000	1	44.907242
1	2	pop	51	1186	32500	1	45.666359
2	3	sport	74	4658	142228	1	45.503300
3	4	lounge	51	2739	160000	1	40.633171
4	5	pop	73	3074	106880	1	41.903221
...
1533	1534	sport	51	3712	115280	1	45.069679
1534	1535	lounge	74	3835	112000	1	45.845692
1535	1536	pop	51	2223	60457	1	45.481541
1536	1537	lounge	51	2557	80750	1	45.000702
1537	1538	pop	51	1766	54276	1	40.323410

1538 rows × 9 columns

```
In [3]: data = data[['engine_power','price']]
data.columns=['Eng','pri']
```


```
In [4]: data.head()
```

Out[4]:

	Eng	pri
0	51	8900
1	51	8800
2	74	4200
3	51	6000
4	73	5700

```
In [5]: sns.lmplot(x='Eng',y='pri',data=data,order=2,ci=None)
```

```
Out[5]: <seaborn.axisgrid.FacetGrid at 0x15913588fd0>
```



```
In [6]: data.info()
```

```
<class 'pandas.core.frame.DataFrame'>  
RangeIndex: 1538 entries, 0 to 1537  
Data columns (total 2 columns):  
#   Column  Non-Null Count  Dtype  
---  ---      -  
0    Eng      1538 non-null    int64  
1    pri      1538 non-null    int64  
dtypes: int64(2)  
memory usage: 24.2 KB
```

```
In [7]: data.describe()
```

```
Out[7]:
```

	Eng	pri
count	1538.000000	1538.000000
mean	51.904421	8576.003901
std	3.988023	1939.958641
min	51.000000	2500.000000
25%	51.000000	7122.500000
50%	51.000000	9000.000000
75%	51.000000	10000.000000
max	77.000000	11100.000000

```
In [8]: data.fillna(method='ffill')
```

```
Out[8]:
```

	Eng	pri
0	51	8900
1	51	8800
2	74	4200
3	51	6000
4	73	5700
...
1533	51	5200
1534	74	4600
1535	51	7500
1536	51	5990
1537	51	7900

1538 rows × 2 columns

```
In [9]: x=np.array(data['Eng']).reshape(-1,1)
        y=np.array(data['pri']).reshape(-1,1)
```

```
In [10]: data.dropna(inplace=True)
```

C:\Users\chinta pavani\AppData\Local\Temp\ipykernel_3916\1368182302.py:1:
SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame


See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy (https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)

```
data.dropna(inplace=True)
```

```
In [11]: X_train,X_test,y_train,y_test = train_test_split(x, y, test_size = 0.25)
# Splitting the data into training data and test data
regr = LinearRegression()
regr.fit(X_train, y_train)
print(regr.score(X_test, y_test))
```


```
0.10465570991708761
```

```
In [12]: y_pred = regr.predict(X_test)
plt.scatter(X_test, y_test, color = 'b')
plt.scatter(X_test, y_test, color = 'k')
plt.show()
```




```
In [13]: df500 = data[:500]
# Selecting the 1st 500 rows of the data
sns.lmplot(x = "Eng", y = "pri", data = df500, order = 1, ci = None)
```

Out[13]: <seaborn.axisgrid.FacetGrid at 0x15915668850>




```
In [14]: df500.fillna(method = 'ffill', inplace = True)
x = np.array(df500['Eng']).reshape(-1, 1)
y = np.array(df500['pri']).reshape(-1, 1)
df500.dropna(inplace = True)
X_train, X_test, y_train, y_test = train_test_split(x, y, test_size = 0.25)
regr = LinearRegression()
regr.fit(X_train, y_train)
print("Regression:", regr.score(X_test, y_test))
y_pred = regr.predict(X_test)
plt.scatter(X_test, y_test, color = 'k')
plt.scatter(X_test, y_pred, color = 'b')
plt.show()
```

Regression: 0.02977509782383314



```
In [15]: ▶ plt.figure(figsize = (10, 10))
sns.heatmap(data.corr(), annot = True)
```

Out[15]: <Axes: >



```
In [16]: ▶ from sklearn.linear_model import LinearRegression
from sklearn.metrics import r2_score
#Train the model
model = LinearRegression()
model.fit(X_train, y_train)
#Evaluating the model on the test set
y_pred = model.predict(X_test)
r2 = r2_score(y_test, y_pred)
print("R2 score:", r2)
```

R2 score: 0.02977509782383314

```
In [17]: ▶ #Model
lr = LinearRegression()
#Fit model
lr.fit(X_train, y_train)
#predict
#prediction = lr.predict(X_test)
#actual
actual = y_test
train_score_lr = lr.score(X_train, y_train)
test_score_lr = lr.score(X_test, y_test)
print("\nLinear Regression Model:\n")
print("The train score for lr model is {}".format(train_score_lr))
print("The test score for lr model is {}".format(test_score_lr))
```

Linear Regression Model:

The train score for lr model is 0.07606212793945111
The test score for lr model is 0.02977509782383314

```
In [18]: ▶ #Ridge Regression Model
ridgeReg = Ridge(alpha=10)
ridgeReg.fit(X_train,y_train)
#train and test scorefor ridge regression
train_score_ridge = ridgeReg.score(X_train, y_train)
test_score_ridge = ridgeReg.score(X_test, y_test)
print("\nRidge Model:\n")
print("The train score for ridge model is {}".format(train_score_ridge))
print("The test score for ridge model is {}".format(test_score_ridge))
```

Ridge Model:

The train score for ridge model is 0.0760619628143433
The test score for ridge model is 0.02976225611691863

```
In [19]: ▶ #Lasso regression model
print("\nLasso Model: \n")
lasso = Lasso(alpha = 10)
lasso.fit(X_train,y_train)
train_score_ls =lasso.score(X_train,y_train)
test_score_ls =lasso.score(X_test,y_test)
print("The train score for ls model is {}".format(train_score_ls))
print("The test score for ls model is {}".format(test_score_ls))
```

Lasso Model:

The train score for ls model is 0.07606073478409348
The test score for ls model is 0.0297372990132454


```
In [21]: ▶ #Using the linear CV model
from sklearn.linear_model import LassoCV
#Lasso Cross validation
lasso_cv = LassoCV(alphas = [0.0001, 0.001,0.01, 0.1, 1, 10], random_state:
#score
print(lasso_cv.score(X_train, y_train))
print(lasso_cv.score(X_test, y_test))
```

0.07606073478409348

0.0297372990132454

C:\Users\chinta pavani\AppData\Local\Programs\Python\Python311\Lib\site-p
ackages\sklearn\linear_model_coordinate_descent.py:1568: DataConversionW
arning: A column-vector y was passed when a 1d array was expected. Please
change the shape of y to (n_samples,), for example using ravel().

y = column_or_1d(y, warn=True)

```
In [22]: ▶ from sklearn.linear_model import ElasticNet
regr=ElasticNet()
regr.fit(x,y)
print(regr.coef_)
print(regr.intercept_)
```

[-128.05913739]

[15219.18170389]

```
In [23]: ▶ y_pred_elastic=regr.predict(X_train)
```

```
In [24]: ▶ mean_squared_error=np.mean((y_pred_elastic-y_train)**2)
print("Mean Squared Error on test set",mean_squared_error)
```

Mean Squared Error on test set 4275696.811777942

```
In [ ]: ▶
```