

Name - Saurav Bhandari

Course - MCA (2B)

Student Id - 207110000.

2). Steps for Network Creation:-


Step 1:- Create LAN-1 with 4 PC and create LAN2 with 4 PCs

Step 2:- Connect both LAN with router and configure the router.

Step 3:- Default Gateway for LAN-1 is 10.0.0.5.

Default Gateway for LAN-2 is 192.168.1.5.

Step 4:- Sending Pdu to see if connection is established



PC0

Physical Config Desktop Programming Attributes

IP Configuration

Interface: FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address: 10.0.0.1

Subnet Mask: 255.0.0.0

Default Gateway: 10.0.0.5

DNS Server: 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address: /

Link Local Address: FE80:2E0:A3FF:FE11:85AE

Default Gateway:

DNS Server:

802.1X


☐ Use 802.1X Security

Authentication: MD5

Username:

Password:


☐ Top





Logical Physical x 1553, y: 500

[Root] 10.23.00



Simulation Panel

Event List

Vis.	Time(sec)	Last Device	At Device	T
	0.000	-	PC0	
	0.001	PC0	Switch0	
	0.002	Switch0	Router0	
	0.003	Router0	Switch1	
	0.004	Switch1	PC5	
	0.005	PC5	Switch1	
	0.006	Switch1	Router0	
	0.007	Router0	Switch0	
	0.008	Switch0	PC0	
	0.381	-	Switch1	

Reset Simulation ☒ Constant Delay Captured to 0.381 s

Play Controls



Event List Filters - Visible Events

ACL Filter, ARP, BGP, Bluetooth, CAPWAP, CDP, DHCP, DHCPv6, DNS, DTP, EAPOL, EIGRP, EIGRPv6, FTP, H.323, HSRP, HSRPv6, HTTP, HTTPS, ICMP, ICMPv6, IPSec, ISAKMP, IoT, IoT TCP, LACP, LLDP, Meraki, NDP, NETFLOW, NTP, OSPF, OSPFv6, PAgP, POP3, PPP, PPPoE, PTP, RADIUS, RER, RIP, RIPng, RTP, SCOP, SMTP, SNMP, SSH, STP, SYSLOG, TACACS, TCP, TFTP, Telnet, UDP, USB, VTP

Edit Filters

Show All/None

Time: 00:17:46.018 PLAY CONTROLS



Copper Straight-Through


Scenario 1

New

Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
	Successful	PC0	PC5	ICMP		0.000	N	0	(edit)	(delete)



PC4

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface: FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address: 192.168.1.1

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.1.5

DNS Server: 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address: /

Link Local Address: FE80::202:1:FF:FEA2:C30B

Default Gateway:

DNS Server:

802.1X

☐ Use 802.1X Security

Authentication: MD5

Username:

Password:

☐ Top

