

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Discover, Falsify, Revise: Auditing Input-Use Claims from Source Code to Predictive Contribution in Agent-Discovered Cell Models	[Paper] [Paper: PDF p. 1]
Authors	Mengran Li, Bo Li, Chengyang Zhang, Yang Yan, Jinfeng Xu, Zhenchao Tang	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
URL	https://arxiv.org/abs/2609.27234	[Paper metadata]
PDF URL	https://arxiv.org/pdf/2609.27234v1	[Paper metadata]
Publication date	2026-09-24	[Paper metadata]
Core method name	CELLAUDIT	[Paper] [Paper: PDF p. 1–2]
Primary task	Perturbation response prediction (chemical & genetic) under multimodal readouts (morphology + transcriptomics)	[Paper] [Paper: PDF p. 1–2, Fig 1A]
Key datasets	BBBC036/BBBC047 (Cell Painting + L1000), LINCS–Pilot1, LKCP Batch 2, sci-Plex3, Norman CRISPRa (GSE133344)	[Paper] [Paper: PDF p. 5, 8, 31; Table 2, 27]
Evaluation metric (primary)	Global Pearson correlation coefficient (Global PCC) on concatenated morphology–transcriptomics responses	[Paper] [Paper: PDF p. 5, Table 1, Table 21]
Input-use evidence metrics	Factorial PCC effect E_{compd} , target-loss gain ΔL_{compd} , compound-shuffle PCC drop, scaffold-aware intervals	[Paper] [Paper: PDF p. 4, 6, 25; Eq 4–6; Table 1, 16, 47]
Code/model release status	Project page provided (https://limengran98.github.io/CellAudit/); no explicit GitHub or model weights in text	[Paper] [Paper: PDF p. 1]

02 一句话总结

该论文提出 CELLAUDIT 框架，系统性审计由大语言模型代理（如 CellScientist）生成的细胞响应预测器是否真正利用了其声称使用的扰动输入（如化合物身份），而非仅依赖控制背景或数据伪影；它通过三重验证——源码可进入性（source consumption）、拟合预测依赖性（fitted dependence）、目标相关预测增益（target-relevant contribution）——揭示了高预测性能与真实扰动使用之间存在显著gap，并在 BBBC047、sci-Plex 和 Norman 等多个 perturbation prediction 场景中验证了该框架对模型修订和发现质量的提升作用；其核心贡献是将 agentic discovery 的范式从 “generate-score-revise” 推进至 “discover-falsify-revise”，但所有实证均限于离线审计与重训练，未涉及在线闭环干预或生物学机制解释。

03 研究问题

论文直面 agentic model discovery 中一个被忽视的根本矛盾：当语言模型代理基于 held-out predictive score（如 Global PCC）迭代生成、选择和修订预测器时，该 score 的提升无法保证模型真正利用了其设计声明的扰动输入（如 compound identity），而可能仅通过拟合 control profiles、plate effects 或其他混杂结构实现 [Paper] [Paper: PDF p. 1–2]。这一 “prediction-claim gap” 导致 discovery 过程缺乏可信度保障，尤其在 perturbation prediction 这类需因果解释的生物任务中风险极高。因此，研究问题聚焦于：**如何构建一个可扩展、可复现、证据链完整的审计流程，以区分“模型声称使用扰动”、“模型输出实际依赖扰动”和“该依赖确实提升了对观测响应的预测”这三个递进层次？** 并进一步追问：该审计能否指导有效修订、提升下游发现质量、并在新数据上泛化其结论？

04 研究背景与发展路径

背景始于两个并行趋势：一是 AI virtual cell 的兴起（如 CellScientist、CellForge、HarmonyCell），其依赖 LLM 代理自动设计、训练、评估预测器，追求 high-scoring models [Paper] [Paper: PDF p. 1–2]；二是 perturbation prediction 领域对模型可靠性日益增长的质疑，已有工作指出模型常 shortcut 到 control 或 context 而非 perturbation [Paper] [Paper: PDF p. 1, 10]。然而，现有方法（如 saliency maps、permutation tests）多为 post-hoc 行为测试，不追溯至源码声明，亦不区分“依赖”与“有益依赖” [Paper] [Paper: PDF p. 2]。发展路径由此清晰：作者拒绝将 audit 视为单一测试，而是构建一个**证据分层框架**——从注册的 input-use claim 出发（e.g., “compound query attends to morphology features”），经源码静态检查（是否可进入）、冻结 checkpoint 上的行为干预（是否改变预测）、再到目标损失对比（是否提升预测），形成一条从声明到证据的完整链条 [Paper] [Paper: PDF p. 2–4]。该路径直接回应了 agentic discovery 对 scalable, claim-aware validation 的迫切需求，而非仅优化预测本身。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Prediction–claim gap	A high-scoring agent-selected predictor (Global PCC=0.3153) is <i>exactly invariant</i> to compound replacement, while a control-only predictor achieves nearly identical performance (0.3142) [Paper] [Paper: PDF p. 1, 5]	The cited compound-query pathway is mathematically inactive due to singleton key-value attention, blocking information flow [Paper] [Paper: PDF p. 1, 3, 6]	Figure 1B shows zero compound Δ PCC; Table 1 reports $E_{\text{cmpd}}=0.0000$ for Prediction-score; [Paper] [Paper: PDF p. 6] identifies "one-key attention cannot transmit compound identity" as the root cause.
Fitted dependence $\neq$ Target-relevant contribution	Among 48 generated candidates, 47 show fitted dependence (prediction changes under compound swap) on both folds, but only 20 exhibit positive target-loss scaffold intervals (i.e., loss gain >0) on both folds [Paper] [Paper: PDF p. 2, 6]	An executable pathway may have negligible effect after fitting, and input dependence may not translate to predictive benefit due to noise, redundancy, or misalignment with target metric [Paper] [Paper: PDF p. 2, 4]	Figure 2a,b visualizes this divergence; green outlines mark the 20/48 with positive intervals; Table 1 shows only 0/5 refits pass the reference threshold for compound use in Prediction-score.
Predictive generalization $\neq$ Claim generalization	When LINCS-selected designs are refit on independently acquired LKCP, dose contribution persists (+0.0237–+0.0341 Global PCC), but compound-identity contribution vanishes (–0.000070 to +0.0033) [Paper] [Paper: PDF p. 8–9]	Input-use claims are data- and acquisition-context-dependent; a pathway functional in one assay may be irrelevant or confounded in another due to technical variation (e.g., plate batch, imaging protocol) [Paper] [Paper: PDF p. 9]	Figure 4a,b separates compound/dose allocations; Table 35–36 report the stark contrast; [Paper] [Paper: PDF p. 9] states "dose contribution persists, whereas support for compound identity does not persist".
Manual verification scalability bottleneck	Agentic discovery generates increasingly numerous and diverse models, making manual code inspection and behavioral testing infeasible [Paper] [Paper: PDF p. 1]	The combinatorial explosion of candidate architectures, fusion strategies, and readout designs exceeds human capacity for rigorous validation [Paper] [Paper: PDF p. 1]	Figure 1A–C illustrates the automated pipeline; Section 4.1–4.3 details deterministic source checking and frozen-checkpoint intervention; Table 25 shows path-constrained runs achieve 100% valid candidates via deterministic compilation.

06 核心思想

论文的核心思想是：**perturbation prediction** 模型的可信度不能仅由其预测分数担保，而必须通过一个可分解、可审计、可修订的三阶段证据链来确立——即“声明可进入 → 输出真依赖 → 依赖有增益”。这一思想源于对 agentic discovery 本质缺陷的深刻洞察：score-based feedback 是 blind 的，它奖励结果却无视过程。因此，CELLAUDIT 不是设计一个更强的预测器，而是设计一个“元验证器”，它将模型的 input-use claim（如“compound identity modulates FiLM layer”）作为待检验的科学假设，而非设计文档的装饰性描述。其创新在于将软件工程中的“契约式设计”（design by contract）引入生物AI，要求每个 claim 必须附带可执行的、

可证伪的测试协议（source check + replacement rule + threshold），并将 falsification 结果（而非仅 score）作为 revision 的核心驱动力，从而将 discovery 过程本身纳入科学方法论的约束之下。

07 方法总览

CELLAUDIT 方法是一个闭环的、证据驱动的模式审计与修订框架，严格遵循 “Discover–Falsify–Revise” 范式。其总览分为三个不可分割的阶段：（1）**Discover**：在固定数据划分（Folds 1–3）和评估协议下，LLM 代理（如 CellScientist）执行 agentic search，生成候选模型并基于 Fold-3 score 选择 checkpoint；（2）**Falsify**：对选定的 frozen checkpoint 执行三重审计——① **Source Inspection**：使用 AST checker 验证注册的 input-use statement 是否在代码中被实现（implemented）、被矛盾（implementation-contradicted）或未解析（unresolved）[Paper] [Paper: PDF p. 4]；② **Fitted Dependence Test**：在 held-out folds（4/5）上，对注册输入（如 compound）进行 deterministic replacement（e.g., shuffle within same control group），测量 prediction-space distance（RMS change）；③ **Target-relevant Contribution Test**：在同一 replacement 下，计算 higher-is-better score decrease (Δm_q) 和 loss increase (ΔL_q)，以量化该依赖是否带来预测增益 [Paper] [Paper: PDF p. 4, Eq 1]；（3）**Revise**：根据 falsification 结果指导修订——若 source 被 contradicted，则强制编译显式通路（path-constrained）；若 dependence 存在但 contribution 弱，则采用 residual learning over control-only baseline（falsification-guided）[Paper] [Paper: PDF p. 4, Eq 2]。整个流程强调 “freeze before test”：source、checkpoint、audit rules 在 held-out evaluation 前完全冻结，确保证据无污染。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Source Code Checker (AST-based)	Static analysis of registered input-use statements to classify them as implemented, implementation-contradicted, or unresolved	To ground audit in the model's actual implementation, not just its claimed behavior; detects structural defects invisible to behavioral tests (e.g., singleton attention)	Input: Registered input coordinate + cited source location (e.g., cross_attn.compound_query). Output: Classification label + resolved/unresolved status [Paper] [Paper: PDF p. 4]	Figure 1B identifies "Singleton attention: no query effect"; Table 1 labels the Prediction-score source as "Contradicted ^a "; [Paper] [Paper: PDF p. 6] explicitly cites "one-key attention cannot transmit compound identity" as the defect.	Removal would collapse CELLAUDIT into a pure behavioral test, losing the ability to localize why a model fails —e.g., distinguishing a bug in code from a fundamental limitation of the architecture or data.

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Frozen Checkpoint Replacement Engine	Applies deterministic, response-blind input interventions (e.g., compound shuffle, dose replacement) to a frozen model's predictions on held-out data	To isolate the effect of a single input variable, controlling for all other sources of variation (training dynamics, optimizer state); enables causal-like attribution without retraining	Input: Frozen checkpoint, held-out data batch, replacement rule (e.g., "shuffle compound within same control vector class"). Output: Interventional predictions $\mathbb{E}(x_{-q}, \tilde{x}_q)$ and metrics (Δm_q , ΔL_q) [Paper] [Paper: PDF p. 4, 6]	Table 1 reports exact zero compound ΔPCC for Prediction-score; Figure 2a plots prediction change (RMS) vs. target-loss gain; Table 5 shows compound effects averaged over 32 permutations per refit.	Removal would make it impossible to attribute prediction changes to specific inputs, conflating compound effects with dose, context, or noise; all quantitative evidence in Tables 1, 5, 11, 47 would vanish.
Scaffold-Aware Uncertainty Quantifier	Computes confidence intervals by resampling Murcko scaffold groups (for chemical tasks) or biological groups, treating scaffolds—not individual compounds—as the statistical unit	To quantify uncertainty over <i>held-out chemical families</i> , not just random compound samples; addresses the reality that generalization failure often occurs at the scaffold level, not per-compound level	Input: Set of held-out Murcko scaffold labels, 32 fixed replacement maps per refit, 5 paired refits. Output: Scaffold 95% CI (e.g., for $\mathbb{E}_{\text{cmpd}}$) [Paper] [Paper: PDF p. 24–25, Table 16]	Table 16 reports "Scaffold 95% CI" for BBBC047/Fold 5 compound PCC drop as [+0.0024, +0.0079]; [Paper] [Paper: PDF p. 24] states "This preserves within-scaffold response dependence and quantifies uncertainty over held-out chemical families."	Removal would revert to standard i.i.d. intervals, grossly underestimating uncertainty for chemical generalization and potentially overstating significance of scaffold-level effects (e.g., falsely claiming compound use generalizes across all scaffolds).

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Falsification-Guided Residual Trainer	Trains a perturbation-specific residual $h(c,p,a)$ added to a frozen control-only predictor $g(c)$: $\hat{y} = g(c) + \alpha h(c,p,a)$, with α selected on Fold-3	To directly address the case where dependence exists but contribution is weak, by forcing the model to learn <i>only the perturbation-specific delta</i> over a strong baseline, thus decoupling context modeling from perturbation modeling	Input: Frozen $g(c)$, perturbation inputs (p,a) , Fold-3 data. Output: Residual h and scale α [Paper] [Paper: PDF p. 4, Eq 2]	Table 1 shows Falsification-guided achieves $SE_{\text{cmpd}} = 0.0053$ and positive ΔL_{cmpd} ; [Paper] [Paper: PDF p. 6] states it "recovers positive mean compound contributions while retaining predictive gains over the control-profile-only baseline."	Removal would leave no mechanism to recover target-relevant contribution when the base model is already highly predictive via context; the "Guided" row in Table 1 would show no improvement over "Control only".

09 关键公式与符号

论文中明确给出的可核验公式仅有 Equation 1 和 Equation 2；其余符号/指标虽频繁出现，但未以公式形式定义。关键公式与符号如下：

- Equation 1** ([Paper] [Paper: PDF p. 4])：定义了输入替换下的预测得分变化 Δm_q 和损失变化 ΔL_q ：
$$\Delta m_q = m(f(x), y) - m(f(x_{-q}, \tilde{x}_q), y), \quad \Delta L_q = L(f(x_{-q}, \tilde{x}_q), y) - L(f(x), y).$$

其中 m 是 higher-is-better metric（如 Global PCC）， L 是 loss（如 MSE）， x_{-q} 表示移除第 q 个输入， $\tilde{x}_q$ 是其替换值。
- Equation 2** ([Paper] [Paper: PDF p. 4])：定义了 falsification-guided discovery 的残差学习形式：
$$\hat{y} = g(c) + \alpha h(c, p, a).$$

其中 $g(c)$ 是在 Folds 1–2 上拟合并冻结的 control-only 预测器， $h(c,p,a)$ 是 perturbation-specific 残差， α 是可学习的缩放因子。
- 关键符号/指标**（未以公式形式定义，但全文核心）：
 - Global PCC**: 所有后处理行和所有维度上展平后的联合输出与目标之间的 Pearson 相关系数 [Paper] [Paper: PDF p. 22]。
 - $SE_{\text{cmpd}} / SE_{\text{ctrl}}$** : 因子效应（factorial effect），定义为在另一个输入的两个状态（e.g., high/low dose）下，PCC 下降的平均值 [Paper] [Paper: PDF p. 4, Table 1]。
 - ΔL_{cmpd}** : 化合物替换导致的目标损失（MSE）增加量，用于衡量 target-relevant contribution [Paper] [Paper: PDF p. 4, Table 1]。
 - Reference threshold $\tau_{j,q}$** : 基于 32 次固定参考值的成对绝对差异的 95th 百分位数，用于判定 effect 是否 “supported” [Paper] [Paper: PDF p. 22]。
 - Murcko scaffold**: 基于 Bemis-Murcko 算法的化合物骨架分组，用作化学泛化不确定性估计的统计单元 [Paper] [Paper: PDF p. 5, 22]。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
BBBC047 Prediction-score audit	Does the agent-selected predictor use compound identity?	Compound shuffle vs. correct input on Fold 4/5; 5 paired refits	$\Delta PCC = 0.0000$ on both folds; $E_{\text{cmpd}} = 0.0000$; all 5 refits fail reference threshold [Table 1]	The predictor is compound-invariant; its high score (0.3153) is achieved without using compound identity.	That the model uses <i>no</i> perturbation information — dose and context effects remain strong ($E_{\text{ctrl}} > 0.19$).	[Paper] [Paper: PDF p. 5–6; Table 1]
BBBC047 Disjoint control wells	Does the compound invariance persist when control inputs and targets use physically disjoint wells?	Shared vs. Disjoint control banks; same model refit on newly constructed data [Paper] [Paper: PDF p. 6]	Score-selected source remains exactly invariant (0.0000 ΔPCC) in all refits; Guided design shows positive but smaller compound gain [Table 6, 9]	The mismatch is not an artifact of physical well reuse; it reflects a fundamental design/implementation flaw.	That <i>all</i> models suffer from this flaw — the Guided design successfully recovers compound use.	[Paper] [Paper: PDF p. 6; Table 6, 9]
48-candidate stratified audit	Is fitted dependence sufficient evidence for target-relevant contribution?	48 candidates across BBBC036/047; measure RMS change and ΔL_{cmpd} on both folds [Paper] [Paper: PDF p. 2, 6]	47/48 show fitted dependence ($RMS > 0$), but only 20/48 have positive ΔL_{cmpd} intervals on <i>both</i> folds [Figure 2a,b]	Fitted dependence and target-relevant contribution are empirically distinct and must be tested separately.	That the 27 candidates with negative/inconclusive ΔL_{cmpd} are useless — they may still provide value in other contexts or with different metrics.	[Paper] [Paper: PDF p. 2, 6; Figure 2a,b]
sci-Plex audit-enriched feedback	Does returning audit diagnostics (not just score) to the agent improve discovery outcomes?	Audit vs. Score feedback; 5 paired trajectories; same anchor, permissions, budget [Paper] [Paper: PDF p. 7]	Audit yields higher mean PCC (+0.0024 on Fold 4) and larger mean compound/dose loss gains, but paired CIs include zero [Figure 3b,c; Table 68]	Audit-enriched feedback <i>tends</i> to improve both prediction and input-use contribution, but the evidence is suggestive, not conclusive, at $n=5$.	That audit feedback <i>guarantees</i> improvement — the paper explicitly states "evidence for improved discovery remains suggestive rather than conclusive" [Paper] [Paper: PDF p. 2].	[Paper] [Paper: PDF p. 7; Figure 3; Table 68]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
LINCS→LKCP transfer	Does predictive generalization imply claim generalization?	Refit frozen LINCS-selected designs on LKCP; test compound/dose allocation [Paper] [Paper: PDF p. 8]	Dose allocation persists (+0.0237/+0.0341), but compound-identity allocation vanishes (−0.000070/+0.0033); none pass compound criterion on LKCP [Figure 4a; Table 35]	Predictive generalization and input-use claim generalization are dissociable; a claim validated in one acquisition may fail in another.	That dose is <i>always</i> generalizable — the paper notes LINCS compound-identity criterion passes for 35/50 refits on Fold 4, showing variability even within the same cohort.	[Paper] [Paper: PDF p. 8–9; Figure 4a; Table 35]

11 对结论的正确理解

论文的结论必须严格限定于其证据范围：CELLAUDIT 成功揭示并量化了 agentic discovery 中普遍存在的 “prediction–claim gap”，证明了高预测分数（如 Global PCC）与真实扰动输入使用之间不存在必然联系；它提供了一套可操作的、三阶段的审计协议（source → dependence → contribution），并验证了该协议能指导出更可信的模型修订（如 falsification-guided residual learning）；其关于 “predictive generalization ≠ claim generalization” 的结论，是基于 LINCS→LKCP 这一特定 transfer setting 的实证，表明剂量（dose）贡献比化合物身份（compound identity）贡献更具跨平台鲁棒性。**关键边界在于：所有结论均基于 offline, frozen-checkpoint auditing 和 subsequent retraining，不涉及在线干预、生物学机制推断、或对未见 perturbation 类型（如 novel CRISPR guides）的泛化承诺；其 “improved discovery” 在 sci-Plex 中仅为趋势性结果（paired CIs span zero），并非统计确证；其方法论价值远大于单个任务上的 SOTA 提升。**

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Paired interval uncertainty in sci-Plex	The paired t-intervals for Audit–Score differences in PCC and compound/dose contributions across five sci-Plex trajectories all include zero, preventing conclusive claims of improvement [Paper] [Paper: PDF p. 2, 7]	The authors call for "larger-scale matched comparisons" to achieve conclusive evidence, implying increased trajectory count or more powerful agents as a future step [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 2, 7] ("evidence for improved discovery remains suggestive rather than conclusive")

Limitation	Specific manifestation	Future direction proposed by authors	Source
Dose identifiability in BBBC047	Due to insufficient observed dose variation within compounds, BBBC047 dose testing is "not identifiable" — no legal 0.1-log-dose contrast exists on either fold [Paper] [Paper: PDF p. 23]	The authors propose using "more diverse dose-response data" in future work to enable robust dose-use auditing [Paper] [Paper: PDF p. 23]	[Paper] [Paper: PDF p. 23] ("Dose is therefore not identifiable in the BBBC047 panels (Table 50)")
Scaffold-group independence assumption	The scaffold-aware bootstrap assumes Murcko scaffold groups are independent biological units, but the paper notes "scaffold labels do not ensure fully independent biological groups" [Paper] [Paper: PDF p. 20, 21]	The authors suggest "developing more biologically grounded grouping criteria" as a future direction to better capture true biological independence [Paper] [Paper: PDF p. 20]	[Paper] [Paper: PDF p. 20, 21] ("These are source-scaffold, not compound-cluster, intervals; scaffold labels do not ensure fully independent biological groups.")
Scope of input-use claims	CELLAUDIT audits only the <i>registered</i> input-use claims (e.g., "compound identity is used"), not all possible spurious correlations or shortcuts the model might exploit [Paper] [Paper: PDF p. 9]	The authors state that "observed-support replacements avoid unobserved combinations but do not establish biological exchangeability, mechanism, or causal effects", pointing to the need for complementary causal inference methods [Paper] [Paper: PDF p. 9]	[Paper] [Paper: PDF p. 9] ("Observed-support replacements avoid unobserved combinations but do not establish biological exchangeability, mechanism, or causal effects.")

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The "singleton key-value attention" diagnosis is overly specific. The paper attributes the BBBC047 compound invariance solely to a "singleton key-value attention pathway whose query cannot transmit compound information" [Paper] [Paper: PDF p. 2, 3]. However, the abstract and main text never show the full attention weight matrix or prove that <i>no other pathway</i> (e.g., through dose embedding, context gating, or residual connections) could carry compound signal.	This risks misdiagnosing a systemic architectural limitation (e.g., insufficient capacity, poor initialization) as a localized coding bug. If the true cause is broader, the "path-constrained" fix (enforcing a compound route) may be insufficient, and the "falsification-guided" fix (residual over control) may merely mask the underlying weakness.	It matters because the entire revision strategy hinges on the precision of the source diagnosis. An incorrect root cause leads to suboptimal or ineffective revisions, undermining CELLAUDIT's utility as a debugging tool.	To test, one could ablate <i>all</i> potential compound pathways simultaneously (e.g., zero out compound fingerprint input <i>and</i> all derived embeddings) and see if invariance persists. Alternatively, perform gradient-based attribution (e.g., integrated gradients) on the compound input to map its influence across all layers, not just the cited attention module.	[Paper] [Paper: PDF p. 1, 2, 3, 6] repeatedly cite "singleton attention" as the sole cause, but provide no evidence excluding other routes; Figure 1B shows the diagnosis but no validation of its exclusivity.
The "reference threshold" for claim qualification is arbitrary and task-dependent. The threshold $\tau_{j,q}$ is defined as the 95th percentile of absolute pairwise differences among 32 reference scores [Paper] [Paper: PDF p. 22], yet its choice (95th vs. 90th or 99th) is not justified, and its magnitude varies wildly across tasks (e.g., BBBC047 compound effect ~ 0.005, sci-Plex compound loss gain ~ 0.022) [Paper] [Paper: PDF p. 7, Table 1].	This makes cross-task comparison of "support" meaningless and introduces a hidden hyperparameter. A model deemed "unsupported" on BBBC047 might be "supported" on sci-Plex simply due to different noise floors, not better design. It conflates statistical detectability with biological relevance.	It matters because the paper's central narrative — that CELLAUDIT reveals a "gap" — relies on the binary "supported/inconclusive/unsupported" classification. If the threshold is arbitrary, the gap size is ill-defined.	To test, one could perform sensitivity analysis: vary the percentile (e.g., 90th, 95th, 99th) and report how the fraction of "supported" models changes across all experiments (Tables 1, 33, 38). Additionally, compare against effect-size benchmarks (e.g., Cohen's d) normalized by task-specific variance.	[Paper] [Paper: PDF p. 22] defines $\tau_{j,q}$ but gives no rationale for the 95th percentile; Table 1 and Table 33 show vastly different raw effect magnitudes across tasks, suggesting threshold calibration is essential.

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The "disjoint control wells" experiment does not eliminate all confounding. While splitting control wells into A/B banks addresses physical overlap, the paper admits this "does not establish that all upstream preprocessing or biological dependence has been removed" [Paper] [Paper: PDF p. 17]. Crucially, the CP targets are still computed as "empirical mid-CDF values relative to the direction' s reference bank", meaning the <i>same</i> control distribution shapes the target for both shared and disjoint arms.	This means the "disjoint" arm still shares the <i>statistical properties</i> of the control distribution (e.g., batch effects, plate artifacts), so the persistence of invariance could reflect shared statistical confounds, not a pure test of compound usage. The experiment's conclusiveness is overstated.	It matters because the paper uses this result to claim the mismatch is "fundamental", not technical. If confounds persist, the revision strategies may be targeting the wrong problem.	To test, one could construct a truly independent control set (e.g., from a different cell line or passage) and repeat the experiment, or use domain-adversarial training to explicitly remove control-distribution features from the compound representation before feeding it to the model.	[Paper] [Paper: PDF p. 17] explicitly states the limitation: "This intervention separates physical wells at the reconstructed CP reference layer; it does not establish that all upstream preprocessing or biological dependence has been removed."

14 学到的知识

- **审计必须分层：**一个声称“使用化合物”的模型，其可信度需要三层独立证据支撑——源码中该路径必须可执行（source consumption），其输出必须随化合物变化（fitted dependence），且这种变化必须提升对真实响应的预测（target-relevant contribution）。这三层可以全部失败（如 BBBC047 Prediction-score）、部分失败（如 47/48 candidates show dependence but only 20 show contribution），或全部成功（如 Falsification-guided），缺一不可。
- **干预设计决定证据强度：**CELLAUDIT 的核心力量来自其 deterministic, response-blind replacement rules（如 compound shuffle within same control group）。这种设计避免了反事实预测的陷阱，使 Δm_q 和 ΔL_q 成为可复现、可比较的因果代理指标，远超 post-hoc attribution 方法。
- **不确定性必须匹配问题域：**在化学 perturbation 中，“泛化”意味着对新 scaffold 的鲁棒性，因此 scaffold-aware bootstrap（而非标准 t-test）是量化 claim generalization 的正确方式。忽略此点会导致对模型可靠性的严重误判。
- **Revision must be hypothesis-driven：**针对 source contradiction（e.g., singleton attention），应强制编译显式通路（path-constrained）；针对 weak contribution despite dependence，应采用 residual learning over a strong baseline（falsification-guided）。通用的“调参”或“增大模型”无法解决这些结构性问题。

- **Predictive success is necessary but insufficient:** BBBC047 的案例 (0.3153 vs. 0.3142) 是教科书级的警示——两个模型在 held-out performance 上几乎无法区分，但在科学解释性上天壤之别。任何以 prediction score 为唯一优化目标的 discovery 流程都存在根本性盲区。

15 与既有知识的连接

- **候选连接/方法论连接:** CELLAUDIT 与 perturbation prediction 领域的 benchmarking efforts (如 PerturBench [Wu et al., 2025], PertEval-scFM [Wenteler et al., 2025]) 形成互补。后者关注“模型能预测多好”，而 CELLAUDIT 关注“模型为何能预测好”，填补了从 performance 到 mechanism 的鸿沟。它也呼应了 Viñas Torné et al. (2026) 提出的 Systema 框架对“systematic variation”的警惕，但提供了更精细的、输入级别的审计工具。
- **候选连接/方法论连接:** 在可解释性 AI 领域，CELLAUDIT 区别于 saliency-based 方法 (如 Sanity Checks [Adebayo et al., 2018])，因为它不依赖梯度或扰动输出，而是基于注册声明进行前向干预；它也区别于 ConceptSMILE [Mollapour et al., 2026]，后者审计概念解释的可靠性，而 CELLAUDIT 审计的是模型架构中对具体生物输入 (compound, dose) 的硬编码使用。
- **候选连接/方法论连接:** 在 agentic AI 领域，CELLAUDIT 为 Huang et al. (2025) 提出的“automated hypothesis falsification”提供了首个在生物AI领域的落地实现，将 POPPER-style logic (if claim, then test, else revise) 嵌入到 LLM agent 的闭环中，是 scientific agent 的重要演进。
- **弱连接/方法论连接:** 与 single-cell foundation models (如 scGPT [Cui et al., 2024]) 的连接是弱的——CELLAUDIT 是一个通用审计框架，其输入 (compound fingerprint, dose log) 和输出 (morphology + transcriptomics) 与 scGPT 的输入 (gene expression) 和输出 (perturbed expression) 不同，但其“声明-审计-修订”范式可迁移至 foundation model 的 prompt engineering 或 adapter tuning 中，以验证其是否真正利用了提供的 perturbation context。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** Scaffold-Informed Cross-Modal Alignment Auditor

originating limitation/observation: CELLAUDIT reveals that compound-identity claims fail to generalize from LINCS to LKCP (Figure 4a), while dose claims persist. This suggests that cross-modal alignment (e.g., between morphology and transcriptomics) may be scaffold-dependent, but current methods treat all compounds equally. **core hypothesis:** Aligning modalities using scaffold-aware contrastive learning will improve the generalizability of compound-use claims across acquisitions, compared to standard joint embedding. **delta from paper:** CELLAUDIT audits *post-hoc*; this idea builds a *proactive* alignment mechanism where the scaffold group is used as a hard constraint during training, not just for evaluation. **initial method:** Modify a multimodal foundation model (e.g., scGPT) to include a scaffold-aware triplet loss: for each compound, pull together its morphology and transcriptomics embeddings, while pushing apart embeddings of compounds from *different* Murcko scaffolds. Train on BBBC047, then audit compound-use on LKCP. **validation:** Compare scaffold-aware alignment against standard alignment using CELLAUDIT's $SE_{\{\text{cmpd}\}}$ and scaffold 95% CI on LKCP. Success: scaffold-aware model shows higher mean $SE_{\{\text{cmpd}\}}$ and narrower scaffold CI that remains above zero. **failure modes:** Scaffold groups may be too coarse (missing sub-scaffold biology) or too fine (insufficient samples per group); the triplet loss may overfit to scaffold idiosyncrasies. **innovation status:** unverified

- **name:** Graph-Enhanced Input-Use Falsification for Genetic Perturbations

originating limitation/observation: In the Norman CRISPRa task, CELLAUDIT tests the "pair-input bundle" (multi-hot + anchor), but GEARS uses native GO/coexpression graphs [Paper] [Paper: PDF p. 31–32]. This suggests graph structure may encode compound-use logic that flat multi-hot vectors miss. **core hypothesis:** Replacing the pair-input bundle with a graph-structured perturbation representation (e.g., GNN-encoded pair) will yield more robust and interpretable compound-use claims in combinatorial perturbation prediction. **delta from paper:** CELLAUDIT treats inputs as flat vectors; this idea leverages prior biological knowledge (GO, coexpression) to structure the input space, making the "use" of perturbation information more biologically grounded and auditable at the pathway level. **initial method:** Replace the 105-dim multi-hot pair vector in Norman with a GNN encoder (using GEARS' GO graph) that outputs a dense embedding. Audit this new model using CELLAUDIT's bundle replacement protocol on Fold 4/5. **validation:** Compare the new model's $E_{\{\text{pair}\}}$ and support rate (5/5) against baseline CellScientist and GEARS on Norman. Success: higher $E_{\{\text{pair}\}}$ and evidence of pathway-level contributions (e.g., via GNN attention weights). **failure modes:** Graph encoder may over-smooth signals; lack of ground-truth pathway usage makes "correct" contribution ambiguous. **innovation status:** unverified

- **name:** Perturbation-Conditioned Cell State Representation Auditor

originating limitation/observation: CELLAUDIT focuses on input-use for *prediction*, but user research emphasizes *cell state representation*. The paper shows that control-only predictors can achieve high PCC (0.3142), implying they capture a strong "baseline state"; CELLAUDIT's residual learning ($\hat{y} = g(c) + \alpha h(c,p,a)$) implicitly defines a perturbation-conditioned state $h(c,p,a)$. **core hypothesis:** The residual $h(c,p,a)$ learned by CELLAUDIT's falsification-guided trainer serves as a high-fidelity, perturbation-conditioned cell state representation, superior to representations from unsupervised models (e.g., scVI) for downstream perturbation prediction tasks. **delta from paper:** CELLAUDIT uses the residual as a means to an end (better prediction); this idea treats the residual *itself* as the primary output—a reusable, task-specific cell state embedding. **initial method:** Extract $h(c,p,a)$ from a BBBC047 falsification-guided model. Use it as input to a simple classifier for predicting compound MoA (Mechanism of Action) on a held-out dataset (e.g., MoA annotations from LINCS). Compare against scVI latent space and raw gene expression. **validation:** Evaluate MoA classification accuracy (AUC). Success: $h(c,p,a)$ achieves significantly higher AUC than baselines, demonstrating its perturbation-specific discriminative power. **failure modes:** $h(c,p,a)$ may be overfit to the specific prediction task (morphology+transcriptomics) and not generalize to other MoA definitions. **innovation status:** unverified