

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Correlation-Guided Flow Matching with Annealed Masking for Spatial Transcriptomics Generation	[Paper] [Paper: PDF p. 1]
Authors	Yupei Zhang, Hao Chen, Li Pan, Chao Li, Xiaohan Xing	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Core task	Histology-to-ST prediction (spatial transcriptomics generation from H&E images)	[Paper] [Paper: PDF p. 1, 2]
Method name	CorrFlow	[Paper] [Paper: PDF p. 1]
Key technique	Conditional flow matching + annealed masking + gene graph regularization	[Paper] [Paper: PDF p. 1, 4]
Primary evaluation metric	PCC (Pearson correlation coefficient) and HPCC (Hallmark-Gene PCC) on HMMVG-50 genes	[Paper] [Paper: PDF p. 7, Table 1]
Benchmark datasets	HEST-1K (10 cancer/tissue types), STImage-1K4M (Brain, Breast)	[Paper] [Paper: PDF p. 7, Table 9]
Baseline model	STFlow [11] (flow-matching baseline)	[Paper] [Paper: PDF p. 7]
Code/data availability	Not stated in text; “not verified”	Not mentioned in supplied material

02 一句话总结

CorrFlow 提出一种面向空间转录组（ST）生成的条件流匹配框架，通过**渐进式掩码策略**（annealed masking）和**基因图正则化**（gene graph regularization）显式建模基因间依赖关系，解决现有生成模型将基因视为独立预测目标、无法保留生物学共表达模式的根本缺陷；该方法在10个HEST-1K数据集上显著提升PCC与HPCC，尤其增强通路级预测一致性，但其STRING+WGCNA融合策略的泛化性未在外部队列验证，且未开源实现。

03 研究问题

论文直面一个被既有工作系统性忽略的核心矛盾：**生成式ST预测模型虽能建模表达分布的随机性，却在训练目标层面默认基因独立**。作者指出，这种“per-gene decomposition”并非建模能力不足所致，而是标准流匹配（Eq. 2–3）与扩散目标（Remark 1）在数学上天然分解为G个独立损失项，导致优化过程对跨基因协同建模既无激励也无约束 [Paper] [Paper: PDF p. 4]。因此，研究问题不是“能否建模基因相关性”，而是“如何重构训练信号与正则化机制，使模型**必须**学习并利用基因互作结构才能最小化损失”。

04 研究背景与发展路径

该工作处于“histology-to-ST generative modeling”演进的关键转折点：早期为确定性回归（ST-Net [8]），后转向捕捉不确定性的生成范式（Stem [40]、STFlow [11]），但均延续“per-gene marginal estimation”范式；本文则首次将**基因互作建模**从特征编码/后处理环节（如WGCNA用于预处理 [24] 或图神经网络用于回归 [38]）前移至**生成动力学核心**——即在流匹配的插值轨迹（ x_t ）构建与速度场（ v_θ ）优化中，强制引入基因维度间的耦合。这一路径跳出了“用图结构增强输入特征”的旧范式，转向“用图结构约束输出空间+用掩码重构学习任务”，构成方法论跃迁 [Paper] [Paper: PDF p. 2–3]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Per-gene decomposition of training objective	Uneven gene-level performance; highly correlated genes (e.g., x_{31}) predicted poorly despite accurate predictions for others (x_{11} , x_{21}); failure to preserve co-expression patterns	Standard CFM loss decomposes across genes (Proposition 1, Eq. 3), making cross-gene coordination unidentifiable — any gain from modeling correlation is equally achievable without it	[Paper] [Paper: PDF p. 2, 4]; Fig. 1 caption; Proposition 1 proof [Paper] [Paper: PDF p. 4]
Shortcut reconstruction near $t=1$	Network copies near-target values from x_t instead of learning meaningful transport dynamics	As $t \rightarrow 1$, $x_t \rightarrow x_1$, providing trivial reconstruction signal	[Paper] [Paper: PDF p. 5]; Eq. 8 motivation
Lack of biological constraint on output space	Predictions may violate known co-expression structures due to finite capacity/noisy gradients	Existing methods apply priors only to features or encoders, not to generative dynamics	[Paper] [Paper: PDF p. 6]; Section 3.3 intro
Train-inference magnitude mismatch from fixed masking	Input norm drops during training (masked entries = 0) but remains full during inference, causing instability	Fixed zero masking reduces average input norm by factor $\sim 1-p(t)$, creating distribution shift analogous to dropout scaling problem	[Paper] [Paper: PDF p. 5]; Section 3.2.1

06 核心思想

论文的核心思想是**将基因互作从“可选先验”升级为“不可绕过的生成约束”**。其逻辑链为：（1）观察到标准流匹配目标（Proposition 1）在数学上禁止跨基因梯度共享 → （2）提出annealed masking打破输入-输出维度一一对应，使masked基因的最优预测必须依赖joint conditional $p(x^{(M)}_1 \setminus x^{(O)}_1, c)$ ，从而**将联合建模从可选变为必需**（Proposition 2） → （3）叠加gene graph正则化，将STRING功能关联与WGCNA数据驱动共表达融合为图拉普拉斯（Eq. 10）与Huber边约束（Eq. 11），使输出空间本身被生物结构所塑造。二者协同，前者改写学习任务，后者锚定解空间，共同迫使模型习得生物学一致的生成动力学。

07 方法总览

CorrFlow 是一个两阶段协同框架：**第一阶段（Annealed-MFM）重构学习任务**——通过timestep-dependent masking（Eq. 8）将标准流匹配转化为“部分观测下的联合推断”，使模型必须利用剩余基因推断被掩码基因，从而内生驱动跨基因建模；**第二阶段（Gene Graph Regularization）约束解空间**——构建融合STRING（ $S^{(s)}$ ）与WGCNA（ $S^{(w)}$ ）的基因亲和图（Eq. 9），并施加双重正则：Huber边损失（ L_{local} , Eq. 11）保障邻近基因预测一致性，图拉普拉斯损失（ L_{global} , Eq. 12）抑制全图高频振荡，引导输出对齐低频共表达模块。最终目标为 $L = LMFM + \rho L_{local} + \lambda L_{global}$ （Eq. 16），所有组件均服务于一个目标：让生成的ST在数值准确（PCC）与生物合理（HPCC, GGC-Pearson）上同步提升。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Annealed Masking Schedule	Replaces subset of gene dimensions in x_t with learnable mask tokens m_g , where masking ratio $p(t) = p_{max} \cdot t$ increases linearly with timestep	To break per-gene decomposition (Proposition 1) and suppress shortcut reconstruction near $t=1$; forces joint conditional modeling for masked genes	Input: $x_t \in \mathbb{R}^G, t \in [0,1]$; Output: $\tilde{x}_t \in \mathbb{R}^G$ with masked entries replaced by m_g [Paper] [Paper: PDF p. 5, Eq. 5]	Proposition 2 proof [Paper] [Paper: PDF p. 5]; Ablation shows $PCC \downarrow 0.004$ (Table 2); Hyperparameter study confirms $f(t)=t$ optimal (Table 3)	Removal $\rightarrow$ reverts to per-gene marginal estimation; ablation shows PCC drops to 0.609 [Paper] [Paper: PDF p. 8, Table 2]
Learnable Mask Token m_g	Adapts token value during backprop to preserve input statistics across masking ratios	To avoid train-inference magnitude mismatch caused by fixed-zero masking (dropout scaling problem)	Input: mask set M ; Output: $m_g \in \mathbb{R}^G$, shared across spatial locations [Paper] [Paper: PDF p. 5]	Explicitly motivated as mitigation for norm shift [Paper] [Paper: PDF p. 5]; no ablation on token vs. fixed zero, but design choice enables stable optimization	Expected: Fixed-zero masking would cause training instability and degraded convergence; not directly ablated but implied critical for stability

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Gene Affinity Graph Fusion	Fuses STRING functional prior $S^{(s)}$ and WGCNA data-driven co-expression $S^{(w)}$ via weighted average $S = \alpha S^{(s)} + (1-\alpha)S^{(w)}$	To combine stable cross-dataset prior knowledge with dataset-specific co-expression structure, avoiding over-reliance on either alone	Input: $S^{(s)}$ (STRING), $S^{(w)}$ (WGCNA); Output: fused affinity matrix $S \in \mathbb{R}^{G \times G}$ [Paper] [Paper: PDF p. 6, Eq. 9]	Ablation shows both w/o WGCNA (PCC=0.607) and w/o STRING (PCC=0.604) underperform full model (0.613) [Paper] [Paper: PDF p. 8, Table 2]	Removal of either source $\rightarrow$ loss of complementary information; PCC drops more for STRING removal (-0.009) than WGCNA (-0.006), suggesting STRING provides stronger anchor
Huber-based Local Constraint (Llocal)	Penalizes discrepancy $\Delta n_{ij} = z_i - z_j$ between z-scored predictions of connected genes $(i,j) \in E$, weighted by S_{ij}	To enforce pairwise consistency among functionally related genes, robust to outliers on weak edges	Input: predicted expression $\hat{x}_{1,n}$, graph S ; Output: scalar loss Llocal [Paper] [Paper: PDF p. 6, Eq. 11]	Ablation shows w/o Llocal $\rightarrow$ PCC=0.605 [Paper] [Paper: PDF p. 8, Table 2]; hyperparameter study shows $\rho=0.3$ optimal [Paper] [Paper: PDF p. 15, Table 6]	Removal $\rightarrow$ loss of fine-grained local coherence; ablation confirms larger drop than w/o Lglobal (0.605 vs 0.609)
Graph Laplacian Global Constraint (Lglobal)	Penalizes $\hat{x}^T L_1 n L \hat{x}_{1,n}$, where L is normalized Laplacian of fused graph	To suppress global oscillations and align predictions with low-frequency eigenmodes (large-scale co-expression modules)	Input: $\hat{x}_{1,n}$, graph Laplacian L ; Output: scalar loss Lglobal [Paper] [Paper: PDF p. 6–7, Eq. 12]	Ablation shows w/o Lglobal $\rightarrow$ PCC=0.609 [Paper] [Paper: PDF p. 8, Table 2]; hyperparameter study shows $\lambda=10^{-3}$ optimal [Paper] [Paper: PDF p. 15, Table 6]	Removal $\rightarrow$ loss of global module-level smoothness; smaller PCC drop than Llocal, indicating complementary role

09 关键公式与符号

- **No verifiable closed-form equation for the core method:** The paper defines components (Eq. 5, 8, 9, 10, 11, 12, 16) but does not present a single unified equation for CorrFlow' s forward pass or loss; the overall objective is modularly composed.
- **Key symbols & metrics:**
 - $x_t = (1-t)x_0 + tx_1$ (Eq. 1): Linear interpolant in flow matching; $x_0 \sim \text{ZINB prior}$, $x_1 = \text{ground-truth ST}$.
 - $p(t) = p_{\max} \cdot t$ (Eq. 8): Annealed masking ratio; $p_{\max} \in (0, 1)$ controls max masking intensity.
 - $S = \alpha S^{(s)} + (1-\alpha) S^{(w)}$ (Eq. 9): Fused gene affinity matrix; $S^{(s)} = \text{STRING}$, $S^{(w)} = \text{WGCNA}$, $\alpha \in [0, 1]$.
 - $L = I - A$, $A = D^{-1/2} S D^{-1/2}$ (Eq. 10): Normalized graph Laplacian and adjacency.

- $rg = \text{cov}(\hat{y}_{:,g}, y_{:,g}) / (\sigma(\hat{y}_{:,g}) \sigma(y_{:,g}))$ (Eq. 17): Gene-wise Pearson correlation coefficient (PCC).
- $\text{Pearson} = (1/|G|) \sum_g rg$ (Eq. 18): Mean PCC over gene set G.
- $\text{HPCC} = (1/|K|) \sum_k (1/|P_{k \cap G}|) \sum_{g \in P_{k \cap G}} rg$ (Eq. 13): Hallmark-Gene PCC, averaged over MSigDB Hallmark pathways with ≥ 5 genes in G.
- $\text{GGC-Pearson} = \text{corr}(\text{vec}_{\Delta}(\hat{C}), \text{vec}_{\Delta}(C))$ (Eq. 20): Correlation between upper-triangular vectors of predicted vs. ground-truth gene-gene correlation matrices.

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Main benchmark (HEST-1K, 10 datasets)	CorrFlow > STFlow in average PCC/HPCC	Same HMMVG-50 genes, patient-stratified CV, identical backbone architecture	PCC: 0.613 vs 0.600 (+0.013); HPCC: 0.628 vs 0.613 (+0.015); all $p < 0.05$ [Table 12]	CorrFlow's dependency-aware design yields statistically significant gains over strongest flow-matching baseline	That gains generalize to <i>all</i> cancer types equally (e.g., PAAD missing in Table 4 expansion)	[Paper] [Paper: PDF p. 8, Table 1; p. 19, Table 12]
Ablation study (HMMVG-50)	Each component contributes positively	Full model vs. variants removing masking, Lgraph, Llocal, Lglobal, WGCNA, or STRING	Full model best (0.613); removals cause PCC drops: masking (−0.004), Lgraph (−0.008), STRING (−0.009)	All proposed components are complementary and necessary for peak performance	That masking is <i>more important</i> than graph (drop magnitudes similar; no statistical test on delta)	[Paper] [Paper: PDF p. 8, Table 2; p. 15, Table 5]
Hyperparameter study (masking/graph)	Optimal settings exist and are identifiable	Varying $f(t)$, $p_{\max}$, α , ρ , λ on HMMVG-50	Best: $f(t)=t$, $p_{\max}=0.75$, $\alpha=0.6$, $\rho=0.3$, $\lambda=10^{-3}$ [Tables 3, 6]	Design choices are empirically grounded, not arbitrary	That these settings are globally optimal across <i>all</i> gene panels or datasets (e.g., PAAD excluded from Table 4)	[Paper] [Paper: PDF p. 8–9, Tables 3, 6]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Expanded gene sets (HMHVG-100/150/200)	Dependency-aware design scales with gene panel size	Same HEST-1K, broader gene sets	Consistent PCC/HPCC gains over STFlow across all sizes (e.g., PCC +0.007 at 100 genes) [Table 4]	Benefit of modeling dependencies persists beyond top-50 marker genes	That gains increase with panel size (margins are stable, not growing)	[Paper] [Paper: PDF p. 14, Table 4; p. 17, C.1]
GGC-Pearson evaluation	CorrFlow better preserves gene-gene correlation structure	Compared to STFlow, BLEEP-UNI on HMHVG-50	Avg. GGC-Pearson: 0.648 vs 0.633 (STFlow) [Table 7]	Improved dependency modeling translates to better preservation of global co-expression topology	That this directly causes improved downstream biological utility (no downstream task validation)	[Paper] [Paper: PDF p. 17, Table 7; p. 15, B]
Supplementary STImage-1K4M	Generalizability to larger, non-benchmark ST collections	Brain & Breast cancer categories, random 8:1:1 split	PCC: 0.542 vs 0.530 (STFlow) [Table 9]	Gains hold on larger, less standardized datasets	That generalizability extends to <i>fully independent external cohorts</i> (no such validation performed)	[Paper] [Paper: PDF p. 18, Table 9; p. 19, C.3]

11 对结论的正确理解

论文结论应被理解为：在HEST-1K标准化患者分层交叉验证框架下，CorrFlow通过annealed masking与gene graph regularization的协同，实现了对STFlow基线的统计显著且稳健的PCC/HPCC提升，且该提升与基因互作建模的理论动机一致。关键限定包括：（1）提升幅度虽小（+0.013 PCC）但稳定，在10个数据集、多基因面板、多指标（PCC/HPCC/GGC-Pearson/MSE）上均成立；（2）HPCC增益（+0.015）大于PCC，证实其对通路级生物学一致性的特异性增强；（3）所有结论均基于同一骨干网络（STFlow），差异仅在于损失与正则，排除了架构优势干扰；（4）“biologically coherent”指定量指标（HPCC, GGC-Pearson）提升及可视化中空间模式更贴近ground truth（Fig. 3a），而非定性生物学发现。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Lack of external cohort validation	Evaluation uses HEST-1K (cross-platform but internal) and STImage-1K4M (non-standard splits); no fully independent external cohort with different tissue prep/sequencing/scanner	Incorporate independently collected ST cohorts to assess clinical robustness under out-of-distribution variations	[Paper] [Paper: PDF p. 19, D]
Insufficient clinical translation readiness	Prediction quality still insufficient for direct clinical use due to intrinsic challenge of inferring molecular states from morphology alone	Improve robustness via stronger dependency-aware modeling and higher-quality ST training data	[Paper] [Paper: PDF p. 19, D]
Limited downstream utility assessment	Evaluation focuses on reconstruction fidelity (PCC) and structure preservation (GGC), not downstream biological/clinical tasks	Assess benefits for tissue-domain identification, pathway activity estimation, biomarker discovery, patient stratification, and prognosis modeling	[Paper] [Paper: PDF p. 20, D]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
STRING+WGCNA fusion assumes static functional associations, but gene interactions are context-dependent (e.g., tumor vs. normal, cell-type specific)	The fused graph S may misrepresent true co-expression in specific disease contexts, leading to over-regularization on irrelevant edges	Could degrade performance on datasets where STRING prior is weak (e.g., novel cancer subtypes) or WGCNA fails (low N spots)	Compare CorrFlow using cell-type-specific co-expression networks (e.g., from scRNA-seq) vs. bulk WGCNA on same ST dataset; measure PCC delta per cell type	[Paper] [Paper: PDF p. 6, Eq. 9]; STRING/WGCNA are bulk-level resources, not context-aware
Annealed masking with $p(t)=p_{max} \cdot t$ treats all genes identically, ignoring their biological roles (e.g., housekeeping vs. regulatory)	Masking key regulators uniformly may hinder learning of master regulatory logic, while masking noisy genes adds little signal	May limit ability to capture hierarchical gene regulation, not just pairwise correlation	Stratify masking probability by gene centrality (e.g., degree in STRING) or variance; test if adaptive masking improves HPCC on regulatory pathways	[Paper] [Paper: PDF p. 5, Eq. 8]; no gene-specific masking strategy explored

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Graph Laplacian Lglobal (Eq. 12) penalizes high-frequency oscillations but assumes smoothness = biological coherence	Some biologically valid expression patterns (e.g., sharp boundaries in tumor-stroma interface) require high-frequency variation, which Lglobal may suppress	Could blur spatially resolved biological signals, harming domain identification	Visualize spatial residuals ($\hat{y}-y$) in high-Lglobal regions (e.g., tumor margins) vs. low-Lglobal; correlate with histology-defined domains	[Paper] [Paper: PDF p. 7, Eq. 12]; Laplacian smoothness is a generic assumption, not biology-validated for ST
HPCC metric (Eq. 13) aggregates only over Hallmark pathways with ≥ 5 genes in G, excluding many disease-specific signatures	For cancer datasets like PAAD or SKCM, Hallmark coverage may be low, making HPCC an incomplete proxy for disease-relevant coherence	May underestimate true biological utility in oncology contexts where custom pathways matter more	Compute PCC on cancer-specific pathway databases (e.g., Oncogenic Signatures) and compare delta CorrFlow-STFlow	[Paper] [Paper: PDF p. 7, Eq. 13]; MSigDB Hallmark is general, not cancer-focused

14 学到的知识

- **Flow matching的可塑性远超标准应用：**其插值轨迹（ x_t ）不仅是数学工具，更是可编辑的“学习界面”——通过掩码（Eq. 5）、重加权或注入结构，能将任意先验（如基因图）无缝嵌入动力学训练，比扩散模型的score matching更易耦合结构约束。
- **渐进式掩码（annealed masking）是诱导联合建模的轻量级杠杆：**不需修改网络架构，仅通过输入扰动（ $p(t)$ ）即可将优化目标从边际估计（Proposition 1）转向条件联合（Proposition 2），且理论保证收敛（Theorem 1）。
- **多源图融合需谨慎平衡：**STRING提供跨数据集稳定性，WGCNA offers dataset specificity； $\alpha=0.6$ （Table 3）表明功能先验略占优，但二者缺一不可（Table 2 ablation），提示在single-cell foundation models中融合scRNA-seq co-expression与 PPI networks时，需动态调整权重。
- **评估必须分层：**PCC衡量单基因空间保真，HPCC衡量通路级协调，GGC-Pearson衡量全局拓扑保真——三者提升方向一致（Table 1/7），证实CorrFlow的改进是系统性的，非指标偏倚。
- **计算效率与科学严谨可兼得：**CorrFlow与STFlow参数量完全相同（Table 14），证明结构化正则（Lgraph）和掩码（LMFM）不增加模型复杂度，仅改变训练动态，这对资源受限的biomedical AI部署至关重要。

15 与既有知识的连接

- **候选连接/方法论连接：**
- *single-cell foundation models:* CorrFlow’s gene graph regularization (Eq. 9–12) directly inspires integrating scRNA-seq-derived co-expression graphs (e.g., from CellxGene) as dynamic priors, replacing static STRING/WGCNA.
- *spatial transcriptomics:* The annealed masking strategy (Eq. 8) is transferable to spot-to-spot imputation tasks where spatial neighbors serve as conditioning context, analogous to masking spatial coordinates.

- *graph neural networks*: CorrFlow' s dual graph constraints (Llocal + Lglobal) provide a blueprint for GNNs in ST: local message passing (Huber on edges) + global spectral filtering (Laplacian), moving beyond standard GCN layers.
- *multi-omics*: The fusion weight α (Eq. 9) formalizes how to balance prior knowledge (e.g., chromatin accessibility) and data-driven omics correlations (e.g., ATAC-RNA co-variation).
- *perturbation prediction*: Proposition 2' s joint conditional modeling (Eq. 7) is foundational for predicting multi-gene perturbation effects—masking a gene set M and inferring it from O mirrors knockdown/knockout experiments.
- *cross-modal alignment*: CorrFlow' s conditioning on histology features z and spatial q (Fig. 2) exemplifies tight modality binding; its success suggests that alignment should occur in the *generation space*, not just feature space.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Cell-Type-Aware Gene Graph (CTAG)

originating limitation/observation: [Analysis] STRING+WGCNA fusion ignores context-dependency; current graph is bulk-level, not cell-type-specific [Paper] [Paper: PDF p. 6, Eq. 9]. **core hypothesis**: Using scRNA-seq-derived cell-type-specific co-expression graphs as dynamic priors will improve CorrFlow' s accuracy in heterogeneous tissues (e.g., tumor microenvironment). **delta from paper**: Replace static $S^{(w)}$ with cell-type-weighted ensemble: $S^{(w)}_{ct} = \sum_c w_c \cdot S^{(w)}_c$, where w_c is cell-type proportion from histology segmentation, and $S^{(w)}_c$ is co-expression graph for cell type c . **initial method**: Integrate UNI [5] histology encoder with cell-type classifier (e.g., based on nuclei morphology); compute w_c per spot; fetch precomputed $S^{(w)}_c$ from scRNA-seq atlas (e.g., Human Cell Atlas). **validation**: Test on LYMPH_IDC (Fig. 3a) where tumor/stroma boundaries are clear; measure PCC delta in stromal vs. tumor regions. **failure modes**: Poor cell-type segmentation $\rightarrow$ erroneous w_c ; sparse scRNA-seq for rare cell types $\rightarrow$ noisy $S^{(w)}_c$. **innovation status**: unverified

- **name**: Hierarchical Annealed Masking (HAM)

originating limitation/observation: [Analysis] Uniform masking ignores gene functional hierarchy; masking master regulators may disrupt learning [Paper] [Paper: PDF p. 5, Eq. 8]. **core hypothesis**: Prioritizing masking of downstream effector genes (high variance, low centrality) while sparing upstream regulators (low variance, high STRING degree) will yield more biologically interpretable joint modeling. **delta from paper**: Replace Bernoulli masking with stratified sampling: mask probability $p_g(t) = p(t) \cdot (1 - \text{centrality}_g)$, where centrality_g is degree in STRING or variance-normalized expression variance. **initial method**: Precompute gene centrality from STRING; during training, sample M with $p_g(t)$ instead of uniform $p(t)$. **validation**: Compare HPCC on regulatory pathways (e.g., KEGG MAPK) vs. metabolic pathways; expect larger HPCC gain in regulatory sets. **failure modes**: Over-suppression of regulator masking may revert to marginal estimation; centrality metrics may not reflect true regulatory hierarchy in cancer. **innovation status**: unverified

- **name**: Spatial Boundary-Aware Laplacian (SBAL)

originating limitation/observation: [Analysis] Standard Lglobal (Eq. 12) may suppress biologically valid sharp expression boundaries [Paper] [Paper: PDF p. 7, Eq. 12]. **core hypothesis:** Modifying the graph Laplacian to preserve high-gradient spatial interfaces (e.g., tumor-stroma) will improve domain identification utility without sacrificing global coherence. **delta from paper:** Replace constant weight w_{ij} in Lglobal with spatially adaptive weight: $w_{ij} \leftarrow w_{ij} \cdot \exp(-\beta \cdot \|\nabla I_i - \nabla I_j\|^2)$, where ∇I is histology gradient magnitude at spots i, j . **initial method:** Compute Sobel gradients on histology patches; embed gradient difference into edge weights before computing L. **validation:** Quantify boundary sharpness (e.g., gradient magnitude of $\hat{y}$) at histology-defined tumor margins; correlate with domain segmentation accuracy (e.g., Dice score). **failure modes:** Gradient noise in low-contrast regions $\rightarrow$ unstable weights; requires precise histology-ST spatial alignment. **innovation status:** unverified