

|                                                         |
|---------------------------------------------------------|
| Source coverage: Full paper                             |
| Extraction confidence: High                             |
| Locator mode: page-grounded                             |
| Primary analytical lens: methods                        |
| Secondary analytical lens: None                         |
| Context verification: Paper-only                        |
| Card completeness: Complete relative to supplied source |

01 基本信息

| Field                  | Value                                                                                               | Source                                                                                                      |
|------------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Title                  | CellMSA: Context Modeling for Single-Cell Representation Learning                                   | [Paper] [Paper: PDF p. 1]                                                                                   |
| Authors                | Suyuan Zhao, Minghao Liu, Yizhen Luo, Zaiqing Nie                                                   | [Paper] [Paper: PDF p. 1]                                                                                   |
| Venue                  | arXiv preprint (NeurIPS 2026 submission)                                                            | [Paper] [Paper: PDF p. 1], [Paper] [Paper: PDF p. 10]                                                       |
| Year                   | 2026                                                                                                | [Paper] [Paper: PDF p. 1]                                                                                   |
| Pretraining scale      | ~109 million human cell observations (65.6M primary)                                                | [Paper] [Paper: PDF p. 1], [Paper] [Paper: PDF p. 3], [Paper] [Paper: PDF p. 6], [Paper] [Paper: PDF p. 26] |
| Core innovation        | MSA-inspired inductive bias for single-cell modeling via context-dependent gene-pair representation | [Paper] [Paper: PDF p. 1], [Paper] [Paper: PDF p. 2], [Paper] [Paper: PDF p. 4]                             |
| Key modules            | CellMSA-Module (Outer-product Mean + Pair-weighted Averaging), GenePairformer                       | [Paper] [Paper: PDF p. 4], [Paper] [Paper: PDF p. 5], [Paper] [Paper: PDF p. 15]                            |
| Pretraining objectives | LMGM (masked gene modeling), LRec (reconstruction), LCCE (cell-level contrastive learning)          | [Paper] [Paper: PDF p. 6]                                                                                   |
| Downstream tasks       | Batch integration, cell type/state classification, perturbation prediction                          | [Paper] [Paper: PDF p. 7], [Paper] [Paper: PDF p. 8], [Paper] [Paper: PDF p. 9]                             |
| Code                   | <a href="https://github.com/PharMolix/CellMSA">https://github.com/PharMolix/CellMSA</a>             | [Paper] [Paper: PDF p. 1]                                                                                   |

02 一句话总结

CellMSA 提出一种受蛋白质多序列比对（MSA）启发的单细胞表征学习框架，通过跨批次、跨细胞类型的上下文检索与建模，生成上下文依赖的基因对（gene-pair）表示，并将其注入目标细胞编码器，从而提升细粒度细胞状态建模能力。该方法在 batch 集成、细胞类型/状态分类和扰动预测等任务上系统性超越现有基线模型，尤其在疾病相关基因网络解析中展现出可解释的生物学意义。其核心价值在于将“跨样本一致性与变异比较”这一被蛋白结构预测验证有效的归纳偏置，首次完整迁移到单细胞转录组建模中，且不牺牲基因级分辨率。

03 研究问题

单细胞基础模型为何难以稳健捕获与细胞状态强相关的细粒度基因-基因依赖关系？→ 作者观察到：现有方法或独立编码单细胞（忽略跨样本信号），或仅建模同一批次内细胞（上下文信息贫乏、易退化为去噪），导致模型无法区分技术噪声与真实生物学变异，更难识别状态特异的共表达模式 [Paper] [Paper: PDF p. 1–2]。→ 进一步假设：若能像 AlphaFold 利用 MSA 聚合同源序列的保守性与共进化信号一样，聚合相似细胞（跨批次、跨类型）的表达一致性与差异性，则可稳定提取 marker 基因与功能相关的基因共表达模式 [Paper] [Paper: PDF p. 2, Fig. 1]。→ 因此，研究问题聚焦于：如何设计一种可扩展、基因级对齐的上下文建模机制，使单细胞模型能从丰富但异构的细胞集合中提炼出状态特异的基因对关系？

04 研究背景与发展路径

单细胞基础模型演进呈现两条主线：一是大规模预训练范式（Geneformer/scGPT/UCE），但受限于单细胞独立编码范式；二是多细胞上下文建模尝试（CellPLM/STATE/Stack），但存在两大瓶颈：（1）压缩式上下文聚合（如基因加权平均、模块化）丢失基因级细节 [Paper] [Paper: PDF p. 2]；（2）上下文组织局限于同批同型细胞，缺乏跨批次鲁棒性与跨类型对比性 [Paper] [Paper: PDF p. 2]。CellMSA 并非简单叠加多细胞输入，而是将“MSA 类比”作为第一性原理：将目标细胞与来自 same-batch / cross-batch / cross-type 的邻居共同构成“单细胞 MSA”，在保持基因位置对齐的前提下，通过 Outer-product Mean 模块聚合跨细胞共变信号，再经 Pair-weighted Averaging 实现基因对表示与上下文基因表示的迭代精炼 [Paper] [Paper: PDF p. 4–5, Fig. 2, Appendix A.1]。这一路径直接回应了前述瓶颈——既避免压缩损失（保留  $G \times G$  维 pair 表示），又拓展上下文语义（三类邻居提供 denoising / biological stability / functional contrast 三重信号） [Paper] [Paper: PDF p. 4]。

05 论文识别的核心痛点

| Pain point | Manifestation                                                          | Cause or author explanation                                                                                                                             | Evidence from the paper                                                                                                                                                   |
|------------|------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 孤立建模导致噪声敏感 | 单细胞转录组高度稀疏，易受测序深度、dropout 和批次效应干扰，模型难以区分生物变异与随机噪声                      | 现有单细胞基础模型将每个细胞视为孤立输入，缺乏跨样本统计支撑 [Paper] [Paper: PDF p. 1]                                                                                                | “when the model relies on only a single observation of a cell, it is often difficult to distinguish biological variation from stochastic noise” [Paper] [Paper: PDF p. 2] |
| 上下文信息贫乏且低效 | 同批多细胞建模虽有改进，但上下文组织方式限制其信息增益：仅同批同型细胞 → 主要提供局部实验条件下的共性，缺乏跨批次稳定性与跨类型功能性对比 | 现有方法压缩上下文（如 gene-weighted averaging）并限制上下文来源，导致 “context mainly reflects shared patterns under local experimental conditions” [Paper] [Paper: PDF p. 2] | “Such compression can discard gene-level information... these methods may be less effective at improving robustness across batches” [Paper] [Paper: PDF p. 2]             |

| Pain point | Manifestation                         | Cause or author explanation                                                       | Evidence from the paper                                                                                                                                                                                                            |
|------------|---------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 基因依赖建模粗粒度  | 模型难以捕获与特定细胞状态（如疾病亚型）精细关联的基因-基因协同/拮抗关系 | 独立编码或低维压缩范式无法支持高保真 gene-pair 关系学习，而此类关系是理解细胞状态转变的分子基础 [Paper] [Paper: PDF p. 1–2] | “By comparing consistency and variation across cells, models can capture fine-grained gene-gene dependencies associated with cell states, which are essential for learning high-quality representations” [Paper] [Paper: PDF p. 1] |

06 核心思想

CellMSA 的核心思想是将“多序列比对（MSA）”这一在蛋白质结构预测中被证明能有效提取残基保守性与共进化信号的归纳偏置（inductive bias），迁移至单细胞转录组建模领域，构建“单细胞 MSA”以驱动基因对关系学习。其本质不是模仿 MSA 的形式，而是复用其**信息萃取逻辑**：AlphaFold 通过聚合同源序列在多个位点上的共变模式推断三维结构约束；CellMSA 则通过聚合相似细胞（跨批次、跨类型）在多个基因位点上的共表达/差异表达模式，推断细胞状态特异的基因功能依赖网络。该思想成功的关键在于三点：（1）**上下文构造的生物学合理性**：same-batch（去噪）、cross-batch（跨批次稳定性）、cross-type（功能对比）三类邻居分别提供互补信号 [Paper] [Paper: PDF p. 4]；（2）**表示粒度的基因级对齐**：所有细胞共享同一基因词汇表与位置索引，确保 Outer-product Mean 可计算任意基因对 (u,v) 在上下文中的联合变异 [Paper] [Paper: PDF p. 4–5]；（3）**双通路交互架构**：CellMSA-Module 在低维空间提炼 gene-pair 表示，GenePairformer 在高维空间将其作为 attention bias 注入目标细胞编码，实现“上下文提炼”与“目标精编”的解耦与协同 [Paper] [Paper: PDF p. 5]。

07 方法总览

CellMSA 是一个两阶段上下文感知的单细胞表征学习框架：（1）**上下文构造阶段**：对每个目标细胞，从 three sources（same-batch, cross-batch, cross-type）检索共 40 个邻居细胞，构成 MSA-like 输入矩阵（S=41 行 × G 列），并为每行邻居添加 relation-type embedding 以区分来源 [Paper] [Paper: PDF p. 4]；（2）**上下文感知编码阶段**：首先由 CellMSA-Module 处理整个 MSA 输入，通过交替执行 Outer-product Mean（聚合跨细胞共变）与 Pair-weighted Averaging（用更新的 pair 表示调制上下文基因表示），最终输出 context-dependent gene-pair 表示  $P^{L, MSA} \in \mathbb{R}^{G \times G \times d_p}$ ；随后，GenePairformer 以目标细胞基因序列为输入，将  $P^{L, MSA}$  投影为 head-specific pair biases  $R^{0, \cdot}$ ，并在每一层 Transformer self-attention 中将其加入 logits 计算  $R^{L+1, H}_{uv} = R^{L, H}_{uv} + Q^{L, H}_{u(K^{L, H}_{vT} / \sqrt{d_H})}$ ，引导模型在编码目标细胞时显式关注 context 提炼出的基因对关系 [Paper] [Paper: PDF p. 4–5, Fig. 2]。预训练采用三目标联合优化：LMGM（掩码基因预测）、LRec（细胞表达重构）、LCCE（细胞对比学习）[Paper] [Paper: PDF p. 6]。

08 核心模块拆解

| Module         | Function                                                                                                                                      | Why needed                                                                                               | Input and output                                                                                                                                                                             | Supporting evidence                                                                                                                                                                                                                                                                                 | Known or expected effect of removal                                                                                                                                                                                                                                |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CellMSA-Module | 从 MSA-like 上下文中提炼 context-dependent gene-pair representation; 通过 Outer-product Mean (跨细胞共变聚合) 与 Pair-weighted Averaging (pair 表示反向调制上下文) 交替更新 | 解决 “如何在压缩基因维度前提下, 高效聚合多细胞上下文信息” 的核心挑战; 低维投影 ( $d' < d$ ) 降低计算开销 [Paper] [Paper: PDF p. 4–5]              | Input: MSA input ( $S \times G \times d$ ), initial $P \in \mathbb{R}^{G \times G \times d \times d}$ ; Output: Final $P \in \mathbb{R}^{G \times G \times d \times d}$                      | “We first project the input gene representations ... into a lower-dimensional space ... allowing the model to extract pairwise gene dependencies across multiple cells at relatively low cost” [Paper] [Paper: PDF p. 5]; Fig. 2 & Appendix A.1 detail structure                                    | Removal causes catastrophic drop in PT state classification (Acc $\downarrow$ 0.958 $\rightarrow$ 0.854) and perturbation prediction (Pearson $\Delta \downarrow$ 0.433 $\rightarrow$ 0.355), proving its necessity for fine-grained modeling [Table 4: PDF p. 10] |
| GenePairformer | 以目标细胞序列为输入, 将 CellMSA-Module 输出的 gene-pair representation 作为 attention bias 注入 Transformer 编码过程, 实现 context-guided 的 target-cell encoding     | 解决 “如何将提炼出的 gene-pair 关系有效注入目标细胞表征学习” 的问题; pair bias 设计使模型能显式利用跨细胞证据指导基因间注意力计算 [Paper] [Paper: PDF p. 5] | Input: Target cell sequence $h \in \mathbb{R}^d$ , pair bias $R \in \mathbb{R}^{d \times d}$ ; Output: Final cell embedding $z_i \in \mathbb{R}^d$ (from $\langle \text{cls} \rangle$ token) | “The resulting attention logits are then used to further refine the pair representation, enabling iterative interaction between sequence features and pairwise structure” [Paper] [Paper: PDF p. 5]; Eq. for $\text{Attention}_{L,H}^{uv}$ shows explicit pair bias usage [Paper] [Paper: PDF p. 5] | Degenerates to standard Transformer without CellMSA-Module; ablation shows full model outperforms w/o CellMSA-Module across all tasks [Table 4: PDF p. 10]                                                                                                         |

| Module                        | Function                                                                                                              | Why needed                                                                 | Input and output                                                                                                                                              | Supporting evidence                                                                                                                                                                                                                                                                                                                                                                                                             | Known or expected effect of removal                                                                                                                                                                       |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MSA-like Context Construction | 为每个目标细胞系统性构建三类生物学意义明确的上下文：same-batch (denoising)、cross-batch (batch-robust patterns)、cross-type (functional contrast) | 解决“上下文应包含哪些细胞才能提供最大信息增益”的问题；三类邻居提供互补信号，避免单一来源的偏差 [Paper] [Paper: PDF p. 4] | Input: Target cell $c_i$ ;<br>Output: Neighbor set $N_i = N^{\text{same batch}} \cup N^{\text{cross batch}} \cup N^{\text{cross type}}$ ( $16+16+8=40$ cells) | “ $N^{\text{same batch}}$ ... used to capture local similarity and support denoising; $N^{\text{cross batch}}$ ... used to encourage the model to extract biologically meaningful patterns that are stable across batches; $N^{\text{cross type}}$ ... used to provide a contrastive background” [Paper] [Paper: PDF p. 4]; Appendix C.1 details hierarchical clustering for cross-type selection [Paper] [Paper: PDF p. 26–27] | Ablation shows “Only Same-batch Context” yields lower performance than full model (PT Acc $\downarrow 0.958 \rightarrow 0.929$ ), confirming value of cross-batch/cross-type signals [Table 4: PDF p. 10] |

09 关键公式与符号

论文未给出可核验的完整数学公式（如损失函数的显式求和形式），但明确定义了关键符号、模块操作与指标：

- **关键符号：**
- $X \in R^{N \times G}$ ：单细胞表达矩阵（N 细胞数，G 基因数） [Paper] [Paper: PDF p. 3]
- $N_i = N^{\text{same batch}}_i \cup N^{\text{cross batch}}_i \cup N^{\text{cross type}}_i$ ：目标细胞 i 的三类邻居集合 [Paper] [Paper: PDF p. 4]
- $P^l \in R^{G \times G \times d_p}$ ：第 l 层的基因对表示（pair representation） [Paper] [Paper: PDF p. 5]
- $m^l_{\{sg\}} \in R^{d'}$ ：第 s 行（细胞）第 g 基因在 CellMSA-Module 第 l 层的低维上下文表示 [Paper] [Paper: PDF p. 5]
- $R^{\{L+1, H\}}_{\{uv\}}$ ：GenePairformer 第 L 层第 H 头的 attention logits，含 pair bias 项 [Paper] [Paper: PDF p. 5]
- LMGM, LRec, LCCE：三个预训练目标函数 [Paper] [Paper: PDF p. 6]

- **关键操作**（非公式，但具数学定义）：
- **Outer-product Mean**:  $p^{\{l+1\}}_{uv} = p^l_{uv} + W^l_p (1/S \sum_s a^l_{su} \otimes b^l_{sv})$ ，其中  $a^l_{su}$ ,  $b^l_{sv}$  是  $m^l_{su}$ ,  $m^l_{sv}$  的线性投影， $\otimes$  为外积 [Paper] [Paper: PDF p. 5, Appendix A.1]
- **Pair-weighted Averaging**:  $m^{\{l+1\}}_{su} = m^l_{su} + W^l_o \text{Concath } \gamma^{\{l,h\}}_{su} \otimes \sum_v \text{softmax}_v(W^{\{l,h\}}_b p^{\{l+1\}}_{uv}) v^{\{l,h\}}_{sv}$ ，其中  $\gamma$  为门控， $v$  为值表示 [Paper] [Paper: PDF p. 5, Appendix A.1]
- **关键指标**：
- **Pearson  $\Delta$** ：扰动预测主指标，计算真实与预测扰动效应向量 ( $\Delta_{real\_p}$ ,  $\Delta_{pred\_p}$ ) 的 Pearson 相关系数 [Paper] [Paper: PDF p. 9, C.5]
- **NMI, ARI, ASW, cLISI, BRAS, iLISI, kBET, Conn, PCR**：batch 集成评估指标，分属 Biological conservation 与 Batch correction 两大维度 [Paper] [Paper: PDF p. 7, C.4]

10 实验设计与证据链

| Experiment                         | Claim tested                                                                 | Comparison and conditions                                                                                                                                                                                                 | Result                                                                                                                                                       | Supported conclusion                                                                                                                                  | Unsupported stronger conclusion                                                                                                       | Source                               |
|------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| Batch Integration (Tabula Sapiens) | CellMSA achieves superior batch mixing while preserving biological structure | Compared against PC-HVG, scVI, scGPT, Geneformer, STATE-SE, Stack; label-informed context retrieval for CellMSA/Stack; metrics: NMI/ARI/ASW/cLISI (bio), BRAS/iLISI/kBET/Conn/PCR (batch); macro-averaged over 24 tissues | CellMSA achieves highest total score (0.736), best NMI (0.895), ARI (0.805), ASW (0.699), and top-tier batch scores (e.g., kBET 0.627, Conn 0.945) [Table 1] | CellMSA's MSA-inspired context modeling enables more robust and biologically faithful integration than existing methods under label-informed settings | That CellMSA is universally superior under <i>all</i> context retrieval protocols (label-free results show advantage but smaller gap) | [Paper] [Paper: PDF p. 7], [Table 1] |

| Experiment                            | Claim tested                                                                              | Comparison and conditions                                                                                                                                    | Result                                                                                                                                                                   | Supported conclusion                                                                                                                                                           | Unsupported stronger conclusion                                                                                                                                                                                      | Source                                                          |
|---------------------------------------|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| <b>Cell Type/State Classification</b> | CellMSA captures fine-grained cellular variation for broad and disease-focused tasks      | Cell type: Tabula Sapiens-Blood (immune subtypes); PT state: Kidney Atlas (aPT/dPT/dPT-DTL); 5-run avg $\pm$ std; MLP head on frozen embeddings              | CellMSA achieves best macro-F1 for cell type (0.912) and PT state (0.931), outperforming CellPLM (0.906) and Stack (0.909) [Table 2]                                     | CellMSA's context-aware representations encode both broad cell identity and subtle, disease-associated state differences within a lineage                                      | That this advantage generalizes to <i>all</i> cell types/states beyond the two evaluated (no evidence for other tissues)                                                                                             | [Paper] [Paper: PDF p. 8], [Table 2]                            |
| <b>Perturbation Prediction</b>        | CellMSA provides a more robust latent space for modeling perturbation-induced transitions | Using Replogle dataset (4 cell lines, 100 perturbations); combined with STATE-ST module; metrics: Pearson $\Delta$ (primary), PRAUC, Spearman-FC, DE Overlap | CellMSA+STATE-ST achieves highest Pearson $\Delta$ (0.433), +8.8% over strongest baseline (Stack: 0.358) [Table 3]                                                       | The gene-pair representations learned by CellMSA enhance the model's ability to predict complex transcriptional shifts, likely due to capturing stable regulatory dependencies | That CellMSA alone (without STATE-ST) can directly predict perturbations (the framework is encoder-only, prediction requires downstream module)                                                                      | [Paper] [Paper: PDF p. 9], [Table 3]                            |
| <b>Interpretability (PT Disease)</b>  | CellMSA's gene-pair representations capture disease-associated network reconfiguration    | Analyzed differential hub scores & gene-pair heatmaps for PT marker genes in Kidney Atlas (healthy vs disease); GO enrichment on top genes from head 7       | Heads 6/7 preferentially capture disease state; head 7 heatmap shows altered interactions; GO reveals ECM reorganization, integrin signaling, dedifferentiation [Fig. 4] | CellMSA learns biologically interpretable, disease-relevant latent modes, anchored in known pathological markers and pathways                                                  | That these modes represent <i>causal</i> regulatory relationships (authors explicitly state they reflect "statistical associations rather than explicit causal regulatory relationships") [Paper] [Paper: PDF p. 10] | [Paper] [Paper: PDF p. 9], [Fig. 4], [Paper] [Paper: PDF p. 10] |

| Experiment               | Claim tested                                                 | Comparison and conditions                                                                                                                     | Result                                                                                                                                                            | Supported conclusion                                                                                             | Unsupported stronger conclusion                                                                                                                  | Source                                          |
|--------------------------|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| Ablation Study (Context) | Performance gains stem from effective MSA context leveraging | Ablated: (1) w/o CellMSA-Module, (2) w/o Context, (3) Only Same-batch Context; evaluated on PT state classification & perturbation prediction | Full model consistently best; removing CellMSA-Module causes largest drop (PT Acc ↓ 0.104); adding cross-batch/cross-type improves over same-batch-only [Table 4] | The architectural design (CellMSA-Module) and the multi-source context construction are both critical components | That the specific neighbor counts (16/16/8) are globally optimal (Fig. 5 shows saturation beyond 40 neighbors, but not optimality of this split) | [Paper] [Paper: PDF p. 10], [Table 4], [Fig. 5] |

11 对结论的正确理解

CellMSA 的核心结论是：引入 MSA-inspired 上下文建模范式（即跨批次、跨类型细胞的基因级对齐与共变聚合）能显著提升单细胞基础模型在多个下游任务上的性能，并赋予其可解释的生物学洞察力。需正确理解以下边界：（1）**性能优势具有条件性**：主要在 label-informed context retrieval 设置下被证实（Table 1, Table 2），label-free 设置下优势缩小但仍存在（Appendix B.1.1, Table A.27）；（2）**解释性基于统计关联**：Figure 4 的 GO 富集和 marker 基因重叠（如 CUBN, HAVCR1）证明其捕捉到已知病理信号，但作者明确强调这是“statistical associations”，非因果推断 [Paper] [Paper: PDF p. 10]；（3）**泛化性有数据支撑但非无限**：预训练于 ~109M 细胞（818 cell types），下游验证覆盖 24 组织（Tabula Sapiens）、肾脏疾病（Kidney Atlas）、多细胞系扰动（Replogle），但未验证 spatial transcriptomics、multi-omics 或 rare cell types；（4）**计算开销是权衡结果**：CellMSA-Module 的  $O(SG^2d_p^2)$  复杂度是其获取 gene-pair 表示的必要代价，作者通过低维投影（d'）控制开销 [Paper] [Paper: PDF p. 16]。

12 作者明确承认的限制

| Limitation                            | Specific manifestation                                                                                                           | Future direction proposed by authors                                                                                                            | Source                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| Statistical vs. Causal Interpretation | Learned gene-pair patterns reflect statistical associations, not explicit causal regulatory relationships                        | Incorporate prior knowledge of gene regulation and causal machine learning methods to strengthen biological grounding                           | [Paper] [Paper: PDF p. 10]                  |
| Context Retrieval Dependency          | Performance gain in label-informed setting relies on availability of high-quality cell-type annotations for context construction | The label-free ablation (Appendix B.1.1) shows CellMSA retains an advantage, but the gap narrows, indicating annotation quality impacts utility | [Paper] [Paper: PDF p. 7], [Appendix B.1.1] |

| Limitation                          | Specific manifestation                                                                                                                | Future direction proposed by authors                                                                                                                                         | Source                     |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>Pretraining Data Composition</b> | Corpus includes non-primary observations (e.g., re-aggregations), potentially overrepresenting certain atlas structures or cell types | Authors audit non-primary data origin but note "this contextual distinction does not remove the possibility of overrepresenting particular cells" [Paper] [Paper: PDF p. 26] | [Paper] [Paper: PDF p. 26] |
| <b>Computational Cost</b>           | CellMSA-Module introduces additional complexity ( $O(SG^2d_p^2)$ ) compared to standard Transformers                                  | The design choice (low-d' projection) is made to manage cost, but no alternative low-cost, high-fidelity gene-pair extraction method is proposed                             | [Paper] [Paper: PDF p. 16] |

### 13 批判性分析

| [Analysis] Observation                                                                                                                                                                                                                                                                                          | Potential issue or alternative explanation                                                                                                                                                                                          | Why it matters                                                                                                                                                                                                             | How to test it                                                                                                                                                                                                                                            | Basis                                                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Context size saturation at 40 cells (Fig. 5)</b> suggests diminishing returns, yet the fixed 16/16/8 split may not be optimal for all biological questions. For instance, disease-state classification might benefit more from enriched cross-type (e.g., related injury states) than cross-batch neighbors. | The current static neighbor count ignores task-specific information needs. An adaptive context sampling strategy (e.g., prioritizing neighbors with highest differential expression for the target state) could yield higher gains. | Fixed context size is a practical simplification, but biological questions vary in their dependency on different context types. Ignoring this may limit peak performance on specialized tasks like rare disease subtyping. | Implement a dynamic context sampler that weights neighbors by task-relevant signals (e.g., DE score for PT states) and compare ablation performance against fixed-size baselines on PT classification and perturbation tasks.                             | [Paper] [Paper: PDF p. 10, Fig. 5] shows saturation, but [Paper] [Paper: PDF p. 4] defines the split as fixed; no analysis of per-task context utility is provided. |
| <b>STRING validation shows 52% overlap (Table A.29)</b> , but this is descriptive, not statistically significant. The 48% non-overlapping pairs could represent novel biology <i>or</i> false positives from expression correlation.                                                                            | The STRING comparison lacks a null model (e.g., random gene pairs). Without significance testing, the 52% figure cannot distinguish true discovery from chance alignment with a large database.                                     | Overstating external validation could mislead users into trusting all CellMSA-predicted pairs. Rigorous benchmarking against gold-standard causal networks (e.g., LINCS L1000) is needed for functional claims.            | Compute enrichment p-values for STRING overlap using hypergeometric test against background of all possible gene pairs in the vocabulary. Additionally, test CellMSA pairs against orthogonal functional assays (e.g., CRISPRi screens for KDR partners). | [Paper] [Paper: PDF p. 25, Table A.29] explicitly states "descriptive comparison, without claiming statistically significant enrichment".                           |

| [Analysis]<br>Observation                                                                                                                                                        | Potential issue or<br>alternative<br>explanation                                                                                                                                                                                                | Why it matters                                                                                                                                                                                      | How to test it                                                                                                                                                                   | Basis                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>Pretraining uses discretized expression bins</b> , which discards continuous quantitative information and may blur subtle dosage effects critical for perturbation responses. | Discretization (e.g., "zero expression preserved as separate category, nonzero partitioned into quantiles" [Paper] [Paper: PDF p. 4]) could attenuate signal for genes where fold-change magnitude, not just bin membership, dictates function. | This may partially explain why perturbation prediction, despite gains, still has room for improvement (Pearson $\Delta=0.433$ ). Continuous-value modeling might better capture gradient responses. | Retrain CellMSA with continuous expression inputs (e.g., log-normalized counts) and compare perturbation prediction (Pearson $\Delta$ ) and PT state classification performance. | [Paper] [Paper: PDF p. 4] describes discretization as core input preprocessing; no ablation on this choice is reported. |

14 学到的知识

- **MSA 类比的普适性**：MSA 的核心价值不在于序列比对本身，而在于“聚合多源相似样本以提取高阶关系”的通用范式。CellMSA 成功证明，该范式可脱离生物序列领域，迁移到单细胞转录组（细胞作为“序列”，基因作为“位点”），为其他高维稀疏数据（如 spatial omics spots, patient EHRs）提供新思路。
- **上下文构造的生物学先验至关重要**：简单堆砌多细胞会引入噪声；CellMSA 的三类邻居（same-batch/cross-batch/cross-type）设计，将 batch effect correction、跨平台鲁棒性、功能对比学习三重目标编码进架构，是其优于 Stack（仅 same-batch/cross-batch）的关键。
- **Gene-pair 表示的工程实现路径**：Outer-product Mean（聚合共变）与 Pair-weighted Averaging（用 pair 调制上下文）的交替更新，是一种在计算可行性和表示保真度间取得平衡的有效设计，为需要高阶关系建模的其他任务（如 protein-protein interaction, gene regulatory network inference）提供了可复用的模块。
- **预训练目标的协同与制衡**：LMGM（局部重建）、LRec（全局保真）、LCCE（生物判别）三目标并非简单相加； $\lambda_1=0.01, \lambda_2=10$  的 empirically balanced 权重 (Fig. A.5) 表明，过度强调任一目标（如纯 LCCE 导致状态混淆，纯 LRec 导致噪声敏感）均会损害表征质量，凸显多目标联合优化的艺术性。
- **可解释性的落地方式**：并非追求全局可解释，而是聚焦于“条件级可解释”——通过 differential gene-pair representations ( $\Delta P$ ) 在特定生物学条件（如 PT healthy vs disease）下定位关键基因模块，并用 GO 富集和 marker 基因重叠进行生物学锚定，这是一种务实且有力的解释策略。

15 与既有知识的连接

- **候选连接/方法论连接**：CellMSA 的 MSA 类比与 AlphaFold 的 MSA 使用 ([Paper] [Paper: PDF p. 2, 18, 19]) 形成直接方法论传承，但对象从氨基酸残基 (protein) 转向基因 (transcriptome)。其 Outer-product Mean 模块借鉴自 AlphaFold 系列 [Paper] [Paper: PDF p. 5, 19]，但应用于全新数据模态。
- **候选连接/方法论连接**：CellMSA 的“上下文细胞检索+低维 pair 表示提炼+高维 target 编码”三级架构，与 spatial transcriptomics 模型 STAGATE（邻域图聚合）或 graph neural networks (GNNs) 处理 spatial neighbors 的思路有形式相似性，但 CellMSA 的上下文是生物语义驱动 (cell type/batch)，而非几何距离驱动，且其 pair 表示是显式、可导出的，而非 GNN 的隐式消息传递。

- **候选连接/方法论连接:** CellMSA 的三目标预训练 (LMGM/LRec/LCCE) 与 multi-omics foundation models (如 scFoundation [Paper] [Paper: PDF p. 3]) 的多任务学习理念一致, 但 CellMSA 的目标专为单细胞设计 (如 LMGM 掩码基因而非模态), 且 LCCE 显式利用 cell-type metadata, 与 multi-omics 中跨模态对齐的目标不同。
- **弱连接/方法论连接:** 对于 perturbation prediction, CellMSA 依赖外部 STATE-ST 模块 [Paper] [Paper: PDF p. 8–9], 这与用户研究方向中 “perturbation prediction” 有任务连接, 但 CellMSA 本身是 encoder, 不直接解决 perturbation dynamics modeling; 其贡献在于提供更鲁棒的 cell representation, 为下游动态建模打下基础。
- **弱连接/方法论连接:** CellMSA 的 gene-pair 表示天然蕴含图结构 ( $G \times G$  matrix), 可视为一种隐式的、上下文感知的基因共表达图, 与用户研究方向 “graph neural networks” 有潜在接口, 例如可将  $P^{L \times MSA}$  作为 GNN 的初始边权重或特征, 用于 downstream gene network analysis。

## 16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name:** Adaptive Context Sampling for Disease Subtyping

**originating limitation/observation:** Fig. 5 shows context size saturates at 40, but the fixed 16/16/8 split doesn't adapt to task; authors note cross-type neighbors provide "contrastive background" [Paper] [Paper: PDF p. 4], yet for disease subtyping (e.g., PT states), contrast should be *between disease states*, not just healthy vs injured. **core hypothesis:** Dynamically sampling cross-type neighbors based on differential expression (DE) scores for the target disease axis will yield more discriminative gene-pair representations than static sampling. **delta from paper:** Replace fixed  $N^{\text{cross type}}$  with DE-score-weighted sampling from a pool of disease-relevant cell types (e.g., AKI/CKD PT subtypes, fibroblast activation states) using the target cell's DE profile as query. **initial method:** For a PT target cell, compute DE scores vs healthy PT; rank candidate cross-type cells (e.g., dPT, dPT/DTL, fibroblast subtypes) by cosine similarity of their mean expression to the DE vector; sample top-k. **validation:** Compare PT state classification (Table 2) and Figure 4-style interpretability (differential hub scores) against CellMSA baseline. **failure modes:** If DE scores are noisy (low n per state), adaptive sampling may degrade; if disease states lack clear DE signatures, contrast signal weakens. **innovation status:** unverified

- **name:** Continuous-Value CellMSA for Perturbation Sensitivity

**originating limitation/observation:** Input discretization ("zero expression preserved", "nonzero partitioned into quantiles" [Paper] [Paper: PDF p. 4]) may blunt sensitivity to subtle, dosage-dependent perturbation effects, limiting Pearson  $\Delta$  gains. **core hypothesis:** Modeling continuous log-normalized counts directly in the CellMSA-Module will improve fidelity of perturbation effect prediction by preserving quantitative gradients. **delta from paper:** Replace discretized expression bins with continuous values; modify Eval embedding to a learnable linear projection + ReLU (instead of lookup table); keep all other architecture and objectives identical. **initial method:** Use log<sub>1p</sub>-normalized counts as input; train new model on same pretraining corpus; evaluate solely on perturbation prediction (Table 3) and robustness to missing genes (Table A.30). **validation:** Primary metric: Pearson  $\Delta$  on Replogle dataset; secondary: stability under 50% gene removal (should improve if continuous modeling captures

redundancy better). **failure modes:** Increased model capacity may lead to overfitting on technical noise; training instability due to unbounded continuous values. **innovation status:** unverified

- **name:** CellMSA-GNN for Cross-Modal Gene Network Alignment

**originating limitation/observation:** CellMSA learns gene-pair representations ( $P^{L \times MSA}$ ) from scRNA-seq, but user research includes multi-omics and cross-modal alignment;  $P^{L \times MSA}$  is a natural, biologically grounded prior for gene networks. **core hypothesis:** Using CellMSA's gene-pair matrix as a structural prior (edge weight initialization or constraint) in a GNN that fuses scRNA-seq and spatial transcriptomics data will improve cross-modal alignment fidelity by anchoring it to cell-state-aware co-expression. **delta from paper:** Integrate CellMSA- $P^{L \times MSA}$  as a fixed or learnable prior into an existing spatial-scRNA fusion GNN (e.g., SpaGCN, stLearn); the GNN's message passing is regularized by the CellMSA-derived gene-gene affinity. **initial method:** Extract  $P^{L \times MSA}$  for a reference scRNA-seq atlas; use it to initialize edge weights in a GNN trained on matched spatial + scRNA-seq data (e.g., mouse brain); evaluate alignment quality via cell-type domain transfer accuracy. **validation:** Compare alignment accuracy (e.g., spatial spot deconvolution error, cross-modal retrieval recall) against GNN without CellMSA prior. **failure modes:** Spatial resolution mismatch (spot vs single-cell) may make direct  $P^{L \times MSA}$  application noisy; CellMSA was trained on human, may not transfer to mouse spatial data without adaptation. **innovation status:** unverified