

Source coverage: Full paper

Extraction confidence: High

Locator mode: page-grounded

Primary analytical lens: methods

Secondary analytical lens: discovery

Context verification: Paper-only

Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Rethinking Class Imbalance for Single-Cell Foundation Models: A Systematic Benchmark Across Architectures and Long-Tail Loss Functions	[Paper] [Paper: PDF p. 1]
Authors	Zeyu Dong, Jiahui Zhong	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
URL	http://arxiv.org/abs/2609.23325v1	[Paper metadata]
PDF URL	https://arxiv.org/pdf/2609.23325v1	[Paper metadata]
Publication date	2026-09-20	[Paper metadata]
Code availability	https://github.com/jz890/sc-imbalance	[Paper] [Paper: PDF p. 7]
Field	single-cell foundation models, long-tail learning, class imbalance, loss function design	[Paper] [Paper: PDF p. 1–2]
Core datasets	Multiple Sclerosis (MS), Zheng68K, human Pancreas	[Paper] [Paper: PDF p. 2–3]
Core backbones	scGPT, scBERT, Geneformer	[Paper] [Paper: PDF p. 2–3]
Evaluated losses	CE, weighted CE, class-balanced loss, focal loss, LDAM, logit-adjusted softmax	[Paper] [Paper: PDF p. 3]
Total runs	162 (3 backbones × 3 datasets × 6 losses × 3 seeds)	[Paper] [Paper: PDF p. 1]

02 一句话总结

该论文系统评估了六种长尾损失函数在三种单细胞基础模型（scGPT/scBERT/Geneformer）和三个真实数据集（MS/Zheng68K/Pancreas）上的泛化能力，发现整体准确率严重掩盖罕见细胞类型（如疾病相关病理亚群）的系统性失败；作者揭示罕见类失败存在两种机制可区分的范式——“损失敏感型”（可通过损失选择恢复）与“严重纠缠型”（所有损失均失效），并证明前者收益由绝对训练样本数而非相对频率决定；该工作提供了首个可复现、机制驱动的单细胞长尾基准与实用指南，直击single-cell foundation models在临床级细粒度泛化中的关键瓶颈。

03 研究问题

论文聚焦于：当单细胞基础模型在标准benchmark上报告高准确率（如97.5%）时，其对罕见细胞类型的分类失败是否具有系统性、可诊断、且可干预的机制？作者不满足于观察“性能下降”的现象，而是追问：这种失败是源于预训练偏差、数据结构固有缺陷、还是损失函数设计失配？若可干预，哪些损失函数最鲁棒？其有效性是否依赖于特定架构？更重要的是，是否存在一种先验可判别的几何信号，能提前区分“换损失就能救”和“换啥损失都白搭”的两类罕见类？这些问题共同构成一个闭环：从现象→归因→诊断→干预→验证。

04 研究背景与发展路径

单细胞基础模型（scGPT/scBERT/Geneformer）已成为细胞类型注释默认主干，但其高聚合准确率被证实由常见细胞类型主导 [Paper] [Paper: PDF p. 1]；罕见细胞（如早期过渡态、病理亚群）的系统性失败已被多个研究记录（Alsabbagh et al. 2023; Naziri et al. 2025），但此前工作集中于采样策略（如随机过采样）或专用模型设计（Zhao et al. 2025），尚未在损失函数层面进行跨架构控制实验 [Paper] [Paper: PDF p. 1–2]。本文承接 Alsabbagh 等人的采样基准，将变量轴切换至损失函数，并固定采样分布与批次构成，以隔离损失选择的独立效应 [Paper] [Paper: PDF p. 2]；同时区别于 Representation-level 方法（如 Weerasekara et al. 2026 的 post-pretraining 原型重塑），本文专注 loss-level 干预——即直接替换分类头损失，与预训练主干无缝组合，提供更轻量、更易部署的实践路径 [Paper] [Paper: PDF p. 2]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Aggregate metrics mask rare-class failure	Accuracy > Macro-F1 > rare-class recall across all 9 (backbone, dataset) settings [Paper] [Paper: PDF p. 3]	Dataset structure—not pretraining—drives the gap; common classes dominate accuracy while rare ones collapse [Paper] [Paper: PDF p. 1, 3]	Figure 2 (left): Pancreas shows highest accuracy but largest drop to rare-recall; Table 1 shows consistent ordering across all columns [Paper] [Paper: PDF p. 3–4]
Loss functions fail on a subset of rare classes regardless of architecture	Two MS classes (oligodendrocyte C, phagocyte) achieve near-zero F1 under <i>all</i> six losses and <i>all</i> three backbones [Paper] [Paper: PDF p. 5]	Insufficient training samples (n=3 each) + real transcriptional overlap (e.g., phagocyte ingests oligodendrocyte RNA) → geometric absorption into neighbor classes [Paper] [Paper: PDF p. 5–6]	Figure 3 (left): two darkest rows across all three backbone columns; Figure 4: UMAP shows both classes embedded inside unrelated classes’ neighborhoods; Section 5.1 confirms same failure in non-foundation baselines (5-NN, RF) [Paper] [Paper: PDF p. 5–7]
Reweighting efficacy is misattributed to relative frequency	Weighted CE performs best on MS (most imbalanced <i>ratio</i>) but worst on Zheng68K (less imbalanced ratio yet higher absolute rare-class counts) [Paper] [Paper: PDF p. 4]	Absolute training-set size—not class share or dataset imbalance ratio—predicts ΔF1 gain; smaller absolute n → larger reweighting benefit [Paper] [Paper: PDF p. 4]	Figure 3 (right): strong negative Pearson correlation ($r = -0.77, p < 0.001$) between $\log(\text{training size})$ and $\Delta F1_c$; MS rare classes have smallest absolute counts despite comparable ratio to Zheng68K [Paper] [Paper: PDF p. 4]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Losses make hidden trade-offs obscured by Macro-F1	Logit adjustment boosts rare-recall but incurs largest precision penalty among all six losses [Paper] [Paper: PDF p. 4]	It shifts decision thresholds rather than improving feature separability → more false positives [Paper] [Paper: PDF p. 4]	Figure 2 (right): logit-adjusted point lies far below y=x line; Table 1 shows it has lowest rare-precision (0.632 vs CE's 0.664 on Zheng68K) despite highest rare-recall (0.685) [Paper] [Paper: PDF p. 4–5]

06 核心理念

论文的核心思想是：单细胞长尾泛化失败不是单一维度问题，而是一个具有可诊断几何根源的双模态现象，其干预策略必须分层设计——先用嵌入几何指标（如NC1、最近邻熵）预筛“可救”与“不可救”类，再对前者匹配损失函数，且该匹配应基于绝对样本数而非相对频率。这一思想源于对现象的深度解耦：作者观察到Figure 3左图中F1热图呈现三段式分布（全黑→灰度渐变→全亮），进而提出假设：黑色区域反映数据稀缺+生物学纠缠的双重瓶颈，灰色区域反映损失函数与表示能力的错配，白色区域则说明CE已足够。后续Figure 4的UMAP可视化与Section 5.2的NC1量化分析共同验证了该假设——几何吸收（absorption）与神经坍塌（neural collapse）指标能提前标记出损失无效区，从而将“调参”升级为“诊断-决策”流程。

07 方法总览

论文采用控制变量+多维诊断方法论：（1）构建162-run正交实验矩阵（3 backbones × 3 datasets × 6 losses × 3 seeds），所有超参取默认值以评估off-the-shelf鲁棒性 [Paper] [Paper: PDF p. 3]；（2）定义严格评估协议：使用10%训练数据作验证集选checkpoint，测试集仅评估一次，罕见类定义为训练集频率<5% [Paper] [Paper: PDF p. 3]；（3）引入三类互补诊断工具：a) 几何分析（UMAP可视化、NC1 trace ratio、最近邻熵）定位嵌入空间失败模式 [Paper] [Paper: PDF p. 6–7]；b) 线性探针（linear probe）在冻结嵌入上独立训练，分离表示能力与分类器训练瓶颈 [Paper] [Paper: PDF p. 6]；c) 跨架构一致性检验（如phagocyte在scGPT/scBERT/Geneformer下均被oligodendrocyte A误判）排除架构特异性噪声 [Paper] [Paper: PDF p. 6]。整个方法链路清晰指向机制归因，而非经验调优。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Loss-function grid	Systematically compare six long-tail losses (CE, weighted CE, class-balanced, focal, LDAM, logit-adjusted)	Isolate loss-axis effect from sampling/architecture confounders; test off-the-shelf robustness without hyperparameter tuning	Input: logits + ground truth; Output: scalar loss per sample	Table 1 reports rankings; Section 4.2 identifies class-balanced/LDAM as most consistent [Paper] [Paper: PDF p. 3–4]	Would collapse study to single baseline (CE), losing ability to distinguish loss-sensitive vs. entangled regimes (Figure 3 left) [Paper] [Paper: PDF p. 5]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Embedding geometry analyzer	Compute $NC1 = \text{tr}(\Sigma_W)/\text{tr}(\Sigma_B)$, nearest-neighbor entropy, and UMAP visualization on frozen test embeddings	Diagnose whether rare-class failure stems from representation collapse (high NC1) or classifier miscalibration (low NC1 but high confusion)	Input: frozen test-set embeddings + labels; Output: NC1 per class, entropy per class, visual clusters	Figure 4 shows absorption; Section 5.2 reports oligodendrocyte C' s high NC1 (1.19–1.79) vs. phagocyte' s low NC1 (0.17–0.32) [Paper] [Paper: PDF p. 6–7]	Without NC1/nearest-neighbor analysis, “severely entangled” would remain anecdotal; no basis to claim geometric signature precedes loss choice [Paper] [Paper: PDF p. 6]
Linear probe module	Fit class-balanced logistic regression on frozen CE-fine-tuned embeddings (5-fold CV)	Decouple representation quality from classifier training dynamics; test if discriminative signal exists but is unused	Input: frozen embeddings + labels; Output: CV-F1 per class	Section 5.3: probe achieves $F1=0.175\text{--}0.465$ on entangled classes, exceeding best trained head (0.000–0.329) [Paper] [Paper: PDF p. 6]	Removal would leave bottleneck attribution ambiguous—could not conclude failure lies in loss design rather than data scarcity alone [Paper] [Paper: PDF p. 6]
Absolute-size correlator	Correlate $\Delta F1_{c} = \max_{\ell} F_{\ell}^{(c)} - F_{(CE)}^{(c)}$ with $\log(\text{training size})$ per rare class	Challenge assumption that reweighting benefit scales with relative frequency; identify actionable predictor for loss selection	Input: per-class $\Delta F1_{c}$ and training count; Output: Pearson r, p-value	Figure 3 (right): $r = -0.77$ ($p < 0.001$) for $n=19$ recoverable classes [Paper] [Paper: PDF p. 4]	Without this analysis, guideline “use class-balanced loss for rare classes” remains generic; no basis to prioritize which rare classes to target first [Paper] [Paper: PDF p. 4]

09 关键公式与符号

- **No verifiable closed-form equations are presented in the paper.** All listed equations are partial fragments extracted from context, lacking full derivation or standalone definition:
- Equation 1: $\text{Macro-F1} = 1/C \sum_{c=1}^C F1_{c}$ — standard macro-averaged F1 definition [Paper] [Paper: PDF p. 3]
- Equation 2: $\text{Recall}_R = 1/|R| \sum_{c \in R} \text{Recall}_c$ — rare-class macro-recall over set R of rare classes (defined as training frequency <5%) [Paper] [Paper: PDF p. 3]
- Equation 3: $\Delta F1_{c} = \max_{\ell \in L} F^{\ell}_{\{1,c\}} - F^{\text{(CE)}}_{\{1,c\}}$ — per-class F1 gain from best loss over CE [Paper] [Paper: PDF p. 4]
- Equation 4: $NC1 = \text{tr}(\Sigma_W) / \text{tr}(\Sigma_B)$ — neural collapse trace ratio; Σ_W = average within-class scatter, Σ_B = between-class scatter of centroids [Paper] [Paper: PDF p. 6]

- **Key symbols/variables:**
- $\mathcal{R}$: set of rare classes (training frequency <5%) [Paper] [Paper: PDF p. 3]
- $\mathcal{L}$: set of six evaluated losses {CE, weighted CE, class-balanced, focal, LDAM, logit-adjusted} [Paper] [Paper: PDF p. 4]
- κ_{c1} : lower values indicate tighter, better-separated clusters; used to quantify embedding geometry [Paper] [Paper: PDF p. 6]
- $\Delta F1, c$: per-class F1 improvement metric central to Section 4.3's core finding [Paper] [Paper: PDF p. 4]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Aggregate metric gap analysis	Aggregate accuracy masks rare-class failure across architectures	Compare accuracy, Macro-F1, rare-recall under plain CE across all 9 (backbone, dataset) cells	Accuracy > Macro-F1 > rare-recall in all 9 cases (e.g., scBERT/MS: 0.858 > 0.639 > 0.596)	Gap is inherent to data imbalance structure, not backbone-specific	That pretraining is irrelevant—authors note variance arises from config differences, not pretraining bias [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3], Figure 2 (left), Table 1
Loss ranking by Macro-F1 & rare-AUPRC	Class-balanced loss and LDAM are most consistent generalists	Rank each loss by mean position across 9 (backbone, dataset) cells; also rank by rare-class macro-AUPRC	Class-balanced: mean rank 2.4 (F1), 0.734 (AUPRC); LDAM: 2.6 (F1), 0.690 (AUPRC); logit-adjusted: 5.2 (F1), 0.700 (AUPRC)	Class-balanced is strongest balanced performer; LDAM trades calibration for boundary shaping	That LDAM is universally superior—it underperforms on AUPRC and shows dataset-specific variance [Paper] [Paper: PDF p. 3–4]	[Paper] [Paper: PDF p. 3–4], Table 1
$\Delta F1, c$ vs. log(training size) regression	Absolute training-set size predicts reweighting benefit	Correlate $\Delta F1, c$ with log(count) for all rare classes (n=19 recoverable + 4 entangled)	Strong negative correlation: $r = -0.77$ ($p < 0.001$, $n=19$); robust to exclusion thresholds	Benefit scales with scarcity, not relative frequency; explains why MS gains more than Zheng68K	That this holds for <i>all</i> rare classes—4 entangled classes break the trend and are excluded from primary fit [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 3 (right)

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Logit adjustment precision-recall trade-off	Logit adjustment trades rare-class precision for recall	Plot rare-precision vs. rare-recall for all losses (averaged over 9 cells); compute spreads	Logit-adjusted has lowest precision (0.632) but highest recall (0.685) on Zheng68K; 10.6-point spread in rare-precision vs. 5.9-point in rare-recall	Trade-off is loss-specific and concentrated in rare classes; not an artifact of threshold choice	That it degrades non-rare performance—non-rare precision/recall spreads are only 1.1/2.1 points [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 2 (right), Table 1
Linear probe on frozen embeddings	Discriminative signal exists for entangled classes but is unused by trained heads	Fit class-balanced logistic regression on frozen CE embeddings (5-fold CV); compare to best trained F1	Probe achieves F1=0.175–0.465 on oligodendrocyte C/phagocyte, exceeding best trained head (0.000–0.329)	Bottleneck is in classifier training (loss design), not representation collapse	That nonlinear probes would close the gap—no test of expressive classifiers beyond linear [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6], Section 5.3

11 对结论的正确理解

论文结论不可简化为“换损失就能提升罕见类性能”。正确理解必须包含三层限定：（1）**适用范围限定**：结论仅适用于“损失敏感型”罕见类（Figure 3左图中非全黑行），对“严重纠缠型”（两全黑行）完全不适用，后者需数据增补或拒判（reject-option）；（2）**预测依据限定**：重加权收益由绝对训练样本数预测（Figure 3右图），而非相对频率或数据集不平衡比——这意味着在Zheng68K中训练数≈70的罕见类，其收益远低于MS中训练数=3的同类，即使前者相对频率更低；（3）**指标解读限定**：Macro-F1提升不等于均衡改善，logit调整的F1增益伴随精度显著下降（Figure 2右图），其本质是阈值偏移而非特征解耦。因此，“class-balanced loss is recommended”的真正含义是：在损失敏感型、绝对样本稀疏（<50）的罕见类上，它提供最稳健的F1与精度-召回平衡。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited backbone coverage	Only scGPT, scBERT, Geneformer evaluated; scFoundation and CellPLM untested	Extend benchmark to other existing single-cell foundation models (scFoundation, CellPLM) [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Classifier expressivity ceiling	Linear probe outperforms trained heads on entangled classes, suggesting room for improvement with more expressive classifiers	Test nonlinear classifier heads (beyond linear probe) to extract additional signal from frozen representations [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]
Isolated imbalance axis	Study focuses solely on cell-type class imbalance; ignores compounding variables like demographic composition or batch effects	Investigate interactions between class imbalance and demographic composition (Al Amin et al. 2025) or batch effects (Maan et al. 2024) [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
NC1’ s sensitivity to small-n classes may confound interpretation	Phagocyte’ s low NC1 (0.17–0.32) is attributed to tight clustering inside another class, but NC1 denominator $\text{tr}(\Sigma_B)$ shrinks when centroid distances collapse—low NC1 could reflect global embedding collapse, not local absorption	Misattribution could lead to false confidence in representation quality for tiny classes; undermines NC1’ s use as a standalone diagnostic	Compute NC1 on subsampled versions of larger classes (e.g., downsample oligodendrocyte A to $n=3$) and compare NC1 distributions; or use alternative metrics like Silhouette score per class	[Paper] [Paper: PDF p. 6]: “phagocyte’ s small cell count means a handful of tightly clustered cells embedded inside another class’ s region can produce low within-class scatter despite total confusability” — acknowledges small-n bias but doesn’ t validate NC1’ s robustness
Linear probe’ s 5-fold CV may overestimate separability	Probe is trained/tested on <i>frozen test-set embeddings</i> , meaning no train/test split—CV internal to test set measures memorization capacity, not generalization	If probe overfits test embeddings, its superior F1 doesn’ t prove signal is generalizable; weakens claim that “bottleneck is in loss design”	Repeat probe on <i>train-set embeddings only</i> , using standard train/test split, and report generalization gap (test F1 vs. CV F1); compare to trained head’ s test F1	[Paper] [Paper: PDF p. 6]: “measuring CV-internal separability, not train/test generalization” — explicitly states limitation but doesn’ t quantify its impact

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
“Severely entangled” label conflates data scarcity and biology	Oligodendrocyte C’ s confusion with excitatory neurons is attributed to shared self-antigen presentation (B2M, HLA-C), yet its n=3 makes it impossible to disentangle whether biology or scarcity dominates	Blurring these causes risks misallocating resources—e.g., prioritizing wet-lab validation of biological overlap over data collection	Synthesize additional oligodendrocyte C cells via generative models (e.g., scGen) and retrain; if F1 improves significantly, scarcity dominates; if confusion persists, biology dominates	[Paper] [Paper: PDF p. 6]: “oligodendrocyte C is an MS-specific pathological subcluster; its confusion... reflects shared self-antigen- presentation” — cites biology but provides no ablation of scarcity

14 学到的知识

- **单细胞长尾失败是双模态的**：不能笼统说“罕见类性能差”，必须区分“损失敏感型”（换LDAM/class-balanced可救）与“严重纠缠型”（所有损失均失效），后者需几何诊断先行。
- **绝对样本数是关键预测器**：在单细胞场景中，重加权收益由罕见类的绝对训练样本数（而非占比）决定，这颠覆了传统长尾学习中强调“有效样本数”相对比例的直觉，对实验设计有直接指导意义——优先为n<10的类收集数据。
- **几何指标可前置诊断**：NC1 trace ratio与最近邻熵能在不训练任何分类器前，从冻结嵌入中识别出注定失败的类（如oligodendrocyte C的NC1=1.79），使计算资源聚焦于可优化区域。
- **Macro-F1是危险的平滑器**：它掩盖了logit调整“用精度换召回”的本质（Figure 2右图），实践中必须联合查看精度-召回曲线或AUPRC。
- **线性探针是解耦利器**：在冻结嵌入上独立训练线性分类器，能清晰分离表示能力（probe性能）与分类器训练瓶颈（trained head性能），本文用此证明损失设计是主要瓶颈。

15 与既有知识的连接

- **候选连接/方法论连接**：本文的“损失敏感 vs. 严重纠缠”二分法，与Kang et al. (2020)提出的representation-classifier decoupling框架高度呼应——前者对应classifier calibration failure（可解耦优化），后者对应representation failure（需新数据或新预训练）。本文用线性探针实证了该框架在单细胞领域的适用性 [Paper] [Paper: PDF p. 6]。
- **候选连接/方法论连接**：NC1计算直接继承自Papayan et al. (2020)的neural collapse理论，并首次将其应用于单细胞长尾诊断，将经典模式识别指标（Fisher ratio）与现代foundation model瓶颈关联 [Paper] [Paper: PDF p. 6]。
- **候选连接/方法论连接**：绝对样本数预测 $\Delta F1_c$ 的发现，与Cui et al. (2019)的effective-number-of-samples框架形成张力——后者强调相对频率修正，本文证明在单细胞小样本 regime 下，绝对计数更具判别力，提示该框架需针对生物数据特性校准 [Paper] [Paper: PDF p. 4]。
- **弱连接/方法论连接**：用户研究方向中的graph neural networks与spatial transcriptomics未被本文覆盖，但其几何诊断思路（如UMAP、NC1）可迁移至空间图嵌入的neighborhood absorption分析；multi-omics对齐亦可借鉴“冻结表示+线性探针”范式解耦模态特异性瓶颈。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** Geometry-Guided Loss Selection Pipeline

originating limitation/observation: Authors show NC1 and nearest-neighbor entropy diagnose “severely entangled” classes pre-training, but don’t integrate this into automated loss selection [Paper] [Paper: PDF p. 6–7]. **core hypothesis:** A pipeline that first computes NC1/entropy on frozen backbone embeddings, then routes classes to loss functions (e.g., class-balanced for $NC1 < 0.8$, abstain for $NC1 > 1.5$), will outperform uniform loss application. **delta from paper:** Adds conditional routing layer atop the static loss grid; uses geometry as gatekeeper. **initial method:** On MS dataset, compute NC1 per class on scGPT CE embeddings; assign class-balanced loss to classes with $NC1 < 0.8$, LDAM to $0.8-1.5$, and reject-option (output “insufficient data”) to $NC1 > 1.5$; evaluate rare-class F1 gain vs. uniform class-balanced. **validation:** Compare rare-class F1 and precision-recall curves; measure % of entangled classes correctly routed to reject. **failure modes:** NC1 threshold may not generalize across datasets/backbones; reject-option lacks clinical utility without uncertainty quantification. **innovation status:** unverified

- **name:** Absolute-Count Adaptive Reweighting

originating limitation/observation: Paper finds absolute training size predicts $\Delta F1_c$, but all reweighting losses use fixed formulas (e.g., inverse-frequency) not tuned to absolute n [Paper] [Paper: PDF p. 4]. **core hypothesis:** A reweighting scheme where class weight = $f(n_c)$ with f learned from the $\Delta F1_n$ curve (Figure 3 right) will outperform static reweighting. **delta from paper:** Replaces hand-designed weight functions (e.g., Cui et al. 2019) with data-driven, absolute-count-aware weights. **initial method:** Fit a spline to Figure 3’s ($\log n_c$, $\Delta F1_c$) points; use predicted $\Delta F1_c$ as weight multiplier in loss; train on MS and test generalization to Zheng68K. **validation:** Compare Macro-F1 and rare-AUPRC against class-balanced loss; check if weight distribution correlates with actual $\Delta F1$ gain. **failure modes:** Overfitting to MS’s specific n_c distribution; fails if $\Delta F1_n$ relationship is dataset-specific. **innovation status:** unverified

- **name:** Entanglement-Aware Perturbation Prediction

originating limitation/observation: “Severely entangled” classes (e.g., oligodendrocyte C) show transcriptional overlap with confusers (excitatory neurons) due to shared stress markers (B2M, HLA-C) [Paper] [Paper: PDF p. 6]; user’s perturbation prediction interest aligns with modeling such biological entanglement. **core hypothesis:** Modeling the entanglement as a latent perturbation (e.g., “myelin stress $\rightarrow$ oligodendrocyte C $\rightarrow$ excitatory neuron marker expression”) enables synthetic data generation that improves classification. **delta from paper:** Shifts from diagnosing failure to generating corrective interventions using biological priors. **initial method:** Train a VAE on oligodendrocyte C and excitatory neuron cells; use latent space interpolation to generate hybrid cells; augment MS training set and retrain scGPT with class-balanced loss. **validation:** Measure F1 gain on oligodendrocyte C; verify generated cells express expected stress markers (B2M) via gene-level metrics. **failure modes:** Generated cells may not capture true biological transitions; VAE may collapse to mean. **innovation status:** unverified