

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: resource
Secondary analytical lens: methods
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-05	[Paper] [Paper: PDF p. 1]
Core contribution	First large-scale, standardized, multi-platform benchmark for virtual ST models, enabling controlled comparison of architectures under unified PFM encoding and downstream biological evaluation	[Paper] [Paper: PDF p. 2–4]
Target task	Predicting spatial gene expression (spot-level) from H&E image patches ("virtual ST")	[Paper] [Paper: PDF p. 2, Fig. 1a]
Key datasets	STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium/Xenium); STP-BENCH-EXTERNAL (185,831 spots, same 6 cancers, cross-institution/tissue/platform)	[Paper] [Paper: PDF p. 4, Fig. 1b]
Evaluated models	21 models: 14 regression-based, 4 bi-modal retrieval, 3 generative	[Paper] [Paper: PDF p. 6, Fig. 1c]
Primary encoder	UNlv2 pathology foundation model (PFM), used as default where architecturally compatible	[Paper] [Paper: PDF p. 7–8, Fig. 2a]
Evaluation metrics	PCC (Equation 1), MAE (Equation 2), SSIM; plus downstream: Cell2location PCC, SpaGCN ARI	[Paper] [Paper: PDF p. 31–32, Fig. 4]
Code & data	Publicly released at https://github.com/NEXGEM/STP-Bench and Hugging Face	[Paper] [Paper: PDF p. 37]

02 一句话总结

STP-BENCH 是首个系统化、大规模、多平台的 virtual ST 统一基准，通过强制统一使用 UNiv2 等病理基础模型（PFM）作为图像编码器，剥离了图像表征能力对模型性能评估的干扰，揭示出多数现有架构并未超越线性探针基线；它进一步证明基因可预测性存在普适性天花板（由形态-转录耦合强度决定），而多尺度建模（如 TRIPLEX、DeepSpot）仅在特定生物学程序（基质重塑、免疫浸润）上带来边际增益；该基准覆盖从 spot-level 表达到 cell-type deconvolution 和 spatial domain identification 的完整生物推理链，但其效用高度依赖原始 ST 平台的数据质量（Xenium > Visium）。

03 研究问题

论文直面 virtual ST 领域的核心方法论困境：**如何公平、可靠、生物学可解释地评估模型进步？** 作者观察到，既有工作因三重缺陷导致结论不可靠——（1）数据层面：小规模、异构、单平台数据集（如仅 Visium）缺乏统计效力与泛化代表性；（2）方法层面：各模型捆绑私有图像编码器（ResNet50、CTransPath 等），使架构创新与编码器能力混杂，无法归因性能来源；（3）评估层面：仅报告 aggregate PCC，忽略 per-gene 可预测性、下游任务效用及鲁棒性。因此，研究问题被精炼为：**能否构建一个资源完备、协议统一、评估多维的基准，以解耦 encoder 与 architecture 的贡献，并实证刻画 virtual ST 的能力边界与生物学适用性？** [Paper] [Paper: PDF p. 2-4]

04 研究背景与发展路径

virtual ST 的演进呈现“范式并行、编码器跃迁”双主线：

- **范式主线：**从早期回归模型（ST-Net）→ 引入邻域/全局上下文（TRIPLEX, DeepSpot）→ 多模态对齐（BLEEP, STco）→ 生成式建模（STFlow, Stem） [Paper] [Paper: PDF p. 3]；
- **编码器主线：**从 ImageNet-CNN（ResNet50）→ 小规模病理 CNN → 大规模 ViT-based PFM（UNiv2, Virchow2） [Paper] [Paper: PDF p. 10]。

然而，两条主线在评估中从未解耦：Wang et al. [50] 保留原生 encoder，混淆架构贡献；HEST-1K [51] 虽用大样本但仅测 PFM embedding 与基因的简单回归，未覆盖真实 virtual ST 架构。STP-BENCH 的发展路径正是对这一断裂的缝合：**以 PFM 为统一接口，将全部 21 种架构“插拔”到同一表征层，再通过 multi-granularity 评估反推架构的真实附加值** [Paper] [Paper: PDF p. 4]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
评估不公平	模型排名随 encoder 切换剧烈波动（如 CFANet 从第16跳至第6）	各模型原生 encoder 在预训练域、规模、范式上差异巨大，性能提升可能源于 encoder 而非 architecture	[Paper] [Paper: PDF p. 9, Fig. 2b]
能力边界模糊	HMHVGs 与 marker genes 预测性能悬殊（PCC≈0.4 vs ≈0.2），且跨模型一致性高	基因可预测性由形态-转录内在耦合强度决定，而非模型能力；低表达 marker genes 在 Visium 上信噪比过低	[Paper] [Paper: PDF p. 9-10, Fig. 2a,c,d]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
下游效用存疑	Cell2location 和 SpaGCN 性能在 Xenium 上显著优于 Visium，且与 spot-level PCC 高度相关	虚拟 ST 的生物学价值受原始 ST 数据质量（如 transcript counts）制约，非纯算法问题	[Paper] [Paper: PDF p. 14–15, Fig. 4a–c]
鲁棒性未经检验	Cross-tissue 泛化 gap 达 -0.35，远超 cross-institution (-0.10)	形态-表达映射具有强组织特异性，跨癌种迁移需克服生物学异质性，非技术 batch effect	[Paper] [Paper: PDF p. 17, Fig. 5b]
扩展性误导	Inter-cohort scaling (BRCA+LUAD+PRAD) 导致负向迁移	简单拼接多癌种数据会引入冲突的形态先验，损害 tissue-specific mapping	[Paper] [Paper: PDF p. 18, Fig. 5d]

06 核心思想

论文的核心思想是 “解耦评估 + 边界测绘”：

- **解耦评估**：将 virtual ST 流程形式化为 `H&E patch → [PFM encoder] → [architecture head] → gene expression`，强制固定 `[PFM encoder]` 层 (UNiv2)，使所有比较聚焦于 `[architecture head]` 的增量价值，从而终结 “是模型好还是 encoder 好” 的归因混乱 [Paper] [Paper: PDF p. 7–9]；
- **边界测绘**：不满足于 aggregate PCC，而是系统测绘三个维度的能力边界：(1) **基因维度**：识别哪些基因（如 COL1A1, LAG3）因依赖多尺度形态（纤维化梯度、淋巴聚集）而受益于 TRIPLEX/DeepSpot；(2) **生物学维度**：验证虚拟 profile 是否足以支撑 Cell2location (cell abundance) 和 SpaGCN (spatial domains) 等下游任务；(3) **鲁棒性维度**：量化 cross-institution (技术)、cross-tissue (生物)、cross-platform (技术+生物) 三类迁移的性能衰减，揭示 tissue-specificity 是最大瓶颈 [Paper] [Paper: PDF p. 11–19]。

07 方法总览

STP-BENCH 的方法框架是 “三支柱评估体系”：

1. **统一性能基准 (Fig. 1d)**：在 STP-BENCH-INTERNAL 上，用 PCC/MAE/SSIM 评估 21 模型对 HMHVGs 和 16 TME marker genes 的预测；强制 UNiv2 编码器 (w/ PFM)，对比 native encoder (w/o PFM) 以量化 encoder 贡献；
2. **多粒度生物学分析 (Fig. 1e–f)**：(i) **基因级**：绘制 gene-wise PCC heatmap (Fig. 3a)，识别 margin-gain genes (Fig. 3b)；(ii) **基因集级**：用 singscore 计算 GO pathway activity PCC (Fig. 3c–e)；(iii) **细胞/组织级**：用 Cell2location (Fig. 4a) 和 SpaGCN (Fig. 4b–c) 评估虚拟 profile 的下游效用；
3. **鲁棒性与可扩展性 (Fig. 1g)**：在 STP-BENCH-EXTERNAL 上测试 cross-institution/tissue/platform 泛化 (Fig. 5a–b)，并进行 intra-/inter-cohort 数据缩放实验 (Fig. 5c–d)，检验 performance 是否随数据量/多样性单调提升。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Unified PFM Encoder (UNlv2)	Extracts histomorphological features from 224×224 H&E patches into fixed-dim embeddings	To isolate architecture contribution by eliminating encoder variability; UNlv2' s large-scale pathology pretraining provides superior morphological semantics	Input: H&E patch; Output: 1024-dim embedding	[Paper] [Paper: PDF p. 7–10, Fig. 2e shows UNlv2 > CTransPath > ResNet50]	Severe ranking inversion (e.g., CFANet drops from 6th to 16th) and overall performance collapse for w/o PFM models [Paper] [Paper: PDF p. 9, Fig. 2b]
Multi-scale Context Integration (TRIPLEX/DeepSpot)	Fuses local (target spot), neighborhood (surrounding spots), and global (whole-slide) morphological context	To capture long-range dependencies (e.g., fibrosis gradients, immune fronts) that single-patch encoders miss	Input: UNlv2 embeddings of target/neighbor/global patches; Output: fused representation for regression	[Paper] [Paper: PDF p. 11, 13, 25–26; Fig. 3b shows largest ΔPCC for stromal/immune genes]	Loss of gain on stromal (COL1A1) and immune (LAG3) genes; gene set PCC for "T Cell Activation" drops significantly [Paper] [Paper: PDF p. 13, Fig. 3e]
Bi-modal Contrastive Alignment (BLEEP/STco/mclSTExp)	Learns joint embedding space for H&E patches and gene expression via contrastive loss	To enable retrieval-based inference and leverage spatial coordinate info (STco/mclSTExp)	Input: UNlv2 patch emb + gene expr vector (+ coords); Output: shared 512-dim space for nearest-neighbor retrieval	[Paper] [Paper: PDF p. 6, 26–27; Fig. 2a shows moderate PCC, outperformed by top regressors]	Reduced robustness to cross-tissue shift (lower Spearman ρ in Extended Data Fig. 5–6) and weaker gene set recovery [Paper] [Paper: PDF p. 17]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal	
Generative Conditional Modeling (STFlow/Stem)	Models conditional distribution $p(\text{expr} \setminus$	H&E) via flow matching/diffusion	To capture expression uncertainty and multimodality beyond point estimates	Input: UNiv2 patch emb (+ coords for STFlow); Output: sampled gene expression vector	[Paper] [Paper: PDF p. 6–7, 28–29; Fig. 2a shows lowest PCC among top performers]	Poorer downstream utility: lowest ARI in SpaGCN (Fig. 4c) and weakest cell abundance correlation (Fig. 4a) [Paper] [Paper: PDF p. 14]
Downstream Task Pipeline (Cell2location/SpaGCN)	Translates predicted gene expr into cell-type abundances or spatial domains	To assess if virtual ST preserves biologically meaningful structure beyond spot-level numbers	Input: predicted spot-by-gene matrix; Output: cell-type PCC or domain ARI	[Paper] [Paper: PDF p. 14–15, Fig. 4a–c; shows TRIPLEX/DeepS pot top performers]	If removed, evaluation reduces to purely statistical metrics (PCC), losing biological interpretability — a key stated limitation of prior work [Paper] [Paper: PDF p. 2–3]	

09 关键公式与符号

论文未提出新公式，但明确定义并使用了三个核心评估指标：

- **Equation 1 (PCC):** $\text{PCC}_{g,s} = \frac{\sum (\hat{y}_{i,g} - \bar{y}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{[\sum (\hat{y}_{i,g} - \bar{y}_g)^2 \cdot \sum (y_{i,g} - \bar{y}_g)^2]}}$ [Paper] [Paper: PDF p. 31]
- $\hat{y}_{i,g}$, $y_{i,g}$: predicted & ground-truth log-normalized expression of gene g at spot i
- $\bar{y}_g$, $\bar{y}_g$: mean of predicted & ground-truth across all N spots in section s
- *Use:* Primary metric for spot-level accuracy; reported as mean across genes and folds.
- **Equation 2 (MAE):** $\text{MAE}_{g,s} = (1/N) \sum |\hat{y}_{i,g} - y_{i,g}|$ [Paper] [Paper: PDF p. 32]
- *Use:* Quantifies absolute error magnitude in log-expression space; complements PCC.
- **SSIM:** Computed via `skimage.metrics.structural_similarity` on spatial grids [Paper] [Paper: PDF p. 32]
- *Key symbols:* `data_range=1.0`, min-max normalized expression images, rescaled coordinates to discrete grid.
- *Use:* Captures spatial coherence of expression landscapes, beyond spot-wise correlation.
- **Other critical symbols:**

- **HMHVg** : High-mean highly-variable genes (200 genes selected by rank-sum of mean & std) [Paper] [Paper: PDF p. 33]
- **TME markers** : 16 immune/stromal/epithelial checkpoint genes (e.g., **CD3E** , **ACTA2** , **PDCD1**) [Paper] [Paper: PDF p. 7, 33]
- **ARI** : Adjusted Rand Index for spatial domain agreement [Paper] [Paper: PDF p. 36]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Fig. 2a	Unified PFM standardization reorders model rankings	21 models on STP-BENCH-INTERNAL (7 datasets), w/ UNlv2 vs w/o PFM; evaluated on HMHVgs & marker genes	Most w/ PFM models < linear probing baseline; TRIPLEX/DeepS pot > baseline; w/o PFM models generally worse	UNlv2 encoder is dominant factor; architectural gains are marginal and model-specific	That any specific architecture is universally superior — rankings change with encoder [Paper] [Paper: PDF p. 9]	[Paper] [Paper: PDF p. 8–9, Fig. 2a]
Fig. 2c-d	Gene expression level (not morphology) drives predictability gap	NCCHE-LUAD-Xenium (high counts) vs NCCHE-LUAD-Visium (low counts); stratified by expression quantile	Xenium: $PCC \approx 0.58$ for both HMHVgs & markers; Visium: $PCC \approx 0.4$ vs ≈ 0.19 ; Kruskal-Wallis $p < 1e-12$	Low transcript counts in Visium, not inherent morphological uncoupling, limit marker gene prediction	That morphology cannot encode immune biology — it <i>can</i> , given sufficient signal (Xenium proves it)	[Paper] [Paper: PDF p. 10, Fig. 2c-d]
Fig. 3a	Gene-wise predictability is model-agnostic	Gene-wise PCC heatmap across 20 models (excluding zero-shot) on STP-BENCH-INTERNAL	Smooth separation: genes easy/hard for one model are easy/hard for all; curved boundary shows architectural shifts	Prediction ceiling is set by morphology-transcript coupling strength, not model capacity	That model design is irrelevant — TRIPLEX/DeepS pot <i>do</i> shift the boundary for specific genes [Paper] [Paper: PDF p. 11]	[Paper] [Paper: PDF p. 11, Fig. 3a]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Fig. 4a-c	Spot-level accuracy translates to downstream biological utility	Cell2location PCC & SpaGCN ARI on three cohorts (Xenium/Visium), using same six models	TRIPLEX/DeepSpot top in both tasks; Xenium cohorts >> Visium cohorts; rare cell types (plasma cells) poorly recovered	Virtual ST utility is platform-dependent and scales with spot-level PCC; major lineages (epithelial, T cells) are recoverable	That virtual ST can replace real ST for rare cell analysis — plasma/mast cells show low correlation [Paper] [Paper: PDF p. 14]	[Paper] [Paper: PDF p. 14–15, Fig. 4a–c]
Fig. 5a-b	Internal rankings generalize across domain shifts	Cross-institution/tissue/platform on STP-BENCH-EXTERNAL; Spearman ρ between internal & external PCC	$\rho > 0.86$ for institution/tissue; $\rho = 0.62$ for platform; cross-tissue gap (-0.35) >> cross-institution (-0.10)	Architectural superiority is robust to technical variation but fragile to biological heterogeneity	That cross-tissue generalization is feasible with current models — gap is too large for practical use	[Paper] [Paper: PDF p. 17, Fig. 5a-b]

11 对结论的正确理解

- **“Most models fail to beat linear probing”** 意味着：在 UNIV2 提供强大形态表征的前提下，当前复杂架构（如多头注意力、图网络、生成式解码）未能提供足够增量价值，**并非模型无效，而是 UNIV2 已捕获大部分可预测信号**；TRIPLEX/DeepSpot’s gains confirm that *some* architectural innovations *do* matter for specific biological programs [Paper] [Paper: PDF p. 9, 11, 13].
- **“Gene predictability is universal”** 指：PCC 高低排序在模型间高度一致，**反映的是形态-转录关联的客观强度分布，而非模型缺陷**；这为 prioritizing genes for wet-lab validation (e.g., high-margin COL1A1) is valid [Paper] [Paper: PDF p. 11].
- **“Xenium > Visium in downstream tasks”** 表明：虚拟 ST 的生物学效用**受限于输入 ST 数据的质量下限**；提升虚拟 ST 不应只优化模型，更需推动高灵敏度 ST 技术（如 Xenium）普及 [Paper] [Paper: PDF p. 14–15, 19].
- **“Cross-tissue gap is large”** 揭示：virtual ST 的临床落地需 **tissue-specific training or domain adaptation**, not generic multi-cancer models — simple data aggregation harms performance (Fig. 5d) [Paper] [Paper: PDF p. 17–19].
- **“Rankings preserve under domain shift”** 说明：内部 benchmark 选出的 top models (TRIPLEX/DeepSpot) are reliable choices for deployment in new institutions, but **not for new cancer types** [Paper] [Paper: PDF p. 17].

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer/tissue scope	STP-BENCH covers only 6 cancer types and 2 platforms (Visium/Xenium)	Extend benchmark to additional tumor types, normal tissues, and emerging platforms (e.g., Stereo-seq, Slide-seq)	[Paper] [Paper: PDF p. 20]
Restricted gene panel	Analysis focused on HMMVGs (200 genes) and 16 TME markers; lowly expressed or functionally diverse genes unexamined	Systematically investigate low-abundance genes and broader functional categories (e.g., metabolic pathways)	[Paper] [Paper: PDF p. 20]
Spot-level resolution only	All evaluations performed at spot-level (multi-cell aggregates); no single-cell ST or virtual scST evaluation	Extend benchmarking principles to single-cell resolution as scST datasets and models mature	[Paper] [Paper: PDF p. 20]
No perturbation modeling	Benchmark assesses steady-state prediction, not response to interventions (e.g., drug treatment, genetic knockdown)	Incorporate perturbation-response datasets to evaluate virtual ST for causal inference	[Paper] [Paper: PDF p. 20]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
TRIPLEX/DeepSpot's multi-scale advantage may be confounded by training data scale	These models were trained on larger datasets (e.g., WUSTL-BRCA has 157k spots); their gain could stem from more data, not architecture	Over-attributing success to multi-scale design risks misleading future architecture search; simpler models might match if given equal data	Re-train all models (including linear probe) on identical subset (e.g., 50k spots) of WUSTL-BRCA and re-evaluate gene-wise margins	[Paper] [Paper: PDF p. 21 states WUSTL-BRCA has 157,138 spots, largest in INTERNAL; TRIPLEX/DeepSpot top performers]
The “universal gene predictability” pattern may break under extreme morphological divergence	Gene concordance was observed across 6 cancers, but may vanish when comparing e.g., brain (GBM) vs. prostate (PRAD) due to fundamental tissue architecture differences	Assuming universality could lead to overconfidence in cross-tissue transfer; needs validation on truly divergent pairs	Compute gene-wise PCC correlation (Spearman) between GBM and PRAD cohorts specifically; if $p < 0.5$, universality fails	[Paper] [Paper: PDF p. 38 Extended Data Fig. 1 shows GBM and PRAD in same figure, but no direct cross-cohort gene correlation reported]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Using expm1 + clip for Cell2location input discards count distribution information	Clipping negative values after expm1 forces non-negativity but distorts zero-inflated, overdispersed ST count distributions that Cell2location expects	May artificially inflate Cell2location PCC for models predicting near-zero values, biasing downstream evaluation	Compare Cell2location results using raw predicted logits (no expm1/clip) vs. clipped counts; if PCC difference >0.1, clipping is problematic	[Paper] [Paper: PDF p. 35 states “rounded and clipped to non-negative integers” ; Cell2location is designed for counts]
SSIM computation ignores spatial sparsity	SSIM treats expression as continuous image; but ST data is sparse (many zeros), and SSIM’s luminance/contrast terms may be unstable on degenerate constant images	Could misrepresent spatial coherence for low-expression genes; undermines SSIM’s value as complementary metric	Report SSIM only for genes with >10% non-zero spots; compare SSIM-PCC correlation with and without zero-filtering	[Paper] [Paper: PDF p. 32 says “NaN entries from degenerate constant images” are excluded, but no threshold for sparsity defined]
Cross-platform (Visium→Xenium) “improvement” may reflect dataset imbalance	Fig. 5b right panel shows some models above “No Gap” line; but STP-BENCH-EXTERNAL Xenium data may have higher quality/less noise than INTERNAL Xenium	Suggests cross-platform is “easy” when it may just be easier test set; misleads on true platform-agnostic capability	Evaluate cross-platform on held-out INTERNAL Xenium samples (not just EXTERNAL) to control for data quality	[Paper] [Paper: PDF p. 4–5 defines INTERNAL as 609k spots (incl. NCCHE-LUAD-Xenium), EXTERNAL as 185k spots (incl. other sources); no statement on quality parity]

14 学到的知识

- **Encoder is king, architecture is niche:** For virtual ST, investing in a strong PFM (UNiv2/Virchow2) yields larger gains than complex architecture tweaks; TRIPLEX/DeepSpot’s edge is narrow ($\Delta\text{PCC} \sim 0.1$) and confined to stromal/immune genes requiring multi-scale context [Paper] [Paper: PDF p. 9–13].
- **Data quality > algorithm:** Xenium’s higher transcript counts directly enable better marker gene prediction (PCC 0.58 vs 0.19) and downstream utility, proving that virtual ST’s ceiling is set by experimental ST, not computational limits [Paper] [Paper: PDF p. 10, 14–15].
- **Biological granularity is hierarchical:** Spot-level PCC strongly predicts Cell2location PCC and SpaGCN ARI (concordance across Fig. 2/4), meaning improvements must start at the gene level; no “free lunch” for downstream tasks [Paper] [Paper: PDF p. 14, 19].
- **Robustness is asymmetric:** Models generalize well across institutions (technical) but catastrophically fail across tissues (biological), demanding tissue-aware training strategies, not generic multi-task learning [Paper] [Paper: PDF p. 17–19].
- **Negative transfer is real:** Adding LUAD/PRAD data to BRCA training *harms* BRCA performance (Fig. 5d), confirming that morphological priors are cancer-type-specific; data curation must prioritize homogeneity over volume [Paper] [Paper: PDF p. 18].

15 与既有知识的连接

- **Candidate connection / methodological connection:** STP-BENCH' s multi-granularity evaluation (gene → gene set → cell type → spatial domain) mirrors the hierarchical validation framework used in single-cell foundation model benchmarks (e.g., scFoundation, scGPT), but adapts it to spatial context and spot-level constraints.
- **Candidate connection / methodological connection:** The finding that multi-scale context (TRIPLEX) aids stromal gene prediction aligns with graph neural network (GNN) literature showing that aggregating neighborhood information (e.g., via GCNConv in SEPAL) improves prediction of spatially structured phenotypes — though STP-BENCH shows GNNs (SEPAL) underperform pure multi-scale regression.
- **Candidate connection / methodological connection:** The emphasis on cross-platform (Visium↔Xenium) generalization connects to cross-modal alignment work in multi-omics, where bridging modalities with different noise profiles (e.g., scRNA-seq ↔ ATAC-seq) requires careful handling of technical artifacts — STP-BENCH confirms this challenge persists in spatial omics.
- **Weak connection / methodological connection:** While STP-BENCH evaluates perturbation-agnostic prediction, user' s interest in *perturbation prediction* remains unaddressed; no datasets or models in STP-BENCH involve interventions, making direct transfer impossible.
- **Weak connection / methodological connection:** User' s focus on *single-cell foundation models* is orthogonal; STP-BENCH operates at spot-level (10–100 cells), and its conclusions about PFM dominance do not extrapolate to single-cell resolution where cellular heterogeneity dominates.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **Name:** Tissue-Aware PFM Adapter (TAPA)

Originating limitation/observation: Cross-tissue generalization gap is severe (−0.35) and inter-cohort scaling causes negative transfer, indicating that a single PFM cannot encode all tissue morphologies [Paper] [Paper: PDF p. 17–18, Fig. 5b,d]. **Core hypothesis:** Lightweight, tissue-specific adapters grafted onto a frozen universal PFM (e.g., UNiv2) can learn tissue-invariant morphological representations without catastrophic forgetting. **Delta from paper:** STP-BENCH uses *one fixed PFM*; TAPA introduces *learnable, low-rank adapters per tissue type* (e.g., BRCA-adapter, LUAD-adapter) while keeping UNiv2 backbone frozen. **Initial method:** For each cancer type in STP-BENCH-INTERNAL, train a LoRA adapter on UNiv2' s last layer; freeze UNiv2; train adapter + TRIPLEX head end-to-end on that tissue' s data. **Validation:** Test cross-tissue generalization (e.g., train BRCA-adapter+TRIPLEX on BRCA, test on LUAD) and compare ARI/PCC against vanilla UNiv2+TRIPLEX. **Failure modes:** Adapter overfits to single tissue; adapters don' t compose (BRCA+LUAD adapter ≠ sum of individual adapters); adapter adds latency. **Innovation status:** unverified

- **Name:** Morphology-Guided Gene Set Prior (MGGP)

Originating limitation/observation: Gene set scoring (Fig. 3e) shows TRIPLEX/DeepSpot excel on immune/stromal pathways, but current models predict genes independently; no explicit gene set structure is enforced [Paper] [Paper: PDF p. 13]. **Core hypothesis:** Injecting gene set membership as an

inductive bias (e.g., via graph edges in EGGN or attention masks in TRIPLEX) will improve coherence of predicted gene set activity, especially for low-expression markers. **Delta from paper:** STP-BENCH evaluates gene sets *post-hoc*; MGGP modifies model architecture to *jointly predict genes within biologically coherent sets*. **Initial method:** Modify TRIPLEX' s fusion encoder to include gene set adjacency matrix (from GO BP) as a structural prior in cross-attention; mask attention between unrelated gene sets. **Validation:** Compare singscore PCC for "T Cell Activation" set on NCCHE-LUAD-Xenium between vanilla TRIPLEX and MGGP-TRIPLEX; require $\Delta\text{PCC} \geq 0.05$. **Failure modes:** Over-smoothing kills gene-specific signals; prior matrix is noisy/incomplete; computational overhead. **Innovation status:** unverified

- **Name:** Sparse-ST Imputation Augmentation (SSIA)

Originating limitation/observation: Visium' s low marker gene counts cause poor prediction ($\text{PCC} \approx 0.19$), but this is a data deficiency, not a model failure; STP-BENCH offers no solution for low-count regimes [Paper] [Paper: PDF p. 10, Fig. 2d]. **Core hypothesis:** Augmenting Visium training data with *in silico* high-count pseudo-spots generated by a Xenium-trained STFlow model will boost Visium model performance without wet-lab cost. **Delta from paper:** STP-BENCH treats platforms as separate; SSIA bridges them via *cross-platform generative augmentation*. **Initial method:** Train STFlow on NCCHE-LUAD-Xenium; sample 100k pseudo-spots; add them to WUSTL-BRCA-Visium training set; retrain DeepSpot. **Validation:** Measure PCC gain on Visium marker genes (e.g., CD3E, CD68); require gain > 0.08 over baseline. **Failure modes:** Domain gap causes pseudo-spot artifacts; augmentation dilutes Visium-specific features; STFlow' s own limitations propagate. **Innovation status:** unverified