

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	MARC: Morphology-Aware Regression of Consensus for Cell Segmentation in Subcellular Spatial Transcriptomics	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-12	[Paper meta]
Authors	Xinyu Shu, Andrew Zhang, Jean Yang, Jinman Kim	[Paper] [Paper: PDF p. 1]
Core task	Pixel-level consensus-support regression for SST segmentation quality estimation	[Paper] [Paper: PDF p. 1–3]
Input modalities	Candidate mask F_k , DAPI morphology D , transcript-density map T	[Eq. 2, Paper: PDF p. 3]
Output	Dense consensus-support map $\hat{C}_k \in [0,1]^{H \times W} \rightarrow$ cell-level score $S_{\{k,c\}}$	[Eq. 3, Eq. 8, Paper: PDF p. 3, 5]
Key loss	Foreground-Union Consensus Loss (FUCL)	[Sec 3.4, Eq. 7, Paper: PDF p. 4]
Supervision signal	Leave-one-method-out (LOMO) mean foreground consensus $C^{\{-k\}}$	[Eq. 5, Paper: PDF p. 3]
Evaluation dataset	Xenium FFPE human renal cell carcinoma (4,642 held-out tiles)	[Paper] [Paper: PDF p. 5]
Candidate methods	Cellpose-SAM, BIDCell, ProSeg, Xenium 10x onboard	[Paper] [Paper: PDF p. 5]
Primary metrics	Foreground-union L1 $\downarrow$, Dice $\uparrow$, IoU $\uparrow$, cell-level Spearman $\rho \uparrow$	[Table 1, Paper: PDF p. 4]

02 一句话总结

本文提出 MARC（Morphology-Aware Regression of Consensus），一个面向亚细胞空间转录组（SST）的轻量级质量评估框架，通过回归预测像素级多方法共识支持度，替代传统需运行全部分割流水线的显式共识构

建；其核心价值在于：在无专家标注、不依赖特定分割模型内部结构的前提下，仅用单个候选掩码 + 对齐的 DAPI 形态图 + 转录密度图，即可逼近 leave-one-method-out 显式共识，支撑大规模 SST 数据的鲁棒性质检与低共识细胞筛选；但该共识仅为方法间一致性代理，非生物学真值，且当前验证局限于单一组织类型与平台。

03 研究问题

SST 中细胞分割质量评估面临三重困境：① 缺乏可靠 ground truth（边界本身生物模糊，人工标注成本极高）[Paper] [Paper: PDF p. 1]；② 现有监督方法（如 SegQC）依赖专家修正掩码，不确定性方法（如 Bayesian）依赖生成模型内部输出，二者均无法泛化至外部候选掩码评估 [Paper] [Paper: PDF p. 3]；③ 显式多方法共识虽可作为实用代理，但需并行执行多个计算密集型 pipeline，难以扩展至全组织尺度 [Paper] [Paper: PDF p. 2]。因此，论文聚焦：**能否设计一个轻量、即插即用的模型，在推理时仅需单个候选掩码及基础模态输入，即可高保真地预测其在多方法共识中的像素/细胞级支持强度？** 这一问题直指 SST 分析链中“分割可信度量化”这一未被充分工程化的瓶颈环节。

04 研究背景与发展路径

SST 分析始于细胞分割，而分割质量直接决定下游细胞级转录分配的可靠性 [Paper] [Paper: PDF p. 1]。早期通用分割模型（U-Net、Mask R-CNN、HoVer-Net）未针对 SST 的形态-转录双信号耦合特性优化 [Paper] [Paper: PDF p. 2]；后续 SST 专用方法（BIDCell、ProSeg、Baysor）虽融合多模态，但彼此假设与输入差异导致结果冲突，尤其在致密组织或弱信号区 [Paper] [Paper: PDF p. 2-3]。质量评估随之分化为两条路径：一是基于专家标注的监督范式（不可扩展），二是基于模型自身不确定性的内部估计（绑定生成模型）[Paper] [Paper: PDF p. 3]。共识方法（如 STAPLE、多数投票）曾被用于整合多源分割，但其计算开销阻碍了日常质检 [Paper] [Paper: PDF p. 3]。MARC 的发展路径是：**将共识从“需执行的计算过程”重构为“可学习的映射函数”**——以 LOMO 共识为伪标签，训练一个 U-Net 变体直接从候选掩码+形态+转录中回归共识支持度，从而解耦评估与生成。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Lack of scalable ground truth	Manual annotation is prohibitively time-consuming for large SST datasets; boundaries are biologically ambiguous and cannot be reliably inferred from incomplete signals	SST boundaries are inherently ambiguous due to weak morphological contrast, sparse/displaced transcripts, and cell overlap [Paper] [Paper: PDF p. 1, 3]	“reliable ground-truth boundaries are unavailable because they must be inferred from incomplete morphological and transcript signals” [Paper] [Paper: PDF p. 1]; “cell boundaries may be biologically ambiguous” [Paper] [Paper: PDF p. 3]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Incompatibility of existing QC methods	Supervised QC requires expert masks; uncertainty-based QC requires access to the generating model’s internals — neither supports evaluation of externally produced candidate masks	Existing approaches were not developed specifically for SST and assume either expert annotations or internal model access [Paper] [Paper: PDF p. 3]	“these approaches do not readily support the evaluation of candidate masks produced by different SST segmentation pipelines when expert annotations are unavailable” [Paper] [Paper: PDF p. 2]; “SegQC relies on expert-corrected masks, whereas Bayesian uncertainty methods require access to the model that generated the segmentation” [Paper] [Paper: PDF p. 3]
Computational bottleneck of explicit consensus	Constructing cross-method consensus requires configuring and running all contributing pipelines with method-specific inputs, making it computationally intensive and difficult to scale	Explicit consensus averages outputs from multiple segmentation pipelines using method-specific SST inputs [Paper] [Paper: PDF p. 2]	“explicit consensus construction requires executing multiple computationally intensive pipelines” [Paper] [Paper: PDF p. 1]; “this process is computationally intensive and difficult to scale, limiting its use for routine quality control” [Paper] [Paper: PDF p. 2]

06 核心思想

论文的核心洞察是：多方法共识并非必须“执行”，而可被“建模”为一种可泛化的上下文感知映射关系。具体而言，作者观察到：共识支持强度并非仅由候选掩码几何形状决定，而是强烈依赖于其与局部 DAPI 核形态、转录分子密度的空间一致性 [Paper] [Paper: PDF p. 6]；同时，不同方法的错误模式具有互补性（形态驱动 vs 转录驱动），使得它们的交集/并集区域蕴含丰富质量信号 [Paper] [Paper: PDF p. 2]。因此，MARC 将共识预测建模为一个稠密回归任务：给定候选掩码 F_k 、DAPI 图 D 、转录图 T ，学习函数 f_{θ} 输出连续支持度图 $\hat{C}_k$ ，其目标是逼近 leave-one-method-out 共识 $C^{(-k)}$ 。该思想将 QC 从“后处理计算”升维为“前馈感知建模”，实现了评估效率与泛化能力的统一。

07 方法总览

MARC 是一个端到端的 U-Net 风格回归器，其方法流严格遵循“输入→特征融合→稠密回归→细胞聚合”四步：① **输入构造**：对每个候选方法 k ，拼接三通道张量 $X_k = \text{concat}(D, T, F_k)$ [Eq. 2, Paper: PDF p. 3]；② **特征编码-解码**：四层级 U-Net 提取多尺度形态-转录-掩码联合表征，最终输出单通道 logits Z_k ，经 sigmoid 得 $\hat{C}_k \in [0,1]^{H \times W}$ [Eq. 3–4, Paper: PDF p. 3]；③ **监督构建**：采用 leave-one-method-out 策略，对方法 k ，其伪标签为其余 $K-1=3$ 个方法前景图的算术平均 $C^{(-k)}$ [Eq. 5, Paper: PDF p. 3]；④ **损失与聚合**：使用 Foreground-Union Consensus Loss (FUCL) 聚焦于候选与共识前景的并集区域进行 L1 回归 [Eq. 6–7, Paper: PDF p. 4]，再按原始标签图 M_k 对 $\hat{C}_k$ 像素取均值得到细胞级分数 $S_{\{k,c\}}$ [Eq. 8, Paper: PDF p. 5]。整个流程在推理时完全摆脱多方法 ensemble，仅需单次前向传播。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Leave-one-method-out (LOMO) pseudo-target construction	Generates consensus pseudo-label $\hat{C}^{(-k)}$ by averaging binary foreground maps of all <i>other</i> $K-1$ methods	Avoids trivial self-agreement supervision; enables training without ground truth while preserving multi-method agreement semantics	Input: Set of $K=4$ binary foreground masks $\{F_j\}_{j=1}^4$; Output: $\hat{C}^{(-k)} \in [0,1]^{H \times W}$ [Eq. 5]	“Excluding the candidate method from its own target prevents the model from receiving trivial self-agreement as supervision” [Paper] [Paper: PDF p. 3]; Table 1 uses this exact target for evaluation	Removal would cause degenerate learning (e.g., model collapses to identity mapping on F_k); no ablation reported but logically necessary for problem framing
Foreground-Union Consensus Loss (FUCL)	Computes mean absolute error between $\hat{C}_k$ and $\hat{C}^{(-k)}$ only over pixels in union $U_k = F_k \cup \hat{C}^{(-k)}$	Focuses training signal on biologically meaningful regions (foreground) and disagreement zones where consensus is most informative; avoids dilution by background zeros	Input: $\hat{C}_k, \hat{C}^{(-k)}, U_k$; Output: scalar loss $\mathcal{L}^{(k)}_{\text{FU}}$ [Eq. 7]	“restricting the loss to U_k focuses learning on foreground and disagreement regions” [Paper] [Paper: PDF p. 4]; Figure 2 architecture diagram includes FUCL as core component	Without U_k masking, loss would be dominated by background pixels, degrading foreground precision; Table 2 shows sensitivity/precision trade-offs under different targets, implying foreground weighting matters

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal		
Morphology-transcript-mask tri-channel fusion	Concatenates aligned DAPI morphology D , transcript density T , and candidate foreground F_k into X_k in $\mathbb{R}^{3 \times H \times W}$	Provides complementary contextual cues beyond mask geometry; DAPI informs nuclear integrity, transcripts inform molecular content, jointly disambiguating weak boundaries	Input: D , T , F_k ; Output: X_k [Eq. 2]	Ablation in Table 2 shows adding DAPI boosts cell-level Spearman from 0.4228 to 0.7564, and adding transcripts further to 0.7905; Figure 4 qualitatively shows predictions align with morphology/transcript hotspots	Removing D or T degrades both pixel-level (Dice) and cell-level (ρ) metrics significantly (Table 2), confirming their non-redundant contribution		
Cell-level aggregation via label-map averaging	For each cell instance c in labelled mask M_k , computes $S_{k,c} = \frac{1}{ C_k } \sum_{(x,y) \in C_k} M_k(x,y)$	$M_k = c$	$\sum_{(x,y) \in C_k} M_k(x,y) = C_k S_{k,c}$	Converts dense pixel support into interpretable, rankable cell-level QC scores for manual review or filtering	Input: $\hat{C}_k$, M_k ; Output: scalar $S_{k,c}$ per cell [Eq. 8]	“These scores can be used to rank cells for manual review, filtering, or downstream quality-control analysis” [Paper] [Paper: PDF p. 5]; Figure 3 plots $S_{k,c}$ vs target, showing monotonic relationship	Without aggregation, output remains pixel-level and lacks direct utility for cell-centric downstream tasks (e.g., perturbation response analysis); baseline candidate-copy produces constant scores, proving aggregation is essential for ranking

09 关键公式与符号

论文未提供显式、独立的数学公式（如优化目标完整形式），但明确定义了以下关键符号与关系式：

- M_k : 候选方法 k 输出的带标签掩码（整数矩阵）， $M_k(x,y)=c$ 表示像素 (x,y) 属于细胞实例 c [Paper] [Paper: PDF p. 3];
- F_k : M_k 的二值前景图， $F_k(x,y) = \mathbb{I}(M_k(x,y)>0)$ [Eq. 1];
- D, T : 对齐的 DAPI 形态图像与转录密度图像（实值矩阵） [Paper] [Paper: PDF p. 3];
- $X_k = \text{concat}(D,T,F_k)$: 三通道输入张量 [Eq. 2];
- $\hat{C}_k = f_{\theta}(X_k) = \sigma(Z_k)$: MARC 输出的连续共识支持图，值域 $[0,1]$ [Eq. 3–4];
- $C^{(-k)} = \frac{1}{K-1} \sum_{j \neq k} F_j$: leave-one-method-out 共识伪标签（算术平均） [Eq. 5];
- $U_k = F_k \lor C^{(-k)}$: 前景并集掩码，用于 FUCL 区域约束 [Eq. 6];
- $S_{k,c} = \frac{1}{|\{(x,y): M_k(x,y)=c\}|} \sum_{(x,y): M_k(x,y)=c} \hat{C}_k(x,y)$: 细胞 c 的共识支持得分 [Eq. 8];
- Metrics: Foreground-union L1 (↓), Dice (↑), IoU (↑), Sensitivity (↑), Precision (↑), Cell-level Spearman ρ (↑) [Table 1, Paper: PDF p. 4]。

No closed-form objective function is provided; training uses AdamW optimizer with FUCL loss.

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Main evaluation (Table 1)	MARC predicts explicit LOMO consensus with high fidelity at pixel and cell levels	MARC trained on 4 candidate methods (Cellpose-SAM, BIDCell, ProSeg, Xenium), evaluated on 4,642 held-out test tiles against $C^{(-k)}$ targets	Avg. Dice=0.9002, IoU=0.8186, cell ρ =0.7905; best per-method Dice up to 0.9127 (Xenium)	MARC closely approximates explicit cross-method consensus without multi-method inference	MARC achieves <i>biological ground truth</i> accuracy — paper explicitly states consensus is a surrogate, not ground truth [Paper] [Paper: PDF p. 7]	[Table 1, Paper: PDF p. 4]; [Paper] [Paper: PDF p. 5]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Input ablation (Table 2)	Morphology and transcript signals provide complementary information beyond candidate-mask geometry	Compared: (i) candidate-copy baseline (no learning), (ii) MARC with F_k only, (iii) F_k+D , (iv) F_k+D+T ; all evaluated on same $C^{(-k)}$ targets	Adding D increased avg. Dice from 0.8565→0.8866 and ρ from 0.4228→0.7564; adding T further improved Dice to 0.9002 and ρ to 0.7905	DAPI morphology is the primary contextual cue for cell-level ranking; transcript density provides complementary molecular signal improving both pixel and cell metrics	Transcript density alone drives consensus prediction — ablation shows F_k+T not tested, so T 's standalone contribution is Not assessable from supplied material	[Table 2, Paper: PDF p. 6]; [Paper] [Paper: PDF p. 6]
Target ablation (Sec 4.3)	Mean-consensus and STAPLE consensus targets yield comparable but distinct trade-offs	Two MARC models trained identically except supervision: (i) arithmetic mean $C^{(-k)}$, (ii) STAPLE-fused $C^{(-k)}$; evaluated against respective targets	Mean target: higher sensitivity (0.9168) and cell ρ (0.7905); STAPLE target: higher precision (0.9128)	Mean consensus better preserves cell-level rankings and captures more true positives; STAPLE yields tighter foreground localization	STAPLE target is <i>more accurate</i> — paper notes models evaluated against different targets, so no cross-target accuracy comparison is valid	[Paper] [Paper: PDF p. 5]
Qualitative analysis (Figure 4)	MARC localises weakly supported regions and produces spatially varying predictions	Visual inspection of predicted $\hat{C}_k$ maps alongside D , T , F_k on held-out test region	High $\hat{C}_k$ in regions aligned with nuclear morphology and transcript density; low $\hat{C}_k$ where F_k extends into background or disagrees with D/T	MARC leverages multimodal context to identify ambiguous boundaries; output is spatially resolved and interpretable	MARC identifies <i>biologically erroneous</i> segmentations — paper attributes low scores to "method-specific detections with weak support", not biological error per se	[Figure 4, Paper: PDF p. 6]; [Paper] [Paper: PDF p. 7]

11 对结论的正确理解

论文结论应被精确理解为：**MARC 是一个高效的、共识代理（consensus proxy）学习器，而非真值逼近器（ground-truth approximator）**。其成功体现在两个层面：① **技术有效性**：在给定 LOMO 共识定义下，MARC 能以高精度（Dice≈0.90）和强排序保真度（ $\rho\approx0.79$ ）再生显式共识，且推理开销极低（单次前向）；

② **实用价值**：生成的像素/细胞级支持图可直接用于定位低共识区域、排序细胞以供人工复核、或作为下游分析的置信加权因子。但必须强调：所有结论均锚定于“共识即代理”的前提；论文从未声称 MARC 输出反映生物学真实边界，也未证明其能泛化至未见组织/平台/方法组合。Figure 3 和 Table 1 的相关性/重叠指标，衡量的是与 *LOMO* 共识的一致性，而非与未知真值的一致性。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Consensus as surrogate, not ground truth	Failure modes common across segmentation methods may be reinforced in consensus, leading to systematic bias	Acknowledge usefulness despite limitation; suggest orthogonal validation with membrane/protein markers	[Paper] [Paper: PDF p. 7]
Limited generalisability	Evaluated only on single Xenium renal cell carcinoma dataset; candidate methods share inputs from same assay, reducing independence	Evaluate on additional tissues, platforms, and segmentation methods; incorporate orthogonal markers (e.g., membrane) for validation	[Paper] [Paper: PDF p. 7]
Platform/method dependence	Candidate methods (Cellpose-SAM, BIDCell, etc.) are all trained on or applied to Xenium data, potentially sharing assay-specific biases	Future work will evaluate additional platforms and segmentation methods beyond Xenium ecosystem	[Paper] [Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
MARC’s high cell-level Spearman ($\rho=0.79$) may partly reflect input leakage: since $\$F_k\$$ is directly concatenated, the model could learn to upscale $\$F_k\$’s$ shape rather than infer consensus from $\$D/T\$$ context	The observed gain from adding $\$D\$$ and $\$T\$$ (Table 2) might stem from morphology/transcript-guided <i>refinement</i> of $\$F_k\$$ geometry, not genuine consensus <i>inference</i> from multimodal disagreement patterns	If true, MARC’s “consensus awareness” is superficial — it wouldn’t generalize to candidate masks with fundamentally wrong topology (e.g., severe over/under-segmentation), undermining its QC utility	Train MARC variants with $\$F_k\$$ replaced by <i>distance-transformed</i> or <i>skeletonized</i> versions of $\$F_k\$$; if performance drops sharply, original $\$F_k\$$ geometry is critical; if stable, true multimodal reasoning is occurring	[Eq. 2] uses raw $\$F_k\$$; Table 2 shows $\$F_k\$$ -only baseline achieves Dice=0.8565, suggesting strong baseline from geometry alone

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
FUCL’ s focus on foreground union $\hat{U}_k$ may under-penalize errors in <i>consensus-only</i> regions (where $C^{(-k)} > 0$ but $F_k = 0$), as these pixels are included in $\hat{U}_k$ but contribute less to Dice/IoU after thresholding	Low Dice/Precision in Table 1 for some methods (e.g., ProSeg Precision=0.8626) could indicate FUCL insufficiently constrains false negatives in $C^{(-k)}$ -only areas, allowing $\hat{C}_k$ to ignore them	This would compromise MARC’ s ability to flag candidate masks that <i>miss</i> cells strongly supported by other methods — a critical QC failure mode	Compute per-pixel confusion matrix on $\hat{U}_k$; specifically analyze false negative rate in $C^{(-k)} = 1$ & $F_k = 0$ regions; compare with standard BCE loss on same region	[Eq. 6] defines $\hat{U}_k$ inclusively; [Paper] [Paper: PDF p. 4] states FUCL “focuses learning on foreground and disagreement regions” , but disagreement includes $C^{(-k)}$ -only areas
The choice of arithmetic mean for $C^{(-k)}$ assumes equal reliability of all $K-1$ methods, but methods like BIDCell (self-supervised) and Xenium (onboard) likely have different error profiles	Table 1 shows BIDCell has lowest cell ρ (0.6251) and highest L1 (0.1060), suggesting mean consensus may misrepresent its reliability; STAPLE ablation showed different trade-offs but wasn’ t adopted	Using unweighted mean could bias MARC’ s learning toward majority-vote artifacts rather than robust agreement, limiting transfer to methods with heterogeneous performance	Retrain MARC with STAPLE-derived $C^{(-k)}$ as primary target and evaluate on <i>same</i> mean-consensus test set; if performance improves, weighted consensus is superior	[Paper] [Paper: PDF p. 5] reports STAPLE achieved lower ρ (0.7491 vs 0.7905) but higher precision, yet retains mean due to interpretability (“fraction of supporting methods”)

14 学到的知识

- **共识可学习性**：多方法共识支持度不是必须计算的产物，而是可被 U-Net 类模型从候选掩码+形态+转录三元组中直接回归的稠密场，FUCL 损失设计是实现此学习的关键；
- **模态贡献分层**：在 SST QC 中，候选掩码几何提供基础结构，DAPI 形态是提升细胞级排序能力的主因 ($\rho + 0.33$)，转录密度起精细校准作用 ($\rho + 0.03$)，印证了“形态主导、分子微调”的双信号协同范式；
- **轻量 QC 的可行性**：无需访问分割模型内部状态或专家标注，仅需对齐的三模态输入，即可实现接近显式 ensemble 的共识保真度 (Dice 0.90)，为大规模 SST 数据质控提供了新工程路径；
- **代理目标的务实价值**：当 ground truth 不可得时，精心设计的代理目标（如 LOMO 共识）结合恰当的损失（FUCL），仍能产出高度实用的中间表示 ($\hat{C}_k$)，支撑下游决策（如低共识细胞筛选）；
- **评估指标的语境敏感性**：同一模型在 Dice/IoU（阈值化）与 Spearman ρ （连续值）上表现不同，提示在 QC 任务中需同时关注像素重叠精度与细胞级排序保真度，二者不可相互替代。

15 与既有知识的连接

- **候选连接/方法论连接**：MARC 的“共识代理学习”思路与 multi-omics 整合中的 latent consensus modeling（如 MOFA+ 的 shared factor learning）存在方法论共鸣，均试图从多源不一致观测中推断稳健潜变量；
- **候选连接/方法论连接**：其三模态输入 (F_k, D, T) 与 spatial transcriptomics 中 cell state representation 的多尺度建模（核形态+膜蛋白+转录）逻辑一致，暗示 $\hat{C}_k$ 可作为细胞状态置信度的代理嵌入；

- **候选连接/方法论连接:** U-Net 架构与 graph neural networks 的结合点在于: Figure 1(a) 的显式 consensus 可视为在方法图 (methods as nodes, agreement as edges) 上的消息传递, 而 MARC 将此图计算压缩为单跳节点特征融合, 为 GNN-based consensus modeling 提供简化基线;
- **弱连接/方法论连接:** 虽不直接支持 perturbation prediction 或 cross-modal alignment, 但其生成的 $\hat{C}_k$ 场可作为 perturbation 响应分析的协变量 (例如, 比较扰动前后 consensus 支持度变化), 或作为 multi-omics alignment 的置信加权因子 (例如, 在转录-蛋白共配准中降权低 $\hat{C}_k$ 区域)。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name:** MARC-Align: Consensus-Guided Cross-Modal Alignment

originating limitation/observation: MARC currently operates on aligned D and T , but real-world SST often suffers from modality misalignment; authors note future work should incorporate orthogonal markers [Paper] [Paper: PDF p. 7], yet alignment uncertainty is unmodeled. **core hypothesis:** Consensus support $\hat{C}_k$ is sensitive to spatial misregistration; optimizing alignment to maximize $\hat{C}_k$ over a candidate cell should yield biologically more plausible registration than intensity-based metrics.

delta from paper: Extends MARC from QC to active alignment tool; replaces fixed alignment with differentiable spatial transformer conditioned on $\hat{C}_k$. **initial method:** For a candidate cell c , define alignment loss $L_{\text{align}} = -\frac{1}{|c|} \sum_{(x,y) \in c} \hat{C}_k(x,y)$; optimize transformer parameters via gradient ascent on L_{align} . **validation:** Compare alignment accuracy (vs. ground-truth landmarks) of MARC-Align vs. elastix/ANTs on simulated misaligned Xenium tiles; measure downstream cell-type annotation consistency. **failure modes:** May overfit to consensus artifacts if $C^{(-k)}$ contains systematic biases; requires careful initialization to avoid local maxima in $\hat{C}_k$ landscape. **innovation status:** unverified

- **name:** Perturb-MARC: Consensus-Aware Perturbation Response Modeling

originating limitation/observation: Paper states risk “Not explicit support for perturbation” [Selection reason]; current MARC treats each tile independently, ignoring temporal or treatment-condition context crucial for perturbation studies. **core hypothesis:** Perturbation-induced boundary instability manifests as reduced consensus support $\hat{C}_k$ in affected cells; aggregating $\hat{C}_k$ changes across conditions reveals spatially resolved perturbation sensitivity. **delta from paper:** Adds condition-aware encoding (e.g., treatment vector) to MARC input and trains on paired pre/post-perturbation tiles to predict *change in consensus support* $\Delta \hat{C}_k$ instead of absolute $\hat{C}_k$. **initial method:** Extend X_k to $X_k^{\text{cond}} = \text{concat}(D, T, F_k, \text{treatment_emb})$; train to regress $\Delta C^{(-k)} = C^{(-k)}_{\text{post}} - C^{(-k)}_{\text{pre}}$ using FUCL variant on difference map. **validation:** Apply to published perturbation SST datasets (e.g., drug-treated organoids); correlate $\Delta \hat{C}_k$ hotspots with known pathway activity (e.g., phospho-proteomics) and differential expression. **failure modes:** Requires paired consensus targets, which are expensive to generate; may conflate technical perturbation (e.g., fixation artifact) with biological effect. **innovation status:** unverified

- **name:** Graph-MARC: Consensus Propagation over Cell Graphs

originating limitation/observation: MARC scores cells independently, but cell boundaries are topologically coupled; low-consensus cells often cluster spatially [Figure 4], suggesting graph-based smoothing could improve robustness. **core hypothesis:** Consensus support is not isolated but propagates through cell adjacency graphs; incorporating neighbor-aware aggregation $(S_{k,c}^{\text{graph}} = \alpha S_{k,c} + (1-\alpha) \frac{1}{|\mathcal{N}(c)|} \sum_{c' \in \mathcal{N}(c)} S_{k,c'})$ enhances detection of locally ambiguous regions. **delta from paper:** Replaces simple mean aggregation [Eq. 8] with graph convolutional layer on Delaunay triangulation of cell centroids, using $\hat{C}_k$ as node features. **initial method:** Build cell graph $\mathcal{G}$ from M_k ; apply one-layer GCN to $\hat{C}_k$ pixels pooled per cell; recompute $S_{k,c}^{\text{graph}}$ as smoothed node values. **validation:** Compare precision/recall of low-consensus cell detection (using manual review as gold) between vanilla MARC and Graph-MARC on Figure 4-like examples; measure spatial clustering of detected low- $\hat{C}_k$ cells. **failure modes:** Graph construction depends on M_k quality — if M_k has severe over-segmentation, $\mathcal{G}$ becomes noisy; adds computational overhead. **innovation status:** unverified