

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

- Title: STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images
- arXiv ID: arXiv:2609.05956v1
- Publication date: 2026-09-05
- Authors: Youngmin Chung, Ji Hun Ha, Andrew H. Song, Cristina Almagro-Pérez, Chaeyoung Seo, Won Jun Suh, Jeong Won Beom, Kyoung Bin Oh, Eytan Ruppin, Faisal Mahmood, Joo Sang Lee
- Core contribution: STP-BENCH - a large-scale, standardized, multi-platform benchmark for virtual spatial transcriptomics (ST) models, comprising STP-BENCH-INTERNAL (609,024 spots across 6 cancer types, 202 slides) and STP-BENCH-EXTERNAL (185,831 spots across same 6 cancer types, 73 slides) [Paper: PDF p. 4-5; Figure 1b].
- Code & data: Publicly released at <https://github.com/NEXGEM/STP-Bench> and Hugging Face (<https://huggingface.co/datasets/nexgem/STP-Bench>); MGB-PRAD dataset not publicly available due to privacy restrictions [Paper: PDF p. 37].
- Evaluation scope: 21 re-implemented virtual ST models spanning regression-based (n=14), bi-modal retrieval-based (n=4), and generative-based (n=3) families [Paper: PDF p. 6; Figure 1c].
- Key metrics: Pearson Correlation Coefficient (PCC) [Equation 1, Paper: PDF p. 31], Mean Absolute Error (MAE) [Equation 2, Paper: PDF p. 32], Structural Similarity Index Measure (SSIM) [Paper: PDF p. 7].

02 一句话总结

STP-BENCH is a rigorously controlled, large-scale benchmark that reveals-under unified pathology foundation model (PFM) encoding-the dominance of image representation over architectural complexity in virtual ST prediction, identifies a universal gene-level predictability ceiling tied to morphology-expression coupling, and demonstrates platform-dependent biological utility limits, especially for low-expression marker genes and downstream tasks like cell-type deconvolution [Paper: PDF p. 2, 18-20].

03 研究问题

- How do virtual ST models compare fairly when disentangled from heterogeneous image encoders? [Paper: PDF p. 3-4]
- Which genes and gene sets are reliably recoverable from histomorphology-and why? [Paper: PDF p. 11-13]
- Do predicted expression profiles preserve biologically meaningful structure at coarser granularities (cell type abundance, spatial domains)? [Paper: PDF p. 14-15; Figure 4]
- How robust are models to real-world domain shifts (cross-institution,

cross-tissue, cross-platform)? [Paper: PDF p. 17; Figure 5a-b]

- Does scaling training data (intra-cohort or inter-cohort) improve generalization-or induce negative transfer? [Paper: PDF p. 18; Figure 5c-d]

04 研究背景与发展路径

Virtual ST emerged to address the high cost and technical barriers of experimental spatial transcriptomics (ST), enabling prediction of spatial gene expression directly from H&E-stained histology images [Paper: PDF p. 2-3]. Three modeling paradigms dominate: (1) Regression-based (e.g., ST-Net [25], TRIPLEX [26], DeepSpot [27]), treating prediction as multi-output regression; (2) Bi-modal alignment/retrieval-based, adapting CLIP-style contrastive learning to align image and expression embeddings (e.g., BLEEP [32], STco [33], mclSTExp [34]); and (3) Generative-based, modeling expression as conditional distributions via diffusion (STFlow [40]) or flow matching (Stem [39]) [Paper: PDF p. 3-6]. Critically, performance has been confounded by inconsistent use of image encoders-ranging from ImageNet-pretrained ResNet50 to pathology foundation models (PFMs) like UNIV2 [45]-leading to unfair comparisons where encoder gains masquerade as architectural innovation [Paper: PDF p. 3-4]. Prior benchmarks (e.g., Wang et al. [50], HEST-1K [51]) either retained native encoders (conflating architecture and encoder) or evaluated only PFM embeddings with simple regressors-leaving the full landscape of virtual ST architectures unexamined under controlled conditions [Paper: PDF p. 3-4].

05 论文识别的核心痛点

Pain point / Manifestation / Cause or author explanation / Evidence from the paper

Pain point: Unfair architectural comparison

Manifestation: Model rankings vary drastically when native vs. unified PFM encoders are used (e.g., CFANet jumps from 16th to 6th) [Paper: PDF p. 9]

Cause or author explanation: Prior studies inherit each model's original image encoder, entangling architectural innovation with encoder-specific feature extraction capabilities; encoders differ in pretraining scale, domain, and paradigm [Paper: PDF p. 3-4]

Evidence from the paper: Figure 2b shows rank reversal between "Native" and "Unified" (UNIV2) encoders; CFANet's jump explicitly noted [Paper: PDF p. 9; Figure 2b]; authors state "evaluations in previous works... are likely unfair comparisons" [Paper: PDF p. 9]

Pain point: Shallow biological evaluation

Manifestation: Aggregate PCC masks which genes/gene sets are recoverable and whether predictions support downstream analyses (e.g., cell-type deconvolution) [Paper: PDF p. 4, 14]

Cause or author explanation: Prior work focuses narrowly on average predictive accuracy on highly variable genes, neglecting per-gene reliability, functional coherence, and utility for biological inference [Paper: PDF p. 2-4]

Evidence from the paper: Figure 3a shows gene-wise PCC heatmap revealing consistent predictability patterns across models; Figure 4 evaluates Cell2location and SpaGCN outputs, showing performance gaps mirror gene-level PCC gaps [Paper: PDF p. 12, 15]

Pain point: Poor robustness characterization

Manifestation: Models show large, scenario-dependent generalization gaps (e.g., -0.35 in cross-tissue vs. -0.10 in cross-institution) [Paper: PDF p. 17]

Cause or author explanation: Real-world deployment requires understanding failure modes under domain shifts (institutional batch effects, tissue heterogeneity, platform differences), yet prior benchmarks lack systematic robustness analysis [Paper: PDF p. 4]

Evidence from the paper: Figure 5b quantifies generalization gaps across three scenarios; cross-tissue gap is "sharper" and "far greater obstacles than technical variability" [Paper: PDF p. 17]

Pain point: Unclear data scaling behavior
Manifestation: Inter-cohort scaling (adding new cancer types) often causes negative transfer, decreasing target-tissue performance [Paper: PDF p. 19]
Cause or author explanation: Morphology-to-expression mappings are highly tissue-specific; naive aggregation of heterogeneous sources may dilute tissue-informative signals rather than enrich them [Paper: PDF p. 19]
Evidence from the paper: Figure 5d shows performance drop when adding LUAD and PRAD to BRCA training; authors conclude “simple aggregation… could be detrimental” [Paper: PDF p. 19; Figure 5d]

06 核心思想

The core idea is that virtual ST evaluation must be decoupled into orthogonal axes: (1) encoder quality (dominant factor, driven by PFM scale/domain), (2) architectural capacity (secondary, matters most for multi-scale reasoning on stromal/immune genes), and (3) biological fidelity (measured not just by PCC but by gene-set recovery, cell-type deconvolution, and spatial domain identification). STP-BENCH operationalizes this by standardizing the PFM encoder (UNiv2) across architecturally compatible models, then systematically probing where architectural innovations actually add value: specifically, for genes whose expression depends on meso- to macro-scale tissue organization (e.g., collagens, immune checkpoints), and for downstream tasks requiring spatial coherence [Paper: PDF p. 2, 9, 13, 19].

07 方法总览

STP-BENCH implements a three-tiered evaluation framework:

1. Comprehensive performance evaluation: Benchmarking 21 models on STP-BENCH-INTERNAL using PCC, MAE, and SSIM across two gene sets-200 high-mean highly-variable genes (HMHVGs) and 16 tumor microenvironment (TME) marker genes-with k-fold cross-validation (patient-level for non-HEST datasets) [Paper: PDF p. 7, 30-31].
2. Multi-granularity biological analysis: Gene-wise PCC heatmaps (Figure 3a), gene-set scoring via singscore [84] (Figure 3c-e), cell-type deconvolution with Cell2location [53] (Figure 4a), and spatial domain identification with SpaGCN [58] (Figure 4b-c).
3. Robustness & scalability assessment: Cross-institution/cross-tissue/cross-platform generalization on STP-BENCH-EXTERNAL (Figure 5a-b); intra-cohort (subset sampling) and inter-cohort (multi-cancer merging) scaling experiments (Figure 5c-d) [Paper: PDF p. 7, 14-18].

All models use UNiv2 as default patch encoder unless architecturally incompatible (e.g., M2OST, M2ORT, HistoSPACE, ST-Net), in which case native encoders are retained [Paper: PDF p. 9, 22-23].

08 核心模块拆解

Module / Function / Why needed / Input and output / Supporting evidence / Known or expected effect of removal

Module: UNiv2 PFM encoder
Function: Extracts 1024-dim histology embeddings from 224x224 H&E patches
Why needed: To isolate architectural contributions by standardizing morphological representation across models; UNiv2 outperforms ResNet50, CTransPath, etc. [Paper: PDF p. 10]
Input and output: Input: 224x224 H&E patch -> Output: 1024-dim vector

Supporting evidence: Figure 2e shows UNlv2, Virchow2, H-Optimus1 achieve highest PCC; ResNet50 yields lowest [Paper: PDF p. 10; Figure 2e]; authors state “unified morphological encoding substantially re-orders model rankings” [Paper: PDF p. 2]

Known or expected effect of removal: Removal would revert to unfair comparisons: e.g., CFANet drops from 6th to 16th [Paper: PDF p. 9; Figure 2b]; linear probing baseline becomes non-comparable

Module: Multi-scale context integration (TRIPLEX/DeepSpot)

Function: Fuses local (target spot), neighborhood (surrounding spots), and global (whole-slide) morphological features

Why needed: To capture long-range dependencies (e.g., fibrosis gradients, immune fronts) that isolated patches cannot encode [Paper: PDF p. 13, 19]

Input and output: Input: Target patch embedding + neighbor patch embeddings + slide-level embedding -> Output: fused representation for regression

Supporting evidence: Figure 3b shows TRIPLEX/DeepSpot achieve largest Δ PCC for stromal/immune genes; Figure 4a-c shows top performance in Cell2location/SpaGCN [Paper: PDF p. 11-15]

Known or expected effect of removal: Removal (e.g., using only local branch) would degrade prediction of COL1A1, LAG3, etc. [Paper: PDF p. 13]; likely reduce ARI in Figure 4c and Cell2location PCC in Figure 4a

Module: Gene set scoring (singscore)

Function: Computes per-spot gene set activity by ranking genes within-spot and averaging ranks of set members

Why needed: To assess if virtual ST preserves functional programs beyond individual genes, enabling pathway-level inference

Input and output: Input: Spot-by-gene matrix -> Output: Spot-by-gene set matrix

Supporting evidence: Figure 3c-e shows TRIPLEX/DeepSpot top-performing on T Cell Activation, Cell-Matrix Adhesion pathways; Spearman $\rho=0.902$ between gene- and gene-set PCC [Paper: PDF p. 13]

Known or expected effect of removal: Removal would leave evaluation at gene level only, missing functional coherence; unable to validate if immune programs are recovered as units (not just CD3E/CD8A individually)

Module: Cross-platform pseudo-spot binning (Xenium->Visium)

Function: Aggregates Xenium single-molecule transcripts into 100 μ m $\times$ 100 μ m bins aligned to Visium spacing

Why needed: To enable unified benchmarking across Visium (spot-based) and Xenium (single-molecule) platforms [Paper: PDF p. 6, 22]

Input and output: Input: Xenium transcript coordinates + registered H&E -> Output: pseudo-spot expression matrix + 224 $\times$ 224 patches

Supporting evidence: Figure 1b shows Xenium included in both INTERNAL/EXTERNAL; Online Methods details binning to match Visium geometry [Paper: PDF p. 6, 22]

Known or expected effect of removal: Removal would exclude Xenium data, halving platform diversity; invalidate cross-platform generalization tests in Figure 5a-b (right panel)

Module: Cell2location/SpaGCN downstream evaluation

Function: Applies established biological tools to virtual ST outputs to quantify preservation of cell composition and spatial domains

Why needed: To test if virtual ST is biologically usable, not just statistically correlated; ground-truth annotations serve as upper bound [Paper: PDF p. 14-15]

Input and output: Input: Predicted spot-by-gene matrix -> Output: Cell-type abundance estimates (Cell2location) or spatial domain labels (SpaGCN)

Supporting evidence: Figure 4a shows TRIPLEX/DeepSpot achieve highest PCC with ground-truth abundances; Figure 4c shows highest ARI for spatial domains [Paper: PDF p. 15]

Known or expected effect of removal: Removal would reduce evaluation to synthetic metrics only; unable to claim “biological utility” as stated in abstract [Paper: PDF p. 2]

09 关键公式与符号

- Equation 1 (PCC):

\[

$$\text{PCC}_{g,s} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$$

\]

where $\hat{y}_{i,g}$ and $y_{i,g}$ are predicted and ground-truth log-normalized expression of gene g at spot i in section s , and $\bar{\hat{y}}_g$, $\bar{y}_g$ are their means [Paper: PDF p. 31; Equation 1]. Used for gene-wise, section-wise, and dataset-wise aggregation. NaNs from zero-variance genes set to 0 [Paper: PDF p. 31].

- Equation 2 (MAE):

\[

$$\text{MAE}_{g,s} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$$

\]

computed per gene g in section s on $\log(1+x)$ -transformed counts; aggregated identically to PCC [Paper: PDF p. 32; Equation 2].

- SSIM: Computed per gene per section after projecting expression onto 2D spatial grid (rescaled via spot-center distance), min-max normalization to $[0,1]$, then `skimage.metrics.structural_similarity` with `data_range=1.0` [Paper: PDF p. 32]. Captures spatial coherence beyond spot-level correlation.

10 实验设计与证据链

Experiment / Claim tested / Comparison and conditions / Result / Supported conclusion / Unsupported stronger conclusion / Source

Experiment: Figure 2a (INTERNAL HMMVG/Marker)

Claim tested: Unified PFM encoding reveals true architectural ranking

Comparison and conditions: 21 models trained on STP-BENCH-INTERNAL with UNiv2 (w/ PFM) vs. native encoders (w/o PFM); evaluated on 7 datasets

Result: Most models fail to beat linear probing baseline (UNiv2+linear); TRIPLEX/DeepSpot top performers; HMMVG PCC约0.4, Marker PCC约0.2

Supported conclusion: PFM choice dominates architecture; marker genes are harder to predict due to data sparsity, not inherent uncoupling

Unsupported stronger conclusion: That any model architecturally outperforms linear probing in principle-only TRIPLEX/DeepSpot do so empirically here

Source: [Paper: PDF p. 9; Figure 2a]

Experiment: Figure 2c-d (Dataset-level stratification)

Claim tested: Data sparsity-not morphology-is primary limiter for marker genes

Comparison and conditions: NCCHE-LUAD-Xenium (high counts: HMMVG=52.1, Marker=72.3) vs. NCCHE-LUAD-Visium (low counts: HMMVG=9.2, Marker=0.9)

Result: Xenium: HMMVG PCC=0.586, Marker PCC=0.579; Visium: HMMVG PCC=0.191, Marker PCC=0.191

Supported conclusion: Low transcript counts drive poor marker prediction; high-count platforms enable strong prediction across gene categories

Unsupported stronger conclusion: That all marker genes are inherently less predictable from morphology-Xenium contradicts this

Source: [Paper: PDF p. 10; Figure 2c-d]

Experiment: Figure 3a (Gene-wise heatmap)

Claim tested: Gene predictability is universal across models

Comparison and conditions: 20 models (excluding zero-shot OmiCLIP/STPath) on STP-BENCH-INTERNAL; PCC per gene

Result: Smooth separation: genes easy/hard for one model are easy/hard for all; curved boundary shows architecture shifts predictability threshold
Supported conclusion: Morphology-expression coupling defines a universal ceiling; architecture fine-tunes which genes cross it
Unsupported stronger conclusion: That gene predictability is solely encoder-dependent-boundary curvature implies architectural role
Source: [Paper: PDF p. 11; Figure 3a]

Experiment: Figure 4a (Cell2location)
Claim tested: Virtual ST preserves cell-type spatial abundance structure
Comparison and conditions: Cell2location applied to ground-truth vs. predicted matrices (6 models) on 3 cohorts; PCC per cell type
Result: TRIPLEX/DeepSpot highest mean PCC; malignant epithelial/T cells well-recovered; plasma/mast cells poorly recovered
Supported conclusion: Multi-scale models best preserve coarse biological structure; rare populations remain challenging
Unsupported stronger conclusion: That virtual ST enables quantitative cell typing-PCC <0.5 for many types, and rare cells show low correlation
Source: [Paper: PDF p. 14-15; Figure 4a]

Experiment: Figure 5a (Cross-tissue generalization)
Claim tested: Internal rankings predict external performance under biological shift
Comparison and conditions: Models trained on STP-BENCH-INTERNAL, tested on STP-BENCH-EXTERNAL cross-tissue pairs; Spearman ρ of internal vs. external PCC
Result: $\rho=0.876$ ($p=1.873e-6$); strong rank preservation but large absolute gap (-0.20 to -0.35)
Supported conclusion: Architectural superiority generalizes across tissues; however, biological heterogeneity imposes hard limits
Unsupported stronger conclusion: That cross-tissue transfer is feasible-gaps are severe, suggesting tissue-specific fine-tuning needed
Source: [Paper: PDF p. 17; Figure 5a-b]

11 对结论的正确理解

- STP-BENCH does not claim that virtual ST is “ready for clinical use”; it shows that even top models (TRIPLEX/DeepSpot) achieve only ~0.6 PCC on high-count Xenium data for marker genes, and much lower on Visium [Paper: PDF p. 10; Figure 2c-d].
- The finding that “most models fail to beat linear probing” applies only under unified PFM encoding; it does not invalidate models’ original designs, but reveals that prior reported gains were often encoder-driven [Paper: PDF p. 9, 18].
- “Universal gene predictability” means genes are consistently ranked across models-not that all genes are equally predictable. The boundary between predictable/unpredictable genes shifts with architecture (e.g., TRIPLEX pushes more stromal genes above PCC=0.4) [Paper: PDF p. 11, 13; Figure 3a-b].
- Cross-platform “negligible loss” (Figure 5b right) refers to rank preservation ($\rho=0.620$), not absolute performance; some models gain, some lose, with no consistent trend [Paper: PDF p. 17].
- Negative transfer in inter-cohort scaling (Figure 5d) is observed for the target tissue (BRCA); it does not imply training on multiple cancers is always harmful-just that naive aggregation without tissue-aware adaptation fails [Paper: PDF p. 19].

12 作者明确承认的限制

Limitation / Specific manifestation / Future direction proposed by authors / Source

Limitation: Limited cancer/tissue scope

Specific manifestation: STP-BENCH covers only 6 cancer types and 2 ST platforms (Visium/Xenium)

Future direction proposed by authors: Extend benchmark to additional tumor types, tissue contexts, and emerging sequencing platforms

Source: [Paper: PDF p. 20]

Limitation: Restricted gene panel

Specific manifestation: Analyses focus only on HMMVGs (200 genes) and 16 TME markers; low-expression/functionally diverse genes not systematically studied

Future direction proposed by authors: Systematic investigation of lowly expressed or functionally diverse genes

Source: [Paper: PDF p. 20]

Limitation: Spot-level resolution

Specific manifestation: Evaluation performed at spot-level (aggregating multiple cells), not single-cell ST

Future direction proposed by authors: Extend benchmarking principles to single-cell resolution as datasets/models mature

Source: [Paper: PDF p. 20]

13 批判性分析

[Analysis] Observation / Potential issue or alternative explanation / Why it matters / How to test it / Basis

[Analysis] Observation: PCC as sole primary metric

Potential issue or alternative explanation: PCC measures linear correlation but ignores distributional fidelity (e.g., zero-inflation, overdispersion common in ST); MAE/SSIM are secondary

Why it matters: Over-reliance on PCC may mask failures in predicting sparse, biologically critical genes (e.g., cytokines) even if high-mean genes correlate well

How to test it: Replace PCC with zero-inflated negative binomial (ZINB) likelihood or Earth Mover's Distance on expression histograms; compare rank orders

Basis: Authors note STFlow uses ZINB prior [Paper: PDF p. 29], yet all models are ranked by PCC; no metric captures sparsity structure

[Analysis] Observation: Linear probing baseline uses UNlv2 only

Potential issue or alternative explanation: Baseline is UNlv2 + linear layer; but other PFMs (Virchow2, H-Optimus1) also achieve high PCC (Figure 2e) - is linear probing with those also competitive?

Why it matters: If linear probing with Virchow2 matches TRIPLEX+UNlv2, then encoder choice remains dominant over architecture, undermining the "multi-scale advantage" narrative

How to test it: Re-run Figure 2a with linear probing baselines for all 5 encoders (Figure 2e), not just UNlv2

Basis: Figure 2e shows Virchow2/H-Optimus1 约 UNlv2 in PCC; authors don't report their linear probing performance [Paper: PDF p. 10; Figure 2e]

[Analysis] Observation: Downstream task evaluation uses same gene panel

Potential issue or alternative explanation: Cell2location/SpaGCN use only HMMVGs + marker genes (<=216 genes), not full transcriptome

Why it matters: May underestimate utility: full-gene deconvolution could recover rare populations better; limited gene set constrains domain detection resolution

How to test it: Run Cell2location/SpaGCN on full gene sets where available (e.g., Xenium); compare ARI/PCC trends

Basis: Online Methods states "Gene sets were restricted to HMMVGs and marker genes" [Paper: PDF p. 35-36]

[Analysis] Observation: Cross-platform "Visium->Xenium" asymmetry

Potential issue or alternative explanation: Generalization tested only as Visium-trained -> Xenium-test; not vice versa

Why it matters: Directionality matters: Xenium's higher sensitivity may artificially inflate

Visium->Xenium performance, masking true platform gap

How to test it: Add Xenium-trained -> Visium-test experiments; compare bidirectional gaps

Basis: Authors state “cross-platform transfer (Visium->Xenium)” explicitly [Paper: PDF p. 17];

no mention of reverse direction

14 学到的知识

- Encoder supremacy: In virtual ST, the pathology foundation model (PFM) is the dominant performance driver; architectural innovations yield marginal gains unless they enable multi-scale context integration [Paper: PDF p. 9, 10, 18].
- Gene predictability ceiling: A universal hierarchy exists-genes like COL1A1, LAG3, SFTPC are consistently harder/easier across models-indicating morphology-expression coupling is intrinsic, not model-dependent [Paper: PDF p. 11, 13; Figure 3a].
- Platform dictates biological utility: Xenium’s higher transcript counts enable strong prediction of marker genes (PCC约0.58) and downstream tasks; Visium’s sparsity cripples marker prediction (PCC约0.19), limiting clinical applicability [Paper: PDF p. 10, 14, 19; Figure 2c-d, 4].
- Negative transfer is real: Adding new cancer types to training data harms performance on the target tissue, proving tissue-specific morphology-expression mappings resist naive multi-task learning [Paper: PDF p. 19; Figure 5d].
- Robustness is scenario-specific: Models generalize well across institutions ($\rho > 0.86$) but poorly across tissues ($\rho = 0.62$, large gaps), demanding tissue-aware adaptation strategies [Paper: PDF p. 17; Figure 5a-b].

15 与既有知识的连接

- Single-cell foundation models: STP-BENCH’s finding that encoder quality dominates architecture parallels lessons from scFoundation and scGPT-where pretraining scale and domain matter more than decoder design for single-cell representation [weak connection/parallel methodology].
- Spatial transcriptomics: Validates known platform limitations-Xenium’s superior sensitivity [104] directly explains its higher PCC, connecting technical specs to predictive ceilings [strong connection].
- Graph neural networks: SEPAL and EGGN use GNNs for spatial refinement, but STP-BENCH shows their gains are modest vs. TRIPLEX/DeepSpot-suggesting explicit multi-scale convolution may outperform implicit graph-based aggregation for ST [weak connection/methodology].
- Multi-omics: Bi-modal models (BLEEP, STco) align image-expression spaces, but STP-BENCH reveals their performance lags regression models-implicating joint embedding may be less efficient than direct regression for this modality pair [weak connection/methodology].
- Biomedical AI: The universal gene predictability ceiling mirrors findings in protein structure prediction (e.g., AlphaFold2’s accuracy plateau per residue type), suggesting inherent biological constraints limit AI performance [methodological connection].
- Perturbation prediction / cell state representation: Not addressed-STP-BENCH predicts steady-state spatial expression, not dynamic responses or latent cell states [no connection].
- Cross-modal alignment: STP-BENCH’s failure of bi-modal models (BLEEP, STco) to outperform regression challenges assumptions that contrastive alignment is optimal for histology-transcriptomics; suggests task-specific regression may be more

16 研究想法

- name: Tissue-Aware Encoder Adapter (TAEA)

originating limitation/observation: Inter-cohort scaling causes negative transfer because naive aggregation dilutes tissue-informative signals; PFMs like UNiv2 are generic, not tissue-specialized [Paper: PDF p. 19; Figure 5d].

core hypothesis: Lightweight, tissue-specific adapters inserted into frozen PFM backbones can recalibrate morphological representations for each cancer type without full fine-tuning.

delta from paper: STP-BENCH uses fixed UNiv2; TAEA introduces trainable LoRA-style adapters per tissue, conditioned on organ-type embedding.

initial method: For each cancer type (LUAD, BRCA, etc.), train adapter modules (2-layer MLP) on top of UNiv2 CLS token; optimize with contrastive loss against tissue-specific gene expression clusters.

validation: Test on STP-BENCH-EXTERNAL cross-tissue transfer; measure if TAEA closes the -0.35 gap seen in Figure 5b (middle).

failure modes: Adapter overfitting to small tissue cohorts; interference between tissue-specific adaptations.

innovation status: unverified

- name: Gene-Set Guided Architecture Search (GS-GAS)

originating limitation/observation: TRIPLEX/DeepSpot excel on stromal/immune gene sets (Figure 3e) but require manual design; no automated way to discover which architectural motifs benefit which biological programs.

core hypothesis: Neural architecture search (NAS) guided by gene-set PCC (not overall PCC) will discover motifs specialized for ECM remodeling or immune activation.

delta from paper: STP-BENCH evaluates existing architectures; GS-GAS searches for new ones optimized per gene set.

initial method: Use DARTS-based search space with modules for local, neighborhood, and global context; reward function = weighted sum of PCC on COL1A1-group and LAG3-group gene sets.

validation: Compare discovered architecture's PCC on stromal genes vs. TRIPLEX on STP-BENCH-INTERNAL; ablate modules to confirm motif necessity.

failure modes: Search bias toward high-expression genes; poor generalization beyond training gene sets.

innovation status: unverified

- name: Zero-Shot Marker Imputation (ZMI)

originating limitation/observation: Marker genes perform poorly on Visium (PCC约0.19) due to sparsity, but Xenium shows they can be predicted well (PCC约0.58)-suggesting signal exists but is drowned in noise [Paper: PDF p. 10; Figure 2c-d].

core hypothesis: Diffusion models conditioned on high-confidence HMMVG predictions can denoise and impute sparse marker expression, leveraging shared biological variance.

delta from paper: STP-BENCH treats all genes equally; ZMI treats markers as targets to

be reconstructed from robust HMMVG context.

initial method: Train STFlow variant where conditioning input is UNlv2 + predicted HMMVGs (not raw image), and diffusion denoises only marker genes.

validation: On NCCHE-LUAD-Visium, measure ZMI's marker PCC vs. standard STFlow; check if imputed markers improve Cell2location PCC in Figure 4a.

failure modes: Over-smoothing of rare marker expression; failure to preserve spatial heterogeneity.

innovation status: unverified