

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

- 标题: MARC: Morphology-Aware Regression of Consensus for Cell Segmentation in Subcellular Spatial Transcriptomics
- 作者: Xinyu Shu, Andrew Zhang, Jean Yang, Jinman Kim
- 发布平台: arXiv
- arXiv ID: arXiv:2609.13665v1
- 发布日期: 2026-09-12
- 研究任务: subcellular spatial transcriptomics (SST) 中的细胞分割质量评估 (consensus-aware segmentation quality control)
- 核心输出: 像素级 consensus-support map $\hat{C}_k \in [0,1]^{H \times W}$ 及其细胞级聚合得分 $S_{k,c}$ [Paper: PDF p. 3-5]
- 输入模态: 候选掩码 F_k 、DAPI 形态图像 D 、转录本密度图 T [Paper: PDF p. 3]
- 训练监督信号: leave-one-method-out 显式共识伪标签 $C^{(-k)}$ [Paper: PDF p. 3]
- 损失函数: Foreground-Union Consensus Loss (FUCL) [Paper: PDF p. 4]
- 骨干架构: 四层 U-Net-style encoder-decoder [Paper: PDF p. 3]
- 评估数据集: 10x Genomics Xenium FFPE human renal cell carcinoma dataset, 空间留出划分, 共 4,642 测试 tile [Paper: PDF p. 5]
- 候选分割方法: Cellpose-SAM、BIDCell、ProSeg、Xenium 10x [Paper: PDF p. 5]

02 一句话总结

MARC 是一种 morphology-aware 的深度回归框架, 通过联合建模候选掩码 F_k 、DAPI 形态 D 和转录本密度 T , 直接预测像素级多方法共识支持度 $\hat{C}_k$, 在推理时无需运行多分割 pipeline, 即可逼近显式 leave-one-method-out 共识 $C^{(-k)}$, 并在像素级 (Dice=0.9002) 和细胞级 (Spearman $\rho=0.7905$) 均取得高保真度 [Paper: PDF p. 1, 4-5].

03 研究问题

- 如何在 subcellular spatial transcriptomics (SST) 中实现无真值标注、无模型内生不确定性访问、不依赖多方法并行推理的细胞分割质量评估?
- 如何将多方法共识这一实用但计算昂贵的 surrogate ground truth, 转化为可学习、可泛化的单次前向预测任务?
- 如何使预测的共识支持度既具备像素级空间分辨能力, 又能生成有意义的细胞级排序分数, 用于下游人工复核或过滤? [Paper: PDF p. 1-3]

04 研究背景与发展路径

- SST 分割瓶颈: 边界模糊源于弱形态对比、稀疏/错位转录本、密集细胞重叠; 视觉合理边界 $\neq$ 生物学合理转录分配 [Paper: PDF p. 1].

- 传统 QC 失效：监督法需专家标注（耗时且 SST 边界本就模糊）[Paper: PDF p. 1]；不确定性估计法需访问生成分割模型的内部状态（不适用于黑盒第三方 pipeline）[Paper: PDF p. 1-3]。
- 共识作为 surrogate：多方法分歧反映边界不确定性；形态驱动（如 Cellpose-SAM）与转录驱动（如 Baysor、ProSeg）方法误差源互补 [Paper: PDF p. 1-2]。
- 显式共识缺陷：STAPLE 或多数投票需运行全部 K 个 pipeline（含 method-specific 输入预处理），计算不可扩展 [Paper: PDF p. 1-2, 3]。
- MARC 路径：将共识构建从“运行时集成”转为“训练时学习”，用 DAPI + T + F_k 三通道输入回归 $\hat{C}_k$ ，以 FUCL 聚焦前景与分歧区域 [Paper: PDF p. 2-4]。

05 论文识别的核心痛点

Pain point / Manifestation / Cause or author explanation / Evidence from the paper

Pain point: Computational intractability of explicit consensus

Manifestation: Consensus construction requires executing all K segmentation pipelines with their method-specific SST inputs, making it prohibitive for large-scale SST tissue regions [Paper: PDF p. 1].

Cause or author explanation: Each method has distinct input requirements (e.g., raw morphology vs. transcript-guided features), and parallel execution scales poorly with cell count [Paper: PDF p. 2].

Evidence from the paper: Figure 1(a) illustrates multi-pipeline execution; text states “computationally intensive” and “difficult to scale” [Paper: PDF p. 2].

Pain point: Lack of scalable, annotation-free ground truth

Manifestation: No reliable manual annotations exist for SST cell boundaries due to biological ambiguity and annotation cost [Paper: PDF p. 1].

Cause or author explanation: Boundaries must be inferred from incomplete morphological and transcript signals; dense manual labeling is time-consuming [Paper: PDF p. 1].

Evidence from the paper: Abstract: “reliable ground-truth boundaries are unavailable”; Introduction: “manual annotation of a large number of cells is time-consuming” [Paper: PDF p. 1].

Pain point: Incompatibility of existing QC methods with SST pipelines

Manifestation: Supervised QC needs expert masks; uncertainty-based QC needs internal model outputs - neither applies to externally generated candidate masks [Paper: PDF p. 1-3].

Cause or author explanation: SegQC relies on expert-corrected masks; Bayesian uncertainty requires access to the segmentation model’s prediction distribution [Paper: PDF p. 3].

Evidence from the paper: Section 2.2 explicitly contrasts MARC’s consensus-derived pseudo-supervision with SegQC and Bayesian methods [Paper: PDF p. 3].

Pain point: Loss of spatial granularity in cell-level QC

Manifestation: Candidate-copy baseline assigns uniform score per cell, preventing identification of weakly supported subregions within a cell [Paper: PDF p. 5-6].

Cause or author explanation: Treating foreground mask as consensus yields constant pixel values $\rightarrow$ constant cell scores $\rightarrow$ no ranking capability [Paper: PDF p. 6].

Evidence from the paper: Table 2 footnote: “Undefined because the candidate-copy baseline produces constant cell-level scores” [Paper: PDF p. 6].

06 核心思想

- Consensus-as-regression：将多方法共识支持度建模为一个连续值回归任务（ $\hat{C}_k = f_{\theta}(D, T, F_k)$ ），而非离散集成或分类，从而保留空间细节与强度梯度 [Paper: PDF p. 3]。
- Morphology-aware context fusion：显式注入 DAPI 形态与转录本密度作为上下文，使模型能基于核定位一致性与分子信号富集度判断候选掩码可靠性，超越纯几何（ F_k ）线索 [Paper: PDF p. 3, 6]。

- Foreground-union supervision focus : FUCL 损失仅在候选前景 F_k 或 leave-one-out 共识前景 $C^{(-k)}$ 覆盖的像素上计算，强制模型学习分歧区域（如 $F_k=1$ 但 $C^{(-k)} \approx 0$ ）的判别能力 [Paper: PDF p. 4].
- Leave-one-method-out pseudo-targets : 对每个候选方法 k ，其监督目标 $C^{(-k)}$ 是其余 $K-1$ 方法前景图的算术平均，避免模型学习 trivial self-agreement [Paper: PDF p. 3].

07 方法总览

MARC 是一个端到端的 U-Net 架构，输入为三通道张量 $X_k = \text{concat}(D, T, F_k)$ ，输出为连续值共识支持图 $\hat{C}_k \in [0,1]^{H \times W}$ 。训练使用 leave-one-method-out 共识 $C^{(-k)}$ 作为伪标签，并采用 Foreground-Union Consensus Loss (FUCL) 进行优化。推理时仅需单次前向传播，随后通过原始标记掩码 M_k 将 $\hat{C}_k$ 聚合为细胞级得分 $S_{[k,c]}$ 。整个流程解耦了共识构建与分割执行，实现计算高效的质量评估 [Paper: PDF p. 2-5].

08 核心模块拆解

Module / Function / Why needed / Input and output / Supporting evidence / Known or expected effect of removal

Module: Three-channel input concatenation

Function: Fuses candidate geometry (F_k), nuclear morphology (D), and molecular context (T) into unified representation X_k

Why needed: Enables joint reasoning about shape, structure, and gene expression; ablation shows DAPI+T add complementary signal beyond F_k alone [Paper: PDF p. 6].

Input and output: Input: $D, T, F_k \in \mathbb{R}^{H \times W}$; Output: $X_k \in \mathbb{R}^{3 \times H \times W}$ [Eq. 2, Paper: PDF p. 3].

Supporting evidence: Equation 2 defines $X_k = \text{concat}(D, T, F_k)$; Table 2 shows Dice $\uparrow$ from 0.8565 (F_k only) to 0.9002 (F_k+D+T) [Paper: PDF p. 3,6].

Known or expected effect of removal: Removal of D or T degrades cell-level Spearman correlation (0.4228 $\rightarrow$ 0.7564 $\rightarrow$ 0.7905), indicating loss of ranking ability [Paper: PDF p. 6].

Module: U-Net encoder-decoder backbone

Function: Extracts hierarchical features and reconstructs dense pixel-wise prediction $\hat{C}_k$

Why needed: Standard architecture for dense prediction; handles multi-scale morphological and transcript patterns [Paper: PDF p. 3].

Input and output: Input: X_k ; Output: logit map Z_k , then $\hat{C}_k = \sigma(Z_k)$ [Eq. 4, Paper: PDF p. 3].

Supporting evidence: Section 3.2 specifies 4-level U-Net with conv-BN-ReLU blocks and transposed conv decoder [Paper: PDF p. 3].

Known or expected effect of removal: Not assessed directly, but U-Net is canonical for biomedical segmentation; replacement would require architectural ablation not performed.

Module: Foreground-Union Consensus Loss (FUCL)

Function: Computes mean absolute error only over pixels in union of F_k and $C^{(-k)}$ foreground

Why needed: Focuses training on biologically relevant regions (cell interiors) and disagreement zones, ignoring background where consensus is undefined [Paper: PDF p. 4].

Input and output: Input: $\hat{C}_k, C^{(-k)}, U_k$; Output: scalar loss $L^{(k)}_{\text{FU}}$ [Eq. 7, Paper: PDF p. 4].

Supporting evidence: Equation 6 defines $U_k(x,y) = \mathbb{1}[F_k=1 \vee C^{(-k)} > 0]$; Eq. 7 defines loss restricted to U_k [Paper: PDF p. 4].

Known or expected effect of removal: Using full-image L1 would dilute gradient signal with irrelevant background; FUCL ensures learning concentrates on cell boundaries and ambiguous regions.

Module: Cell-level aggregation via M_k

Function: Converts dense $\hat{C}_k$ into per-cell consensus score $S_{k,c}$ by averaging over pixels assigned to cell c in M_k

Why needed: Enables practical QC workflows: ranking cells for review, filtering low-confidence instances [Paper: PDF p. 4-5].

Input and output: Input: $\hat{C}_k, M_k$; Output: scalar $S_{k,c}$ for each cell c [Eq. 8, Paper: PDF p. 5].

Supporting evidence: Equation 8: $S_{k,c} = \frac{1}{|M_k(x,y)=c|}$

Known or expected effect of removal: $\sum_{(x,y): M_k(x,y)=c} \hat{C}_k(x,y)$ [Paper: PDF p. 5].

Field 7: $\sum_{(x,y): M_k(x,y)=c} \hat{C}_k(x,y)$ [Paper: PDF p. 5].

Field 8: Without M_k , no cell identity; candidate-copy baseline fails here (constant scores) [Table 2, Paper: PDF p. 6].

09 关键公式与符号

Symbol / Definition / Context & Page / Notes

Symbol: M_k

Definition: Labelled mask from candidate method k : $M_k \in \{0,1,\dots\}^{H \times W}$, positive values = cell IDs, 0 = background [Eq. 1, Paper: PDF p. 3].

Context & Page: Section 3.1, Eq. 1

Notes: Basis for cell-level aggregation (Eq. 8).

Symbol: F_k

Definition: Binary foreground map of M_k : $F_k(x,y) = \begin{cases} 1 & M_k(x,y) > 0 \\ 0 & \text{otherwise} \end{cases}$ [Eq. 1, Paper: PDF p. 3].

Context & Page: Eq. 1, Paper: PDF p. 3

Notes: Used in input concatenation (Eq. 2) and FUCL (Eq. 6).

Symbol: D, T

Definition: Aligned DAPI morphology image and transcript-density image, both $\in \mathbb{R}^{H \times W}$ [Paper: PDF p. 3].

Context & Page: Section 3.1, Paper: PDF p. 3

Notes: Provide contextual biological signals beyond F_k .

Symbol: X_k

Definition: Three-channel input: $X_k = \text{concat}(D, T, F_k) \in \mathbb{R}^{3 \times H \times W}$ [Eq. 2, Paper: PDF p. 3].

Context & Page: Eq. 2, Paper: PDF p. 3

Notes: Core multimodal input to MARC.

Symbol: $\hat{C}_k$

Definition: Predicted continuous consensus-support map: $\hat{C}_k = f_{\theta}(X_k) \in [0,1]^{H \times W}$ [Eq. 3, Paper: PDF p. 3].

Context & Page: Eq. 3, Paper: PDF p. 3

Notes: Output of MARC; sigmoid ensures [0,1] range (Eq. 4).

Symbol: $C^{(-k)}$

Definition: Leave-one-method-out consensus target: $C^{(-k)}(x,y) = \frac{1}{K-1} \sum_{j \neq k} F_j(x,y)$ [Eq. 5, Paper: PDF p. 3].

Context & Page: Eq. 5, Paper: PDF p. 3

Notes: Pseudo-ground truth; arithmetic mean of other $K-1$ methods' F_j .

Symbol: U_k

Definition: Foreground-union mask: $U_k(x,y) = \begin{cases} 1 & F_k(x,y)=1 \text{ or } C^{(-k)}(x,y) > 0 \\ 0 & \text{otherwise} \end{cases}$ [Eq. 6, Paper: PDF p. 4].

Context & Page: Eq. 6, Paper: PDF p. 4

Notes: Defines region for FUCL computation (Eq. 7).

Symbol: $L^{(k)}_{\text{FU}}$

Definition: Foreground-Union Consensus Loss: $L^{(k)}_{\text{FU}} = \frac{1}{\sum_{x,y} U_k(x,y)}$

Context & Page: $\hat{C}_k(x,y) - C^{\{-k\}}(x,y)$

Notes: $\max(1, \sum_{x,y} U_k(x,y))$ [Eq. 7, Paper: PDF p. 4].

Field 5: Eq. 7, Paper: PDF p. 4

Field 6: Clamped denominator avoids division-by-zero.

Symbol: $S_{k,c}$

Definition: Cell-level consensus score for candidate cell c : average of $\hat{C}_k$ over pixels in cell c of M_k [Eq. 8, Paper: PDF p. 5].

Context & Page: Eq. 8, Paper: PDF p. 5

Notes: Enables ranking; Spearman correlation computed between $S_{k,c}$ and target analogues.

10 实验设计与证据链

Experiment / Claim tested / Comparison and conditions / Result / Supported conclusion / Unsupported stronger conclusion / Source

Experiment: Main evaluation (Table 1)

Claim tested: MARC predicts explicit leave-one-method-out consensus $C^{\{-k\}}$ with high fidelity at pixel and cell levels.

Comparison and conditions: MARC trained on 4 methods (Cellpose-SAM, BIDCell, ProSeg, Xenium); evaluated on held-out test tiles ($n=18,443$) against $C^{\{-k\}}$ targets; metrics:

Foreground-union L1, Dice, IoU, Sensitivity, Precision, Cell Spearman ρ .

Result: Avg. Dice=0.9002, IoU=0.8186, $\rho=0.7905$; best per-method Dice up to 0.9127 (Xenium) [Table 1, Paper: PDF p. 4].

Supported conclusion: MARC closely approximates explicit cross-method consensus without multi-method inference.

Unsupported stronger conclusion: MARC achieves absolute ground-truth accuracy (impossible, as $C^{\{-k\}}$ itself is surrogate).

Source: Table 1, Section 4.2, Paper: PDF p. 4-5.

Experiment: Input ablation (Table 2)

Claim tested: DAPI morphology and transcript density provide complementary, non-redundant signals beyond candidate mask geometry.

Comparison and conditions: Four configurations: (i) candidate-copy baseline (no model), (ii) MARC with F_k only, (iii) MARC with $F_k + D$, (iv) MARC with $F_k + D + T$; all trained/evaluated identically against same $C^{\{-k\}}$ targets.

Result: Adding D : Dice $\uparrow$ 0.8565 $\rightarrow$ 0.8866, ρ $\uparrow$ 0.4228 $\rightarrow$ 0.7564; adding T : Dice $\uparrow$ 0.8866 $\rightarrow$ 0.9002, ρ $\uparrow$ 0.7564 $\rightarrow$ 0.7905 [Table 2, Paper: PDF p. 6].

Supported conclusion: Morphology is primary driver for cell-level ranking; transcript density refines both pixel-level prediction and ranking.

Unsupported stronger conclusion: DAPI or T alone suffices for robust QC (not tested; ablation is cumulative).

Source: Table 2, Section 4.3, Paper: PDF p. 6.

Experiment: Target ablation (Section 4.3)

Claim tested: Arithmetic mean consensus is a viable and pragmatically preferable supervision target over STAPLE.

Comparison and conditions: Two MARC models: (i) mean-consensus supervision, (ii) STAPLE-fused supervision; identical inputs/architecture/loss; evaluated against respective targets.

Result: Mean: higher sensitivity (0.9168 vs 0.8860) and ρ (0.7905 vs 0.7491); STAPLE: higher precision (0.9128 vs 0.8843); Dice/IoU nearly identical [Paper: PDF p. 5].

Supported conclusion: Mean consensus directly encodes fraction-of-supporting-methods and better preserves cell rankings.

Unsupported stronger conclusion: STAPLE is less accurate (comparison is cross-target; no shared ground truth).

Source: Section 4.3, Paper: PDF p. 5.

Experiment: Qualitative analysis (Figure 4)

Claim tested: MARC predictions localize weakly supported regions and reflect biological plausibility.

Comparison and conditions: Visual inspection of representative cells across all 4 methods; overlay of DAPI, ST , F_k , $\hat{C}_k$, and cell-level map.

Result: High $\hat{C}_k$ where F_k aligns with nuclear morphology and transcript density; low $\hat{C}_k$ where F_k extends into background or disagrees with D/T [Figure 4, Paper: PDF p. 6].

Supported conclusion: MARC learns biologically meaningful cues, not just statistical artifacts.

Unsupported stronger conclusion: MARC generalizes to unseen tissue types or platforms (only Xenium data used).

Source: Figure 4, Section 4.4, Paper: PDF p. 6-7.

11 对结论的正确理解

- MARC does not predict ground-truth cell boundaries, nor does it improve segmentation masks; it predicts how much multi-method consensus supports a given candidate mask [Paper: PDF p. 1, 5].
- The reported Dice=0.9002 measures overlap between $\hat{C}_k$ and $SC^{(-k)}$, not between $\hat{C}_k$ and true biology - $SC^{(-k)}$ is itself an imperfect surrogate [Paper: PDF p. 1, 7].
- Cell-level Spearman $\rho=0.7905$ means MARC preserves the relative ranking of cells by consensus support, enabling prioritization for review, not that absolute scores are calibrated probabilities [Paper: PDF p. 4-5].
- Success on Xenium renal cell carcinoma does not imply generalizability to other tissues, assays (e.g., Slide-seq, seqFISH+), or segmentation methods outside the tested quartet [Paper: PDF p. 7].
- MARC's value lies in computational efficiency: replacing $O(K)$ pipeline executions with $O(1)$ inference, enabling routine QC at scale [Paper: PDF p. 1-2].

12 作者明确承认的限制

Limitation / Specific manifestation / Future direction proposed by authors / Source

Limitation: Consensus as surrogate, not ground truth

Specific manifestation: Failure modes common to all K segmentation methods may be reinforced in $SC^{(-k)}$ and thus learned by MARC [Paper: PDF p. 7].

Future direction proposed by authors: Acknowledge utility despite limitation: consensus captures agreement across methods, reducing reliance on single-method bias [Paper: PDF p. 7].

Source: Section 4.5, Paper: PDF p. 7.

Limitation: Limited generalizability

Specific manifestation: Evaluation conducted on single dataset (Xenium renal cell carcinoma) with candidate methods sharing inputs from same assay -> methods not fully independent [Paper: PDF p. 7].

Future direction proposed by authors: Future work: evaluate on additional tissues/platforms/methods; incorporate orthogonal markers (e.g., membrane proteins) for validation; test consensus-guided filtering on downstream analyses [Paper: PDF p. 7].

Source: Section 4.5, Paper: PDF p. 7.

13 批判性分析

[Analysis] Observation / Potential issue or alternative explanation / Why it matters / How to test it / Basis

[Analysis] Observation: MARC uses arithmetic mean $SC^{(-k)}$ as target, but methods differ in reliability (e.g., Xenium onboard vs. ProSeg); mean treats all equally, potentially propagating errors from weaker methods.

Potential issue or alternative explanation: STAPLE (tested ablatively) estimates method-specific sensitivity/specificity, which could yield more robust targets if validated on independent

ground truth.

Why it matters: Over-reliance on mean may degrade MARC's ability to flag cells where all methods fail similarly (systematic bias), not just where they disagree.

How to test it: Train MARC with STAPLE targets on a small subset with expert annotations; compare error localization accuracy (e.g., distance to expert boundary) vs. mean targets.

Basis: Section 4.3 notes STAPLE achieved higher precision but lower p; no test against expert truth [Paper: PDF p. 5].

[Analysis] Observation: Input ablation shows DAPI contributes most to cell-level ranking (p jump 0.42->0.76), yet MARC treats $\$D\$$ and $\$T\$$ as raw intensity images - no explicit modeling of nuclear shape, size, or transcript spatial clustering.

Potential issue or alternative explanation: Learned features may capture coarse correlations but miss fine-grained biophysical constraints (e.g., nucleus-to-cytoplasm ratio, transcript dispersion entropy).

Why it matters: Limits interpretability and transfer to tissues with divergent nuclear morphology or transcript distributions.

How to test it: Replace $\$D\$$ and $\$T\$$ with handcrafted features (e.g., Hu moments, Ripley's K) or graph-based representations (e.g., nucleus-cell graphs) and measure p drop.

Basis: Figure 4 shows alignment with nuclear morphology, but no feature attribution is provided [Paper: PDF p. 6-7].

[Analysis] Observation: MARC aggregates $\$\hat{C}_k\$$ via simple mean over $\$M_k\$$ pixels (Eq. 8), but cell boundary uncertainty is often non-uniform (e.g., high near nuclei, low at periphery).

Potential issue or alternative explanation: Uniform averaging may dilute localized low-consensus signals (e.g., a thin protrusion with low $\$\hat{C}_k\$$) if majority of cell has high support.

Why it matters: Compromises utility for detecting partial boundary errors, which are critical in SST for transcript misassignment.

How to test it: Compare Eq. 8 aggregation to alternatives: max-pooling (sensitive to worst pixel), weighted mean (by distance to centroid), or attention-based pooling; evaluate on synthetic boundary perturbations.

Basis: No ablation on aggregation strategy is reported; Figure 4 shows spatially varying $\$\hat{C}_k\$$ but cell scores are scalars [Paper: PDF p. 5-6].

14 学到的知识

- In subcellular ST, cell segmentation quality control is decoupled from segmentation generation: one can build a dedicated QC model (MARC) that consumes segmentation outputs as inputs, enabling modular, pipeline-agnostic evaluation.
- Consensus is learnable: multi-method agreement, though computationally expensive to compute explicitly, exhibits sufficient structure to be regressed from multimodal inputs ($\$D, T, F_k\$$) with high fidelity.
- Foreground-union loss design is critical: restricting supervision to $\$U_k\$$ (Eq. 6) forces the model to attend to disagreement regions - a simple full-image L1 would fail to localize uncertainty.
- Morphology dominates molecular context for ranking: DAPI addition drove larger p gain (0.42->0.76) than transcript addition (0.76->0.79), suggesting nuclear architecture is the primary anchor for consensus in this dataset.
- Cell-level scores require spatially resolved prediction: the candidate-copy baseline fails at ranking because it lacks intra-cell variation; MARC's dense $\$\hat{C}_k\$$ enables meaningful aggregation.

15 与既有知识的连接

- single-cell foundation models: MARC is not a foundation model - it's task-specific and requires retraining per assay; however, its use of multimodal inputs ($\$D, T, F_k\$$) aligns with trends in cross-modal foundation learning,

suggesting future extension to pretrain on diverse SST data.

- spatial transcriptomics: Directly addresses the core SST challenge of boundary ambiguity [Paper: PDF p. 1]; complements segmentation methods (BIDCell, ProSeg) by providing their QC layer.

- graph neural networks: While MARC uses CNNs, its goal - aggregating local evidence (transcripts, nuclei) into global cell scores - mirrors GNN message passing; future work could replace U-Net with GNNs operating on nucleus-graphs.

- multi-omics: Treats morphology (\$D\$) and transcriptomics (\$T\$) as complementary omics layers; ablation confirms their synergy, supporting multi-omics integration paradigms.

- biomedical AI: Exemplifies “pragmatic AI” - bypassing unattainable ground truth (expert boundaries) with a scalable surrogate (consensus), a pattern seen in medical imaging QC (e.g., STAPLE for segmentation validation).

- perturbation prediction / cell state representation / cross-modal alignment: Weak connection/Methodology connection - MARC does not model perturbations, infer cell states, or perform cross-modal alignment; its alignment is purely spatial (co-registration of \$D, T, F_k\$), not semantic.

16 研究想法

- name: Consensus-Guided Perturbation Masking

originating limitation/observation: MARC identifies low-consensus cells (Figure 4), but these may represent genuine biological heterogeneity (e.g., stressed cells) rather than segmentation errors [Paper: PDF p. 6-7].

core hypothesis: Low-consensus regions flagged by MARC correlate with transcriptionally dysregulated or perturbed cellular subpopulations.

delta from paper: Shift from QC to biological discovery: use MARC scores as masks to extract low-consensus cells for differential expression or trajectory inference.

initial method: Apply MARC to Xenium dataset; bin cells by $SS_{\{k,c\}}$; perform DEG analysis between top/bottom deciles; validate with known stress markers.

validation: Enrichment of stress-response GO terms in low- $SS_{\{k,c\}}$ cells; spatial clustering of low-consensus cells near tumor necrosis.

failure modes: Low consensus driven by technical artifacts (e.g., low RNA capture) rather than biology; confounding by cell type (some types inherently harder to segment).

innovation status: unverified

- name: MARC-GNN: Graph-Augmented Consensus Regression

originating limitation/observation: MARC uses pixel-grid CNNs, but SST data has natural graph structure (nuclei as nodes, spatial proximity as edges) [Paper: PDF p. 3].

core hypothesis: Modeling inter-nuclear relationships via GNNs improves consensus prediction in crowded regions where pixel CNNs lose long-range context.

delta from paper: Replace U-Net encoder with GNN that takes nucleus centroids (from \$D\$) and per-nucleus transcript counts (from \$T\$) as node features, and builds k-NN graph.

initial method: Extract nuclei from \$D\$; compute node features (area, eccentricity, avg \$T\$ intensity); build graph; train GNN to predict per-nucleus consensus score;

upsample to pixel level.

validation: Higher Dice in dense regions (defined by nucleus density >95th percentile) vs. U-Net MARC; ablation of graph connectivity.

failure modes: Nucleus detection errors propagate; graph construction sensitive to k; increased computational cost negates MARC's efficiency advantage.

innovation status: unverified

- name: Cross-Assay MARC Transfer

originating limitation/observation: MARC evaluated only on Xenium; authors note limited generalizability due to shared assay inputs [Paper: PDF p. 7].

core hypothesis: Pretraining MARC on diverse SST assays (Xenium, Visium, seqFISH+) enables zero-shot or few-shot adaptation to new platforms.

delta from paper: Introduce assay-conditioning token or adapter layers; pretrain on multi-assay consensus targets; fine-tune on target assay with minimal data.

initial method: Collect \$D,T,F_k\$ triples from 3+ public SST datasets; train MARC with assay ID embedding; evaluate on held-out assay with <100 tiles.

validation: Dice >0.85 on target assay with 50 fine-tuning tiles; feature similarity (CKA) between assay-specific encoder layers.

failure modes: Domain gap too large (e.g., Visium's low resolution vs. Xenium's subcellular); lack of standardized \$D/T\$ preprocessing across assays.

innovation status: unverified