

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Authors	Youngmin Chung, Ji Hun Ha, Andrew H. Song, et al.	[Paper] [Paper: PDF p. 1]
Venue	arXiv	[Paper] [Paper: PDF p. 1]
URL	https://arxiv.org/abs/2609.05956	[Paper meta]
PDF URL	https://arxiv.org/pdf/2609.05956	[Paper meta]
Publication date	2026-09-05	[Paper meta]
Core contribution	First large-scale, standardized benchmark for virtual ST; unifies encoder, evaluation granularity, biological utility metrics, and domain-shift robustness testing	[Paper] [Paper: PDF p. 2–4, Fig. 1]
Code & data release	Publicly released at https://github.com/NEXGEM/STP-Bench and Hugging Face (https://huggingface.co/datasets/nexgem/STP-Bench)	[Paper] [Paper: PDF p. 37]
Key datasets	STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium/Xenium); STP-BENCH-EXTERNAL (185,831 spots, 6 cancer types, cross-institution/tissue/platform)	[Paper] [Paper: PDF p. 4–5, Fig. 1b]
Evaluated models	21 models: 14 regression-based, 4 bi-modal retrieval, 3 generative	[Paper] [Paper: PDF p. 6, Fig. 1c]
Primary metric	Pearson Correlation Coefficient (PCC) per gene, averaged across spots → sections → folds	[Paper] [Paper: PDF p. 31, Eq. 1]

02 一句话总结

该论文构建了STP-BENCH——首个面向虚拟空间转录组学（virtual ST）的统一、大规模、多维度系统性基准，覆盖6种癌症、双平台（Visium/Xenium）、超60万spots，并强制统一病理基础模型（PFM）作为图像编码器以解耦架构与表征影响。其核心发现是：多数现有模型在统一PFM下无法超越线性探针基线；基因可预测性存在强普适性天花板，而多尺度架构（如TRIPLEX、DeepSpot）仅对特定生物学程序（如基质重塑、免疫浸润）提供边际增益；平台间数据质量（如Xenium高计数）是下游生物效用的决定性瓶颈。该工作不提出新模型，而是为single-cell foundation models、spatial transcriptomics和multi-omics领域提供可复现、可归因、可迁移的黄金评估标尺。

03 研究问题

论文直面虚拟ST领域长期存在的**评估不可比性**问题：当不同研究使用异构数据集、私有训练流程、原生图像编码器及单一平均指标时，报告的“性能提升”究竟源于模型架构创新，还是图像表征能力差异？进一步地，若剥离编码器影响，模型是否真能可靠恢复特定生物学信号（如细胞类型丰度、空间结构域）？其泛化能力在跨机构、跨组织、跨平台等现实场景中如何变化？这些问题阻碍了领域从“工程调参”走向“机制理解”与“临床可部署”。

04 研究背景与发展路径

虚拟ST起源于ST实验成本高昂的现实约束，其技术谱系已分化为三支：（1）**回归式**（如ST-Net），将H&E patch到基因表达映射建模为多输出回归；（2）**双模态对齐式**（如BLEEP），借鉴CLIP范式学习形态-表达联合嵌入空间；（3）**生成式**（如STFlow），将预测建模为条件生成任务以捕获分布不确定性。尽管方法演进迅速，但评估始终滞后：Wang et al. [50] 未标准化编码器，导致架构与表征贡献混淆；HEST-1K [51] 虽规模大但仅测试简单回归器，未覆盖主流架构。STP-BENCH并非延续单点改进，而是重构评估范式——它将“公平比较”定义为**控制变量法**：固定PFM（UNiv2）、固定数据划分（患者级CV）、固定下游任务（Cell2location/SpaGCN）、固定指标体系（PCC/SSIM/MAE/ARI），从而将模型比较锚定在架构设计本身。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
评估不公平	模型排名随图像编码器剧烈波动（如CFANet从第16跃至第6）	原有研究混用ImageNet预训练、病理域微调、从头训练等异构编码器，性能差异实为表征能力差异	[Paper] [Paper: PDF p. 9, Fig. 2b]
生物学效用黑箱	高PCC值无法保证下游分析可用（如Cell2location输入需count-scale整数）	传统评估止步于spot-level相关性，忽略预测结果是否保留空间结构、细胞组成等生物学先验	[Paper] [Paper: PDF p. 14–15, Fig. 4]
泛化性未经检验	模型在内部验证集表现好，但在跨机构/组织/平台时性能断崖式下跌	现有基准缺乏外部独立测试集，且未系统设计domain shift场景（如Visium→Xenium）	[Paper] [Paper: PDF p. 17, Fig. 5a–b]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
数据质量影响被掩盖	Xenium数据上所有模型PCC均显著高于Visium (+0.2–0.4)，但原因未被归因	Visium低计数（尤其marker genes）导致信噪比低，而Xenium高灵敏度补偿了domain shift损失	[Paper] [Paper: PDF p. 10, Fig. 2c–d]
基因级可解释性缺失	“哪些基因易预测”无共识，模型优势是否集中于特定通路未知	以往工作仅报告平均PCC，未进行gene-wise heatmap或gene set scoring分析	[Paper] [Paper: PDF p. 11–13, Fig. 3]

06 核心思想

论文的核心思想是：**虚拟ST的评估必须从“单一数字竞赛”升维为“多粒度因果归因”**。这体现为三个递进层次：（1）**解耦归因**：通过强制统一PFM（UNiv2），将模型性能差异从“编码器能力”剥离，聚焦“架构设计”本身；（2）**生物学归因**：不仅测spot-level PCC，更测cell-type abundance（Cell2location）、spatial domain（SpaGCN）、gene set activity（singscore），验证预测是否承载真实生物学结构；（3）**鲁棒性归因**：设计Cross-Institution/Tissue/Platform三类domain shift，量化性能衰减是否由技术变异（可控）或生物异质性（本质）主导。最终，STP-BENCH不是静态榜单，而是诊断工具——它揭示了当前技术的真正瓶颈：不是架构复杂度，而是形态-表达映射的固有局限性与数据质量天花板。

07 方法总览

STP-BENCH的方法框架是“一基准、三支柱、五维度”：

- **一基准**：STP-BENCH数据集，含INTERNAL（609k spots, 6 cancers, 2 platforms）与EXTERNAL（186k spots, 6 cancers, 3 generalization axes）；
- **三支柱**：(i) **统一编码器**：UNiv2作为默认PFM，仅对架构不兼容模型（如M2OST/M2ORT）保留原编码器；(ii) **统一实现**：21模型全部重实现，统一训练超参（lr=1e-4, 200 epochs）、统一CV策略（患者级5-fold）、统一后处理（Softplus输出）；(iii) **统一评估协议**：所有指标（PCC/SSIM/MAE/ARI）计算逻辑严格标准化（[Paper] [Paper: PDF p. 31–32, Eq. 1–2]）；
- **五维度**：（1）spot-level predictive accuracy（PCC on HMHVG/marker genes）；（2）gene-wise predictability heatmap；（3）gene set scoring（singscore on GO BP terms）；（4）biological granularities（Cell2location/SpaGCN）；（5）robustness & scalability（cross-domain gaps/data scaling curves）。整个流程确保任何性能差异均可追溯至具体设计选择。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
UNiv2 PFM Encoder	Extracts 1024-d histology embeddings from 224×224 H&E patches	To isolate architectural contribution by eliminating encoder variability; UNiv2 outperforms ResNet50/CTransPath in all settings	Input: H&E patch; Output: spot-level embedding vector	[Paper] [Paper: PDF p. 10, Fig. 2e]; [Paper] [Paper: PDF p. 25–26, TRIPLEX/DeepSpot implementation]	Severe ranking inversion (e.g., CFANet drops from 6th to 16th) and ~ 0.1 – 0.2 PCC drop for most models [Paper] [Paper: PDF p. 9, Fig. 2b]
Gene Set Scoring (singscore)	Computes per-spot gene set activity score via rank-based averaging of member genes	To bridge gene-level prediction to functional pathway recovery, beyond correlation	Input: predicted/ground-truth expression matrix; Output: spot-by-gene-set activity matrix	[Paper] [Paper: PDF p. 13, Fig. 3c–e]; [Paper] [Paper: PDF p. 35, Online Methods]	Loss of biological interpretability: model may predict genes well but fail to recover coherent pathways (e.g., T Cell Activation) [Paper] [Paper: PDF p. 13]
Cell2location Deconvolution	Estimates spatial cell-type abundance from expression matrix using scRNA-seq reference	To test if virtual ST preserves cellular composition structure required for clinical interpretation	Input: virtual ST expression (expm1-transformed, integer-clipped); Output: per-spot cell-type abundance vectors	[Paper] [Paper: PDF p. 14–15, Fig. 4a]; [Paper] [Paper: PDF p. 35, Online Methods]	Failure to recover rare populations (plasma/mast cells) would remain undetected without this module [Paper] [Paper: PDF p. 14]
SpaGCN Spatial Clustering	Identifies spatial domains via graph neural network on expression + coordinates	To verify if predicted expression retains tissue architecture topology (e.g., tumor core vs. stroma)	Input: virtual ST expression (expm1/clipped), spatial coordinates; Output: domain labels per spot	[Paper] [Paper: PDF p. 14–15, Fig. 4b–c]; [Paper] [Paper: PDF p. 36, Online Methods]	Without this, high PCC could mask spatial blurring (e.g., predicted expression smooths boundaries) [Paper] [Paper: PDF p. 14]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Cross-Platform Generalization Test	Evaluates Visium-trained models on Xenium external data (and vice versa)	To quantify impact of platform-specific technical artifacts (e.g., spot size, sensitivity) on real-world deployment	Input: model trained on Visium INTERNAL; Output: PCC on Xenium EXTERNAL	[Paper] [Paper: PDF p. 17, Fig. 5a–b right]; [Paper] [Paper: PDF p. 17, "cross-platform transfer"]	Would miss the key finding that Xenium's higher sensitivity compensates for domain shift, yielding near-zero generalization gap [Paper] [Paper: PDF p. 17]

09 关键公式与符号

论文明确给出两个核心公式，均用于spot-level评估：

- **Equation 1 (PCC):**
$$\text{PCC}_{\{g,s\}} = \frac{\sum_{i=1}^N (\hat{y}_{\{i,g\}} - \bar{\hat{y}}_g)(y_{\{i,g\}} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{\{i,g\}} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{\{i,g\}} - \bar{y}_g)^2}}$$
 [Paper] [Paper: PDF p. 31]
- 符号： $\hat{y}_{\{i,g\}}$ \$: spot \$ i \$ 基因 \$ g \$ 的预测 $\log(1+x)$ 表达； $y_{\{i,g\}}$ \$: 对应真实值； $\bar{\hat{y}}_g, \bar{y}_g$ \$: 各自在spots上的均值； N \$: spots数量。
- **Equation 2 (MAE):**
$$\text{MAE}_{\{g,s\}} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{\{i,g\}} - y_{\{i,g\}}|$$
 [Paper] [Paper: PDF p. 32]
- 符号： 同上，衡量log-scale绝对误差。
- 其他关键指标： SSIM （structural similarity index, [Paper] [Paper: PDF p. 32])、ARI （Adjusted Rand Index, [Paper] [Paper: PDF p. 36])、singscore （rank-based gene set scoring, [Paper] [Paper: PDF p. 13, 35])。
- 无其他可核验公式；所有模型架构细节见Online Methods，但未以公式形式呈现。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Fig. 2a (INTERNAL HMHVG)	Unified PFM reveals true architectural ranking	21 models, UNlv2 encoder, 7 datasets, HMHVG genes	TRIPLEX/DeepS pot > linear probe (0.394/0.423 vs 0.378); most models < baseline	Multi-scale regression architectures outperform simple baselines under fair comparison	TRIPLEX is universally best (it underperforms on marker genes in some cohorts)	[Paper] [Paper: PDF p. 8, Fig. 2a top]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Fig. 2c-d (Dataset-level stratification)	Data sparsity, not morphology, drives marker gene gap	NCCHE-LUAD-Xenium (high counts) vs NCCHE-LUAD-Visium (low counts)	Xenium: PCC=0.579 (marker); Visium: PCC=0.191; Kruskal-Wallis $p<1e-12$	Low transcript counts—not morphological uncoupling—limit marker gene prediction	All marker genes are inherently unpredictable from H&E	[Paper] [Paper: PDF p. 10, Fig. 2c–d]
Fig. 3a (Gene-wise heatmap)	Gene predictability is model-agnostic	20 models, union of HMMVG+marker genes, INTERNAL	Smooth separation: genes easy/hard for one model are easy/hard for all	Existence of universal gene-level predictability ceiling tied to morphology-expression coupling	This ceiling is fixed; no architecture can overcome it for low-predictability genes	[Paper] [Paper: PDF p. 11, Fig. 3a]
Fig. 4a (Cell2location)	Virtual ST preserves cell-type composition structure	6 models on 3 cohorts, Cell2location with matched scRNA-seq refs	TRIPLEX/DeepSpot achieve highest PCC for epithelial/T cells; plasma/mast cells low	Top-performing models retain coarse biological structure; rare populations remain challenging	Virtual ST enables clinical-grade deconvolution (not validated on clinical endpoints)	[Paper] [Paper: PDF p. 14–15, Fig. 4a]
Fig. 5a (Cross-Tissue generalization)	Biological heterogeneity dominates technical variation	Models trained on LUAD, tested on BRCA/PDAC/etc.	Spearman $\rho=0.876$ ($p=1.87e-6$) but generalization gap = -0.2 to -0.35	Internal rankings generalize across tissues, but absolute performance drops sharply	Cross-tissue transfer is feasible with minor fine-tuning (gap too large for minor tuning)	[Paper] [Paper: PDF p. 17, Fig. 5a center]

11 对结论的正确理解

论文结论必须严格限定于其证据范围：（1）“多数模型不超越线性探针” 仅在**UNiv2编码器+HMMVG/marker 基因+spot-level PCC**条件下成立，不否定其在其他编码器、其他基因集或生成式任务中的价值；（2）“基因预测天花板” 指**200 HMMVG + 16 marker genes**的集合，未覆盖低表达基因或非GO BP通路；（3）“Xenium优势” 源于其**更高计数**（mean counts=72.3 vs Visium’s 0.9 for markers），而非平台本身优越，若Visium数据质量提升，结论可能逆转；（4）“TRIPLEX/DeepSpot最优” 是**综合PCC/gene set/cell-type/domain多维度**的观察，但其在Visium上对marker基因的PCC（0.191）仍远低于Xenium（0.579），说明平台依赖性**是硬约束**；（5）“负向迁移” 指**inter-cohort scaling**中**BRCA+LUAD+PRAD训练导致BRCA测试性能下降**，但未证明所有多癌种训练均失败，可能因训练策略不当而非本质不可行。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer/tissue scope	Only 6 cancer types (LUAD, BRCA, etc.) and 2 platforms (Visium/Xenium); no normal tissue or rare cancers	Extend benchmark to additional tumor types, tissue contexts, and emerging sequencing platforms (e.g., Stereo-seq)	[Paper] [Paper: PDF p. 20]
Restricted gene panel	Analysis limited to 200 HMVGs and 16 TME markers; systematic investigation of lowly expressed or functionally diverse genes not performed	Systematic investigation of low-expression genes and broader functional gene sets	[Paper] [Paper: PDF p. 20]
Spot-level resolution only	Evaluation performed at spot-level (aggregated multi-cell signals); no single-cell ST or virtual ST models evaluated	Extend principles to single-cell resolution as scST datasets and models become available	[Paper] [Paper: PDF p. 20]
Encoder compatibility constraints	5 models (OmiCLIP, M2ORT, etc.) retained native encoders due to architectural incompatibility with PFM drop-in	Develop more modular, encoder-agnostic virtual ST architectures	[Paper] [Paper: PDF p. 9, 22–23]
Downstream tool dependency	Cell2location/SpaGCN performance depends on their own assumptions (e.g., scRNA-seq reference quality)	Integrate multiple deconvolution/clustering tools to assess robustness	[Paper] [Paper: PDF p. 35–36, Online Methods]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
UNiv2 as sole PFM may overfit to its pretraining bias	UNiv2 was trained on large WSI collections, potentially overemphasizing global patterns while underrepresenting rare morphologies (e.g., necrosis, treatment effect). Other PFMs (Virchow2, H-Optimus1) show similar but not identical rankings [Paper] [Paper: PDF p. 17]	If UNiv2’ s bias aligns fortuitously with ST prediction, conclusions about "architecture irrelevance" may not generalize to other PFMs or clinical edge cases	Re-run full benchmark with Virchow2 as primary PFM; compare ranking stability and gene-wise predictability shifts	[Paper] [Paper: PDF p. 17, Extended Data Fig. 5–6]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
singscore’ s rank-based approach discards magnitude information	singscore computes gene set scores by averaging ranks, ignoring absolute expression levels. A model could perfectly rank genes but mispredict magnitudes, yielding high singscore but poor biological utility	Downstream tasks like drug response prediction depend on absolute expression, not just rank order	Replace singscore with magnitude-aware metrics (e.g., GSVA, AUCell) and re-evaluate gene set PCC	[Paper] [Paper: PDF p. 13, 35]
Cross-platform "negligible loss" conflates directionality	Fig. 5b (right) shows small gaps, but Fig. 5a (right) reveals Visium→Xenium often gains while Xenium→Visium loses. The "negligible" label masks asymmetry	For clinical deployment, bidirectional transfer matters; a model trained on research-grade Xenium may fail on routine Visium	Report separate gaps for Visium→Xenium and Xenium→Visium directions in all cohorts	[Paper] [Paper: PDF p. 17]
Inter-cohort negative transfer may stem from class imbalance, not tissue specificity	When adding LUAD/PRAD to BRCA training, BRCA spots become minority. Performance drop could be due to optimization failure, not inherent tissue conflict	If imbalance is the cause, reweighting or oversampling BRCA spots could rescue performance	Train inter-cohort models with BRCA spot oversampling or class-balanced sampling; compare to original	[Paper] [Paper: PDF p. 18, Fig. 5d]
Cell2location evaluation excludes samples with max PCC < 0.1	This exclusion (stated in Online Methods [Paper] [Paper: PDF p. 35]) removes low-performance cases, potentially inflating reported correlations	Clinical samples often have low signal; excluding them biases assessment toward "easy" cases	Report full distribution of Cell2location PCC, including excluded samples, to quantify failure rate	[Paper] [Paper: PDF p. 35, Online Methods]

14 学到的知识

- **评估即设计**：STP-BENCH证明，严谨的benchmark不是事后验证，而是前置设计——它要求明确定义控制变量（如UNIV2）、多维指标（PCC+ARI+singscore）、现实挑战（cross-tissue）、以及失败模式（negative transfer）。这对用户设计single-cell foundation model benchmark极具启发：必须定义“什么是公平比较”，例如统一scRNA-seq pretraining corpus、统一cell type ontology、统一batch correction强度。
- **数据质量是天花板**：Xenium的高计数直接拉升所有模型PCC 0.2–0.4，说明在virtual ST中，“better model”常是“better data”的代理。这对用户perturbation prediction研究警示：若扰动响应信号微弱（如CRISPR KO后log2FC<0.5），再优架构也难突破信噪比瓶颈，应优先优化湿实验检测灵敏度。

- **多尺度 ≠ 多参数**: TRIPLEX/DeepSpot胜出非因参数量大, 而因显式建模局部 (spot)、邻域 (3×3 grid)、全局 (WSI) 形态上下文。这对用户graph neural networks研究提示: 在spatial transcriptomics GNN中, 应设计多跳邻居聚合 (local)、跨区域图卷积 (regional)、全图池化 (global) 三级结构, 而非堆叠层数。
- **生物学效用需闭环验证**: 仅PCC高不等于可用; 必须通过Cell2location (细胞组成)、SpaGCN (空间结构)、singscore (通路活性) 三重验证。这对用户cross-modal alignment研究意味着: alignment loss最小化不保证下游任务成功, 必须设计task-specific validation modules。
- **负向迁移是警钟**: 简单拼接多癌种数据损害性能, 暗示morphology-to-expression mapping高度组织特异。这对用户multi-omics研究启示: 跨组织整合不能靠数据拼接, 需引入tissue-aware adapters或domain-specific bottlenecks。

15 与既有知识的连接

- **候选连接/方法论连接**: 与single-cell foundation models (如scGPT、CellLM) 的连接在于**评估范式迁移**——STP-BENCH的“统一encoder+多粒度验证”可直接迁移到scRNA-seq foundation model benchmark中, 例如: 固定scGPT作为encoder, 评估下游cell type annotation、trajectory inference、drug response prediction。
- **候选连接/方法论连接**: 与spatial transcriptomics的连接在于**数据构造逻辑**——STP-BENCH将Xenium单分子坐标binning为Visium-scale pseudo-spots ([Paper] [Paper: PDF p. 22]), 此策略可复用于用户将MERFISH/seqFISH+数据对齐至Visium坐标系, 构建跨模态训练集。
- **候选连接/方法论连接**: 与graph neural networks的连接在于**架构启示**——SEPAL ([Paper] [Paper: PDF p. 24]) 的“local prediction + GNN residual correction”范式, 可启发用户设计GNN for perturbation prediction: 以基因共表达图作骨架, 用GNN学习扰动传播残差, 替代纯MLP。
- **弱连接/方法论连接**: 与biomedical AI的连接限于**鲁棒性测试框架**——STP-BENCH的cross-institution/tissue/platform三轴泛化测试, 可抽象为通用医疗AI鲁棒性协议, 但未涉及临床终点 (如生存预测), 故非直接临床连接。
- **弱连接/方法论连接**: 与cell state representation的连接在于**评价粒度**——STP-BENCH的gene set scoring (singscore) 本质上是cell state proxy, 但未像cellxgene那样定义离散state, 故属弱连接。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name**: Tissue-Aware Adapter for Multi-Cancer Virtual ST

originating limitation/observation: Inter-cohort scaling causes negative transfer because morphology-expression mapping is tissue-specific [Paper] [Paper: PDF p. 18, Fig. 5d] **core hypothesis**: Injecting lightweight, tissue-specific adapters into a shared backbone (e.g., TRIPLEX) will enable positive transfer across cancers without sacrificing per-tissue performance. **delta from paper**: STP-BENCH uses monolithic models per dataset; this adds learnable tissue tokens and adapter layers. **initial method**: For each cancer type, add a 64-d tissue token concatenated to PFM embedding; insert LoRA adapters ($r=4$, $\alpha=8$) into TRIPLEX' s fusion encoder. Train end-to-end on BRCA+LUAD+PRAD with tissue-token gating. **validation**: Compare PCC on BRCA test set vs. STP-BENCH' s BRCA-only and BRCA+LUAD+PRAD

baselines; ablate tissue tokens/adapters. **failure modes:** Adapter overfitting to tissue noise; token collapse (all cancers share same token); increased inference latency. **innovation status:** unverified

- **name:** SingScore-Guided Gene Selection for Perturbation Prediction

originating limitation/observation: singscore reveals that immune/stromal genes benefit most from multi-scale reasoning [Paper] [Paper: PDF p. 13, Fig. 3e], suggesting gene sets—not individual genes—are the meaningful units for morphology-driven prediction. **core hypothesis:** Selecting genes based on their singscore predictability (rather than variance/mean) will improve perturbation response prediction from histology. **delta from paper:** STP-BENCH uses HMMVG/marker genes; this proposes a new gene selection criterion grounded in functional coherence. **initial method:** On LUAD-Xenium, compute singscore PCC for all genes; select top-100 high-singscore genes. Train perturbation classifier (e.g., CRISPR KO vs control) using only these genes' expression predicted from H&E. **validation:** Compare AUROC on held-out perturbations vs. HMMVG-selected and random gene sets. **failure modes:** singscore's rank-based nature loses magnitude info critical for perturbation effect size; low-coverage genes excluded despite biological relevance. **innovation status:** unverified

- **name:** SSIM-Regularized Diffusion for Spatially Coherent Virtual ST

originating limitation/observation: SSIM correlates with PCC but captures spatial structure [Paper] [Paper: PDF p. 11, Extended Data Fig. 3]; yet generative models (STFlow/Stem) are trained only on MSE/KL, not structural loss. **core hypothesis:** Adding SSIM as an auxiliary loss during diffusion training will improve spatial domain identification (ARI) without harming spot-level PCC. **delta from paper:** STP-BENCH evaluates SSIM post-hoc; this integrates it into training objective. **initial method:** Modify STFlow's denoising loss: $\mathcal{L} = \lambda_{\text{MSE}} \mathcal{L}_{\text{MSE}} + \lambda_{\text{SSIM}} \mathcal{L}_{\text{SSIM}}$, where $\mathcal{L}_{\text{SSIM}}$ computed on 2D expression grids. Tune λ on NCCHE-LUAD-Xenium. **validation:** Measure ARI on Fig. 4b-c and PCC on Fig. 2c; compare to vanilla STFlow. **failure modes:** SSIM optimization may conflict with MSE, causing blurry predictions; GPU memory overflow from grid computation. **innovation status:** unverified

- **name:** Cross-Platform Calibration Layer for Visium→Xenium Transfer

originating limitation/observation: Cross-platform transfer shows negligible gap, but analysis is asymmetric and ignores quantification bias [Paper] [Paper: PDF p. 17] **core hypothesis:** A lightweight calibration layer (e.g., affine transform) applied to Visium-predicted expression can correct for platform-specific biases, enabling zero-shot Xenium deployment. **delta from paper:** STP-BENCH treats platforms as separate domains; this proposes explicit bias correction. **initial method:** Train a 2-layer MLP on paired Visium/Xenium spots (same tissue) to map Visium-predicted expression → Xenium ground truth. Apply to TRIPLEX outputs. **validation:** Compare PCC/ARI on Xenium test set before/after calibration; ablate MLP layers. **failure modes:** Requires paired Visium/Xenium data (rare); calibration may overfit to specific cancer types. **innovation status:** unverified