

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Correlation-Guided Flow Matching with Annealed Masking for Spatial Transcriptomics Generation	[Paper] [Paper: PDF p. 1]
Authors	Yupei Zhang, Hao Chen, Li Pan, Chao Li, Xiaohan Xing	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.LG)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-01	[Paper] [Paper: PDF p. 1]
Core task	Histology-to-ST prediction (conditional generation of spatial gene expression from H&E images)	[Paper] [Paper: PDF p. 1–2]
Method name	CorrFlow	[Paper] [Paper: PDF p. 1]
Key innovation	Annealed masked flow matching + gene graph-regularized optimization	[Paper] [Paper: PDF p. 1–2]
Primary evaluation metric	PCC (Pearson correlation coefficient) and HPCC (Hallmark-Gene PCC) on HMMVG-50 genes	[Paper] [Paper: PDF p. 7–8, Table 1]
Benchmark datasets	HEST-1K (10 cancer-type datasets), STImage-1K4M (Brain, Breast)	[Paper] [Paper: PDF p. 7, Table 9]
Baseline comparator	STFlow [11] (flow-matching baseline), Stem [40], TRIPLEX, BLEEP, ST-Net	[Paper] [Paper: PDF p. 7, Table 1]

02 一句话总结

CorrFlow 是首个将基因共表达图结构显式嵌入条件流匹配（CFM）框架的 histology-to-ST 生成方法，通过**渐进式掩码策略**（annealed masking）和**基因图正则化**（gene graph regularization）双路径建模基因间依赖关系。它不把每个基因当作独立预测目标，而是强制模型在推理时联合建模相关基因——既提升单基因空间表达预测精度（PCC $\uparrow$ 0.013），更显著增强通路级生物一致性（HPCC $\uparrow$ 0.015），且在 HMMVG-100/150/200 扩展基因集上保持稳定增益。该设计直击现有生成模型“忽略基因互作”的结构性缺陷，为 spatial transcriptomics 的生物可信生成提供了可验证、可解耦的方法论范式。

03 研究问题

论文聚焦于一个根本性建模失配：当前基于扩散或流匹配的 histology-to-ST 生成模型虽定义了基因表达的联合分布，但其标准训练目标（如 Eq. 2 / Eq. 3）在数学上**强制分解为 G 个独立的 per-gene 损失项** [Paper] [Paper: PDF p. 4, Prop. 1]。这导致优化过程对基因间协变结构无激励——即使网络共享参数，也无法保证学习到生物学真实的共表达模式。因此，研究问题明确为：**如何重构生成模型的训练动力学，使其显式鼓励跨基因联合建模，而非仅优化边缘预测？** 这一问题不是工程调优问题，而是由 Proposition 1 严格证明的理论局限，必须从目标函数层面解决。

04 研究背景与发展路径

背景始于 ST 技术高成本与 histology 图像易获取之间的张力，催生了从 H&E 预测 ST 的范式迁移：早期为确定性回归（ST-Net），后转向检索（BLEEP）、再升级为生成建模（Stem、STFlow）。但所有生成方法均沿用标准 CFM 或扩散目标，其 per-dimension 分解特性 [Paper] [Paper: PDF p. 4, Prop. 1] 成为瓶颈。作者指出，这一缺陷被长期忽视，因多数工作聚焦于图像编码器或空间建模，而未审视生成动力学本身是否适配生物学先验。发展路径由此清晰分叉：既有工作优化“如何更好编码 histology”，而 CorrFlow 转向优化“如何更好定义生成目标”——将基因互作从后处理（如结果聚类）前移至训练损失中，形成“目标驱动的生物约束”。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper		
Per-gene decomposition of training objective	Uneven gene-level performance; correlated genes (e.g., x_{31} in Fig. 1) predicted poorly despite accurate prediction of others (x_{11}, x_{21})	Standard CFM loss decomposes as sum over genes (Eq. 3), so optimal predictor for gene g depends only on marginal $*p(x_{1^g} \setminus$	$x_t, t, c)$, <i>not joint</i> $p(x_{1^{(M)}} \setminus$	$x_1^{(O)}, c)^*$ [Paper] [Paper: PDF p. 4–5]	[Paper] [Paper: PDF p. 2, Fig. 1 caption]; [Paper] [Paper: PDF p. 4, Prop. 1 & proof]; [Paper] [Paper: PDF p. 5, Remark 1]
Shortcut reconstruction near $t=1$	Network copies $x_t \approx x_1$ instead of learning transport dynamics	As $t \rightarrow 1$, linear interpolant $x_t \rightarrow x_1$, providing trivial reconstruction signal [Paper] [Paper: PDF p. 5]	[Paper] [Paper: PDF p. 5, § 3.2.1]; [Paper] [Paper: PDF p. 2, Fig. 1 “Diffusion/Flow Matching” panels show inconsistent trajectories]		
Lack of biological structure enforcement in output space	Predictions may violate known co-expression modules or pathway coherence	Finite capacity and noisy gradients cause violations of prior knowledge, even if input conditioning is rich [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6, § 3.3 intro]; [Paper] [Paper: PDF p. 9, Fig. 3(c) shows gains concentrated on high AvgAbsCorr genes]		

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Over-reliance on single-source priors	WGCNA alone lacks generalizability; STRING alone lacks dataset-specificity	Data-driven co-expression (WGCNA) captures context-specific modules but is noisy; functional prior (STRING) is stable but static [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6, § 3.3.1]; [Paper] [Paper: PDF p. 8, Table 2 ablation: w/o WGCNA → PCC 0.607, w/o STRING → 0.604]

06 核心思想

核心思想是**将基因互作从隐式归纳偏置 (implicit inductive bias) 升格为显式训练约束 (explicit training constraint)**。作者不满足于让大模型“可能学会”依赖，而是通过两个正交机制“强制建模”：(1) **动态掩码打破输入-输出对应**——在流匹配的 x_t 输入中渐进遮蔽基因，使模型无法依赖被遮蔽维度的自身历史值，被迫从剩余基因推断，从而将最优解从 $E[x_1^g \mid x_t, t, c]$ 推向 $E[x_1^{(M)} \mid x_1^{(O)}, c]$ (Prop. 2)；(2) **图正则化锚定输出空间**——融合 STRING（功能先验）与 WGCNA（数据驱动共表达）构建基因亲和图，用 Huber 局部平滑项 (Eq. 11) 和 Laplacian 全局平滑项 (Eq. 12) 双重约束预测表达向量 $\hat{x}_1$ ，使其在图谱上呈现低频、一致的响应模式。二者协同：前者重塑学习信号，后者稳定输出结构。

07 方法总览

CorrFlow 将 histology-to-ST 生成建模为**条件流匹配 (CFM)**，但彻底重构其训练范式。给定 histology 特征 z 、空间坐标 q 、时间步 t 和线性插值 $x_t = (1-t)x_0 + t x_1$ (Eq. 1)，标准 CFM 直接以 x_t 为输入预测 x_1 ；CorrFlow 则：(1) 对 x_t 应用 **timestep-dependent annealed masking** (Eq. 8)，生成掩蔽输入 $\tilde{x}_t$ (Eq. 5)，迫使模型从可见基因推断掩蔽基因；(2) 用 **gene graph-regularized objective** (Eq. 16) 替代单一重建损失，其中图正则项 $L_{graph} = \rho L_{local} + \lambda L_{global}$ (Eq. 12) 作用于最终预测 $\hat{x}_1$ 。整个流程在 Algorithm 1 中形式化，其本质是**用掩码制造“信息缺口”，用图结构提供“生物指南针”，共同引导模型学习基因间的条件依赖**。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Annealed Masking Schedule	Progressively increases masking ratio $p(t) = p_{max} \cdot t$ to prevent shortcut copying near $t=1$ and enforce cross-gene inference	Standard CFM suffers from $t \rightarrow 1$ shortcut (copying $x_t \approx x_1$); independent masking fails to incentivize joint modeling [Paper] [Paper: PDF p. 5]	Input: x_t, t ; Output: masked $\tilde{x}_t$ where $g \in M$ replaced by learnable token m_g (Eq. 5, 8)	[Paper] [Paper: PDF p. 2, Fig. 1 “Ours”]; [Paper] [Paper: PDF p. 5, Prop. 2 proof]; [Paper] [Paper: PDF p. 8, Table 2: w/o masking → PCC 0.609]	Severe degradation in high-correlation gene prediction (Fig. 3c); increased shortcut behavior near $t=1$ (Table 3: $f(t)=1-t$ worst)

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Gene Graph Construction	Fuses STRING functional prior $S^{(s)}$ and WGCNA data-driven co-expression $S^{(w)}$ via weighted average $S = \alpha S^{(s)} + (1-\alpha) S^{(w)}$ (Eq. 9) to build robust gene affinity matrix	Neither prior alone suffices: STRING lacks context, WGCNA is noisy/dataset-specific [Paper] [Paper: PDF p. 6]	Input: STRING DB, training x_i ; Output: sparsified/symmetrized $S \in \mathbb{R}^{G \times G}$	[Paper] [Paper: PDF p. 6, § 3.3.1]; [Paper] [Paper: PDF p. 8, Table 2: w/o STRING $\rightarrow$ 0.604, w/o WGCNA $\rightarrow$ 0.607]; [Paper] [Paper: PDF p. 9, Table 3: $\alpha=0.6$ optimal]	Reduced biological coherence (lower HPCC); weaker GGC-Pearson (Table 7: Ours 0.648 vs STFlow 0.633)
Local Graph Constraint (L_{local})	Enforces pairwise consistency among graph-connected genes using Huber penalty on z-scored predictions $z_i - z_j$ (Eq. 11)	Edges encode functional links; local smoothness ensures co-regulated genes have similar standardized expression	Input: $\hat{x}_i, n, S$; Output: scalar loss term	[Paper] [Paper: PDF p. 6, § 3.3.2]; [Paper] [Paper: PDF p. 7, Eq. 11]; [Paper] [Paper: PDF p. 15, Table 5: w/o $L_{local} \rightarrow$ PCC 0.605]	Increased gene-wise variance; breakdown of module-level expression patterns (e.g., KRT7 spatial gradients in Fig. 3a less sharp)
Global Graph Constraint (L_{global})	Enforces global smoothness via normalized graph Laplacian L , penalizing rapid oscillations in $\hat{x}_i, n$ across the gene graph (Eq. 12)	Captures large-scale co-expression modules missed by pairwise terms; aligns output with low-frequency eigenmodes of G	Input: $\hat{x}_i, n, L$; Output: scalar loss term	[Paper] [Paper: PDF p. 6–7, § 3.3.2]; [Paper] [Paper: PDF p. 7, Eq. 12]; [Paper] [Paper: PDF p. 15, Table 5: w/o $L_{global} \rightarrow$ PCC 0.609]	Loss of pathway-level coordination; HPCC gain diminishes disproportionately (Table 1: HPCC $\uparrow$ 0.015 vs PCC $\uparrow$ 0.013)
Learnable Mask Token	Replaces masked genes with trainable vector $m \in \mathbb{R}^G$, not fixed zero, to avoid train-inference magnitude mismatch	Fixed zero masking reduces input norm by $p(t)$, causing instability during inference when no masking applied [Paper] [Paper: PDF p. 5]	Input: mask set M ; Output: m_g for $g \in M$	[Paper] [Paper: PDF p. 5, § 3.2.1]; [Paper] [Paper: PDF p. 14, Algorithm 1 line 4]	Training instability, slower convergence, lower final PCC (not directly ablated but implied in design rationale)

09 关键公式与符号

- 无完整可核验的端到端生成公式；核心是损失函数组合（Eq. 16），非闭式采样公式。
- 关键符号与指标：
- x_0 : ZINB prior sample [Paper] [Paper: PDF p. 3]
- x_i : Ground-truth ST expression vector ($\mathbb{R}^G$) [Paper] [Paper: PDF p. 4]
- x_t : Linear interpolant $(1-t)x_0 + t x_i$ (Eq. 1) [Paper] [Paper: PDF p. 4]
- $\tilde{x}_t$: Masked input, with $g \in M$ replaced by m_g (Eq. 5) [Paper] [Paper: PDF p. 5]

- $p(t)$: Annealed masking ratio = $p_{max} \cdot t$ (Eq. 8) [Paper] [Paper: PDF p. 5]
- S : Fused gene affinity matrix = $\alpha S^{(s)} + (1-\alpha) S^{(w)}$ (Eq. 9) [Paper] [Paper: PDF p. 6]
- L : Normalized graph Laplacian = $I - A$, $A = D^{-1/2} S D^{-1/2}$ (Eq. 10) [Paper] [Paper: PDF p. 6]
- r_g : Gene-wise PCC = $cov(\hat{y}_{:,g}, y_{:,g}) / (\sigma(\hat{y}_{:,g}) \sigma(y_{:,g}))$ (Eq. 17) [Paper] [Paper: PDF p. 14]
- $HPCC$: Hallmark-Gene PCC = $(1/|K|) \sum_{k \in K} (1/|P_k \cap G|) \sum_{g \in P_k \cap G} r_g$ (Eq. 13), $K = \{k : |P_k \cap G| \geq 5\}$ [Paper] [Paper: PDF p. 7]
- $GGC\text{-}Pearson$: Correlation between $\text{vec}\triangle(\hat{C})$ and $\text{vec}\triangle(C)$, where $\hat{C}_{\{g,h\}} = \text{corr}(\hat{y}_{:,g}, \hat{y}_{:,h})$ (Eq. 19) [Paper] [Paper: PDF p. 15]
- $MSE\text{-}Mean$: $(1/G) \sum_g MSE_g$, $MSE_g = (1/N) \sum_i (\hat{y}_{\{ig\}} - y_{\{ig\}})^2$ (Eq. 21, 22) [Paper] [Paper: PDF p. 15–16]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Main benchmark (Table 1)	CorrFlow > STFlow on average PCC/HPCC across 10 HEST-1K datasets	Same HMMVG-50 genes, patient-stratified CV, identical backbone architecture	PCC: 0.613 vs 0.600; HPCC: 0.628 vs 0.613; $p < 0.05$ for all pairwise Wilcoxon tests (Table 12)	Annealed masking + graph regularization improves both numerical accuracy and biological coherence	Not that CorrFlow is universally superior on all genes/datasets (e.g., PRAD PCC gain small: 0.495 vs 0.494)	[Paper] [Paper: PDF p. 8, Table 1]; [Paper] [Paper: PDF p. 19, Table 12]
Ablation study (Table 2)	Each component contributes uniquely	Remove one module at a time; same HMMVG-50, 10-dataset avg	w/o masking: 0.609; w/o L_{graph} : 0.605; full model: 0.613	Both masking and graph regularization are necessary and complementary; graph term has larger impact	Not that masking is unimportant—it enables the dependency-aware signal critical for HPCC gain	[Paper] [Paper: PDF p. 8, Table 2]; [Paper] [Paper: PDF p. 9, Fig. 3b/c]
Hyperparameter study (Table 3)	$p_{max}=0.75$ and $\alpha=0.6$ are optimal	Vary p_{max} , masking schedule $f(t)$, fusion weight α on HMMVG-50	$p_{max}=0.75$ best; $f(t)=t > f(t)=0.75 > f(t)=1-t$; $\alpha=0.6$ best	Annealing must be strong enough to expose dependencies but not erase context; STRING prior should slightly dominate WGCNA	Not that $\alpha=0.6$ is globally optimal—optimal α may vary by tissue type (not tested)	[Paper] [Paper: PDF p. 9, Table 3]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Expanded gene sets (Table 4)	Gain persists beyond HMMVG-50	Evaluate on HMMVG-100/150/200; same conditions as main benchmark	PCC: +0.007 (100), +0.009 (150), +0.005 (200); HPCC: +0.003, +0.006, +0.002	Dependency-aware design scales to broader, biologically richer gene sets	Not that gain increases with gene count—margin stabilizes/decreases slightly	[Paper] [Paper: PDF p. 14, Table 4]; [Paper] [Paper: PDF p. 17, C.1]
GGC-Pearson (Table 7)	CorrFlow better preserves gene-gene correlation structure	Compare $\text{corr}(\text{vec}\triangle(\hat{C}), \text{vec}\triangle(C))$ on HMMVG-50	0.648 vs STFlow 0.633 (avg); wins on 7/10 datasets	Explicit gene dependency modeling improves structural fidelity beyond per-gene metrics	Not that GGC-Pearson is the sole arbiter of biological quality—other structures (e.g., spatial autocorrelation) not measured	[Paper] [Paper: PDF p. 17, Table 7]; [Paper] [Paper: PDF p. 15, § B]
Supplementary STImage-1K4M (Table 9)	Benefit extends to larger, non-benchmark ST collections	Brain/Breast subsets; random 8:1:1 split (no patient stratification)	PCC: 0.542 vs STFlow 0.530; HPCC (Breast only): 0.473 vs 0.464	Method generalizes beyond HEST-1K’s controlled setting	Not clinical robustness—no external cohort validation (acknowledged in Appendix D)	[Paper] [Paper: PDF p. 18, Table 9]; [Paper] [Paper: PDF p. 19, C.3]

11 对结论的正确理解

CorrFlow 的核心结论是**方法论有效性**，而非绝对性能霸权：它确证了“显式建模基因依赖”这一设计原则能带来统计显著且生物可解释的增益（PCC +0.013, HPCC +0.015, GGC-Pearson +0.015），但增益幅度温和（~2% relative），且高度依赖于基准设置（如 HEST-1K 的 patient-stratified CV）。其成功源于对 Proposition 1 揭示的理论缺陷的精准修补，而非黑箱性能突破。例如，HPCC 的更大提升（+0.015 vs PCC +0.013）直接印证了“通路级一致性改善优于单基因精度”的设计预期；而 Table 4 中 HMMVG-200 增益收窄，说明依赖建模的边际效益随基因数增加而递减。结论应理解为：**在现有生成范式下，引入生物结构约束是稳健、可复现、且方向正确的改进路径，但并非万能解药。**

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Lack of external cohort validation	Evaluation uses HEST-1K (cross-platform but internal) and STImage-1K4M (no standardized splits); no fully independent external cohort tested	Incorporate independently collected ST cohorts to assess clinical robustness under variations in tissue prep, sequencing platform, staining, scanner, cohort composition	[Paper] [Paper: PDF p. 19, Appendix D]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Insufficient clinical translation readiness	Prediction quality remains insufficient for direct clinical use due to intrinsic challenge of inferring molecular states from morphology alone	Improve robustness via stronger dependency-aware modeling and higher-quality ST training data	[Paper] [Paper: PDF p. 19, Appendix D]
Downstream utility unassessed	Current evaluation focuses on reconstruction fidelity (PCC, GGC) and structure preservation, not biological/clinical utility	Assess generated ST profiles in downstream tasks: tissue-domain identification, pathway activity estimation, biomarker discovery, patient stratification, prognosis modeling	[Paper] [Paper: PDF p. 19–20, Appendix D]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The "annealed masking" (Eq. 8) couples masking ratio $p(t)$ linearly to t , but the theoretical justification (preventing shortcut) does not require linearity—any increasing $p(t)$ would suffice. The choice $p(t)=p_{max} \cdot t$ appears empirically driven (Table 3), not theoretically mandated.	Non-linear schedules (e.g., quadratic $p(t)\propto t^2$) might better match the true difficulty curve of inference, as early t may need more aggressive masking to break initial independence assumptions.	If linear annealing is suboptimal, the reported gains could be inflated by hyperparameter tuning rather than fundamental design superiority. It risks conflating schedule choice with core masking principle.	Run ablation on $p(t)=t^2$, $p(t)=\sqrt{t}$, and compare against $p(t)=t$ under identical p_{max} and seeds; measure not just PCC but also gene-level variance reduction (to probe dependency strength).	[Paper] [Paper: PDF p. 5, Eq. 8]; [Paper] [Paper: PDF p. 9, Table 3 shows $f(t)=t$ best but doesn't test non-linear forms]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The gene graph S fuses STRING and WGCNA (Eq. 9), but STRING's "functional associations" include indirect/low-confidence links, while WGCNA's co-expression is sensitive to batch effects and normalization. The weighted average $\alpha S^{(s)} + (1-\alpha) S^{(w)}$ treats both matrices as equally reliable, ignoring their distinct uncertainty profiles.	This fusion may propagate noise from either source, especially in low-coverage genes or tissues with weak co-expression signals. The optimal α (0.6) may reflect noise suppression rather than biological weighting.	Biologically misleading edges could misguide the Laplacian regularizer (Eq. 12), harming rather than helping global smoothness, particularly in heterogeneous tissues like HCC (where CorrFlow's PCC gain is largest: +0.051).	Replace simple averaging with uncertainty-aware fusion: e.g., $S = (\alpha / \sigma_s^2) S^{(s)} + ((1-\alpha) / \sigma_w^2) S^{(w)}$, where σ_s^2, σ_w^2 are estimated variances of edge weights; validate on datasets with known gold-standard modules.	[Paper] [Paper: PDF p. 6, Eq. 9]; [Paper] [Paper: PDF p. 6, § 3.3.1 mentions "stable prior" vs "dataset-specific"]; [Paper] [Paper: PDF p. 8, Table 2 shows WGCNA/STRING removal hurts performance]
The Huber penalty (Eq. 11) uses a fixed threshold β , but gene expression dynamic ranges vary widely across genes (e.g., housekeeping vs low-abundance TFs). Applying the same β to z-scored $z_i - z_j$ may over-penalize biologically meaningful variation in high-variance genes.	This could artificially flatten expression differences in key regulatory genes, reducing predictive power for functionally critical but variable markers. It assumes uniform biological tolerance for deviation, which contradicts known gene-specific regulation.	May explain why gains are modest on some datasets (e.g., READ PCC +0.021) and why HPCC gains exceed PCC gains—the Huber term prioritizes pathway-level consistency over individual gene extremes.	Implement gene-specific β_g proportional to running EMA of σ_g (already computed for z-scoring); compare PCC/HPCC trade-off and inspect top-performing genes in Fig. 3c.	[Paper] [Paper: PDF p. 6, Eq. 11]; [Paper] [Paper: PDF p. 6, mentions z-scoring with EMA estimates μ_i, σ_i]; [Paper] [Paper: PDF p. 9, Fig. 3c shows gains on high AvgAbsCorr genes]

14 学到的知识

- **流匹配的 per-dimension 分解是硬性数学约束，非实现缺陷：** Proposition 1 严格证明标准 CFM 损失必然分解为 G 个独立项，这决定了任何仅靠增大模型容量都无法根本解决基因依赖建模问题——必须修改目标函数本身。
- **掩码是诱导联合建模的通用接口：** Annealed masking 不是 ST 领域专属技巧，其核心是“制造可控的信息缺口”，可迁移到任何需建模变量间条件依赖的生成任务（如 multi-omics imputation、cell state trajectory modeling）。
- **图正则化的尺度分离价值：** L_{local} (Huber on edges) 和 L_{global} (Laplacian on spectrum) 不是冗余，而是分别约束微观 (pairwise) 和宏观 (module-level) 结构，这种双尺度设计对生物系统建模尤为关键。
- **评估必须匹配假设：** 论文用 HPCC 和 GGC-Pearson 直接检验“生物一致性”假设，而非仅报告 PCC——这提示我们：若提出“提升生物意义”的方法，必须设计对应的、不可被 PCC 单一指标替代的评估协议。

- **超参敏感性揭示设计意图:** $p_{max}=0.75$ 最优 (Table 3) 表明: 掩码需足够强以暴露依赖, 但不能过强致上下文丢失; $\alpha=0.6$ 表明外部先验 (STRING) 略重于数据驱动 (WGCNA), 反映作者对泛化性的重视。

15 与既有知识的连接

- **候选连接/方法论连接:**
- *single-cell foundation models:* CorrFlow' s gene graph construction (STRING+WGCNA) parallels scFoundation' s use of gene co-expression graphs for pretraining; its annealed masking could inspire masked autoencoding for scRNA-seq foundation models to enforce gene dependencies during representation learning.
- *spatial transcriptomics:* Direct extension of STFlow [11]—same backbone, different loss—making it a natural upgrade path; the HMMVG-50/100/150/200 ablations provide a template for evaluating gene-panel scalability in other ST methods.
- *graph neural networks:* The fused gene graph S and Laplacian L (Eq. 10, 12) are standard GNN inputs; CorrFlow demonstrates how GNN-style regularization can be embedded into generative dynamics, not just discriminative models.
- *multi-omics:* The dual-prior fusion (STRING functional + WGCNA co-expression) mirrors strategies in multi-omics integration (e.g., MOFA+), suggesting applicability to predicting ST from multi-modal inputs (e.g., histology + proteomics).
- *biomedical AI:* The explicit focus on HPCC (MSigDB Hallmark pathways) and GGC-Pearson provides a blueprint for developing clinically interpretable evaluation metrics beyond accuracy.
- **弱连接/方法论连接:**
- *perturbation prediction:* While CorrFlow predicts steady-state ST, its dependency-aware loss could be adapted to predict perturbation responses by masking genes representing knockouts/knockdowns and conditioning on perturbation vectors.
- *cell state representation:* The annealed masking strategy—inferring masked genes from context—mirrors how cell state representations should allow imputation of missing modalities (e.g., RNA from ATAC), suggesting cross-task methodological transfer.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name:** Adaptive Graph-Aware Annealing

originating limitation/observation: [Analysis] The fixed linear annealing $p(t)=p_{max} \cdot t$ lacks theoretical grounding and may not match the true difficulty of dependency inference; Table 3 shows $f(t)=t$ best but doesn' t explore adaptive alternatives. **core hypothesis:** Inference difficulty for gene g depends on its connectivity in the gene graph S ; highly connected genes (hubs) should be masked earlier/more frequently to force stronger dependency exploitation. **delta from paper:** Replace global $p(t)$ with gene-specific $p_g(t) = p_{max} \cdot t \cdot \text{deg}(g)/\text{max_deg}$, where $\text{deg}(g)$ is node degree in S . **initial method:** Compute S once; compute $\text{deg}(g)$; modify Algorithm 1 line 3 to sample M with probability $p_g(t)$ per gene. **validation:** Compare PCC/HPCC on HEST-1K; analyze gene-level PCC gain distribution (should

concentrate on high-*deg* genes). **failure modes:** Over-masking hubs may destabilize training; degeneracy in S (many genes with same *deg*) reduces adaptivity. **innovation status:** unverified

- **name:** Uncertainty-Calibrated Graph Fusion

originating limitation/observation: [Analysis] Simple weighted average $\alpha S^{(s)} + (1-\alpha) S^{(w)}$ ignores differing uncertainties in STRING (curated but incomplete) and WGCNA (noisy but context-specific); optimal $\alpha=0.6$ may reflect noise suppression. **core hypothesis:** Fusion weights should be inversely proportional to per-edge uncertainty estimates, making the graph more robust to low-confidence links. **delta from paper:** Replace Eq. 9 with $S = (w_s / \sigma_s^2) S^{(s)} + (w_w / \sigma_w^2) S^{(w)}$, where σ_s^2, σ_w^2 are estimated variances of edge weights from STRING confidence scores and WGCNA bootstrap resampling. **initial method:** Extract STRING confidence scores; run WGCNA with 100 bootstrap replicates to estimate σ_w^2 per edge; set w_s, w_w to normalize total weight. **validation:** Measure stability of L_{global} penalty (Eq. 12) across folds; compare HPCC on pathways enriched for high-uncertainty genes. **failure modes:** Uncertainty estimation adds computational overhead; poor calibration of σ_s^2 could worsen fusion. **innovation status:** unverified

- **name:** Multi-Scale Gene Graph Regularization

originating limitation/observation: The current L_{local} (edge-based Huber) and L_{global} (Laplacian) operate at two scales, but biological modules exist hierarchically (e.g., protein complexes $\rightarrow$ pathways $\rightarrow$ hallmarks). **core hypothesis:** Adding a mid-scale regularizer targeting predefined modules (e.g., MSigDB Hallmark sets) will further improve HPCC without degrading PCC. **delta from paper:** Introduce $L_{module} = \gamma \sum_{k \in K} \|\Pi_k \hat{x}_1\|^2$, where Π_k is projection onto Hallmark set P_k , and γ is new hyperparameter. **initial method:** Precompute Π_k for each Hallmark set in K ; add L_{module} to Eq. 16. **validation:** Ablate L_{module} ; check HPCC gain on K and PCC on all genes; ensure no over-smoothing (monitor MSE-Mean in Table 8). **failure modes:** Over-constraining may reduce flexibility for novel/unannotated modules; Π_k may be ill-conditioned for small P_k . **innovation status:** unverified