

```
> Source coverage: Full paper
> Extraction confidence: High
> Locator mode: page-grounded
> Primary analytical lens: methods
> Secondary analytical lens: discovery
> Context verification: Paper-only
> Card completeness: Complete relative to supplied source
```

01 基本信息

```
- **Title**: Learning Interpretable Tumor Microenvironment
  Representations by Fitting Pan-Cancer Cell State-Niche Correlation
- **Authors**: Xiao Xiao, Jiashu He, Shiyang Zhang, Meiyi
  Mao
- **Source**: arXiv preprint (v1), 2026-08-26
- **URL**: http://arxiv.org/abs/2608.26208v1
- **PDF URL**: https://arxiv.org/pdf/2608.26208v1
- **Model name**: GITIII-scale (graph inductive bias trans-
  former for intercellular interaction investigation-scale)
  [Paper: PDF p. 2]
- **Core data**: Pan-cancer specimen-matched imaging-based
  spatial transcriptomics (IST) and scRNA-seq (4,254,069 sp-
  atial cells; imputed to 20,000-gene vocabulary) [Paper: PD-
  F p. 2, p. 5, p. 23]
- **Key modalities**: IST (CosMx, Xenium, MERFISH; 312-6,1-
  75 genes), scRNA-seq (full transcriptome), integrated via
  SpaLM [Paper: PDF p. 2, p. 5, p. 7, p. 23]
- **Target biological problem**: Cell state-niche correlat-
  ion — quantifying how much a cell's deviation from its cel-
  l-type mean expression ( $z_i = x_i - \mu_t(i)$ ) is attributable to
  neighboring cells [Paper: PDF p. 1-3, Eq. 1]
- **Not verified**: Institutional affiliations beyond auth-
  or footnotes (e.g., “Yale University”), formal journal ve-
  nue, code/data repository URLs (though GitHub link appears
  in Reproducibility Statement [Paper: PDF p. 11], it is no-
  t independently verified from external sources).
```

02 一句话总结

GITIII-scale 是首个可解释的、层级化泛癌空间转录组基础模型，通过将 sender-receiver 细胞对、距离与直接接触建模为 token，采用双层 transformer 架构（一层可加性图 transformer 实现基因级可分解影响张量 $l(g)_{ij}$ ，一层多层图 transformer 生成 TME embedding），在 specimen-matched scRNA-seq + IST 数据上自监督预训练，以预测细胞状态偏差 z_i ，并在未见癌症类型中更准确恢复 niche-associated state 变化，同时支持 LR 轴归因分析 [Paper: PDF p. 1-2, p. 4-5, Fig. 1, Fig. 2]。

03 研究问题

```
- 如何从空间分辨的单细胞数据中，**无偏地量化细胞状态 ( $z_i$ ) 与其局部 niche 的因果性关联强度**，而非仅识-
  别共表达的 ligand-receptor 对？[Paper: PDF p. 1-2]
- 如何构建一个**可扩展、可迁移、且具备单细胞/单基因级可解释性**的基础模型，使其能泛化至未见癌症类型与平台，同-
  时克服现有 spatial foundation models 无法建模 cell state-niche correlation 的缺陷？[Paper: PDF p. 1-2, p. 8]
- 如何在缺乏 ground truth 的情况下，**将模型学习到的 niche influence 张量  $l(g)_{ij}$  与已知的 ligand-receptor 生物化学知识桥接**，实现可验证的通路级生物学解释？[Paper:
  PDF p. 6-7, Fig. 1c]
```

04 研究背景与发展路径

- **临床驱动**：肿瘤微环境（TME）中细胞状态受邻近细胞调控（如 VEGF→KDR 驱动内皮增殖），识别 dysregulated CCI 是靶点发现核心 [Paper: PDF p. 1-2] .
- **技术缺口**：scRNA-seq 提供全转录组但丢失空间；IST 提供单细胞空间但仅测 panel (312-6, 175 genes)；二者配对 (specimen-matched) 是唯一能同时获得 niche + full-state 的方案 [Paper: PDF p. 2] .
- **方法学演进**：
 - *CCI inference tools* (CellPhoneDB, NicheNet, LIANA+)：基于统计检验或先验网络打分 LR 对，**不建模下游转录效应** [Paper: PDF p. 2, p. 17] .
 - *Spatial foundation models* (TERRA, HEIST, Novae, SpatialFormer)：目标为组织结构、空间域或细胞身份，**非 cell state-niche correlation**；其嵌入无法分解为 sender-specific, gene-specific influence [Paper: PDF p. 2, p. 8, p. 15-16] .
 - *Dataset-specific graph models* (NCEM, GITIII)：可建模 state-niche 关联，但**无法跨样本迁移**，每个新数据集需重训练 [Paper: PDF p. 2, p. 17-18] .
 - **本文定位**：GITIII-scale 是 GITIII 的泛癌扩展，通过架构解耦 (additive head + niche head)、pan-cancer 预训练、full-transcriptome imputation，弥合了可解释性、可迁移性与生物学深度之间的鸿沟 [Paper: PDF p. 2, p. 17-18] .

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation
Evidence from the paper		
-----	-----	-----
-----	-----	-----
Lack of cell state-niche correlation modeling Existing spatial foundation models are "perfectly domain-discriminative while carrying no information about how the niche shifted the receiver's state" [Paper: PDF p. 2]; their embeddings cannot be decomposed into directional CCIs [Paper: PDF p. 2]. Their self-supervised objectives target tissue architecture, spatial domains, or expression similarity — none of which measures zi's dependence on Ni [Paper: PDF p. 2]. "A model can therefore be perfectly domain-discriminative while carrying no information about how the niche shifted the receiver's state..." [Paper: PDF p. 2]		
Partial biological measurement Models trained on spot-level data blur cell-level correlation; models trained on IST alone see only a "panel-sized slice of the biology", missing ligands/receptors outside the panel [Paper: PDF p. 2]. Neither scRNA-seq nor IST alone provides both single-cell resolution and full transcriptome; paired data removes this dilemma [Paper: PDF p. 2]. "Neither technique alone captures both the niche and the state it induces — but profiling the same specimen with both does..." [Paper: PDF p. 2]		
Non-transferable CCI modeling Previous deep learning CCI methods (e.g., Xiao et al., 2025; Li et al., 2023a) are dataset-specific and "have not being scaled up or trained in a large corpus to learn generalizable CCI features" [Paper: PDF p. 2]. They lack pan-cancer pretraining and full-transcriptome alignment, preventing knowledge transfer across tissues [Paper: PDF p. 17-18]. "GITIII is fit		

ted to a single dataset at a time, so nothing it learns in one tissue transfers to the next..." [Paper: PDF p. 17] |

| ****Interpretability-accuracy trade-off**** | Conventional CI analysis identifies candidate LR events but "does not model their downstream transcriptional consequences at single-cell level" [Paper: PDF p. 3]; interpretable models often sacrifice accuracy [Paper: PDF p. 9]. | Additivity enables exact decomposition ($l(g)_{ij}$), but limits higher-order effects (e.g., co-presence requirements); non-additive models lose per-sender attribution [Paper: PDF p. 5, p. 9]. |

"Additivity makes the first head interpretable, but also limits it... a sum of influence... cannot express the effect that requires a combination of neighbors..." [Paper: PDF p. 5]; "Exact decomposability therefore costs almost nothing in accuracy" [Paper: PDF p. 9]. |

06 核心理念

- ****Cell state-niche correlation as primary signal****: Define $z_i = x_i - \mu_t(i)$ as the target, isolating niche-driven deviation from cell-type baseline, avoiding confounding by batch effects or panel sensitivity [Paper: PDF p. 3, Eq. 1; p. 5].
- ****Hierarchical, dual-head architecture****:
 - ***Level 1 (Interpretable)***: A single-layer graph transformer (no FFN) computes per-gene, per-sender influence $l(g)_{ij}$ via normalized attention, ensuring $\hat{z}^{(1)}(g)_i = \sum_j l(g)_{ij}$ is an ****exact, additive decomposition****, enabling sender- and gene-level attribution [Paper: PDF p. 4-5, Eq. 6, Fig. 1b].
 - ***Level 2 (Expressive)***: A multi-layer graph transformer reads the same tokens to generate h_i (TME embedding), capturing higher-order interactions (e.g., combinatorial signals) that additive sum cannot [Paper: PDF p. 5, Eq. 7, Fig. 1b].
- ****Bridging data-driven influence and prior biology****: The influence tensor $l(g)_{ij}$ is not biologically annotated; pathway attribution uses external LR databases (CellChat, NeuronChat) + data-driven distance scalars $sc_{g(d)}$ + weighted LASSO to link $l(g)_{ij}$ to specific (ℓ, r) axes [Paper: PDF p. 6-7, Fig. 1c].
- ****Pan-cancer foundation via specimen-matched data****: Pretraining on 4.25M cells from 4 tumor contexts/2 platforms, enabled by SpaIM-based imputation to shared 20k-gene space, allows transfer to unseen cancers/platforms [Paper: PDF p. 2, p. 5, p. 7, p. 23].

07 方法总览

GITIII-scale 是一个自监督、层级化、图增强的 transformer 模型, 输入为 masked cellular neighborhoods N_i ($k=49$ neighbors + receiver), 输出为: (1) gene-level influence tensor $l \in \mathbb{R}^{N \times k \times G}$ (additive head), (2) TME embedding $h_i \in \mathbb{R}^{1024}$ (graph transformer head). 核心流程:

1. ****Input construction****: For each (receiver i , sender j) pair, tokenize:
 - Sender expression $x_j \rightarrow S_j \in \mathbb{R}^{32 \times 256}$ (via MLPs_{nd})

- Receiver expression $x_i \rightarrow R_i \in \mathbb{R}^{32 \times 256}$ (via MLPrec)
- Distance $d_{ij} \rightarrow u_{ij} \in \mathbb{R}^{256}$ (5D decay features + MLP) [Paper: PDF p. 4, Eq. 2; p. 18, Eq. 1]
- Contact $c_{ij} \in \mathbb{R}^{256}$ (binary Delaunay edge $\rightarrow$ embedding) [Paper: PDF p. 4]

2. ****Pair encoding****: $SAB([S_j; u_{ij}; c_{ij}]) \rightarrow \tilde{S}_{ij}$; then $SAB([\tilde{S}_{ij}; R_i; u_{ij}; c_{ij}]) \rightarrow H_{ij}$ [Paper: PDF p. 4-5, Eq. 3-4]

3. ****Pooling****: $MCAB(H_{ij}) \rightarrow e_{ij} \in \mathbb{R}^{256}$ (per-pair vector) [Paper: PDF p. 4-5, Eq. 5]

4. ****Head 1 (Additive)****: $e_{ij} \rightarrow \alpha(g)_{ij}$ (gene-wise attention over senders) & $l(g)_{ij} = \alpha(g)_{ij} \times WV(e_{ij})(g) \rightarrow \hat{z}^{(1)}(g)_i = \sum_j l(g)_{ij}$ [Paper: PDF p. 5, Eq. 6]

5. ****Head 2 (TME embedding)****: $e_{ij} \rightarrow W_{pe i1}, \dots, W_{pe ik} \rightarrow SAB_{stack} \rightarrow MCAB \rightarrow h_i \rightarrow \hat{z}^{(2)}_i = W_{out} h_i$ [Paper: PDF p. 5, Eq. 7]

6. ****Objective****: Maximize per-gene Pearson correlation $\rho(g) = \text{corr}_{i \in B}(\hat{z}^{(2)}(g)_i, z^{(2)}(g)_i)$ across same-type cells B , weighted by intra-type std [Paper: PDF p. 5, Eq. 8].

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Same-type masking	Replace expression of receiver i and all same-type neighbors in N_i with $\mu_t(i)$, removing z_i from input	Prevents model from "cheating" by copying nearby same-type cells' states (spatial autocorrelation), forcing true CCI learning	[Paper: PDF p. 3, p. 8]. Input: x_i, x_j ; Output: masked x_i, x_j (set to $\mu_t(i)$) [Paper: PDF p. 3, p. 8, p. 22].	"Neighboring cells of the same type tend to be in similar states simply because they share similar niche features... a model given access to neighboring cells of the same cell type... could reach high accuracy by copying them, thus learning nothing about cell-cell communication" [Paper: PDF p. 3].	Severe performance drop: unmasked baseline would inflate PCC/ R^2 without learning CCI; authors confirm masking is "intended to make a fair comparison" and "truly evaluate whether different models can encode cell state-niche correlations" [Paper: PDF p. 8].
Cell-as-token tokenization	Map G -dimensional gene expression to $T=32$ tokens of width $d=256$ (S_j, R_i)	Avoids prohibitive sequence length of gene-as-token (20k/gene); focuses attention on inter-cell relationships, not intra-gene	[Paper: PDF p. 3]. Input: $x_j \in \mathbb{R}^G \rightarrow S_j \in \mathbb{R}^{32 \times 256}$; $x_i \in \mathbb{R}^G \rightarrow R_i \in \mathbb{R}^{32 \times 256}$ [Paper: PDF p. 4, Eq. 2].	"Treating genes as tokens... yields sequences of tens of thousands of elements per cell and makes a neighborhood of fifty cells computationally prohibitive; it also places the attention mechanism between genes, when the relationships of interest here are between cells" [Paper: PDF p. 3].	Intractable computation: 50 cells $\times$ 20k genes = 1M tokens, exceeding GPU memory; attention would model gene co-expression, n

ot CCI. |

| ****Distance & contact tokenization**** | Encode d_{ij} as $u_{ij} \in \mathbb{R}^{256}$ (5D decay features) and $c_{ij} \in \mathbb{R}^{256}$ (binary contact) | Captures physical constraints of signaling (diffusion range, juxtacrine contact), critical for biological plausibility [Paper: PDF p. 4, p. 18]. | Input: d_{ij} (μm); Output: $u_{ij} \in \mathbb{R}^{256}$, $c_{ij} \in \mathbb{R}^{256}$ [Paper: PDF p. 4, p. 18, Eq. 1]. | "The effective interaction range reported in the case study... is fit from data" and ablation shows "dropping the distance embedding [causes] a 27% relative loss" [Paper: PDF p. 9, p. 18]. | Major performance loss: Ablation shows variance explained drops from 0.1684 to 0.1236 (-27%) without distance embedding [Paper: PDF p. 9]. |

| ****Additive head (single-layer graph transformer)**** | Compute $l(g)_{ij} = \alpha(g)_{ij} \times WV(e_{ij})(g)$ with $\alpha(g)_{ij}$ normalized across j , yielding $\hat{z}(1)(g)_i = \sum_j l(g)_{ij}$ | Ensures exact, linear decomposition of prediction into per-sender, per-gene contributions — the foundation of interpretability [Paper: PDF p. 5, Eq. 6]. | Input: $e_{ij} \in \mathbb{R}^{256}$; Output: $l(g)_{ij} \in \mathbb{R}$, $\hat{z}(1)(g)_i \in \mathbb{R}$ [Paper: PDF p. 5, Eq. 6]. | "Each entry of the influence tensor $l...$ is computed from the features of cells i and j and their distance using a one-layer aggregation, so no multi-layer GNN can distort it" [Paper: PDF p. 5]. | Loss of interpretability: Without additivity, $l(g)_{ij}$ would be entangled with non-linear transforms; authors note "exact decomposability... costs almost nothing in accuracy" [Paper: PDF p. 9]. |

| ****Pathway attribution pipeline**** | From $l(g)_{ij} \rightarrow sc, g(d) \rightarrow S(\ell, r)_i \rightarrow \text{weighted LASSO} \rightarrow \text{top LR axes}$ | Bridges data-driven influence and prior LR biochemistry, enabling biological hypothesis generation where ground truth is absent [Paper: PDF p. 6–7]. | Input: $l(g)_{ij}$, LR database, d_{ij} ; Output: ranked (ℓ, r) pairs correlated with $z(g)_i$ [Paper: PDF p. 6–7, Fig. 1c]. | "The influence tensor identifies the cell state... but it does not point out the signaling axis... Bridging that gap requires external knowledge of ligand-receptor biochemistry" [Paper: PDF p. 6]. | Uninterpretable output: Without this, GILLL-scale produces $l(g)_{ij}$ but no biological labels; case study (Fig. 3c) validates KDR axis, confirming pipeline utility [Paper: PDF p. 10]. |

09 关键公式与符号

ID	Formula	Meaning	Key symbols	Source
Eq. 1	$x_i = \mu_t(i) + z_i, z_i = x_i - \mu_t(i)$	Decomposition of cell expression into cell-type mean ($\mu_t(i)$) and cell-state deviation (z_i)	x_i : measured expression vector; $\mu_t(i)$: mean of cell type $t(i)$; z_i : cell-state component	[Paper: PDF p. 3]
Eq. 2	$S_j = \text{reshape}(\text{MLPsnd}(x_j)), R_i = \text{reshape}(\text{MLPrec}(x_i)) \in \mathbb{R}^{T \times d}, T = 32, d = 256$	Tokenization of sender/receiver cells into $T=32$ tokens of width $d=256$	S_j : sender token matrix; R_i : receiver token matrix; MLPsnd/MLPrec: separate encoders	[Paper: PDF p. 4]

| ****Eq. 3**** | $\tilde{S}_{ij} = \text{SAB}([S_j; u_{ij}; c_{ij}]) \in \mathbb{R}^{(T+2) \times d}$ | Self-attention block over sender token, distance token, and contact token | u_{ij} : distance token; c_{ij} : contact token; SAB: self-attention block | [Paper: PDF p. 5] |

| ****Eq. 4**** | $H_{ij} = \text{SAB}([\tilde{S}_{ij}; R_i; u_{ij}; c_{ij}]) \in \mathbb{R}^{(2T+4) \times d}$ | Self-attention block over augmented sender-receiver pair tokens | $\tilde{S}_{ij}$: processed sender tokens; R_i : receiver tokens | [Paper: PDF p. 5] |

| ****Eq. 5**** | $e_{ij} = \text{Wc flatten}(\text{MCAB}(H_{ij}))$, $\text{MCAB}(\cdot) \in \mathbb{R}^{L \times d}$, $e_{ij} \in \mathbb{R}^{256}$ | Cross-attention pooling to fixed-size per-pair vector | MCAB: multi-head cross-attention block; $L=4$ latent queries; flatten: vectorization | [Paper: PDF p. 5] |

| ****Eq. 6**** | $\alpha(g)_{ij} = \exp(\text{WA}(e_{ij})(g)) / \sum_{j'} \exp(\text{WA}(e_{ij'})(g))$, $l(g)_{ij} = \alpha(g)_{ij} \text{WV}(e_{ij})(g)$, $\hat{z}^{(1)}(g)_i = \sum_j l(g)_{ij}$ | Additive head: per-gene attention over senders, yielding decomposable influence tensor | $\alpha(g)_{ij}$: attention weight for gene g ; $l(g)_{ij}$: influence of sender j on gene g of receiver i | [Paper: PDF p. 5] |

| ****Eq. 7**** | $\hat{z}^{(2)}_i = \text{Wout } h_i$, $h_i = \text{flatten}(\text{MCAB}(\text{SAB}([W_{pe1}, \dots, W_{peik}; R_i])))$ | TME embedding head: deeper graph transformer for higher-order effects | h_i : TME embedding ($\mathbb{R}^{1024}$); W_{pei} : positionally embedded pair vectors | [Paper: PDF p. 5] |

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Benchmarking on held-out samples GITIII-scale recovers cell state-niche correlation better than existing foundation models on unseen cancer types/platforms Compared against TERRA, HEIST, Novae, SpatialFormer (frozen), NCEM-GCN, GAT, k-NN proportion probe on 3 held-out samples (Xenium breast, MERFISH CRC, MERFISH melanoma); all use same masked neighborhoods, same MLP probe (1024-unit), same train/val/test split (0.7/0.15/0.15), 5 seeds [Paper: PDF p. 7-8, Table S1]. GITIII-scale achieves highest R^2 (0.168 ± 0.003) and PCC (0.398 ± 0.004) on Xenium breast; best or second-best on all other samples [Paper: PDF p. 8, Fig. 2, Table S1]. GITIII-scale's TME embeddings encode more cell state-niche correlation than baselines, even under distribution shift (unseen cancer/platform) [Paper: PDF p. 2, p. 8]. GITIII-scale is universally superior — but strongest baseline varies (TERRA on breast/melanoma, HEIST on CRC), and authors note "comparison only reflects differences in model objectives and design" [Paper: PDF p. 11]. [Paper: PDF p. 8, Fig. 2, Table S1]						
Ablation: corpus size Model performance scales with training corpus size/diversity Trained variants on cumulative subsets: 2.35M $\rightarrow$ 4.25M cells; same architecture, matched optimization steps [Paper: PDF p. 9, Fig. 2]. Var						

iance explained increases monotonically from 0.1290 (2.35M) to 0.1684 (4.25M); gain attributed to corpus size/diversity, not extra optimization [Paper: PDF p. 9, Fig. 2]. | GITIII-scale benefits from large, diverse pan-cancer data, validating the pretraining strategy [Paper: PDF p. 2, p. 9]. | Performance saturates at 4.25M — no evidence for saturation; authors plan to "keep collecting data to further scale the model" [Paper: PDF p. 10]. | [Paper: PDF p. 9, Fig. 2] |

| ****Ablation: model capacity**** | Model performance scales with parameter count | Halved and quartered model width (2B $\rightarrow$ 0.9B $\rightarrow$ 0.4B params); same architecture otherwise [Paper: PDF p. 9, Fig. 2]. | Variance explained degrades from 0.1684 (2B) to 0.1577 (0.9B) to 0.1489 (0.4B) [Paper: PDF p. 9, Fig. 2]. | GITIII-scale's capacity is necessary for optimal performance, supporting its "scale" designation [Paper: PDF p. 2, p. 9]. | Linear scaling law holds — no evidence for sub/super-linear scaling; ablation only tests width, not depth or attention heads. | [Paper: PDF p. 9, Fig. 2] |

| ****Ablation: neighborhood size (k)**** | Signal extends beyond immediate neighbors | Tested k=49 (original), k=35, k=25, k=10 on breast sample; same architecture [Paper: PDF p. 9, Fig. 2]. | Variance explained drops sharply: 0.1684 (k=49) $\rightarrow$ 0.1603 (k=35) $\rightarrow$ 0.1398 (k=25) $\rightarrow$ 0.1022 (k=10), a 39% relative loss [Paper: PDF p. 9, Fig. 2]. | Cell state-niche correlation involves broader neighborhoods, not just direct contacts; k=49 is justified [Paper: PDF p. 3, p. 9]. | k=10 is sufficient for some genes — but ablation shows it's worst-performing overall; no gene-specific k analysis. | [Paper: PDF p. 9, Fig. 2] |

| ****Case study: endothelial MKI67**** | GITIII-scale identifies biologically validated, drug-targetable LR axis in unseen tissue | Applied pathway attribution (Sec 2.4) to MKI67 in endothelial cells of held-out breast sample [Paper: PDF p. 9–10, Fig. 3]. | KDR (VEGFR2) axis selected as top-ranked; received signal strength correlates with MKI67 (PCC = 0.23, $P = 3.3 \times 10^{-8}$) [Paper: PDF p. 10, Fig. 3c]; distance scaler matches physical diffusion law [Paper: PDF p. 10, Fig. 3b]. | GITIII-scale's interpretability pipeline recovers canonical, therapeutically relevant biology (VEGF $\rightarrow$ KDR $\rightarrow$ endothelial proliferation) in a cancer type absent from training [Paper: PDF p. 2, p. 10]. | Causality — authors explicitly state "our analysis can only tell correlation instead of causality" [Paper: PDF p. 10]. | [Paper: PDF p. 9–10, Fig. 3] |

11 对结论的正确理解

- GITIII-scale ****does not predict absolute gene expression x_i** , but only the ****deviation $z_i = x_i - \mu_t(i)$ **** from cell-type mean, making it robust to batch effects and platform-specific biases [Paper: PDF p. 3, p. 5].
- Its superiority in benchmarking ****reflects its objective alignment****, not inherent architectural superiority: base lines were designed for spatial domains/cell identity, not

cell state-niche correlation, so their underperformance is expected and acknowledged by authors [Paper: PDF p. 11].

- The "interpretability" is **operationalized as exact additive decomposition** ($\hat{z}(1)(g)_i = \sum_j l(g)_{ij}$), not post-hoc saliency; this is mathematically guaranteed by the single-layer, no-FFN design [Paper: PDF p. 5, Eq. 6].
- Pathway attribution (e.g., KDR for MKI67) is a **statistical association analysis** leveraging external LR databases and data-driven distance scalars, not a mechanistic simulation; it generates hypotheses for validation, not causal proof [Paper: PDF p. 6-7, p. 10].
- Pan-cancer generalization is **enabled by specimen-matched data + imputation**, not by architectural tricks alone; without SpaIM-based 20k-gene alignment, cross-platform transfer would fail [Paper: PDF p. 5, p. 18, p. 23].

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
-----	-----	-----	-----
Data scarcity	"Specimen-level matched publicly available scRNA-seq and IST data are rare", limiting corpus size and model scaling	"We will keep collecting data to further scale the model"	[Paper: PDF p. 10]. [Paper: PDF p. 10]
Causal inference gap	"It is hard to systematically evaluate the analysis accuracy... since there is no ground truth", and "our analysis can only tell correlation instead of causality"	"Further biological validation will be performed to better evaluate and train our model"	[Paper: PDF p. 10]. [Paper: PDF p. 10]
Input dependency	"Our model requires inputs imputed from specimen-level paired IST and scRNA-seq data", limiting applicability to datasets without such pairing	Not explicitly stated, but implied by focus on expanding matched corpus	[Paper: PDF p. 10]. [Paper: PDF p. 10]
Computational constraint on imputation	"Due to limited computational resources, the imputation of full transcriptomics... is only performed on the SpaIM model"	Not explicitly stated, but suggests potential for improved imputation methods	[Paper: PDF p. 10]. [Paper: PDF p. 10]

13 批判性分析

[Analysis]	Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
-----	-----	-----	-----	-----	-----
	Same-type masking may over-correct	Masking *all* same-type neighbors (including those of different functional states) could discard biologically relevant autocrine/paracrine signals within a type (e.g., immune cell cytokine feedback loops), conflating technical leakage with biological			

cal signal. | Over-masking risks losing genuine intra-type CCI, biasing the model toward inter-type interactions and underestimating niche complexity. | Compare performance with partial masking (e.g., mask only receiver + nearest same-type neighbor) vs. full masking on a dataset with known intra-type signaling; measure impact on pathways like IFN G-IFNGR. | Authors state masking is to prevent "copying" [Paper: PDF p. 3], but do not validate that all same-type neighbors are truly non-informative for z_i . |

| ****Distance scaler $sc, g(d)$ is fitted per (c, g) but applied globally**** | The spline is fitted separately for each (receiver type, target gene) pair, yet the same $sc, g(d)$ is used for ***all*** sender cells j in N_i , regardless of sender type ℓ . This ignores sender-type-specific diffusion kinetics (e.g., membrane-tethered vs. secreted ligands). | Using a single distance decay for all senders may misattribute influence, especially when multiple LR axes converge on one gene (e.g., VEGF and ANGPT2 both regulating MKI67). | Fit sender-type-aware scalers $sc, \ell, g(d)$ and compare LASSO coefficient stability and biological plausibility of top LR axes. | Authors note "signal strength decay trend is different for the correlated LR targeting each (receiver type, target gene) combination" but do not extend this to sender type [Paper: PDF p. 6]. |

| ****Additive head's "exact decomposability" assumes linearity of biological reality**** | Equation 6 enforces $\hat{z}(1)(g)_i = \sum_j l(g)_{ij}$, but real CCI often involves non-linear integration (e.g., AND-gate logic requiring two ligands). The model's accuracy parity with head 2 (0.1902 vs 0.1934) may reflect head 2 compensating for this limitation in the loss, not true biological linearity. | If biology is intrinsically non-additive, the additive head's interpretability is mathematically sound but biologically incomplete, potentially obscuring synergistic mechanisms. | Simulate synthetic niches with known non-additive rules (e.g., $z = f(\ell_1 \times r_1 + \ell_2 \times r_2)$ where f is sigmoid) and test if GLTIII-scale recovers correct $l(g)_{ij}$ or if head 2's h_i better captures the rule. | Authors acknowledge additivity "limits" modeling of combinatorial effects [Paper: PDF p. 5] but do not quantify the error introduced. |

| ****TME embedding h_i conflates neighborhood composition and geometry**** | h_i is derived from pooled e_{ij} vectors, which encode $(S_j, R_i, u_{ij}, c_{ij})$, but the pooling (MCAB) and subsequent SAB stack do not explicitly disentangle ***which*** senders are present (composition) from ***how*** they are arranged (geometry). | This conflation may hinder downstream tasks requiring pure composition (e.g., predicting cell-type proportions) or pure geometry (e.g., detecting spatial motifs), reducing h_i 's versatility. | Train auxiliary decoders on h_i to reconstruct sender cell-type counts vs. pairwise distances; measure reconstruction error disparity. If geometry reconstruction is poor, disentanglement is needed. |

| Architecture description states h_i is "cellular-neighborhood embedding" [Paper: PDF p. 2] but gives no mechanism for explicit disentanglement. |

14 学到的知识

- **Cell state-niche correlation is a well-defined, measurable quantity**: Defined rigorously as $z_i = x_i - \mu_t(i)$, it isolates niche-driven variation from cell-intrinsic programs, enabling objective evaluation of CCI models [Paper: PDF p. 1-3, Eq. 1].
- **Interpretability can be built into architecture, not just post-hoc**: GLTIII-scale's single-layer, no-FFN graph transformer guarantees additive decomposition ($\hat{z}(1)(g)_i = \sum_j l(g)_{ij}$), proving that mathematical transparency need not sacrifice accuracy ("costs almost nothing") [Paper: PDF p. 5, p. 9].
- **Specimen-matched multi-omics is foundational for spatial biology**: Pairing IST and scRNA-seq from the *same specimen*, followed by imputation (e.g., SpaIM), is the only current path to full-transcriptome, single-cell, spatially resolved data — enabling pan-cancer foundation models [Paper: PDF p. 2, p. 5, p. 7, p. 23].
- **Distance is not a scalar but a multi-scale feature**: Encoding d_{ij} as 5D decay features (algebraic, cubic, exponential) captures juxtacrine, paracrine, and diffusive regimes simultaneously, and ablation confirms its necessity [Paper: PDF p. 4, p. 9, p. 18].
- **Biological interpretation requires bridging data and priors**: The influence tensor $l(g)_{ij}$ is agnostic to biology; linking it to LR axes demands external databases (CellChat), data-driven calibration (distance scalars), and statistical rigor (weighted LASSO + stability testing) [Paper: PDF p. 6-7, Fig. 1c].

15 与既有知识的连接

- **single-cell foundation models**: Contrasts with scGPT-spatial (Wang et al., 2025), which tokenizes *genes* and targets spot-level reconstruction; GLTIII-scale tokenizes *cells*, targeting cell-state prediction, aligning with user's interest in cell state representation [Paper: PDF p. 15-16].
- **spatial transcriptomics**: Builds on CosMx/Xenium/MERFISH platforms cited, directly addressing user's focus; its use of Delaunay triangulation for contact detection connects to spatial graph methods [Paper: PDF p. 3, p. 22].
- **graph neural networks**: Employs SAB (self-attention blocks) and MCAB (cross-attention) instead of standard GCN/GAT, prioritizing permutation invariance and global context over local message passing; the "graph transformer" is a key innovation for TME [Paper: PDF p. 4-5, p. 15-16].
- **multi-omics**: Core contribution is *specimen-matched* IST+scRNA-seq integration via SpaIM, directly enabling full-transcriptome spatial analysis — a critical step for user's multi-omics interest [Paper: PDF p. 2, p. 5, p. 7, p. 23].
- **perturbation prediction**: While not trained for perturbation, the influence tensor $l(g)_{ij}$ and pathway attribution (e.g., $KDR \rightarrow MKI67$) provide a natural substrate for *in s*

ilico* perturbation: knocking out sender j would reduce $^z(1)(g)i$ by $l(g)ij$, enabling hypothesis generation for user's perturbation prediction interest [Paper: PDF p. 5, p. 10].

- **cross-modal alignment**: SpaIM-based imputation to a shared 20k-gene vocabulary is a form of cross-modal alignment, allowing models trained on diverse panels (312-6,175 genes) to operate on a unified space — essential for pan-cancer generalization [Paper: PDF p. 5, p. 18, p. 23].

- **biomedical AI & drug target discovery**: Case study directly links model output (KDR axis) to clinical relevance (anti-angiogenic therapy), demonstrating end-to-end utility for user's biomedical AI and target discovery interests [Paper: PDF p. 2, p. 10].

- **Weak connection/Methodology connection**: **cell state representation** is central (z_i is the target); **LR signaling pathways** are the biological mechanism of interest; **interpretability** is architecturally enforced. All others are methodologically connected (e.g., GNNs used, but not novel GNN architecture; perturbation not trained, but influence tensor enables it).

16 研究想法

- **name**: SpaIM-free cross-platform alignment via contrastive learning

originating limitation/observation: GITIII-scale requires specimen-matched IST+scRNA-seq for SpaIM imputation, limiting applicability; authors admit "input dependency" is a limitation [Paper: PDF p. 10].

core hypothesis: Contrastive learning between IST and scRNA-seq embeddings, using cell-type and spatial proximity as positive pairs, can align modalities without paired specimens.

delta from paper: Replaces supervised imputation (SpaIM) with unsupervised contrastive alignment; removes need for specimen matching.

initial method: Train dual encoders (IST encoder: CN+Transformer on image-like gene grids; scRNA-seq encoder: gene-token Transformer); pull embeddings of same cell type + similar spatial location (e.g., k-NN in tissue) together, push dissimilar apart.

validation: On unmatched IST/scRNA-seq pairs, measure alignment quality via downstream CCI prediction (R^2 on z_i) vs. SpaIM baseline; test zero-shot transfer to new platforms.

failure modes: Poor cell-type annotation transfer; spatial location ambiguity in dissociated scRNA-seq; batch effects dominating contrastive signal.

innovation status: unverified

- **name**: Non-additive influence tensor with logical gates

originating limitation/observation: Additive head (Eq. 6) cannot model combinatorial CCI (e.g., AND-gate requiring two senders), acknowledged as a "limit" [Paper: PDF p

. 5]; head 2 (Eq. 7) loses decomposability.

****core hypothesis****: A lightweight, interpretable module (e.g., gated sum) can introduce controlled non-linearity into $l(g)_{ij}$ while preserving per-sender attribution for dominant terms.

****delta from paper****: Extends Eq. 6 to $\hat{z}(1)(g)_i = \sum_j l(g)_{ij} \times \sigma(Wg[e_{ij}; e_{ik}] + bg)$ where k is a reference sender, enabling pairwise gating.

****initial method****: Modify additive head to include pairwise interaction terms between top- N senders (by $l(g)_{ij}$ magnitude); retain top- K $l(g)_{ij}$ as additive base, add gated interactions as correction.

****validation****: On synthetic data with known AND/OR rules, compare recovery of true sender contributions vs. original additive head; measure impact on biological plausibility of top LR axes in case study.

****failure modes****: Exploding parameter count; gating coefficients becoming uninterpretable; overfitting to noise in small neighborhoods.

****innovation status****: unverified

- ****name****: Causal CCI discovery via perturbation-conditioned contrastive learning

****originating limitation/observation****: Authors state pathway attribution shows "correlation instead of causality" and call for "biological validation" [Paper: PDF p. 10]; current setup is observational.

****core hypothesis****: Training on *in silico* perturbed neighborhoods (e.g., knock-out sender j) with contrastive loss can learn causal directionality, as perturbations break spurious correlations.

****delta from paper****: Adds perturbation simulation (masking sender j 's expression) and contrastive objective (pull $\hat{z}(1)(g)_i$ and $\hat{z}(1)(g)_i|j$ -close, push $\hat{z}(1)(g)_i|j$ -far) to pretraining.

****initial method****: During pretraining, randomly mask 10% of senders j in N_i ; compute $\hat{z}(1)(g)_i$ and $\hat{z}(1)(g)_i|j$; use NT-Xent loss to align predictions for same i , different j -masks.

****validation****: On datasets with CRISPR perturbation ground truth (e.g., Perturb-seq), measure precision/recall of top-ranked senders for perturbed genes vs. baseline GITII scale.

****failure modes****: Perturbation simulation not reflecting biological reality (e.g., masking $\neq$ KO); contrastive signal drowned by noise in large neighborhoods.

****innovation status****: unverified

- ****name****: Multi-scale TME embedding with explicit geometry disentanglement

****originating limitation/observation****: TME embedding h_i conflates composition and geometry; authors give no mechanism for disentanglement [Analysis: Section 13].

****core hypothesis****: A variational autoencoder (VAE) bottleneck on h_i can be regularized to separate composition (

sender cell-type counts) and geometry (pairwise distance distribution) latents.

****delta from paper****: Replace head 2's final projection (Eq. 7) with a VAE encoder producing μ_{comp} , σ_{comp} , μ_{geom} , σ_{geom} ; decode to reconstruct sender counts and distance histogram.

****initial method****: Add VAE loss (KL divergence + reconstruction MSE) to pretraining objective; use β -VAE to control disentanglement strength; probe each latent for composition/geometry prediction.

****validation****: Quantify disentanglement via DCI (Disentanglement, Completeness, Informativeness) scores; test if geometry latent improves spatial motif detection (e.g., vascular sprouting).

****failure modes****: KL term collapsing latents; reconstruction loss dominating main objective; geometry latent failing to capture higher-order topology (e.g., cycles).

****innovation status****: unverified