

```
> Source coverage: Full paper
> Extraction confidence: High
> Locator mode: page-grounded
> Primary analytical lens: methods
> Secondary analytical lens: discovery
> Context verification: Paper-only
> Card completeness: Complete relative to supplied source
```

01 基本信息

```
- **标题**： Towards a knowledge-enhanced single-cell foundation model
- **作者**： Hanqing Zhang, Jie Bao, Mei Ma, Shuai Liu, Jiaying Ma, Jiaguan Liu, Jiaxiao Li, Zhenbo Li, Wenwen Gong, Zhijun Cao
- **发表平台**： arXiv (2026-09-14)
- **模型名**： scKITE (single-cell Knowledge-Integrated Transformer)
- **核心创新**： Two-stage pretraining with lightweight auxiliary decoders for annotation and regulon prediction; decoders discarded post-pretraining [Paper: PDF p. 2-3]
- **预训练样本量**： 179,067 (0.18M), i.e., <0.5% of Geneformer/scGPT/scFoundation [Paper: PDF p. 2]
- **架构基础**： 12-layer Transformer encoder (hidden dim = 512, 8 heads), no decoder retained at inference [Paper: PDF p. 21-22]
- **输入表示**： Gene tokens + binned expression values (51 levels) + mask embedding, max sequence length = 2,049 [Paper: PDF p. 21]
- **输出表示**： Cell representation  $z_{\text{cell}} = h_{\text{cls}}$  (Eq. 4); gene representation  $z_{\text{gi}} = h_{\text{sub}i}$  (Eq. 5) [Paper: PDF p. 22]
```

02 一句话总结

scKITE 是一种知识增强型单细胞基础模型，通过在两阶段预训练中引入轻量级、仅训练期使用的 annotation 和 regulon 辅助解码器，将细胞层级的自然语言注释与基因层级的 TF-regulon 调控知识注入共享 Transformer 编码器；预训练后丢弃解码器，仅保留编码器用于下游任务，在仅用 0.18M 样本 (<0.5% SOTA 模型数据量) 的情况下，在细胞类型标注、批次整合与扰动响应预测三大任务上全面超越 Geneformer、scGPT 等大模型 [Paper: PDF p. 1-3]。

03 研究问题

```
- 如何在显著扩大预训练数据规模的前提下，提升单细胞基础模型 (scFM) 的生物学意义与下游泛化能力？[Paper: PDF p. 1-2]
- 是否存在比单纯增加 transcriptomic 数据量更高效的知识扩展维度？[Paper: PDF p. 1]

- 细胞层级 (textual annotation) 与基因层级 (regulon) 两类异构生物知识能否被协同建模于同一编码器中，并在下游任务中解耦复用？[Paper: PDF p. 2-3]
- 知识增强是否能同时改善细胞级表征（如跨组织细胞识别）与基因级表征（如 perturbation-response 预测）？[Paper: PDF p. 4, 8]
```

04 研究背景与发展路径

```
- **起点**：scFMs (如 Geneformer、scGPT) 依赖大规模 transcriptomic 预训练，但数据扩展已显现收益递减与计算成本剧增瓶颈 [Paper: PDF p. 1-2]；近期工作揭示其性能在部分数据量下即达 plateau [Paper: PDF p. 2, 13]。
- **转折点**：作者发现“加入生物知识”比“单纯扩数据”带来更稳定、更大幅度的性能提升（平均 +28.8% 下游任务相对提升），提示知识是独立于数据规模的新 scaling 维度 [Paper: PDF p. 2, 3]。
```

- ****方法演进****：从纯自监督 (Stage 1 masked-expression reconstruction) → 知识增强联合监督 (Stage 2 + annotation/regulon decoders) → 解耦部署 (decoders discarded) [Paper: PDF p. 3-4]。
- ****知识源选择依据****：细胞注释文本 (描述 identity/tissue/context) 与 regulon (TF-target 关系) 是两种 readily accessible、互补且结构迥异的生物知识，分别对应 cell-level 和 gene-level 监督需求 [Paper: PDF p. 2]。
- ****技术锚点****：沿袭 Transformer 架构，但摒弃端到端生成式设计 (如 scGPT)，转而采用 encoder-only + auxiliary decoders 的轻量解耦范式 [Paper: PDF p. 3-4]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation
Evidence from the paper		
-----	-----	-----
-----	-----	-----
Data-scaling diminishing returns	Performance plateaus after ~50% of full corpus; marginal gains beyond that point [Paper: PDF p. 3]	Transcriptomic data alone lacks explicit biological semantics; scaling cannot compensate for missing mechanistic grounding [Paper: PDF p. 2, 13]
Lack of biologically grounded supervision	Existing scFMs learn statistical co-expression patterns but fail to encode cell identity hierarchy or TF-regulatory logic [Paper: PDF p. 2, 4, 6]	Standard masked autoencoding objective does not enforce alignment with known biology (e.g., marker genes, TF targets) [Paper: PDF p. 2]
Architectural entanglement of knowledge & inference	Many models bake knowledge into inference-time components (e.g., prompt engineering, joint encoders), harming generalizability and deployment simplicity [Paper: PDF p. 4]	Tight coupling prevents clean separation of knowledge injection (pretrain-only) from representation reuse (inference-only) [Paper: PDF p. 4]
Cross-task representation fragmentation	Prior models often optimize for either cell-level <i>or</i> gene-level tasks, lacking unified representations supporting both [Paper: PDF p. 4]	Single-objective pretraining fails to jointly shape cell embeddings (z_{cell}) and contextual gene embeddings (z_{gi}) [Paper: PDF p. 4]

Annotation decoder attention enriches known marker genes (Fig. 5b-d); regulon decoder attention enriches CollecTRI-supported targets (Fig. 5e-g); both absent in ablation [Paper: PDF p. 10-13]

scKITE discards *all* decoders post-pretraining; downstream tasks require *only* transcriptomic input — no annotation/regulon needed [Paper: PDF p. 4, 23]

scKITE's shared encoder yields both $z_{\text{cell}} = h_{\text{cls}}$ and $z_{\text{gi}} = h_{\text{i}}$, validated on cell-type annotation (Fig. 2), batch integration (Fig. 3), *and* perturbation prediction (Fig. 4) [Paper: PDF p. 4, 22]

06 核心理念

Knowledge as a modular, pretrain-only injection channel into a frozen encoder backbone — scKITE 将生物知识 (cell annotation + gene regulon) 建模为两个轻量、autoregressive、cross-attention-based 辅助解码器，它们仅在 Stage 2 预训练中与共享编码器联合优化；解码器不参与下游推理，其唯一作用是通过 cross-attention 引导编码器学习对生物学信号敏感的隐藏状态；知识由此被“蒸馏”进 encoder 参数中，形成一个无需额外输入即可直接复用的、生物信息富集的通用表征 [Paper: PDF p. 3-4]。该思想本质是将知识监督解耦为 *transient training scaffolds*，而非 *persistent inference modules*，从而兼顾生物学深度与工程简洁性 [Paper: PDF p. 4]。

07 方法总览

scKITE 采用两阶段预训练框架：

- Stage 1 (纯转录组自监督)**：使用 masked-expression reconstruction 目标 ($L_{\text{sub}}^{\text{expr}}$) 预训练 Transformer 编码器，输入为表达值掩码序列，目标是回归原始表达 bin 值 [Paper: PDF p. 3, 22]。
- Stage 2 (知识增强联合监督)**：以 Stage 1 检查点初始化编码器，并引入两个独立的 autoregressive 解码器 (annotation decoder & regulon decoder)，均通过 cross-attention 接入编码器全部隐藏状态 H ；联合优化 $L_{\text{sub}}^{\text{Stage2}} = \lambda_{\text{sub}}^{\text{expr}} L_{\text{sub}}^{\text{expr}} + \lambda_{\text{sub}}^{\text{ann}} L_{\text{sub}}^{\text{ann}} + \lambda_{\text{sub}}^{\text{reg}} L_{\text{sub}}^{\text{reg}}$ ($\lambda = 1$) [Paper: PDF p. 3-4, 23]。
- 下游部署**：仅保留编码器； $z_{\text{cell}} = h_{\text{cls}}$ 用于细胞级任务； $z_{\text{gi}} = h_{\text{i}}$ 用于基因级任务 [Paper: PDF p. 4, 22]。
- 知识构造**：annotation 序列来自 CellWhisperer/CELLxGENE 的元数据衍生文本；regulon 序列由 pySCENIC 推断，经 AUCell 活性筛选、TF-target 排序、序列化生成 [Paper: PDF p. 3, 18-19]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Shared Transformer Encoder	Learns contextualized transcriptomic representations conditioned on both expression and biological knowledge	Core representation engine; must be enriched <i>without</i> requiring knowledge at inference	Input: gene tokens + binned expr + mask embedding (seq len ≤ 2049); Output: $H = [h_{\text{cls}}, h_1, \dots, h_n]$ (Eq. 3) [Paper: PDF p. 22]	All downstream results (Figs. 2-4) depend on this encoder; ablation uses same architecture without knowledge decoders [Paper: PDF p. 3-4]	Removal $\rightarrow$ no representation; replacement with other encoder (e.g., scGPT) yields lower performance (Fig. 2a, 3a, 4b) [Paper: PDF p. 4, 6, 8]
Annotation Decoder	Autoregressively generates natural-language cell identity descriptions using cross-attention to encoder states	Provides cell-level supervision to align encoder representations with biological identity, tissue context, functional state [Paper: PDF p. 2]	Input: encoder hidden states H ; Output: token-level logits over annotation vocabulary (L_{ann} , Eq. 7) [Paper: PDF p. 23]	Decoder cross-attention preferentially attends to cell-type marker genes (Fig. 5b-d); ablation (scKITE w/o	

knowledge) loses hierarchical immune organization (Fig. 2 d-f) [Paper: PDF p. 10-13] | Removal → loss of cell identity grounding: reduced zero-shot F1 (+64.0% gain lost), weaker cross-tissue retrieval (+23.4% accuracy drop), impaired immune compartment separation (ARI/NMI drop) [Paper: PDF p. 2, 4, 6] |

| ****Regulon Decoder**** | Autoregressively generates TF-target regulon sequences using cross-attention to encoder states | Provides gene-level supervision to align encoder representations with transcriptional regulatory logic and context-specific TF activity [Paper: PDF p. 2] | Input: encoder hidden states H ; Output: token-level logits over regulon vocabulary (L_{reg} , Eq. 8) [Paper: PDF p. 23] | Decoder cross-attention enriches CollecTRI-supported TF targets (Fig. 5e-g); enables context-dependent TF-target retrieval (Fig. 5h); ablation loses perturbation-response accuracy [Paper: PDF p. 10-13, 8] | Removal → loss of regulatory grounding: +19.8% Top-20 DE MSE reduction lost; poorer direction-correct DE gene recovery (Fig. 4e); weaker genetic interaction magnitude correlation (Fig. 4g) [Paper: PDF p. 2, 8] |

| ****Masked-Expression Reconstruction Head**** | Regresses binned expression values at masked positions from encoder states | Maintains core transcriptomic fidelity; ensures encoder remains expressive on raw data distribution [Paper: PDF p. 3] | Input: h_i at masked positions; Output: predicted expression bin (L_{expr} , Eq. 6) [Paper: PDF p. 22] | Used in both Stage 1 and Stage 2; masking probability reduced from 30%→10% in Stage 2 to balance knowledge vs. data fidelity [Paper: PDF p. 22-23] | Removal → encoder collapses to knowledge-only mode; likely harms generalizability to unseen cell types/gene programs not covered by annotation/regulon corpora [Analysis] |

09 关键公式与符号

ID	Formula	Meaning	Page	Notes
Eq. 3	$H = [h_{\text{cls}}, h_1, \dots, h_n]$	Encoder outputs contextualized hidden states for input sequence X	p. 22	Foundation for all representations; h_{cls} and h_i are used directly [Paper: PDF p. 22]
Eq. 4	$z_{\text{cell}} = h_{\text{cls}}$	Cell-level representation extracted from <cls> token's hidden state	p. 22	Used for cell type annotation, batch integration, UMAP (Figs. 2-3) [Paper: PDF p. 22]
Eq. 5	$z_{g_i} = h_i$	Gene-level contextual representation for i -th expressed gene	p. 22	Enables perturbation prediction, marker analysis, TF interpretation (Figs. 4-5) [Paper: PDF p. 22]
Eq. 6	$L_{\text{expr}} = \frac{1}{ M } \sum_{i \in M} (\hat{x}_i - x_i)^2$	Masked-expression reconstruction loss (MSE)	p. 22	Stage 1 primary objective; retained in Stage 2 with reduced masking [Paper: PDF p. 22]

| Eq. 9 | $L_{\text{Stage2}} = \lambda_{\text{expr}} L_{\text{expr}} + \lambda_{\text{reg}} L_{\text{reg}} + \lambda_{\text{ann}} L_{\text{ann}}$ | Joint Stage 2 training objective | p. 23 | λ set to 1 for all terms; balances transcriptomic fidelity with two knowledge objectives [Paper: PDF p. 23] |

| Eq. 10 | $\text{AvgBIO} = (\text{NMI} + \text{clip}(\text{ARI}, 0, 1) + \text{ASW}_{\text{cell}}) / 3$ | Composite metric for biological conservation in batch integration | p. 26 | Used in Fig. 3a,b to quantify preservation of cell type structure [Paper: PDF p. 26] |

| Eq. 11 | $\text{ASW}_{\text{batch}} = 1 - \|\text{Silhouette}_{\text{batch}}\|$ | Batch-level silhouette width (higher = better mixing within cell type) | p. 26 | Component of AvgBATCH; computed per eligible cell type [Paper: PDF p. 26] |

| Eq. 12 | $\text{AvgBATCH} = (\text{ASW}_{\text{batch}} + \text{GraphConn}) / 2$ | Composite metric for batch mixing in batch integration | p. 27 | Used in Fig. 3a,b to quantify removal of batch effects [Paper: PDF p. 27] |

| Eq. 13 | $\text{OverallScore} = 0.6 \times \text{AvgBIO} + 0.4 \times \text{AvgBATCH}$ | Weighted summary integration score | p. 27 | Emphasizes biological conservation; used to report mean improvement (e.g., +22.8%) [Paper: PDF p. 27] |

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Data scaling (Fig. 1a)	Knowledge enhancement provides consistent gains across data scales, unlike pure data scaling	scKITE vs. scKITE (w/o knowledge) at 10%, 25%, 50%, 100% of corpus (35,813–358,134 profiles); same architecture, eval tasks	scKITE consistently outperforms ablation; ablation plateaus at 50%; scKITE achieves avg +28.8% relative improvement	Knowledge is a scalable, complementary dimension to data size	Knowledge eliminates need for large data — scKITE still uses 0.18M samples, not zero	[Paper: PDF p. 3, Fig. 1a]
Zero-shot cell annotation (Fig. 2a)	scKITE enables accurate label-free cell typing	scKITE vs. scGPT vs. Geneformer vs. ablation on 5 benchmarks (Human Pancreas, MS, etc.), zero-shot nearest-neighbor	scKITE mean macro-F1 = 0.500 > scGPT (0.430) > Geneformer (0.399); best or comparable on most datasets	scKITE's knowledge-enriched z_{cell} captures sufficient cell identity for direct matching	scKITE generalizes to *all* possible cell types — only 5 benchmarks tested, no out-of-distribution evaluation	[Paper: PDF p. 4, Fig. 2a]
Cross-tissue immune retrieval (Fig. 2f)	Knowledge enhances cross-tissue cell identity preservation	scKITE vs. ablation on Cross-tissue Immune Cell Atlas (9 tissues), directional Top-1 retrieval	scKITE overall accuracy = 66.2			

% > ablation = 42.8% | Annotation supervision improves robustness to tissue context shift | Retrieval works for *any* tissue pair — self-tissue comparisons excluded; some pairs may have low coverage | [Paper: PDF p. 6, Fig. 2f] | Batch integration (Fig. 3a) | scKITE balances biological conservation and batch mixing better than SOTA | scKITE v.s. ablation vs. scGPT vs. Geneformer on 4 datasets (Perirhinal cortex, COVID-19, etc.) | scKITE mean AvgBIO = 0.474 > ablation = 0.338; AvgBATCH = 0.938 > ablation = 0.836; exceeds Geneformer by 6.5%/4.2% | Knowledge enrichment improves integration quality across diverse technical/biological batch sources | scKITE solves *all* batch integration challenges — Liver dataset explicitly notes donor variation not fully removable [Paper: PDF p. 20] | [Paper: PDF p. 6, Fig. 3a] | Perturbation-response prediction (Fig. 4b) | scKITE gene embeddings improve GEARS-based perturbation forecasting | scKITE vs. scGPT vs. scFoundation vs. GEARS vs. ablation on Norman & Replogle datasets, Top-20 DE MSE | scKITE lowest MSE on both datasets; outperforms ablation by 19.8% avg | Contextual gene representations (z_{gi}) encode regulatory logic useful for perturbation response | scKITE predicts *all* perturbations perfectly — MSE is non-zero; unseen-single setting shows scFoundation slightly better [Paper: PDF p. 8, Fig. 4b] | [Paper: PDF p. 8, Fig. 4b] | Direction-correct DE recovery (Fig. 4e) | Knowledge improves fidelity of predicted expression-change direction | scKITE vs. ablation on Norman dataset, 97 held-out perturbations | scKITE higher recovery score in 97/97; significant improvement ($P=0.010$) | Annotation/regulon supervision helps encoder capture directional regulatory logic | Recovery is 100% — scores are fractional (e.g., 0.6 = 12/20 correct directions) | [Paper: PDF p. 8, Fig. 4e] |

11 对结论的正确理解

- *** “知识增强优于数据扩展” *** 指在相同模型容量与评估协议下，添加 annotation/regulon 监督比单纯增加 transcriptomic 数据带来更稳定、更大幅度的 *relative improvement* (+28.8%)，并非宣称知识可完全 replace 数据 [Paper: PDF p. 2–3]。
- *** “scKITE outperforms SOTA with <0.5% data” *** 是实证比较结果 (v.s. Geneformer/scGPT/scFoundation)，但其预训练数据 (0.18M pseudo-bulk profiles) 性质不同于 SOTA 的单细胞粒度数据，且未报告 compute cost 或 wall-clock time savings [Paper: PDF p. 2]。
- *** “解码器仅用于预训练” *** 意味着下游任务 (cell annotation, perturbation prediction) *不接收* annotation/regulon 输入，但其成功 *依赖于* 这些解码器在预训练中对编码器的引导作用 [Paper: PDF p. 4, 23]。
- *** “统一表征支持多任务” *** 指同一编码器产出的 z_{cell} 和 z_{gi} 分别被验证有效于细胞级和基因级任务，但 z_{cell} 和 z_{gi} 是不同 token 的输出，非单一向量 [Paper: PDF p. 4, 22]。
- *** “生物学解释性” *** 基于 cross-attention 分析 (Fig. 5)，显示解码器关注 marker genes/TF targets，但 attention $\neq$ causal mechanism；它表明编码器 *learns to associate* these genes with biological concepts, not that it *models* the underlying biology [Paper: PDF p. 10–13]。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Dependence on annotation quality	Natural-language annotations vary in completeness, specificity, consistency across datasets; derived from metadata, not expert curation [Paper: PDF p. 12]	Incorporate richer cell identity knowledge from curated literature, expert annotations, structured resources [Paper: PDF p. 12]	[Paper: PDF p. 12]
Regulon inference uncertainty	pySCENIC infers *predicted* TF-target relationships, not experimentally validated causal networks; may miss context-specific or indirect regulation [Paper: PDF p. 12]	Integrate additional biological evidence: perturbation-derived causal relationships, chromatin accessibility, TF-binding measurements, experimentally grounded cellular state descriptions [Paper: PDF p. 12-14]	[Paper: PDF p. 12-14]
Context-specific scaling pattern	Observed data-efficiency advantage obtained within specific corpus (CellWhisperer/CELLxGENE), architecture (12-layer), and benchmark suite; not proven universal [Paper: PDF p. 14]	Systematic exploration of which biological knowledge to incorporate and how it should shape representation learning [Paper: PDF p. 14]	[Paper: PDF p. 14]
Pretraining corpus scope	Uses pseudo-bulk profiles (not single-cell), limiting resolution for rare cell states; CELLxGENE metadata may lack granularity for fine-grained subtypes [Paper: PDF p. 18, 3]	Extend to true single-cell resolution; integrate multi-omics knowledge (e.g., ATAC, protein) [Paper: PDF p. 14]	[Paper: PDF p. 14, 18]

13 批判性分析

[Analysis]	Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Cross-attention as proxy for biological grounding	Attention weights reflect decoder's *reconstruction focus*, not necessarily encoder's *intrinsic biological sensitivity*; high attention to marker genes could stem from lexical co-occurrence in annotation text rather than biological causality [Paper: PDF p. 10]	Overstates mechanistic interpretability; risks conflating statistical association with functional relevance	Perform ablation: train scKITE with shuffled/masked marker gene names in annotations; test if attention enrichment persists	[Paper: PDF p. 10, 29]	
Pseudo-bulk pretraining	Using averaged profiles (vs. single-cell) discards cell-to-cell variability, potentially biasing representations toward dominant states and weakening rare-cell detection [Paper: PDF p. 18]	Limits applicability to tasks requiring heterogeneity modeling (e.g., trajectory inference, rare disease cells); may inflate			

batch-integration scores by smoothing batch effects | Retrain scKITE on matched single-cell subset of CELLxGENE; compare performance on rare-cell benchmarks (e.g., hematopoiesis) | [Paper: PDF p. 18] |

| ****GEARS-based perturbation evaluation**** | scKITE's gene embeddings are evaluated *only* within GEARS framework; improvement may reflect better compatibility with GEARS's graph/GO priors rather than intrinsic superiority for perturbation modeling | Obscures whether gains are generalizable to other perturbation predictors (e.g., scGen, DCA) or mechanistic models | Plug scKITE embeddings into alternative frameworks (scGen, VAE-based) and re-evaluate on Norman/Replogle; test zero-shot generalization to new perturbation types (e.g., CRISPRi/a combos) | [Paper: PDF p. 8, 27] |

| ****No cross-modal alignment evaluation**** | Paper claims “multi-omics” relevance in selection reason, but no experiment tests alignment between scKITE's transcriptomic representations and other modalities (e.g., ATAC, protein) [Selection reason] | Misaligns with user's research direction; overstates capability without evidence | Train simple contrastive or alignment head on paired scRNA+ATAC data; measure modality-matching metrics (e.g., CLIP-style recall) | Not assessed in paper; [Selection reason] flags risk |

| ****Unseen perturbation generalization gap**** | In Norman unseen-single setting, scFoundation outperformed scKITE on MSE (Fig. 4c); scKITE only leads in correlation | Suggests scKITE's gene embeddings prioritize *directional fidelity* over *magnitude accuracy*, possibly due to regulon supervision emphasizing binary activation | Decompose MSE into bias (mean error) and variance (error spread); analyze whether scKITE underestimates/overestimates fold-changes | [Paper: PDF p. 8, Fig. 4c] |

14 学到的知识

- ****知识注入的工程范式****: auxiliary decoders 是实现“知识仅用于训练、不参与推理”的优雅方案，避免了 prompt engineering 或 finetuning 的复杂性，为构建 deployable 生物学基础模型提供新模板 [Paper: PDF p. 3-4]。
- ****生物知识的结构化序列化****: 将 TF-regulon 关系 (TF→targets) 和 cell annotation (free-text) 统一为 tokenized sequence, 使异构知识可被同一 Transformer 解码器处理, 是 multi-source knowledge fusion 的关键接口设计 [Paper: PDF p. 3, 18-19]。
- ****表征解耦的实证价值****: $z_{\text{cell}} = h_{\text{cls}}$ 和 $z_{\text{gi}} = h_{\text{i}}$ 的分离设计, 使单个编码器能同时服务细胞级 (clustering, annotation) 和基因级 (perturbation, regulation) 任务, 验证了 contextualized token representations 的通用性 [Paper: PDF p. 4, 22]。
- ****跨尺度评估的必要性****: 论文不仅报告绝对指标 (F1, MSE), 更通过 data scaling curves (Fig. 1a) 和 composite metrics (AvgBIO/AvgBATCH, Eqs. 10-13) 揭示性能变化的 *pattern*, 凸显 scaling behavior 分析对 foundation model development 的重要性 [Paper: PDF p. 3, 24-27]。
- ****可解释性分析的严谨实践****: cross-attention analysis (Fig. 5) employs rigorous controls — matched background genes (by expression/detection), statistical testing (Wilcoxon), external validation (CollectRI), and cell-context stratification — setting a high bar for biological interpretation of deep models [Paper: PDF p. 10-13, 28-31]。

15 与既有知识的连接

- **Single-cell foundation models**: Directly extends Geneformer/scGPT paradigm by replacing pure self-supervision with knowledge-augmented pretraining; contrasts with scFoundation's scale-up approach [Paper: PDF p. 1-2].
- **Graph neural networks**: While scKITE itself is Transformer-based, its perturbation evaluation leverages GEARS's gene co-expression and Gene Ontology *graphs*, suggesting synergy — scKITE embeddings could serve as superior node features for GNNs in regulatory network inference [Paper: PDF p. 8, 27].
- **Perturbation prediction**: Advances beyond GEARS's native embeddings by injecting TF-regulon knowledge, aligning with causal perturbation modeling goals; however, lacks explicit causal graph structure like newer methods (e.g., PERTURB-CNN) [Paper: PDF p. 8].
- **Cell state representation**: Validates that cell identity (via annotation) and regulatory state (via regulon) are complementary axes for cell representation, resonating with latent space disentanglement efforts in VAEs but achieved via supervised pretraining [Paper: PDF p. 2, 4].
- **Multi-omics**: Weak connection/methodology connection — paper uses only transcriptomic input; though knowledge sources (annotations, regulons) are multi-modal *in origin*, no experiment integrates raw multi-omics data (e.g., RNA+ATAC) [Selection reason notes "Risk: 未明示是否支持perturbation或cross-modal alignment"].
- **Spatial transcriptomics**: No direct connection — no spatial data or coordinates used; however, the cell identity and regulatory knowledge injected could theoretically benefit spatial models where cell-type annotation and niche-specific regulation are critical [Not assessed in paper].

16 研究想法

- **name**: scKITE-Spatial
- **originating limitation/observation**: No spatial integration; spatial transcriptomics requires modeling both gene expression *and* location-aware cell-cell interactions [Selection reason & Paper: PDF p. 14].
- **core hypothesis**: Injecting spatial neighborhood graphs (e.g., k-NN on coordinates) as a third auxiliary decoder during Stage 2 will enrich scKITE's encoder with spatial context, improving spot-level annotation and spatial domain detection.
- **delta from paper**: Add spatial decoder (graph autoencoder or GNN-based) parallel to annotation/regulon decoders; supervise on neighborhood reconstruction or spatial gene co-expression.
- **initial method**: Use 10x Visium/Slide-seq data; construct spatial graph per spot; train spatial decoder to reconstruct neighbor identities or spatially smoothed expression.
- **validation**: Test on spatial cell-type deconvolution (SPOTlight), spatial domain segmentation (Tangram), and

cross-modality alignment (RNA→spatial).

- ****failure modes****: Spatial graphs may be noisy in low-resolution data; decoder may dominate training, suppressing biological knowledge signals.

- ****innovation status****: unverified

- ****name****: scKITE-Perturb

- ****originating limitation/observation****: Perturbation evaluation is GEARS-bound; scKITE's gene embeddings show directional fidelity but lag in magnitude accuracy for unseen perturbations (Fig. 4c) [Paper: PDF p. 8].

- ****core hypothesis****: Replacing the regulon decoder with a **perturbation-conditioned** decoder (e.g., predicting post-perturbation expression deltas) will directly optimize gene embeddings for causal response modeling.

- ****delta from paper****: Replace regulon decoder with perturbation decoder; input includes perturbation ID + control expression; output is delta expression bins.

- ****initial method****: Use Norman/Replogle control + perturbed profiles; mask control expression, condition decoder on perturbation vector; optimize $L_{\text{perturb}} / L_{\text{ann}}$ alongside $L_{\text{expr}} / L_{\text{ann}}$.

- ****validation****: Benchmark on unseen perturbation MSE/correlation; test zero-shot generalization to new cell types (e.g., transfer Norman K562 → Replogle RPE1).

- ****failure modes****: May overfit to specific perturbation types; requires careful masking to avoid leakage between control/perturbed states.

- ****innovation status****: unverified

- ****name****: scKITE-MultiOmics

- ****originating limitation/observation****: Selection reason flags "cross-modal alignment" risk; paper uses only RNA, though knowledge sources (annotations, regulons) are inherently multi-modal [Selection reason].

- ****core hypothesis****: Jointly pretraining scKITE on paired RNA+ATAC data, with annotation/regulon decoders **and** an ATAC decoder (predicting chromatin accessibility), will yield representations that intrinsically align modalities.

- ****delta from paper****: Add ATAC decoder; input includes RNA sequence + ATAC peak counts (binned); share encoder; supervise ATAC decoder on masked peak prediction.

- ****initial method****: Use 10x Multiome data; tokenize peaks as "ATAC tokens"; extend global vocabulary; use same cross-attention architecture.

- ****validation****: Measure cross-modal retrieval (RNA→ATAC, ATAC→RNA), joint clustering, and imputation fidelity (e.g., scMVP benchmark).

- ****failure modes****: Modality imbalance (ATAC sparser than RNA) may cause gradient conflict; requires new tokenization strategy for peaks.

- ****innovation status****: unverified