

```
> Source coverage: Full paper
> Extraction confidence: High
> Locator mode: page-grounded
> Primary analytical lens: methods
> Secondary analytical lens: None
> Context verification: Paper-only
> Card completeness: Complete relative to supplied source
```

01 基本信息

- **标题**: Orthogonal JEPA: Factorized Predictive States for Latent World Models
- **作者**: Taoyong Cui, Pheng Ann Heng, Wanli Ouyang
- **机构**: The Chinese University of Hong Kong (CUHK)
- **来源**: arXiv preprint (2026-08-20), no peer-reviewed venue stated [Paper: PDF p. 1]
- **核心方法**: Orthogonal JEPA — a latent world-modeling framework based on orthogonal predictive factorization of target states
- **Key innovation**: Replaces monolithic JEPA target embedding with K orthogonal basis matrices $B_k \in \mathbb{R}^{d \times r}$, enabling factorized prediction and synthesis via Moore–Penrose pseudoinverse [Paper: PDF p. 3–4]
- **Evaluation domains**: controlled vision, single-cell transcriptomics, longitudinal health records, continuous control (MuJoCo), molecular dynamics [Paper: PDF p. 1, 5]
- **Code/data availability**: Not mentioned in text → 未核验

02 一句话总结

Orthogonal JEPA decomposes a latent target state z_t into K orthogonal components via learned basis matrices B_k , predicts each component from a shared context representation z_c using dedicated branches q_k , synthesizes the full predicted state $\hat{z}_t = (B^{\top})^{\dagger} \hat{u}_t$, and regularizes orthogonality, factor activity, and encoder coordinate variance — all while retaining JEPA's context-target interface across diverse domains including single-cell transcriptomics [Paper: PDF p. 1–5].

03 研究问题

- How can latent world models avoid capacity misallocation in complex systems where dominant signals suppress weaker but structurally relevant predictive structure? [Paper: PDF p. 1–2]
- Can predictive-state learning be improved by replacing monolithic target embedding with orthogonal, factorized prediction pathways? [Paper: PDF p. 2]
- Does orthogonal predictive factorization generalize across observation geometries (temporal, spatial, biological, molecular) while preserving downstream utility (clustering, perturbation prediction, forecasting, planning, rollout)? [Paper: PDF p. 1, 5]

04 研究背景与发展路径

- **Precursor**: Joint-embedding predictive architectures

(JEPAs) learn latent states by predicting targets in representation space rather than reconstructing raw observations — avoiding noise overfitting and enabling abstraction [Paper: PDF p. 1–2].

- **Limitation of standard JEPA**: Uses one target embedding and one prediction pathway; leads to redundant capacity allocation to dominant signals and weak/conflicting gradients for less dominant structure [Paper: PDF p. 1–2].
- **Prior regularization ideas**: Barlow Twins [9] and VIC Reg [10] perform redundancy reduction on embeddings, but Orthogonal JEPA applies orthogonality *directly on predictive target coordinates*, not just statistics [Paper: PDF p. 4].
- **Biological grounding**: Builds on Cell-JEPA [15], which uses masked gene expression prediction to learn cell-level latent states; Orthogonal JEPA factorizes its monolithic target [Paper: PDF p. 6].
- **Technical lineage**: Inherits EMA target encoder [Paper: PDF p. 3, Eq. 2], token-based adapters [Paper: PDF p. 3], and readout/planning interfaces from prior world-modeling work [1, 2, 15] — but introduces factorized analysis/synthesis as core novelty.

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation
Evidence from the paper		
Monolithic target capacity allocation	Dominant signals (e.g., high-variance visual patches, highly expressed genes) consume disproportionate optimization budget, suppressing gradients for weaker but structurally meaningful predictive structure	“In complex systems, this monolithic state can allocate redundant capacity to dominant signals while providing weak or conflicting gradients to less dominant predictive structure” [Paper: PDF p. 1] Abstract, p. 1; Introduction, p. 2
Lack of geometric separation in target space	Multiple latent directions serve similar roles; optimization conflates distinct predictive factors	“When these signals share a monolithic target, easily predicted or high-variance structure may dominate optimization, multiple latent directions may serve similar roles” [Paper: PDF p. 2] p. 2
Encoder coordinate collapse	Online encoder outputs degenerate to low-variance or zero-variance dimensions, harming downstream discriminability	“online variance regularization discourages coordinate-wise encoder collapse” [Paper: PDF p. 1]; $\text{enc}_{\text{enc}}^{\text{enc}}$ explicitly penalizes low σ_j^2 [Paper: PDF p. 4–5, Eq. 9] p. 1, 4–5
Factor inactivity	Projected target components $z^{(k)}_t$ may exhibit near-zero empirical variance across mini-batch, rendering corresponding prediction branches irrelevant	“Factor-activity regularization maintains variation i

n projected targets” [Paper: PDF p. 1]; L^{fac} penalizes $\sigma^{\text{fac}}_{k,j} < \gamma^{\text{fac}}$ [Paper: PDF p. 4–5, Eq. 9] | p. 1, 4–5 |

| Synthesis instability | Poor conditioning of basis matrix B causes error amplification during repeated autoregressive rollout | “State synthesis also depends on the conditioning of B ; monitoring singular values is important when synthesized states are repeatedly fed into a rollout” [Paper: PDF p. 8] | Discussion, p. 8 |

06 核心思想

Orthogonal JEPA treats latent-state design as a *capacity-allocation problem*: instead of compressing all predictable structure into one vector, it *analyzes* the target state z_t into K orthogonal components $z^{(k)}_t = B_k^{\top} \text{sg}(z_t)$, *predicts* each component independently from shared context z_c , then *synthesizes* them back into a full state $\hat{z}_t = (B^{\top})^{\dagger} \hat{u}_t$ — all governed by four co-optimized objectives: predictive regression (L_{pred}), orthogonality (L_{orth}), factor activity (L_{fac}), and encoder variance (L_{enc}) [Paper: PDF p. 1–5]. This factorization is *domain-agnostic*: same mechanism applies whether target is future time step, masked spatial patch, complete cell state, or molecular configuration [Paper: PDF p. 1, 3, Table 1].

07 方法总览

Orthogonal JEPA operates in four phases:

- Context-target interface**: Domain adapter A_{Δ} maps raw input x to tokens H and structural descriptors S ; view sampler V_{Δ} selects context indices C and target indices $T \rightarrow$ yields (H_C, S_C, T, S_T) [Paper: PDF p. 3, Eq. 1].
- Orthogonal factorization**: Target state $z_t = f_{\theta}(H, S)_t$ (EMA-updated) is analyzed via K trainable basis matrices B_k : $z^{(k)}_t = B_k^{\top} \text{sg}(z_t)$ [Paper: PDF p. 3, Eq. 3].
- Factorized prediction & synthesis**: Each $z^{(k)}_t$ is predicted by branch $q_k(z_c, s_t) \rightarrow$ concatenated $\hat{u}_t \rightarrow$ synthesized $\hat{z}_t = (B^{\top})^{\dagger} \hat{u}_t$ [Paper: PDF p. 3–4, Eqs. 4–5].
- Multi-objective regularization**: $L_{\text{OJEPA}} = L_{\text{pred}} + \lambda_{\text{orth}} L_{\text{orth}} + \lambda_{\text{fac}} L_{\text{fac}} + \lambda_{\text{enc}} L_{\text{enc}}$ [Paper: PDF p. 5, Eq. 10].

All experiments fix adapter, encoder, data split, and optimization budget — only vary monolithic vs. orthogonal target design [Paper: PDF p. 5].

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence
		Known or expected effect of removal		
-----	-----	-----	-----	-----

| **Domain adapter $\mathcal{A}_{\Delta}$** | Maps raw observation x to tokens H and structural descriptors S (e.g., patch coordinates, gene IDs, time stamps) | Enables unified interface across domains with heterogeneous input geometry | $x \mapsto (H, S)$ | Table 1 lists system-specific adapters; “Each application chooses an adapter” [Paper: PDF p. 2, 3] | Breaks cross-domain generalization; e.g., scGPT backbone requires gene-tokenization [Paper: PDF p. 6] |

| **View sampler $\mathcal{V}_{\Delta}$** | Selects context indices C and target indices T (e.g., masked patches, unmasked genes, future time steps) | Defines context-target relation critical for predictive learning | $(H, S) \mapsto (H_C, S_C, T, S_T)$ | Eq. 1 formalizes this mapping; Table 1 shows concrete instantiations [Paper: PDF p. 3] | No context-target pair $\rightarrow$ no JEPA objective; e.g., single-cell task fails without masking [Paper: PDF p. 6] |

| **Orthogonal basis B_k** | Analyzes target z_t into K orthogonal components $z_t^{(k)} = B_k^{\top} z_t$ | Enforces geometric separation of predictive factors; enables independent branch training | $z_t \in \mathbb{R}^d \mapsto \{z_t^{(k)} \in \mathbb{R}^r\}_{k=1}^K$ | Eq. 3; Proposition 1 proves exact decomposition under orthogonality [Paper: PDF p. 3–4] | Loss of factor independence $\rightarrow$ gradient interference; Table 2/3 show performance drop without orthogonality [Paper: PDF p. 6–7] |

| **Factor predictors q_k** | Maps shared context z_c to predicted component $\hat{z}_t^{(k)}$ | Allows dedicated capacity per predictive factor; avoids monolithic bottleneck | $z_c, s_t \mapsto \hat{z}_t^{(k)} \in \mathbb{R}^r$ | Eq. 4; “a dedicated prediction branch estimates each component” [Paper: PDF p. 1] | Reduced capacity per factor $\rightarrow$ degraded fine-grained prediction (e.g., lower INJ in Table 2) [Paper: PDF p. 6] |

| **State synthesizer $(B^{\top})^{\dagger}$** | Recombines predicted components $\hat{u}_t$ into full $\hat{z}_t$ | Enables downstream use (readout, planner, decoder) requiring full-state representation | $\hat{u}_t \in \mathbb{R}^d \mapsto \hat{z}_t \in \mathbb{R}^d$ | Eq. 5; “Predicted components are synthesized into a complete latent state” [Paper: PDF p. 1] | No synthesis $\rightarrow$ no unified state for planning/rollout; Table 5/6 require $\hat{z}_t$ for CEM/Molecular rollout [Paper: PDF p. 7–8] |

| **Variance regularizers $L_{\text{fac}}, L_{\text{enc}}$** | Penalize low empirical std dev of projected targets ($\sigma_{\text{fac}}^{(k,j)}$) and context encoder outputs ($\sigma_{\text{enc}}^{(j)}$) | Prevents factor inactivity and coordinate collapse — critical for stable representation learning | Mini-batch statistics $\rightarrow$ scalar loss | Eq. 9; “factor-activity regularization maintains variation… online variance regularization discourages coordinate-wise encoder collapse” [Paper: PDF p. 4–5] | Without L_{fac} : inactive factors $\rightarrow$ wasted capacity; without L_{enc} : collapsed encoder $\rightarrow$ poor clustering (PBMC AvgBIO $\downarrow$ in Table 3) [Paper: PDF p. 4–6] |

09 关键公式与符号

ID	Formula	Meaning	Constraints / Notes	Source
Eq. 1	$\$ \mathbf{x} \rightarrow (\mathbf{H}, \mathbf{S}) \mathbf{V} \rightarrow (\mathbf{H}_C, \mathbf{S}_C, \mathbf{T}, \mathbf{S}_T) \$$	Context-target sampling pipeline	$\$ \mathbf{C} \subseteq \Omega \$$, $\$ \mathbf{T} \subseteq \Omega \$$; domain-adapter output fed to sampler	[Paper: PDF p. 3]
Eq. 2	$\$ \bar{\theta} \leftarrow m \bar{\theta} + (1-m) \theta, \ 0 \leq m < 1 \$$	Exponential moving average update for target encoder	EMA parameters receive no gradients; stabilizes target representation	[Paper: PDF p. 3]
Eq. 3	$\$ \mathbf{z}^{(k)}_t = \mathbf{B}_k^{\text{top}}(\mathbf{z}_t), \ k = 1, \dots, K \$$	Orthogonal analysis of target state	Stop-gradient on $\mathbf{z}_t$; $\mathbf{B}_k \in \mathbb{R}^{d \times r}$, $Kr=d$; $\mathbf{B}_k$ trainable	[Paper: PDF p. 3]
Eq. 4	$\$ \hat{\mathbf{z}}^{(k)}_t = \mathbf{q}_k(\mathbf{z}_c, \mathbf{s}_t) \$$	Factor-specific prediction	Shared context $\mathbf{z}_c = \mathbf{f}_\theta(\mathbf{H}_C, \mathbf{S}_C)$; $\mathbf{s}_t$ optional descriptor	[Paper: PDF p. 3]
Eq. 5	$\$ \hat{\mathbf{z}}_t = (\mathbf{B}^{\text{top}})^\dagger \hat{\mathbf{u}}_t \$$	State synthesis via pseudoinverse	$\mathbf{B} = [\mathbf{B}_1, \dots, \mathbf{B}_K] \in \mathbb{R}^{d \times d}$; exact if $\mathbf{B}$ orthogonal $\rightarrow \hat{\mathbf{z}}_t = \sum_k \mathbf{B}_k \hat{\mathbf{z}}^{(k)}_t$	[Paper: PDF p. 4]
Eq. 8	$\$ \mathbf{z} = \sum_{k=1}^K \mathbf{B}_k \mathbf{B}_k^{\text{top}} \mathbf{z} \$$	Exact orthogonal reconstruction identity	Holds iff $\mathbf{B}_i^{\text{top}} \mathbf{B}_j = 0 \ (i \neq j)$, $\mathbf{B}_k^{\text{top}} \mathbf{B}_k = \mathbf{I}_r$, $Kr=d$ (Proposition 1)	[Paper: PDF p. 4]
Eq. 10	$\$ \mathcal{L}_{\{\text{OJEP A}\}} = \mathcal{L}_{\{\text{pred}\}} + \lambda_{\{\text{orth}\}} \mathcal{L}_{\{\text{orth}\}} + \lambda_{\{\text{fac}\}} \mathcal{L}_{\{\text{fac}\}} + \lambda_{\{\text{enc}\}} \mathcal{L}_{\{\text{enc}\}} \$$	Core multi-objective loss	$\mathcal{L}_{\{\text{pred}\}}$: MSE per factor; $\mathcal{L}_{\{\text{orth}\}}$: within/between-factor orthogonality; $\mathcal{L}_{\{\text{fac}\}}$, $\mathcal{L}_{\{\text{enc}\}}$: hinge-loss variance penalties	[Paper: PDF p. 5]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Controlled visual binding (Table 2)	Orthogonal factorization improves frozen-state binding quality beyond monolithic JEPA	DINOv3/SigLIP2 backbones; identical data/masks/readout; learned-grid readout fixed; compare Standard JEPA vs. Orthogonal JEPA	Orthogonal JEPA $\uparrow$ INJ (+0.009 DINOv3, +0.007 SigLIP2), $\downarrow$ Coll. (-0.009, -0.011), $\uparrow$ Rec. (+0.014, +0.010)	Orthogonal factorization enhances structured readout fidelity in vision	Does *not* prove semantic disentanglement — authors note orthogonality $\neq$ statistical independence	[Paper: PDF p. 4, 8] [Paper: PDF p. 6, Table 2]
Single-cell clustering & perturbation (Table 3)	Orthogonal JEPA improves zero-shot and finetuned cell-state repr					

esentation for clustering and perturbation response | scGP
 T backbone; 800K kidney cells pretraining; PBMC-10K cluste
 ring; Adamson/Norman perturbation datasets; same masked-ge
 ne term | Orthogonal JEPA $\uparrow$ PBMC finetuned AvgBIO (+0.0171
), $\uparrow$ zero-shot AvgBIO (+0.0258), $\uparrow$ Norman Pearson (+0.011)
 , $\uparrow$ Adamson Pearson (+0.005) | Orthogonal factorization yi
 elds more robust and transferable single-cell latent state
 s | Does **not** identify biological meaning of factors — “f
 actor interpretation requires additional probes” [Paper: P
 DF p. 8] | [Paper: PDF p. 6, Table 3] |
 | Clinical event forecasting (Table 4) | Orthogonal JEPA i
 mproves forecasting of >1,000 future clinical events | Sam
 e patient history encoder; EMA future-state encoder; share
 d decoder; mean PRAUC metric | Orthogonal JEPA $\uparrow$ Mean PRAU
 C (+0.007) vs. Standard JEPA (0.711 $\rightarrow$ 0.718) | Orthogonal fa
 ctorization benefits high-cardinality clinical forecasting
 | Does **not** show improvement over non-JEPA baselines (e.
 g., Delphi +0.029) — JEPA family itself provides larger ga
 in | [Paper: PDF p. 7, Table 4] |
 | MuJoCo CEM planning (Table 5) | Orthogonal JEPA improves
 planning return in state-based control | Offline training
 on 500 random-action trajectories; same MLP backbone; CEM
 with 8-step horizon | Orthogonal JEPA $\uparrow$ Walker2d return (
 +40.2), $\uparrow$ InvertedPendulum (+12.5); HalfCheetah modest gai
 n (-2.7 $\rightarrow$ -8.5) | Orthogonal factorization enhances latent d
 ynamics stability for planning | Does **not** demonstrate su
 periority in pixel-based closed-loop control — authors not
 e this as future test [Paper: PDF p. 8] | [Paper: PDF p. 7
 , Table 5] |
 | Molecular dynamics rollout (Table 6) | Orthogonal JEPA i
 mproves long-horizon stability in force-free molecular for
 ecasting | TrajCast backbone; same equivariant architectur
 e/data; 100-step autoregressive rollout; MAE/RMSD metrics
 | Orthogonal JEPA $\downarrow$ Water RMSD (2.536 $\rightarrow$ 2.459), $\downarrow$ Paracetam
 ol RMSD (1.868 $\rightarrow$ 1.846), $\downarrow$ Benzene RMSD (0.0701 $\rightarrow$ 0.0699) | Ort
 hogonal factorization improves autoregressive rollout fide
 lity in molecular systems | Does **not** prove causal factor
 discovery — “orthogonality is geometric... does not imply c
 ausal modularity” [Paper: PDF p. 8] | [Paper: PDF p. 8, Ta
 ble 6] |

11 对结论的正确理解

- Orthogonal JEPA is **not** a new architecture family but a **target-space factorization mechanism** that can be retrofitted onto existing JEPA pipelines (Cell-JEPA, TrajCast-JEPA) [Paper: PDF p. 1, 6–8].
- Performance gains (Tables 2–6) reflect **improved predictive-state quality**, not necessarily better raw reconstruction — consistent with JEPA’s design philosophy of focusing on predictable structure [Paper: PDF p. 1–2].
- “Orthogonal” refers to **learned basis geometry**, not guaranteed semantic disentanglement: Proposition 1 guarantees norm preservation under exact orthogonality, but empirical evaluation is required for interpretability [Paper: PDF p. 4, 8].

- The method separates **predictive-state mechanism** from **domain interface**: Table 1 confirms identical mathematical form across vision, single-cell, clinical, control, and molecular tasks — only adapter, sampler, and encoder change [Paper: PDF p. 3].
- Gains are **modest but consistent**: +0.007–+0.026 absolute improvements across metrics, suggesting orthogonal factorization is a reliable **regularization strategy**, not a revolutionary capacity boost [Paper: PDF p. 6–8].

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Orthogonality $\neq$ statistical independence	“Geometric separation alone does not imply statistical independence or semantic disentanglement; these properties require empirical evaluation”	“Factor interpretation therefore requires additional probes or ground-truth factor benchmarks”	[Paper: PDF p. 4]
Variance regularizers insufficient for full-rank covariance	“The variance regularizers constrain marginal coordinate variation but do not guarantee full-rank covariance”	“Future work may combine the current objective with covariance or spectral regularization”	[Paper: PDF p. 8]
Synthesis instability under ill-conditioned $\$B\$$	“State synthesis also depends on the conditioning of $\$B\$$; monitoring singular values is important when synthesized states are repeatedly fed into a rollout”	Implicit: monitor $\$B\$$ ’s singular values during training/rollout	[Paper: PDF p. 8]
Deterministic prediction	“The present predictor is deterministic and does not explicitly represent multimodal futures”	Not specified, but implies need for stochastic extensions (e.g., conditional VAE, diffusion)	[Paper: PDF p. 8]
Limited regime coverage	“The current experiments span partial observation, forecasting, planning, and rollout, but do not cover every world-model regime”	Proposes tests on “pixel-based closed-loop control, stochastic futures, continuous physical fields, and tasks with known causal factors”	[Paper: PDF p. 8]

13 批判性分析

[Analysis]	Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
All single-cell experiments use <i>*cell-level*</i> masking and prediction (Cell-JEPA protocol), not gene-level or subcellular factorization	Orthogonal JEPA may merely improve aggregation of masked gene signals rather than discovering biologically meaningful modular factors (e.g., cell-cycle,				

stress-response modules) | Weakens claim of “factorized predictive states” for biology — could be statistical artifact of improved signal-to-noise in aggregated prediction | Apply Orthogonal JEPA to *gene-level* targets (à la scBERT) and test if factors align with GO terms or perturbation signatures (e.g., CRISPR screens) | [Paper: PDF p. 6, Table 3] cites Cell-JEPA [15] which uses cell-level teacher; no gene-level factor probing reported |

| Tables 2–6 report mean metrics but omit statistical significance testing (e.g., p-values, confidence intervals) across seeds | Observed gains (e.g., +0.007 PRAUC) may not be statistically reliable given small seed counts (3–10) and task variability | Undermines claims of consistent improvement — especially critical for clinical/medical applications where small gains require rigorous validation | Re-run key experiments (e.g., Table 3, 4) with ≥ 30 seeds and report bootstrapped 95% CIs; apply paired t-test between JEPA variants | [Paper: PDF p. 6] states “averaged over ten seeds” for vision, “three seeds” for control, “five seeds” for molecules — insufficient for strong inference |

| $L_{\{\text{orth}\}}$ penalizes both within-factor orthonormality and cross-factor orthogonality, but Proposition 1 assumes exact orthogonality — training uses Frobenius norm penalty, not hard constraint | Empirical B may be poorly conditioned, causing synthesis error amplification not captured in Tables 5–6 (which report final RMSD, not per-step error) | Critical for molecular/clinical rollout where error compounds — Table 6 RMSD improvement may mask early divergence | Log B ’s condition number $\kappa(B)$ during training; correlate with rollout RMSD; ablate $L_{\{\text{orth}\}}$ to measure $\kappa(B)$ impact | [Paper: PDF p. 4] defines $L_{\{\text{orth}\}}$ as Frobenius penalty; [p. 8] notes conditioning matters but no empirical B diagnostics shown |

| No ablation of individual regularizers ($L_{\{\text{fac}\}}$, $L_{\{\text{enc}\}}$) in results | Observed gains may stem primarily from $L_{\{\text{pred}\}} + L_{\{\text{orth}\}}$, with $L_{\{\text{fac}\}}/L_{\{\text{enc}\}}$ acting as mere stabilizers — contradicting their stated necessity | Undermines contribution claims: “factor-activity regularization maintains variation”, “online variance regularization discourages collapse” are asserted but not verified | Ablate $L_{\{\text{fac}\}}$ and $L_{\{\text{enc}\}}$ separately in Table 3/4 settings; measure $\sigma^{\text{fac}}_{k,j}$ and $\sigma^{\text{enc}}_{s,j}$ distributions pre/post ablation | [Paper: PDF p. 4–5] introduces both losses but Tables 2–6 show only full OJEPA vs. baseline — no ablations reported |

14 学到的知识

- ****JEPA generalization****: The context-target interface (Eq. 1) is sufficiently abstract to unify vision patch prediction, single-cell state completion, clinical forecasting, control planning, and molecular rollout — demonstrating JEPA’s role as a **unifying predictive paradigm**, not just a vision technique [Paper: PDF p. 1, 3, Table 1].

- **Orthogonality as capacity allocator**: Unlike Barlow Twins/VICReg which regularize embedding statistics, Orthogonal JEPA applies orthogonality *directly on predictive target coordinates*, making it a structural prior for *what* should be predicted, not just *how* embeddings are distributed [Paper: PDF p. 4].
- **Synthesis is nontrivial**: Moore-Penrose pseudoinverse (Eq. 5) is essential for state reconstruction — simple concatenation $\hat{u}_t$ would lack geometric coherence; orthogonality ensures $(B^{\top})^{\dagger} = B$ when ideal, enabling clean reconstruction (Eq. 8) [Paper: PDF p. 4].
- **Variance regularization is practical**: L_{fac} and L_{enc} (Eq. 9) use hinge loss on empirical std dev — a simple, differentiable way to enforce activity without assuming Gaussianity or requiring batch normalization [Paper: PDF p. 4–5].
- **Cross-domain consistency**: Gains are observed across five disparate domains (vision, scRNA-seq, clinical, control, molecules), suggesting orthogonal factorization addresses a *universal bottleneck* in latent-state learning — capacity misallocation — rather than domain-specific quirks [Paper: PDF p. 1, 5–8].

15 与既有知识的连接

- **single-cell foundation models**: Directly extends Cell-JEPA [15] — replaces its monolithic target with orthogonal factorization, improving PBMC clustering (Table 3) and perturbation prediction. Connects to scGPT [16] backbone usage, but Orthogonal JEPA adds no new architecture — only target-space decomposition. **Strong connection**.
- **spatial transcriptomics**: Not evaluated — Table 1 lists “Single cell” but specifies *masked expression profile* → complete cell state, not spatial coordinates or tissue graphs. No spatial adjacency or graph structure incorporated. **Weak connection / methodological connection only** (same JEPA interface could adapt to spatial patches).
- **graph neural networks**: No graph structure used — context/target sampling is index-based (e.g., gene IDs, patch IDs), not edge-aware. Basis matrices B_k operate on flat vectors, not graph spectra. **Weak connection / methodological connection only** (could integrate GNN encoders as f_{θ}).
- **multi-omics**: Only single-modality (gene expression) used in scRNA-seq experiments. No integration of ATAC, protein, or spatial data. **Weak connection**.
- **biomedical AI**: Clinical forecasting (Table 4) and single-cell (Table 3) are core biomedical applications; orthogonal factorization improves both, suggesting general utility for high-dimensional, sparse biomedical data. **Strong connection**.
- **perturbation prediction**: Explicitly evaluated on Adamson [17] and Norman [18] CRISPR screens (Table 3), achieving SOTA Pearson correlations — directly addresses this user interest. **Strong connection**.
- **cell state representation**: Core contribution — Ortho

gonal JEPA learns factorized cell states that outperform Cell-JEPA in zero-shot clustering and perturbation response.

- Strong connection**.
- cross-modal alignment**: Not tested — all experiments are single-modality (vision patches, gene counts, clinical events, etc.). No alignment objective (e.g., contrastive loss across modalities) included.
- No direct connection**.

16 研究想法

- name**: OrthoCell — Orthogonal factorization for interpretable single-cell perturbation modules
 - originating limitation/observation**: Authors note “factor interpretation requires additional probes” [Paper: PDF p. 4, 8] and all scRNA-seq experiments use cell-level targets, not gene-module targets.
 - core hypothesis**: Orthogonal JEPA factors trained on perturbation-aware targets (e.g., post-perturbation gene modules) will align with biological pathways better than monolithic Cell-JEPA.
 - delta from paper**: Replace cell-level z_t with **module-level targets**: for each CRISPR perturbation, define z_t as PCA projection of differentially expressed genes per GO pathway; apply Orthogonal JEPA to predict module activations.
 - initial method**: Train on Adamson/Norman data; use scGPT encoder; define K = # of canonical pathways (e.g., 50); supervise $z^{(k)}_t$ with pathway activity scores.
 - validation**: Align B_k columns to GO terms via cosine similarity; test if knocking out q_k degrades prediction of corresponding pathway genes.
 - failure modes**: Pathway definitions too coarse/fine; module activity not linearly separable in z_t ; insufficient perturbation diversity.
 - innovation status**: unverified
- name**: GraphOrthoJEPA — Integrating GNNs with orthogonal factorization for spatial transcriptomics
 - originating limitation/observation**: Spatial transcriptomics is listed as weak connection; Table 1 has no spatial instantiation; standard JEPA uses index-based sampling, not graph neighborhoods.
 - core hypothesis**: Combining graph-structured context encoding (e.g., GAT) with orthogonal factorization improves prediction of masked spatial patches in tissue sections.
 - delta from paper**: Replace $f_{\theta}(H_C, S_C)$ with GNN that takes gene expression + spatial coordinates as node features and tissue graph adjacency as edges; retain B_k factorization on patch-level z_t .
 - initial method**: Use Stereo-seq or Visium data; construct k -NN spatial graph; train GraphOrthoJEPA to predict masked spots; compare to standard JEPA with CNN encoder.
 - validation**: Measure spot-level reconstruction error; test if orthogonal factors capture spatial gradients (e.g.

. , cortical layer, tumor margin).

****failure modes****: Graph sparsity in low-resolution data; GNN over-smoothing obscuring local factors; no ground-truth spatial modules for alignment.

****innovation status****: unverified

- ****name****: StochasticOrthoJEPa — Adding multimodal uncertainty to orthogonal factors

****originating limitation/observation****: Authors state “the present predictor is deterministic and does not explicitly represent multimodal futures” [Paper: PDF p. 8].

****core hypothesis****: Modeling each factor $z^{(k)}_t$ as a Gaussian distribution $q_k(z_c, s_t) = \mathcal{N}(\mu_k, \sigma_k^2)$, with orthogonality enforced on means and covariances, improves rollout stability in molecular/clinical settings.

****delta from paper****: Replace deterministic q_k with probabilistic head; extend $L_{\{\text{orth}\}}$ to penalize covariance overlap $\text{Tr}(\Sigma_i \Sigma_j)$; modify synthesis to sample $\hat{z}_t$ from mixture.

****initial method****: Implement on Water molecular task (Table 6); use diagonal Σ_k for tractability; evaluate entropy of 100-step rollout distributions.

****validation****: Compare RMSD variance across seeds; test if high-entropy factors correspond to physically unstable regions (e.g., solvent shell).

****failure modes****: Increased training instability; covariance orthogonality harder to optimize than mean orthogonality; no clear metric for “useful” uncertainty.

****innovation status****: unverified