

Source coverage: Full paper

Extraction confidence: High

Locator mode: page-grounded

Primary analytical lens: methods

Secondary analytical lens: resource

Context verification: Paper-only

Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper: PDF p. 1]
Authors	Youngmin Chung, Ji Hun Ha, Andrew H. Song, et al.	[Paper: PDF p. 1]
Venue	arXiv	[Paper metadata]
Year	2026	[Paper metadata]
Core contribution	First large-scale, standardized, multi-platform benchmark (STP-BENCH) for virtual ST models, enabling controlled comparison of 21 architectures under unified PFM encoding, gene-level interpretability analysis, and downstream biological utility evaluation	[Paper: PDF p. 2–4, Fig. 1]
Key datasets	STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium+Xenium); STP-BENCH-EXTERNAL (185,831 spots, same 6 cancers, cross-institution/tissue/platform)	[Paper: PDF p. 4–5, Fig. 1b]
Evaluated models	21 models: 14 regression-based (e.g., TRIPLEX, DeepSpot, CFANet), 4 bi-modal retrieval (e.g., BLEEP, mclSTExp), 3 generative (e.g., STFlow, Stem)	[Paper: PDF p. 6–7, Fig. 1c]
Primary encoder	UNiv2 pathology foundation model (PFM), used as default patch encoder where architecturally compatible; exceptions noted (e.g., OmiCLIP, M2OST, M2ORT, HistoSPACE, ST-Net)	[Paper: PDF p. 7–9, 22–23]
Main metrics	Pearson Correlation Coefficient (PCC) [Eq. 1], Mean Absolute Error (MAE) [Eq. 2], Structural Similarity Index Measure (SSIM)	[Paper: PDF p. 31–32, Eq. 1–2]

Field	Value	Source
Gene sets	HMHVGs (200 high-mean highly-variable genes); 16 TME marker genes (e.g., CD3E, ACTA2, PDCD1)	[Paper: PDF p. 7, 33]
Downstream tasks	Cell type deconvolution (Cell2location), spatial domain identification (SpaGCN + ARI), gene set scoring (singscore)	[Paper: PDF p. 14–15, Fig. 4; p. 35–36]
Robustness axes	Cross-Institution, Cross-Tissue, Cross-Platform generalization; intra-/inter-cohort data scaling	[Paper: PDF p. 16–18, Fig. 5]

02 一句话总结

该论文构建了STP-BENCH——首个大规模、跨平台、标准化的虚拟空间转录组（virtual ST）系统性基准，覆盖Visium与Xenium双平台、6种癌症、超79万spots；通过统一采用UNiv2等病理基础模型（PFM）作为图像编码器，解耦了模型架构创新与图像表征能力，发现多数现有模型未超越线性探针基线；进一步揭示基因可预测性存在“形态学天花板”，且多尺度架构（如TRIPLEX、DeepSpot）在基质/免疫相关通路中展现出显著优势，为single-cell foundation models与spatial transcriptomics的交叉对齐提供了关键评估框架与实证约束。

03 研究问题

论文直面虚拟ST领域长期存在的**评估不可靠性问题**：当不同研究使用异构小数据集、不一致训练流程、各自原生图像编码器（如ResNet50 vs ViT-L）、且仅报告平均基因精度时，模型性能比较本质上是混淆的。作者追问：若剥离图像编码器差异，真实架构贡献几何？哪些基因/通路可被可靠地从形态学推断？这种推断能否支撑下游生物学分析（如细胞类型反卷积）？模型在现实域偏移（跨医院、跨癌种、跨平台）下是否鲁棒？这些问题共同指向一个核心：**如何建立公平、可复现、多层次、生物学可解释的虚拟ST评估范式？**

04 研究背景与发展路径

虚拟ST起源于ST实验成本高昂的现实约束，其方法论已分化为三大流派：回归式（ST-Net→TRIPLEX/DeepSpot）、双模态对齐式（BLEEP→mclSTExp）、生成式（STFlow/Stem）。早期工作受限于小规模数据（如HEST-1K仅千级spots）和零散评估，导致结论不可比：Wang et al. [50] 保留各模型原生编码器，混淆架构与特征；HEST-1K [51] 仅用PFM嵌入+简单回归，未评估完整模型栈。STP-BENCH并非延续单点技术改进，而是**自上而下重构评估基础设施**——以“统一编码器+多平台大数据+多层次验证”为三支柱，将评估从“谁跑得快”升级为“谁真正理解形态-表达映射”。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Encoder-architecture confounding	Model rankings shift dramatically when native encoders are replaced with UNlv2 (e.g., CFANet jumps from 16th to 6th)	Prior works inherit original image backbones trained on disparate domains/scales (ImageNet vs pathology WSIs), making architectural gains indistinguishable from feature quality	[Paper: PDF p. 9, Fig. 2b]; [Paper: PDF p. 18–19]
Gene-level opacity	Marker genes (e.g., CD3E, PDCD1) show consistently low PCC (~0.2) vs HMMVGs (~0.4), yet no prior work systematically dissected <i>which</i> genes are predictable	Evaluation focused on aggregate metrics obscures biological specificity; predictability is gene-intrinsic, not model-dependent	[Paper: PDF p. 9, Fig. 2a]; [Paper: PDF p. 11, Fig. 3a]; [Paper: PDF p. 19]
Downstream irrelevance	Models may fit gene expression but fail at cell-type deconvolution or spatial domain detection	Spot-level correlation ≠ biological utility; lack of validation on functional granularities limits translational credibility	[Paper: PDF p. 14–15, Fig. 4]; [Paper: PDF p. 19]
Robustness illusion	Cross-tissue generalization gaps reach −0.35 PCC, far worse than cross-institution (−0.10), yet most papers report only in-distribution performance	Morphology-to-expression mapping is highly tissue-specific; batch effects are secondary to biological heterogeneity	[Paper: PDF p. 17, Fig. 5b middle]; [Paper: PDF p. 19]
Data scaling fallacy	Inter-cohort scaling (BRCA+LUAD+PRAD) often <i>lowers</i> performance on target tissue (negative transfer)	Simple aggregation of heterogeneous tissues ignores tissue-specific morphological priors; “more data” ≠ “better data” without domain adaptation	[Paper: PDF p. 18, Fig. 5d]; [Paper: PDF p. 19]

06 核心思想

STP-BENCH的核心思想是**将评估本身升维为科学问题**：它拒绝将虚拟ST视为单一预测任务，而是定义为一个**多粒度验证管道**——从像素（patch encoder choice）、基因（HMMVG vs marker）、通路（GO gene sets）、细胞（Cell2location）、组织（SpaGCN domains）到系统（cross-tissue robustness）。其底层假设是：**真正的虚拟ST模型必须在所有层级上保持一致性**；若某模型在基因层面PCC高但细胞丰度相关性低，则其预测是统计幻觉而非生物学可信。因此，STP-BENCH不是提供“SOTA榜单”，而是绘制一张**可解释的性能地形图**，标定每个模型的能力边界与失效模式。

07 方法总览

STP-BENCH的方法论是“控制变量+多轴验证”：(1) **统一编码器层**：强制UNiv2（或Virchow2/H-Optimus1等）作为patch encoder，仅对架构不兼容者（M2OST/M2ORT/OmiCLIP等）豁免；(2) **分层评估层**：① spot-level（PCC/MAE/SSIM），② gene-level（heatmap + margin analysis），③ gene-set-level（singscore），④ cellular-level（Cell2location PCC），⑤ tissue-level（SpaGCN ARI）；(3) **鲁棒性压力测试层**：Cross-Institution/Tissue/Platform三类域偏移 + intra-/inter-cohort数据缩放。整个流程确保任何性能差异都可归因于模型架构本身，而非数据或特征工程偏差。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
UNiv2-standardized patch encoder	Extracts morphology-aware embeddings from 224×224 H&E patches	To isolate architectural contribution by eliminating encoder variability; PFMs capture histomorphology better than ImageNet models	Input: H&E patch → Output: d-dim embedding (e.g., 1024-dim)	[Paper: PDF p. 7–10, Fig. 2e]; [Paper: PDF p. 22–23]	Severe ranking distortion (Fig. 2b); models like CFANet collapse without PFM [Paper: PDF p. 9]
HMHVG + TME marker gene panel	Defines evaluation targets: 200 highly expressed/variable genes + 16 biologically annotated markers	To move beyond arbitrary gene lists and probe specific biological programs (e.g., immune checkpoints)	Input: Gene symbols → Output: Two disjoint gene sets for stratified evaluation	[Paper: PDF p. 7, 33]; [Paper: PDF p. 9, Fig. 2a]	Loss of biological interpretability; inability to explain why marker genes underperform [Paper: PDF p. 9–10]
Gene-wise PCC heatmap (Fig. 3a)	Visualizes per-gene predictability across all 20 models	To identify intrinsic gene-level ceilings independent of architecture	Input: Predicted & ground-truth expression per spot → Output: 200×20 matrix of PCC values	[Paper: PDF p. 11, Fig. 3a]; [Paper: PDF p. 19]	Obscures universal predictability patterns; prevents discovery of stromal/immune gene advantages [Paper: PDF p. 13]
Cell2location deconvolution pipeline	Estimates spatial cell-type abundances from predicted expression matrices	To test if virtual ST preserves cellular composition structure, not just gene counts	Input: Virtual ST AnnData → Output: Per-spot cell-type abundance vectors → PCC vs ground-truth	[Paper: PDF p. 14–15, Fig. 4a]; [Paper: PDF p. 35]	Breaks downstream utility chain; TRIPLEX/DeepSpot superiority would remain invisible [Paper: PDF p. 14]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Cross-Platform (Visium→Xenium) evaluation	Tests generalization from spot-level (Visium) to single-molecule (Xenium) resolution	To assess if models trained on lower-resolution data can leverage higher-sensitivity platforms	Input: Visium-trained model → Output: PCC on Xenium pseudo-spots	[Paper: PDF p. 16–17, Fig. 5a right]; [Paper: PDF p. 22]	Masks platform-dependence of biological limits; fails to reveal Xenium’s superior signal-to-noise enables better marker prediction [Paper: PDF p. 10]

09 关键公式与符号

论文未提出新公式，但严格定义并依赖三个核心指标：

- **Pearson Correlation Coefficient (PCC)** [Eq. 1, p.31]:

$$\text{PCC}_{g,s} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$$
 其中 $\hat{y}_{i,g}, y_{i,g}$ 是spot i 、gene g 的log-normalized预测/真值； $\bar{\hat{y}}_g, \bar{y}_g$ 为其均值。用于spot/gene/section/dataset各级评估。

- **Mean Absolute Error (MAE)** [Eq. 2, p.32]:

$$\text{MAE}_{g,s} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$$
 在log(1+x)-transformed space计算，量化绝对误差幅度。

- **Structural Similarity Index Measure (SSIM)** [p.32]:

非公式化定义，但明确用于评估预测表达图谱的空间结构保真度（luminance, contrast, structure），输入为二维空间网格上的归一化表达矩阵。**关键符号**: HMHVG (high-mean highly-variable genes), TME (tumor microenvironment), PFM (pathology foundation model), ARI (Adjusted Rand Index), SSIM (Structural Similarity Index Measure), singscore (gene set activity scoring method).

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
UNlv2 vs native encoder (Fig. 2b)	Unified encoder changes model rankings	CFANet with native ResNet50 vs UNlv2; same training protocol	CFANet rank: 16th → 6th	Encoder choice dominates reported architectural gains	"CFANet architecture is superior" — unsupported without UNlv2	[Paper: PDF p. 9, Fig. 2b]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
HMHVG vs marker genes (Fig. 2a)	Gene category dictates predictability ceiling	Same models, same datasets, two gene sets	HMHVG PCC ≈ 0.4 ; marker PCC ≈ 0.2	Predictability is gene-intrinsic; markers are harder due to sparsity	"All genes are equally predictable" — falsified	[Paper: PDF p. 9, Fig. 2a]
Xenium vs Visium (Fig. 2c-d)	Platform resolution affects marker prediction	NCCHE-LUAD-Xenium (high counts) vs NCCHE-LUAD-Visium (low counts)	Xenium marker PCC=0.579; Visium=0.191	Data quality (transcript count) is a key bottleneck for low-abundance genes	"Morphology cannot encode immune states" — contradicted by Xenium success	[Paper: PDF p. 10, Fig. 2c-d]
Multi-scale models on stromal genes (Fig. 3b)	Architectures integrating multi-scale context gain on ECM/immune genes	TRIPLEX/DeepSpot vs LinearProb on COL1A1, LAG3, etc.	$\Delta PCC \geq 0.1$ for 8–85 genes across cohorts	Multi-scale reasoning captures meso/macro tissue patterns (fibrosis, lymphoid aggregates)	"Any deep model suffices for stroma" — false; linear probe fails	[Paper: PDF p. 11–13, Fig. 3b]
Cell2location on virtual ST (Fig. 4a)	Virtual ST preserves cell-type spatial structure	Cell2location applied to TRIPLEX/DeepSpot predictions vs ground-truth	TRIPLEX/DeepSpot achieve highest PCC for epithelial/T cells	Top gene-level performers translate to top cellular-level performers	"Virtual ST enables rare cell detection" — unsupported (plasma/mast cells low PCC)	[Paper: PDF p. 14, Fig. 4a]
Cross-Tissue generalization (Fig. 5b middle)	Biological heterogeneity harms generalization more than technical variation	Models trained on LUAD tested on BRCA/CCRCC	Generalization gap: -0.20 to -0.35 PCC	Morphology-to-expression mapping is highly tissue-specific	"A universal virtual ST model exists" — contradicted	[Paper: PDF p. 17, Fig. 5b middle]
Inter-cohort scaling (Fig. 5d)	Aggregating diverse cancers causes negative transfer	Training on BRCA $\rightarrow$ BRCA+LUAD $\rightarrow$ BRCA+LUAD+P RAD	Performance on BRCA test set decreases with added cancers	Simple data mixing is detrimental without tissue-aware learning	"More multi-cancer data always helps" — falsified	[Paper: PDF p. 18, Fig. 5d]

11 对结论的正确理解

- **"Most models don't beat linear probing"** 意味着在UNIV2编码下，复杂架构未带来显著增益，**不等于模型无效**——TRIPLEX/DeepSpot仍稳定优于基线，且在下游任务中表现突出；这反映的是当前架构对PFM特征的利用效率瓶颈，而非虚拟ST范式失败。
- **"Gene predictability is universal"** 指同一基因在所有模型中PCC排序高度一致（Fig. 3a），**不等于所有基因都难预测**——8–85个基因在特定 cohorts中 $PCC \geq 0.4$ 且 $\Delta PCC \geq 0.1$ ，证实形态学确能编码特定程序。

- **"Cross-platform transfer is stable"** (Fig. 5b right) 指Visium→Xenium无显著性能损失，**不等于Visium→Xenium可逆**——论文未测试Xenium→Visium，且Xenium更高灵敏度可能补偿了域偏移。
- **"Negative transfer in inter-cohort scaling"** 揭示组织特异性，**不等于跨癌种学习不可能**——恰说明需domain-adaptive策略（如tissue-aware adapters），而非放弃多癌种数据。
- **"Performance concordance across granularities"** (gene→cell→domain) 表明虚拟ST质量具有一致性，**不等于所有下游 tasks同等鲁棒**——Cell2location和SpaGCN均显示Xenium数据显著优于Visium，提示平台选择影响最终应用。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer/tissue scope	STP-BENCH covers only 6 cancer types and 2 ST platforms (Visium/Xenium)	Extend benchmark to additional tumor types, tissue contexts (e.g., normal, inflamed), and emerging platforms (e.g., Stereo-seq, Slide-seq)	[Paper: PDF p. 20]
Restricted gene set analysis	Evaluations focus only on HMMVGs and 16 TME markers; lowly expressed or functionally diverse genes unexamined	Systematically investigate low-abundance genes, non-coding RNAs, and broader functional categories beyond current panels	[Paper: PDF p. 20]
Spot-level granularity	All evaluations are at the spot level (aggregated multi-cell signals), not single-cell resolution	Extend principles to single-cell ST datasets and virtual ST models as they become available	[Paper: PDF p. 20]
Lack of wet-lab validation	Predictions are validated computationally against ground-truth ST, not via orthogonal experimental assays (e.g., ISH, IHC)	Future work should integrate computational predictions with targeted spatial proteomics or multiplexed imaging for biological confirmation	[Paper metadata selection note: "virtual prediction's biological validity still requires wet experiment verification"]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
TRIPLEX/DeepSpot superiority may stem from training stability, not multi-scale design	These models use ensemble strategies (e.g., 10 ϕ spot modules for DeepSpot [p.26]) and auxiliary losses (TRIPLEX [p.25]), which improve optimization, not necessarily biological fidelity	Attributing gains solely to "multi-scale reasoning" overestimates architectural insight; could be an implementation artifact	Re-implement TRIPLEX/DeepSpot <i>without</i> ensembles/auxiliary losses but with identical hyperparameters; compare to linear probe	[Paper: PDF p. 25–26, Online Methods]
Gene set scoring (singscore) may mask anti-correlated predictions	singscore uses rank-based averaging; a model predicting <i>inverted</i> expression ranks (e.g., high→low) could yield high PCC despite biological implausibility	High gene-set PCC doesn't guarantee directional correctness of pathway activity (activation vs suppression)	Compute Spearman correlation on <i>signed</i> gene set scores (e.g., using GSVA) and compare to singscore results	[Paper: PDF p. 35, Online Methods]
Cross-platform "stability" conflates improvement with compensation	Fig. 5b right shows negligible loss, but Xenium's higher sensitivity may <i>mask</i> true domain shift degradation	Over-optimistic view of cross-platform utility could mislead clinical deployment where Visium remains dominant	Test on <i>matched</i> Visium/Xenium pairs from same tissue section; compute PCC drop <i>within</i> same biological sample, not across cohorts	[Paper: PDF p. 17, Fig. 5b right]
Cell2location evaluation excludes low-PCC samples	Samples with max model PCC <0.1 are excluded [p.35], potentially biasing toward "easier" tissues	Underestimates real-world failure modes in noisy/low-quality data; limits generalizability claim	Report full distribution of Cell2location PCC, including failed samples, and correlate with ST data QC metrics (e.g., spot QC score, library size)	[Paper: PDF p. 35, Online Methods]
"Universal gene predictability" ignores spatial context dependence	Fig. 3a shows gene-wise consistency, but a gene may be predictable only in specific spatial niches (e.g., tumor core vs invasive margin)	Gene-level PCC averages over all spots, hiding context-specific failures critical for precision oncology	Stratify PCC by spatial domain (e.g., tumor, stroma, immune infiltrate) using ground-truth annotations; compute domain-specific PCC	[Paper: PDF p. 11, Fig. 3a]

14 学到的知识

- **评估即建模**：STP-BENCH证明，严谨的benchmark设计本身就能驱动领域认知升级——它迫使社区正视“encoder-architecture confounding”这一隐藏变量，并催生“morphology-to-expression ceiling”的新概念。

- **多尺度是解药，非万能**：TRIPLEX/DeepSpot的成功不在于堆叠更多层，而在于显式建模局部（spot）、邻域（3×3 grid）、全局（WSI）形态梯度，这对解析基质重塑（COL1A1）、免疫空间组织（LAG3）至关重要，但对上皮标记（KRT5）提升有限。
- **数据质量 > 数据量**：Xenium的高计数直接拉升marker基因PCC至0.58，而Visium的低计数将其压至0.19；这警示single-cell foundation models若仅在低-depth data上预训练，将继承并放大信号噪声比缺陷。
- **负迁移是信号，非噪音**：Inter-cohort scaling失败（Fig. 5d）不是实验缺陷，而是强证据——它量化了组织特异性壁垒，为设计tissue-aware adapters或multi-task pretraining提供了明确目标。
- **下游验证是终极裁判**：Cell2location和SpaGCN结果与基因PCC高度一致（Spearman=0.902 [p.13]），证实spot-level metrics *can proxy biological utility*—但仅当评估覆盖足够广的生物学粒度时成立。

15 与既有知识的连接

- **候选连接/方法论连接**：STP-BENCH的“统一编码器+多粒度验证”范式可直接迁移到**single-cell foundation models**——例如，在scFoundation或CellLM上，可设计类似pipeline：固定scRNA encoder（如scGPT），在multi-dataset scRNA+spatial alignment任务中，评估基因/通路/cluster-level一致性。
- **候选连接/方法论连接**：其**cross-tissue generalization failure**为**graph neural networks**在multi-omics中的应用敲响警钟：若GNN在BRCA图上学习的边权重（e.g., gene-gene co-expression）无法泛化到LUAD，需引入tissue-invariant graph construction或meta-learning。
- **候选连接/方法论连接**：**perturbation prediction**任务（如CROP-seq）可借鉴其robustness分析——测试模型在perturbed vs control tissue morphologies下的预测稳定性，定义“perturbation robustness gap”。
- **弱连接/方法论连接**：**cross-modal alignment**（如H&E↔RNA）的评估常止步于embedding similarity（e.g., CLIP loss），STP-BENCH证明必须延伸至functional alignment（e.g., gene set PCC, cell type PCC），否则alignment无生物学意义。
- **弱连接/方法论连接**：**biomedical AI**的临床落地常卡在“黑箱可信度”，STP-BENCH的gene-wise heatmap（Fig. 3a）提供了一种可解释性模板：不解释单个预测，而解释“模型能/不能做什么”，这对监管审批更实用。

16 研究想法

- **name**: Tissue-Aware Adapter for Virtual ST

originating limitation/observation: Inter-cohort scaling causes negative transfer (Fig. 5d); cross-tissue

generalization gap is large (Fig. 5b middle) **core hypothesis**: Injecting lightweight, tissue-specific adapters into frozen PFM encoders can preserve morphology knowledge while adapting to tissue-specific expression priors

delta from paper: STP-BENCH identifies the problem but does not propose a solution; this adds trainable LoRA-style adapters per tissue type, conditioned on organ ontology embeddings

initial method: For each tissue (BRCA/LUAD/PRAD), add two 64-dim adapter layers after UNiV2's final layer; train adapters + final regressor head only; freeze UNiV2 backbone **validation**:

Compare adapter vs fine-tuning on cross-tissue transfer (LUAD→BRCA); metric: PCC on marker genes and Cell2location PCC

failure modes: Adapters overfit to small tissue cohorts; fail to generalize to unseen tissues (e.g., new cancer type) **innovation status**: unverified

- **name**: Morphology-Guided Gene Set Prior

originating limitation/observation: Gene set scoring (Fig. 3e) shows TRIPLEX/DeepSpot excel on immune/stromal pathways, but current models treat all genes equally **core hypothesis:** Incorporating prior knowledge of gene co-regulation (e.g., from SCENIC or DoRothEA) as a structural constraint during training improves pathway-level fidelity **delta from paper:** STP-BENCH *measures* gene set performance but doesn't *leverage* it in modeling; this adds a graph-regularized loss where edges represent TF-target relationships **initial method:** Construct gene co-expression graph from public scRNA; use GraphSAGE to embed genes; add loss term: MSE between predicted and ground-truth gene set scores (singscore) **validation:** On NCCHE-LUAD-Xenium, compare gene set PCC (Fig. 3e) and ARI (Fig. 4c) vs baseline TRIPLEX **failure modes:** Prior knowledge incompleteness biases predictions; graph sparsity hurts low-degree genes **innovation status:** unverified

- **name:** Spatially-Stratified Gene Predictability Atlas

originating limitation/observation: Gene-wise PCC (Fig. 3a) is averaged over all spots, masking spatial-context dependence (e.g., LAG3 predictable only in immune niches) **core hypothesis:** Partitioning tissue into spatial domains (e.g., tumor/stroma/immune) and computing domain-specific PCC reveals context-dependent morphology-encoding capacity **delta from paper:** STP-BENCH computes global PCC; this introduces spatial stratification *before* aggregation **initial method:** Use SpaGCN (Fig. 4b) to segment each tissue; compute PCC for each gene *within each domain*; build atlas of "predictable genes per domain" **validation:** Correlate domain-specific PCC with histopathology features (e.g., fibrosis score, immune infiltration density) from pathologist annotations **failure modes:** Domain segmentation noise propagates to PCC estimates; small domains yield unstable PCC **innovation status:** unverified

- **name:** Single-Cell Resolution Virtual ST Benchmark Extension

originating limitation/observation: Authors explicitly note spot-level limitation and call for single-cell extension (p.20) **core hypothesis:** STP-BENCH principles (unified encoder, multi-granularity, robustness) scale to single-cell ST, but require new metrics for sub-spot heterogeneity **delta from paper:** This proposes concrete extensions: (1) replace spot-level PCC with cell-type-specific PCC using scRNA reference; (2) add sub-spot spatial variance metrics (e.g., entropy of predicted cell types within spot) **initial method:** Leverage Xenium single-molecule data; define "virtual scST" as per-cell prediction; use CellTypist for cell-type annotation; compute PCC per cell type **validation:** Benchmark existing scST models (e.g., scGPT-ST, SpaFormer) on STP-BENCH-EXTERNAL single-cell subsets **failure modes:** Ground-truth scST data scarcity; ambiguity in cell-type assignment affects PCC reliability **innovation status:** unverified