

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	MARC: Morphology-Aware Regression of Consensus for Cell Segmentation in Subcellular Spatial Transcriptomics	[Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper: PDF p. 1]
Year	2026	[Paper: PDF p. 1]
Authors	Xinyu Shu, Andrew Zhang, Jean Yang, Jinman Kim	[Paper: PDF p. 1]
Core task	Pixel-level consensus-support map prediction for SST candidate segmentation masks	[Paper: PDF p. 3, Eq. 3]
Input modalities	Candidate binary foreground mask F_k , aligned DAPI morphology D , transcript-density map T	[Paper: PDF p. 3, Eq. 2]
Output	Continuous pixel-wise consensus-support map $\hat{C}_k$ in $[0,1]^{H \times W}$, aggregated to cell-level scores $S_{k,c}$	[Paper: PDF p. 3, Eq. 3]; [Paper: PDF p. 5, Eq. 8]
Supervision signal	Leave-one-method-out (LOMO) mean consensus $C^{(-k)}$ computed from other three candidate methods	[Paper: PDF p. 3, Eq. 5]; [Paper: PDF p. 4]
Loss function	Foreground-Union Consensus Loss (FUCL), mean absolute error over union mask U_k	[Paper: PDF p. 4, Eq. 7]
Architecture	Four-level U-Net-style encoder-decoder with 32–256 channel progression; final sigmoid output	[Paper: PDF p. 3, Sec 3.2]; [Figure 2: PDF p. 4]
Evaluation dataset	4,642 held-out tiles from 10x Genomics Xenium FFPE human renal cell carcinoma	[Paper: PDF p. 5, Sec 4.1]
Candidate methods	Cellpose-SAM, BIDCell, ProSeg, Xenium 10x onboard segmentation	[Paper: PDF p. 5, Sec 4.1]; [Table 1: PDF p. 4]

Field	Value	Source
Key metrics	Pixel-level: Foreground-union L1 ↓, Dice ↑, IoU ↑; Cell-level: Spearman ρ ↑	[Table 1: PDF p. 4]; [Paper: PDF p. 5]

02 一句话总结

本文提出 MARC (Morphology-Aware Regression of Consensus)，一种无需多方法推理即可预测 subcellular spatial transcriptomics (SST) 中候选细胞分割掩码的跨方法共识支持度的深度学习框架；它通过将候选掩码 \$F_k\$、DAPI 形态 \$D\$ 和转录密度 \$T\$ 融合为三通道输入，回归出像素级连续共识支持图 \$\hat{C}_k\$，从而绕过显式多管道共识构造的计算瓶颈；该方法在 Xenium 肾癌数据上实现平均 Dice 0.9002 与细胞级 Spearman 相关性 0.7905，证明其可替代显式共识用于大规模 SST 分割质量控制，但其本质仍是共识代理 (surrogate)，非真值。

03 研究问题

SST 中细胞分割质量评估缺乏可靠 ground truth：手动标注成本极高且生物边界本身模糊 [Paper: PDF p. 1]；而现有监督式 QC 方法（如 SegQC）依赖专家修正掩码，不确定性方法（如 Bayesian）需访问生成模型内部状态，均不适用于外部输入的异构候选掩码 [Paper: PDF p. 3]。因此，核心问题是：**如何在无真值、无模型白盒访问权限的前提下，对任意 SST 分割 pipeline 输出的候选掩码进行可扩展、共识感知的质量评估？** 作者假设：多方法间的一致性 (consensus) 虽非真值，却是最可行的代理监督信号；进一步假设：该共识支持度可被建模为形态与分子上下文驱动的回归任务，而非必须执行全部 pipeline。

04 研究背景与发展路径

传统图像分割 QC 依赖人工标注或模型内不确定性估计，但 SST 的特殊性在于：① 分割直接决定 transcript-to-cell 分配，错误边界引发下游生物学误读 [Paper: PDF p. 1]；② 多种 SST 专用方法（Cellpose-SAM、BIDCell、ProSeg、Xenium）因输入模态与假设不同，产生互补但冲突的边界 [Paper: PDF p. 1-2]；③ 显式共识（如 Figure 1a 所示）需运行全部 pipeline，计算不可扩展 [Paper: PDF p. 2]。已有共识方法（如 STAPLE）仍需多方法执行 [Paper: PDF p. 3]；而 MARC 的发展路径是：放弃“执行共识” → 转向“学习共识模式” → 利用 leave-one-method-out 构造伪标签 → 设计 FUCL 聚焦前景与分歧区 → 实现单次前向即得共识支持图。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
No scalable ground truth	Manual annotation prohibitive for large SST datasets; boundaries biologically ambiguous even for experts	SST tissue contains many densely packed cells; weak morphological contrast, sparse/displaced transcripts [Paper: PDF p. 1]	“manual annotation of a large number of cells is time-consuming” [Paper: PDF p. 1]; “cell boundaries may be biologically ambiguous” [Paper: PDF p. 3]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Incompatibility of existing QC methods	SegQC requires expert-corrected masks; Bayesian uncertainty requires access to the segmentation model’s internals	Neither method supports evaluation of externally generated candidate masks when expert annotations are unavailable [Paper: PDF p. 3]	“these approaches do not readily support the evaluation of candidate masks produced by different SST segmentation pipelines when expert annotations are unavailable” [Paper: PDF p. 2]
Computational bottleneck of explicit consensus	Running all complementary segmentation pipelines per tile is computationally intensive and difficult to scale	Each method requires its own SST-specific inputs and configuration [Paper: PDF p. 2]	“explicit consensus averages outputs from multiple segmentation pipelines [...] making consensus construction computationally intensive” [Figure 1a: PDF p. 2]; “this process is computationally intensive and difficult to scale” [Paper: PDF p. 2]
Lack of consensus-aware representation for downstream use	Candidate masks lack interpretable, spatially resolved quality signals usable for filtering or review	Prior work focuses on generating better masks, not evaluating reliability of external candidates [Paper: PDF p. 3]	“Most existing work focuses on generating improved masks rather than evaluating the reliability of an externally generated candidate mask” [Paper: PDF p. 3]

06 核心思想

MARC 的核心思想是将“共识质量评估”重构为一个**形态与分子上下文感知的密集回归任务**，而非分类或不确定性估计：它不试图判断某个像素是否属于细胞（segmentation），而是判断该像素在多方法共识中的支持强度（consensus support）。这一范式转变的关键洞察在于——共识不是离散的“是/否”，而是连续的“支持程度”，且该程度可由局部形态（DAPI）、分子信号（transcript density）与候选几何（ $\mathcal{F}_k$ ）共同解释。因此，MARC 放弃了传统 QC 对真值或模型内部状态的依赖，转而以 leave-one-method-out 共识为可学习的代理目标，并通过 FUCL 强制模型关注最具判别力的区域（即候选与共识前景的并集），最终实现单次前向即输出空间可解释的质量图。

07 方法总览

MARC 将 SST 分割 QC 解耦为两个阶段：① **训练阶段**：以每个候选方法 $\mathcal{K}$ 的掩码 $\mathcal{F}_k$ 、DAPI $\mathcal{D}$ 、转录密度 $\mathcal{T}$ 为输入，构建三通道张量 $X_k = \text{concat}(\mathcal{D}, \mathcal{T}, \mathcal{F}_k)$ ；监督信号为其余 $K-1=3$ 个方法的平均二值前景图 $C^{(-k)}$ ；采用 Foreground-Union Consensus Loss（FUCL）优化 U-Net 回归器 f_{θ} ，输出连续共识支持图 $\hat{C}_k$ ；② **推理阶段**：仅需单次前向，输入任意 $\mathcal{F}_k, \mathcal{D}, \mathcal{T}$ ，即得 $\hat{C}_k$ ，再按原始标签图 M_k 聚合为细胞级分数 $S_{k,c}$ 。全程无需运行其他 segmentation pipeline，突破显式共识的计算墙。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Leave-one-method-out (LOMO) consensus target $C^{\{-k\}}$	Construct pseudo-ground-truth by averaging foreground maps of all <i>other</i> candidate methods	Provides scalable, multi-source supervision without manual labels or model internals	Input: $K-1$ binary foreground masks $F_{j, j \neq k}$; Output: $C^{\{-k\}} \in [0,1]^{H \times W}$	Eq. 5 [Paper: PDF p. 3]; “excludes the candidate method from its own target prevents trivial self-agreement” [Paper: PDF p. 3]	Without LOMO, model would collapse to identity mapping (candidate-copy baseline Dice=0.8189 < MARC’ s 0.9002) [Table 2: PDF p. 6]
Foreground-Union Consensus Loss (FUCL)	Compute MAE only over pixels in union of candidate foreground F_k and LOMO consensus foreground $C^{\{-k\}}$	Focuses training on discriminative regions (agreement + disagreement), avoids background-dominated gradients	Input: $\hat{C}_k, C^{\{-k\}}, U_k$; Output: scalar loss $L^{\{k\}}_{\text{FU}}$	Eq. 6–7 [Paper: PDF p. 4]; “restricting the loss to U_k focuses learning on foreground and disagreement regions” [Paper: PDF p. 4]	Without union masking, loss would be diluted by background zeros; ablation not performed but FUCL is core design claim [Paper: PDF p. 4]
Three-channel input fusion (D, T, F_k)	Encode complementary biological signals: nuclear morphology, transcript abundance, candidate geometry	Candidate mask alone is insufficient (Dice=0.8565); morphology adds ranking power (p jumps from 0.42→0.76); transcripts refine both pixel & cell levels	Input: D, T, F_k (each $H \times W$); Output: $X_k \in \mathbb{R}^{3 \times H \times W}$	Eq. 2 [Paper: PDF p. 3]; Table 2 shows progressive gain from $F_k \rightarrow F_k + D \rightarrow F_k + D + T$ [PDF p. 6]	Removing D : cell-level p drops 0.034 (0.7905→0.7564); removing both D & T : p collapses to 0.4228 [Table 2: PDF p. 6]
Cell-level aggregation (Eq. 8)	Convert dense $\hat{C}_k$ into per-cell quality score $S_{\{k,c\}}$ by averaging over pixels in cell c	Enables practical QC tasks: ranking cells for manual review, filtering low-consensus cells	Input: $\hat{C}_k, M_k$; Output: scalar $S_{\{k,c\}}$ per cell c	Eq. 8 [Paper: PDF p. 5]; “scores can be used to rank cells for manual review” [Paper: PDF p. 5]	Without aggregation, no cell-level interpretation; candidate-copy baseline yields constant scores (p undefined) [Table 2: PDF p. 6]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
U-Net regression head	Predict continuous $\hat{C}_k$ via encoder-decoder with skip connections	Captures multi-scale morphological and transcript context essential for consensus reasoning	Input: X_k ; Output: $\hat{C}_k = \sigma(Z_k)$ (sigmoid-clamped)	Figure 2 [PDF p. 4]; Eq. 4 [Paper: PDF p. 3]; “four-level U-Net-style” [Paper: PDF p. 3]	Standard U-Net replaced by classifier head would lose spatial continuity; no ablation reported but architecture choice aligns with dense prediction need

09 关键公式与符号

论文未提供显式“算法公式”，但明确定义了以下关键符号与可核验关系：

- M_k : 候选方法 k 的带标签掩码（整数矩阵）， $M_k(x,y)=c$ 表示像素 (x,y) 属于细胞实例 c [Paper: PDF p. 3, Sec 3.1]
- F_k : M_k 的二值前景图， $F_k(x,y) = \mathbf{1}[M_k(x,y)>0]$ [Eq. 1: PDF p. 3]
- D, T : 对齐的 DAPI 形态图与转录密度图（均为 $H \times W$ 灰度图） [Paper: PDF p. 3, Sec 3.1]
- $X_k = \text{concat}(D,T,F_k)$: 三通道输入张量 [Eq. 2: PDF p. 3]
- $\hat{C}_k = f_{\theta}(X_k) = \sigma(Z_k)$: 连续共识支持图， $[0,1]$ 区间， f_{θ} 为 U-Net [Eq. 3–4: PDF p. 3]
- $C^{(-k)} = \frac{1}{K-1} \sum_{j \neq k} F_j$: leave-one-method-out 共识目标（ $K=4$ ） [Eq. 5: PDF p. 3]
- $U_k(x,y) = \mathbf{1}[F_k(x,y)=1 \vee C^{(-k)}(x,y)>0]$: 前景并集掩码 [Eq. 6: PDF p. 4]
- $L^{(k)}_{\text{FU}} = \frac{1}{|U_k|} \sum_{x,y} U_k(x,y) \cdot |\hat{C}_k(x,y) - C^{(-k)}(x,y)|$: FUCL 损失 [Eq. 7: PDF p. 4]
- $S_{k,c} = \frac{1}{|\{(x,y): M_k(x,y)=c\}|} \sum_{(x,y): M_k(x,y)=c} \hat{C}_k(x,y)$: 细胞级共识分数 [Eq. 8: PDF p. 5]
- Metrics: Foreground-union L1 (MAE on U_k), Dice, IoU, Sensitivity, Precision (all thresholded at 0.5), Cell-level Spearman ρ [Paper: PDF p. 5]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Table 1 main results	MARC predicts explicit LOMO consensus with high fidelity	MARC vs. explicit $C^{\{-k\}}$ across 4 candidate methods; same test set (18,443 examples)	Avg. Dice=0.9002, L1=0.0981, $\rho=0.7905$	MARC closely approximates explicit cross-method consensus at both pixel and cell levels	MARC predictions are <i>more accurate</i> than explicit consensus (no ground truth comparison)	[Table 1: PDF p. 4]; [Paper: PDF p. 5]
Table 2 input ablation	Morphology and transcript signals provide complementary information beyond candidate geometry	MARC variants: F_k only / F_k+D / F_k+D+T ; all trained & evaluated on same LOMO targets	Adding D : $\rho \uparrow 0.3336$ (0.4228 $\rightarrow$ 0.7564); adding T : $\rho \uparrow 0.0341$ (0.7564 $\rightarrow$ 0.7905); Dice $\uparrow 0.0437$ (0.8565 $\rightarrow$ 0.9002)	DAPI morphology is primary driver for cell-level ranking; transcripts refine both pixel and cell performance	Transcript density is <i>necessary</i> for high performance (baseline F_k+D already achieves $\rho=0.7564$)	[Table 2: PDF p. 6]; [Paper: PDF p. 6]
Figure 3 scatter plots	Cell-level aggregation preserves consensus-based ranking	Predicted $S_{\{k,c\}}$ vs. target $S^{\{\text{target}\}}_{\{k,c\}}$ (computed from $C^{\{-k\}}$) per candidate method	Strong linear trends ($\rho=0.6251-0.8802$); low-consensus cells clearly separable	Aggregation converts dense map into meaningful, rank-preserving cell scores for QC prioritization	The ranking is <i>biologically validated</i> (no external validation, only consensus agreement)	[Figure 3: PDF p. 5]; [Paper: PDF p. 5]
Figure 4 qualitative analysis	MARC localises weakly supported regions spatially	Visual inspection of predicted $\hat{C}_k$ vs. DAPI/ T/F_k on held-out test tiles	High support where F_k aligns with DAPI nuclei & transcript density; low support where F_k extends into background or disagrees with morphology/molecules	MARC produces spatially varying, interpretable consensus maps that reflect multi-modal evidence	Low-prediction regions correspond to <i>true segmentation errors</i> (consensus is surrogate, not ground truth)	[Figure 4: PDF p. 7]; [Paper: PDF p. 7]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Target ablation (mean vs. STAPLE)	Mean consensus supervision yields better sensitivity & ranking than STAPLE	Two MARC models: same inputs/architecture/loss, differing only in target ($C^{(-k)}$)\$ mean vs. STAPLE fusion)	Mean: higher sensitivity (0.9168 vs. 0.8860) & ρ (0.7905 vs. 0.7491); STAPLE: higher precision (0.9128 vs. 0.8843)	Mean consensus is pragmatically preferable for QC (prioritizes recall of low-consensus cells)	STAPLE targets are <i>less accurate</i> (models evaluated against different targets; no shared ground truth)	[Paper: PDF p. 5–6]

11 对结论的正确理解

MARC 并未解决 SST 分割的根本歧义性问题，而是提供了一种**高效、可扩展的共识代理评估工具**：它成功证明，给定一个候选掩码 F_k 及其对应的形态 D 与分子 T 信号，一个轻量 U-Net 可以高保真地回归出该掩码在多方法共识中的支持强度 $\hat{C}_k$ ，其像素级重叠（Dice 0.90）和细胞级排序（ ρ 0.79）均接近显式共识。这意味着：① QC no longer requires running all pipelines —— 单次前向即可获得空间分辨的质量图；② 低共识细胞可被自动识别用于人工复核；③ 共识支持图本身可作为下游分析（如 perturbation prediction）的细胞状态置信度加权因子。但必须清醒认识：**所有结论均相对于 LOMO 共识这一代理目标成立；MARC 的输出是“共识一致性”的度量，而非“生物学正确性”的度量** [Paper: PDF p. 7]。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Consensus as surrogate	Failure modes common to all candidate methods may be reinforced; consensus does not guarantee biological correctness	Acknowledge it’ s a pragmatic alternative to manual annotation, reducing reliance on single-method biases	[Paper: PDF p. 7]
Limited generalisability	Evaluated only on one Xenium renal cell carcinoma dataset; candidate methods share inputs from same assay, thus not fully independent	Evaluate on additional tissues, platforms, and segmentation methods; incorporate orthogonal membrane/protein markers for validation; test if consensus-guided filtering improves downstream analyses	[Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
MARC’s high cell-level Spearman ($\rho=0.79$) may reflect correlation with <i>size</i> or <i>compactness</i> , not true consensus	Candidate masks with larger area or smoother boundaries may inherently receive higher average $\hat{C}_k$ due to geometric averaging bias in Eq. 8, independent of multi-method agreement	Would undermine MARC’s utility for QC: low-consensus small cells (e.g., apoptotic) could be masked by size-driven averaging	Regress $S_{\{k,c\}}$ against cell area/roundness; compute partial correlation controlling for morphology features; compare ρ on size-stratified subsets	Eq. 8 aggregates by pixel count; Figure 4 legends report “area in pixels” but no analysis of area-confounding [Figure 4: PDF p. 7]
FUCL’s union mask U_k may under-supervise <i>background disagreement</i> (e.g., false positives outside all methods’ foreground)	U_k excludes pixels where both $F_k=0$ and $C^{(-k)}=0$; yet false positives in F_k that disagree with <i>all</i> other methods are clinically critical errors	Missed false positives reduce QC sensitivity for over-segmentation; FUCL’s focus on foreground may ignore this failure mode	Train variant with full-image MAE or background-weighted loss; compare false positive rates on held-out examples with known artifacts	FUCL definition explicitly restricts to U_k [Eq. 7: PDF p. 4]; no ablation of loss region reported
Input ablation shows DAPI dominates ranking gain, but transcript density’s role is underspecified	Table 2 shows TS adds only $+0.0341$ to ρ ; yet transcripts are central to SST biology — perhaps TS ’s signal is redundant with DAPI in renal carcinoma, or its encoding (density map) is too coarse	Risks overlooking transcript-specific consensus cues (e.g., gene co-expression patterns) crucial for cell state representation	Replace TS with gene-specific or pathway-level transcript embeddings; test on datasets with stronger transcript-morphology discordance (e.g., immune infiltration)	TS defined as “transcript-density image” [Paper: PDF p. 3]; no details on binning/resolution or gene selection

14 学到的知识

- **Consensus-as-supervision paradigm:** 在无真值场景下，leave-one-method-out 共识是可学习、可泛化的高质量代理监督信号，尤其适用于多源异构方法产出的评估任务。
- **FUCL design principle:** 对密集回归任务，损失函数的空间掩码（如 foreground-union）比全局损失更有效——它 forces the model to attend to discriminative regions (agreement + disagreement)，避免背景主导梯度。
- **Modality contribution hierarchy:** 在 SST QC，候选几何 F_k provides baseline structure; DAPI morphology SD is the dominant signal for *cell-level ranking* (ρ jump $+0.33$); transcript density TS acts as a refinement layer for both pixel accuracy and ranking robustness.
- **Aggregation matters:** Simple averaging (Eq. 8) suffices for cell-level scores, but its sensitivity to cell size/shape is an unexamined confounder — future work should explore attention-based or morphology-aware pooling.

- **Evaluation protocol insight:** Reporting both pixel-level (Dice/IoU) and cell-level (Spearman ρ) metrics is essential; high Dice alone doesn't guarantee useful ranking for QC.

15 与既有知识的连接

- **候选连接/方法论连接:** MARC 的 leave-one-method-out + dense regression framework is directly transferable to **single-cell foundation models**, where consensus among multiple scRNA-seq imputation or batch-correction methods could serve as proxy targets for quality control of latent representations.
- **候选连接/方法论连接:** The foreground-union loss (FUCL) design resonates with **graph neural networks** for spatial omics — one could define a graph where nodes are superpixels and edges encode morphological/transcript similarity, then apply a GNN to predict consensus support, using U_k as node mask for loss.
- **候选连接/方法论连接:** MARC's input fusion (D, T, F_k) exemplifies **multi-omics integration at the image level**, offering a blueprint for fusing spatial proteomics (e.g., CODEX) or metabolomics maps with transcript data in future SST QC.
- **弱连接/方法论连接:** While MARC itself doesn't perform perturbation prediction, its cell-level consensus score $S_{\{k,c\}}$ is a natural confidence weight for **perturbation prediction models** — e.g., downweighting low- $S_{\{k,c\}}$ cells in training to improve robustness.
- **弱连接/方法论连接:** The idea of regressing a “support map” instead of hard segmentation aligns with **cell state representation** goals — one could extend MARC to predict not just consensus, but also state stability (e.g., transcriptional noise) conditioned on multi-modal inputs.

16 研究想法

- **name:** Consensus-Guided Perturbation Filtering (CGPF)

originating limitation/observation: MARC outputs cell-level consensus scores $S_{\{k,c\}}$, but paper does not test whether filtering low-consensus cells improves downstream perturbation prediction [Paper: PDF p. 7]. **core hypothesis:** Cells with low MARC consensus ($S_{\{k,c\}} < \tau$) exhibit higher technical noise and lower biological signal-to-noise ratio, so excluding them during training will improve perturbation response prediction accuracy. **delta from paper:** MARC is purely a QC tool; CGPF integrates its output as a *training filter* for perturbation models (e.g., scGen, trVAE). **initial method:** On a perturbed SST dataset (e.g., drug-treated Xenium), train perturbation predictor using only cells with $S_{\{k,c\}} > 0.7$; compare MSE on held-out perturbed cells vs. full-cell training. **validation:** Downstream metric: correlation between predicted and observed transcript changes for top 100 DEGs; ablation: vary τ (0.5–0.9). **failure modes:** Over-filtering removes biologically rare but high-fidelity perturbed states; consensus may not correlate with perturbation-specific noise. **innovation status:** unverified

- **name:** Multi-Modal Consensus Graph (MMCG)

originating limitation/observation: MARC uses rasterized D, T, F_k ; but spatial relationships (e.g., cell-cell communication) are lost — a graph representation could capture neighborhood consensus. **core hypothesis:** Consensus support is not only pixel-intrinsic but context-dependent: a cell's $S_{\{k,c\}}$ should be modulated by the consensus scores of its spatial neighbors. **delta from paper:** Replace U-Net

with a GNN that takes as node features $[D_c, T_c, \text{area}_c, S^{\{\text{init}\}}_c]$ and edge features (distance, morphology similarity), predicting refined $S^{\{\text{refined}\}}_c$. **initial method:** Build k-NN graph on cell centroids; use GCN or GAT; supervise on LOMO $S^{\{\text{target}\}}_c$; compare ρ with MARC baseline. **validation:** Ablate neighborhood features; visualize attention weights on edges; test on tissue regions with known spatial gradients (e.g., tumor core vs. margin). **failure modes:** Graph construction sensitive to segmentation errors; no guarantee neighborhood consensus improves over pixel-level signal. **innovation status:** unverified

- **name:** Transcript-Embedding MARC (TE-MARC)

originating limitation/observation: Input ablation shows transcript density T contributes modestly ($+0.0341 \rho$); but T is a scalar density map, discarding gene identity — using gene-specific embeddings may unlock stronger signal. **core hypothesis:** Gene-module or pathway-level transcript embeddings (e.g., from scFoundation) contain richer consensus cues than raw density, especially for functionally coherent cell states. **delta from paper:** Replace T (scalar density) with $T_{\{\text{emb}\}} \in \mathbb{R}^{d \times H \times W}$, where each channel is a pathway activity score; modify first conv layer to handle $3+d$ channels. **initial method:** Precompute pathway scores (e.g., Hallmark) on Xenium spots; upsample to image grid; train TE-MARC; ablate pathways (e.g., EMT, proliferation). **validation:** Compare ρ gain vs. baseline MARC; check if pathway ablation degrades ρ more for relevant cell types (e.g., EMT pathway for invasive cells). **failure modes:** Pathway scores noisy at subcellular resolution; embedding dimension d may cause overfitting on small dataset. **innovation status:** unverified