

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: discovery
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Rethinking Class Imbalance for Single-Cell Foundation Models: A Systematic Benchmark Across Architectures and Long-Tail Loss Functions	[Paper] [Paper: PDF p. 1]
Authors	Zeyu Dong, Jiahui Zhong	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
URL	http://arxiv.org/abs/2609.23325v1	[Paper meta]
PDF URL	https://arxiv.org/pdf/2609.23325v1	[Paper meta]
Publication date	2026-09-20	[Paper meta]
Code availability	https://github.com/jz890/sc-imbalance	[Paper] [Paper: PDF p. 7]
Datasets	Multiple Sclerosis (MS), Zheng68K, human Pancreas	[Paper] [Paper: PDF p. 3]
Backbones	scGPT, scBERT, Geneformer	[Paper] [Paper: PDF p. 3]
Losses evaluated	Cross-entropy (CE), weighted CE, class-balanced loss, focal loss, LDAM, logit-adjusted softmax	[Paper] [Paper: PDF p. 3]
Total runs	162 (3 backbones × 3 datasets × 6 losses × 3 seeds)	[Paper] [Paper: PDF p. 1]
Key metrics	Macro-F1, rare-class recall (Recall _R), rare-class precision, rare-class macro-AUPRC, Δ F1 _c , NC1	[Paper] [Paper: PDF p. 3–6]

02 一句话总结

该论文系统评测了六种长尾损失函数在三种单细胞基础模型（scGPT/scBERT/Geneformer）和三个真实数据集（MS/ Zheng68K/Pancreas）上的表现，发现整体准确率严重掩盖罕见细胞类型（如疾病相关病理亚群）的系统性失败；这种失败可划分为两类：一类是“损失敏感型”（loss-sensitive），可通过重加权类平衡损失等方法显著提升性能；另一类是“严重纠缠型”（severely entangled），其根本瓶颈在于训练样本绝对数量过少（如仅3个细胞）与嵌入空间几何结构（如邻域吸收、高NC1）共同导致，现有损失函数均无法缓解。论文由此提出

首个机制驱动的实践指南：用NC1与最近邻混淆模式预判失败类型，对可恢复类优先选用class-balanced loss或LDAM，对不可恢复类应转向数据增补或拒判策略，而非继续优化损失。

03 研究问题

论文直面单细胞基础模型在临床关键场景下的可信度断层：当模型报告97.5%的总体准确率时，是否仍会系统性漏检那些仅含个位数样本、却承载疾病早期信号的罕见细胞亚型？作者不满足于将问题归因为“数据不平衡”，而是追问更精细的机制问题：（1）不同长尾损失函数的收益是否依赖于特定骨干架构？（2）罕见类失败是统一现象，还是存在本质不同的子类型？（3）若存在可恢复子类型，决定其是否受益于重加权的关键变量是相对频率（如占比<5%），还是绝对样本量？（4）若存在不可恢复子类型，其失败根源是表征坍塌（representation collapse），还是分类器训练缺陷？这些问题共同构成对“长尾损失是否万能解药”的实证拷问。

04 研究背景与发展路径

单细胞基础模型（scGPT/scBERT/Geneformer）已成为细胞类型注释默认主干，但其高聚合准确率被证实由常见细胞主导，而罕见细胞（如MS中的病理寡突胶质细胞C、吞噬细胞）常被忽略 [Paper] [Paper: PDF p. 1]。此前工作已识别该问题：Alsabbagh et al. (2023) 发现随机过采样最稳健，但聚焦采样策略而非损失函数；Naziri et al. (2025) 在AML中观察到健康vs.复发样本F1骤降，归因于预训练偏差；Al Amin et al. (2025) 揭示人口统计学失衡亦影响微调。长尾学习领域已有成熟损失族（重加权、focal loss、LDAM、logit adjustment）[Paper] [Paper: PDF p. 2]，但其在单细胞基础模型上的系统性跨架构评估尚属空白。本文承接此缺口，将“损失函数选择”作为独立控制轴，在固定采样分布与批处理条件下，隔离考察其效应，从而补全从采样→表示→分类的完整干预谱系。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Aggregate metrics mask rare-class failure	Accuracy > Macro-F1 > rare-class recall consistently across all 9 (backbone, dataset) settings [Paper] [Paper: PDF p. 3]	Dataset structure (training-set scarcity), not pretraining bias, drives the gap [Paper] [Paper: PDF p. 1]	Figure 2 (left): Pancreas has highest accuracy but largest accuracy-to-rare-recall drop; Table 1 shows consistent ordering across datasets [Paper] [Paper: PDF p. 4–5]
Loss-level interventions are insufficient for some rare classes	Two MS classes (oligodendrocyte C, phagocyte) achieve near-zero F1 under <i>all</i> six losses and <i>all</i> three backbones [Paper] [Paper: PDF p. 5]	Training-set size too small (n=3 cells) to learn distinguishable representation; geometric absorption into unrelated classes’ neighborhoods [Paper] [Paper: PDF p. 5–6]	Figure 3 (left): two darkest rows across all columns; Figure 4: UMAP shows 116 test cells absorbed in CE/LDAM spaces; Section 5.1 confirms same failure in non-foundation baselines (5-NN, RF) [Paper] [Paper: PDF p. 5–7]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Reweighting benefit is misattributed to relative imbalance	Weighted CE performs best on MS (most imbalanced <i>ratio</i>), yet worst on Zheng68K (less imbalanced ratio but larger absolute rare-class counts) [Paper] [Paper: PDF p. 4]	Benefit is predicted by <i>absolute</i> training-set size of the rare class, not its share of dataset or overall imbalance ratio [Paper] [Paper: PDF p. 4]	Figure 3 (right): strong negative Pearson correlation ($r = -0.77, p < 0.001$) between $\log(\text{training size})$ and $\Delta F1_{c \rightarrow c}$; MS rare classes have smallest absolute counts [Paper] [Paper: PDF p. 4]
Loss functions make hidden trade-offs obscured by Macro-F1	Logit adjustment achieves highest rare-class recall on Zheng68K (+0.075 over CE) but lowest rare-class precision among all six losses [Paper] [Paper: PDF p. 4]	It shifts decision threshold rather than improving feature separability, increasing false positives [Paper] [Paper: PDF p. 4]	Figure 2 (right): logit-adjusted point lies far below $y=x$ line; Table 1 shows its rare-class precision is lowest (0.632 vs. CE's 0.650 on Zheng68K) [Paper] [Paper: PDF p. 4–5]

06 核心理念

论文的核心思想不是“设计新损失”，而是**建立一个诊断性框架，将罕见类失败解耦为可修复与不可修复两类，并为每类提供可操作的判别标准与干预路径**。其洞察源于对失败机制的分层归因：第一层是数据层面——若某类训练样本绝对数量极低（如 ≤ 3 ），则任何损失函数都无法克服信息匮乏，表现为嵌入空间中该类样本被完全吸收进其他类的邻域（Figure 4），且NC1指标异常升高（oligodendrocyte C）或异常降低（phagocyte）[Paper] [Paper: PDF p. 6]；第二层是算法层面——对于其余“损失敏感型”类，其可修复性由绝对样本量线性预测，而非相对频率，这解释了为何MS（小绝对数）比Zheng68K（大绝对数）从重加权中获益更多；第三层是评估层面——Macro-F1等单一指标会掩盖precision-recall权衡，必须通过散点图（Figure 2 right）与AUPRC等阈值无关指标揭示真实trade-off。该思想将长尾问题从“如何调参”升维至“何时放弃调参”。

07 方法总览

论文采用**控制变量+多尺度诊断**方法论：（1）**系统性基准构建**：在 $3 \text{ backbone} \times 3 \text{ dataset} \times 6 \text{ loss} \times 3 \text{ seed} = 162$ 次运行中，严格固定数据划分、基因面板、优化器超参、批大小等所有非损失变量，仅改变损失函数，以隔离其效应 [Paper] [Paper: PDF p. 3]；（2）**双轨评估体系**：既报告宏观指标（Macro-F1, $\text{Recall}_{R \rightarrow R}$ ），也深入微观层面——按类分析 $\Delta F1_{c \rightarrow c}$ （Eq. 3）、绘制F1热图（Figure 3 left）、计算NC1（Eq. 4）与最近邻熵 [Paper] [Paper: PDF p. 4–6]；（3）**机制验证实验**：引入非基础模型基线（5-NN, RF）验证失败非预训练特有；用线性探针（linear probe）在冻结嵌入上测试判别信号是否残留，定位瓶颈在分类器训练而非表示坍塌 [Paper] [Paper: PDF p. 6]；（4）**几何可视化**：UMAP投影（Figure 4）直观呈现“吸收”现象，将抽象失败转化为可观察的空间关系。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Rare-class definition & metric suite	Define rare classes (training freq < 5%), compute $\text{Recall}_{R/c}$, $\text{precision}_{R/c}$, macro-AUPRC, $\Delta F1_{c/c}$	To move beyond aggregate accuracy and quantify failure on clinically relevant subpopulations	Input: per-class true labels/predictions; Output: scalar metrics per rare class/dataset	Section 3 defines $R \subseteq \{1, \dots, C\}$; Eq. 2 defines $\text{Recall}_{R/c}$; Table 1 reports all metrics [Paper] [Paper: PDF p. 3–5]	Without this, Figure 2 (right) and Figure 3 (right) would be impossible; conclusions about "loss-sensitive" regime vanish.
Per-class $\Delta F1_{c/c}$ analysis (Eq. 3)	Quantify gain of best loss over CE for each rare class c	To test whether reweighting benefit is uniform or concentrated, and identify predictors (e.g., absolute count)	Input: $F1_{c/c}$ under each loss ℓ ; Output: $\Delta F1_{c/c} = \max_{\ell \in L} F1_{c/c}(\ell) - F1_{c/c}(\text{CE})$	Eq. 3 explicitly defined; Figure 3 (right) plots $\Delta F1_{c/c}$ vs. $\log(\text{training size})$ [Paper] [Paper: PDF p. 4]	Without Eq. 3, the central finding that absolute count predicts benefit ($r = -0.77$) could not be established.
Neural Collapse Geometry (NC1, Eq. 4)	Quantify embedding tightness/separability via trace ratio $\text{tr}(\Sigma_{W/c}) / \text{tr}(\Sigma_{B/c})$	To distinguish geometric causes of failure: high NC1 $\rightarrow$ poor within-class cohesion; low NC1 + absorption $\rightarrow$ small cluster embedded in another class	Input: frozen test-set embeddings per class; Output: scalar NC1 per class	Eq. 4 defined; Section 5.2 reports NC1 values for oligodendrocyte C (1.19–1.79) and phagocyte (0.17–0.32) [Paper] [Paper: PDF p. 6]	Without NC1, the geometric signature difference between the two severely entangled classes (Figure 4) remains qualitative, not quantifiable.
Linear probe on frozen embeddings	Test if discriminative signal exists <i>in the representation</i> independent of classifier training	To determine if failure is due to lack of signal (data scarcity) or inability of loss functions to exploit it	Input: frozen CE-fine-tuned embeddings; Output: F1/recall/precision of logistic regression probe	Section 5.3 describes probe; results show probe F1 > best trained F1 for entangled classes (e.g., scGPT/oligodendrocyte C: 0.465 vs. 0.329) [Paper] [Paper: PDF p. 6]	Without probe, conclusion that "bottleneck is partly in loss design, not solely data scarcity" [Paper] [Paper: PDF p. 6] lacks direct evidence.

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
UMAP visualization with selective highlighting (Figure 4)	Visualize spatial relationship of severely entangled classes' test cells in embedding space	To provide intuitive, geometric evidence of "neighborhood absorption" that precedes any loss choice	Input: scGPT test embeddings; Output: 2D plot with 116 rare cells highlighted	Figure 4 caption and description; shows same 116 cells misclassified in CE and LDAM spaces [Paper] [Paper: PDF p. 7]	Without Figure 4, the claim of "absorption into unrelated classes' neighborhoods" [Paper] [Paper: PDF p. 5] is abstract; visualization makes it concrete and verifiable.

09 关键公式与符号

- **No verifiable closed-form equations are presented in the paper.** All listed equations are definitions or computational recipes, not derived theoretical formulas.
- **Equation 1:** $\text{Macro-F1} = 1/C \sum_{c=1}^C F1_{1,c}$ — Definition of unweighted mean F1 score across C classes [Paper] [Paper: PDF p. 3]. Symbol $F1_{1,c}$ denotes F1 score for class c .
- **Equation 2:** $\text{Recall}_R = 1/|R| \sum_{c \in R} \text{Recall}_c$ — Definition of macro-averaged recall over rare-class set R [Paper] [Paper: PDF p. 3]. Symbol R denotes set of rare classes (training freq < 5%).
- **Equation 3:** $\Delta F1_{1,c} = \max_{\ell \in L} F^{\{(\ell)\}}_{1,c} - F^{\{(CE)\}}_{1,c}$ — Definition of per-class F1 gain from best loss over cross-entropy [Paper] [Paper: PDF p. 4]. Symbol L denotes set of six losses; $F^{\{(\ell)\}}_{1,c}$ is class c 's F1 under loss ℓ .
- **Equation 4:** $\text{NC1} = \text{tr}(\Sigma_W) / \text{tr}(\Sigma_B)$ — Neural collapse trace ratio, where Σ_W is average within-class scatter, Σ_B is between-class scatter of centroids [Paper] [Paper: PDF p. 6]. Lower NC1 indicates tighter, better-separated clusters.
- **Key metrics:** Accuracy, Macro-F1, Recall_R , Precision_R , macro-AUPRC, $\Delta F1_{1,c}$, NC1.
- **Key sets:** R (rare classes), L (loss set), C (total classes).
- **Not assessable from supplied material:** No derivation, proof, or theoretical justification of any equation is provided.

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
162-run benchmark (Table 1, Fig 2 left)	Aggregate metrics mask rare-class failure across architectures	CE vs. 5 other losses; 3 backbones $\times$ 3 datasets $\times$ 3 seeds; fixed data splits, gene panels, optimizers	Accuracy > Macro-F1 > Recall_R consistently across all 9 (backbone, dataset) cells	Gap is inherent to dataset imbalance structure, not backbone-specific	That pretraining is irrelevant — authors note variance arises from config differences [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3–5], Table 1, Figure 2 left
$\Delta F1_c$ vs. $\log(\text{training size})$ (Fig 3 right)	Absolute training-set size, not relative frequency, predicts reweighting benefit	Correlation of $\Delta F1_c$ (Eq. 3) with $\log(\text{count})$ for 19 recoverable rare classes	Strong negative Pearson $r = -0.77$ ($p < 0.001$); robust to exclusion thresholds	Reweighting efficacy is determined by absolute sample count	That this holds for <i>all</i> rare classes — 4 severely entangled classes were excluded [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 3 right
UMAP + linear probe (Fig 4, Sec 5.3)	Severely entangled classes retain discriminative signal in frozen embeddings	Linear probe (class-balanced logistic regression) on CE-fine-tuned frozen embeddings vs. best trained classifier F1	Probe F1 exceeds best trained F1 for oligodendrocyte C (0.465 vs 0.329) and phagocyte (0.462 vs 0.000)	Bottleneck is in classifier training/loss design, not representation collapse	That a more complex nonlinear probe would close the gap — not tested [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6–7], Figure 4, Section 5.3
Non-foundation baselines (Sec 5.1)	Failure is not specific to pretrained representations	5-NN and class-balanced RF on raw gene expression vs. foundation models	Both baselines yield F1=0 on oligodendrocyte C/phagocyte, matching foundation models	Failure stems from data scarcity & geometry, not pretraining artifacts	That these baselines are universally weak — they achieve Macro-F1=0.28/0.65 on MS overall [Paper] [Paper: PDF p. 5]	[Paper] [Paper: PDF p. 5], Section 5.1
NC1 & nearest-neighbor analysis (Sec 5.2)	Two distinct geometric signatures distinguish severely entangled classes	NC1 computed on MS rare classes; nearest-neighbor entropy calculated for phagocyte/oligodendrocyte C	Phagocyte: low NC1 (0.17–0.32), high concentration (entropy 0.71); Oligo-C: high NC1 (1.19–1.79), high dispersion (entropy 0.90)	Failure modes are geometrically distinct, requiring different diagnostics	That NC1 alone suffices for diagnosis — authors use it <i>with</i> nearest-neighbor patterns [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6], Section 5.2

11 对结论的正确理解

论文结论不可简化为“class-balanced loss is best”或“loss functions don’ t work”。正确理解需把握三层限定：（1）**适用范围限定**：class-balanced loss 和 LDAM 是“最一致的通用选择”（mean rank 2.4/2.6），但并非在所有数据集上都最优（e.g., weighted CE wins on MS Macro-F1, LDAM wins on Pancreas Macro-F1）[Paper] [Paper: PDF p. 3]；（2）**问题域限定**：结论仅针对“细胞类型级”类别不平衡，明确排除了人口统计学失衡、批次效应等混杂变量 [Paper] [Paper: PDF p. 6]；（3）**机制限定**：“损失无效”仅适用于“严重纠缠型”类（如MS中n=3的两类），其失效根源是数据稀缺与几何吸收，而非损失函数本身缺陷；对“损失敏感型”类（如microglial cell），class-balanced loss确实能将其F1从0（scBERT）提升至0.86–0.92 [Paper] [Paper: PDF p. 6]。因此，核心贡献是提供了一个**条件化决策树**：先用NC1/UMAP诊断失败类型，再决定是换损失（可恢复）还是补数据（不可恢复）。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited backbone coverage	Only scGPT, scBERT, Geneformer evaluated; scFoundation and CellPLM remain untested [Paper] [Paper: PDF p. 6]	Test other existing single-cell foundation models (scFoundation, CellPLM) [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6]
Classifier expressivity ceiling	Linear probe reveals unused discriminative signal in frozen embeddings, suggesting current losses may not fully exploit it [Paper] [Paper: PDF p. 6]	Explore more expressive, nonlinear classifier heads beyond the six losses tested [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6]
Isolated imbalance axis	Study focuses solely on cell-type class imbalance; does not address compounding variables like demographic composition or batch effects [Paper] [Paper: PDF p. 6]	Investigate interactions with demographic composition (Al Amin et al. 2025) and batch effects (Maan et al. 2024) [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
<i>*The "severely entangled" regime is defined by near-zero F1 across all losses, but F1=0 may reflect label noise or annotation ambiguity rather than pure data scarcity*</i>	The MS dataset retains "two ambiguous MS labels as defined in the source atlas" [Paper] [Paper: PDF p. 3]; oligodendrocyte C and phagocyte may be biologically ill-defined or mislabeled, making them inherently non-separable regardless of samples or loss.	If true, the "data scarcity" interpretation is incomplete; the bottleneck may be ontological (label quality) rather than statistical (sample count). This affects whether data collection or label curation is the priority.	Re-annotate the 3 training cells for oligodendrocyte C/phagocyte using orthogonal modalities (e.g., spatial transcriptomics or protein markers) and re-run experiments. Compare F1 before/after.	[Paper] [Paper: PDF p. 3] states ambiguous labels exist; [Paper] [Paper: PDF p. 6] notes phagocyte is identified by ingested myelin RNA, suggesting biological heterogeneity.
<i>*NC1 is computed on frozen test-set embeddings, but the paper attributes geometric failure to training dynamics*</i>	NC1 measures static geometry post-training; however, neural collapse theory (Papayan et al. 2020) links NC1 to <i>training trajectory</i> . Computing it only on test embeddings misses whether collapse occurs during fine-tuning or is inherited from pretraining.	Misattribution could lead to wrong interventions (e.g., blaming fine-tuning loss when pretraining already induced collapse). For user's sc foundation model work, this affects whether to modify pretraining or fine-tuning.	Compute NC1 at multiple fine-tuning epochs (e.g., epoch 1, 5, 10, 15) and compare to pretraining checkpoint. Plot NC1 trajectory for oligodendrocyte C vs. other classes.	[Paper] [Paper: PDF p. 6] cites Papayan et al. 2020 on neural collapse but applies NC1 only to frozen test embeddings, not dynamics.
The linear probe uses class-balanced logistic regression, but the "best loss" comparison includes non-calibrated losses (e.g., LDAM)	Probe performance is measured by F1, while LDAM is designed to shape decision boundaries, not calibrate probabilities. A probe using LDAM's margin-aware objective might show different signal recovery.	This creates an apples-to-oranges comparison: probe evaluates separability, but losses optimize different objectives. It may underestimate what LDAM <i>could</i> extract if properly tuned.	Train linear probes using each of the six loss functions (not just logistic regression) on the same frozen embeddings and compare their F1.	[Paper] [Paper: PDF p. 6] uses "class-balanced logistic regression" for probe, while losses like LDAM and logit adjustment have fundamentally different objectives.

14 学到的知识

- **诊断先行，干预后置：**在单细胞长尾任务中，不应直接尝试所有损失函数，而应先用NC1 (Eq. 4) 和UMAP最近邻分析 (Figure 4) 对罕见类进行“几何体检”，区分可修复 (loss-sensitive) 与不可修复 (severely entangled) 两类。
- **绝对数量胜于相对比例：**决定重加权效果的关键变量是罕见类的**绝对训练样本数** (如3 vs. 70)，而非其在数据集中的占比 (如1% vs. 5%)。这解释了为何MS (小绝对数) 比Zheng68K (大绝对数) 获益更大，颠覆了“不平衡比率决定一切”的直觉。

- **Macro-F1是危险的简化器**：Figure 2 (right) 清晰显示，logit adjustment虽提升recall，却大幅牺牲precision，而Macro-F1无法揭示此trade-off。必须辅以precision-recall散点图与macro-AUPRC。
- **失败可溯源至几何**：严重纠缠类的失败不是黑箱，而是可观测的空间现象——其测试样本在UMAP中被完全吸收进其他类的邻域（Figure 4），且NC1指标呈现特征性偏移（高或低），这为调试提供了具体靶点。
- **信号未消失，只是未被利用**：线性探针证明，即使仅有3个训练样本，判别性信号仍线性可分地存在于冻结嵌入中（Section 5.3）。这表明当前损失函数的设计存在表达能力缺口，为用户设计新损失（如结合margin与calibration）提供了强动机。

15 与既有知识的连接

- **候选连接/方法论连接**：本文的“两阶段诊断框架”（先几何分析，再损失选择）与Kang et al. (2020) 提出的“解耦表示学习与分类器校准”思想高度一致，均主张将表征质量与决策边界优化分离；本文用NC1和UMAP实现了该思想在单细胞领域的可操作化落地。
- **候选连接/方法论连接**：对“绝对样本量预测重加权收益”的发现，与计算机视觉中Buda et al. (2018) 和 Saini & Susan (2023) 的结论形成跨模态呼应，证实了“有效样本数”（effective-number-of-samples）框架在单细胞领域的普适性。
- **候选连接/方法论连接**：使用UMAP可视化嵌入空间吸收现象（Figure 4），与用户研究方向中“spatial transcriptomics”的空间邻域概念存在方法论共鸣——两者均强调细胞/spot在低维流形中的相对位置与生物学意义的关联。
- **候选连接/方法论连接**：线性探针揭示未被利用的信号（Section 5.3），为用户“perturbation prediction”方向提供启示：若基础模型嵌入中已蕴含扰动响应信号（如药物处理后的状态偏移），但当前分类头未能提取，则可借鉴此探针范式，设计专用扰动解码头。
- **弱连接/方法论连接**：本文聚焦单模态（scRNA-seq）细胞类型分类，与用户“multi-omics”方向无直接交集；但其“几何诊断”思路可迁移至多组学对齐后的联合嵌入空间，用于识别跨模态对齐失败的罕见亚群。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Geometric-aware Loss Gating

originating limitation/observation: Severely entangled classes exhibit distinct NC1 signatures (high vs. low) and nearest-neighbor entropy, yet all losses fail uniformly [Paper] [Paper: PDF p. 6]. **core**

hypothesis: A loss function should *adapt its objective* based on the geometric profile of each class — e.g., apply large-margin constraints for high-NC1 classes (poor cohesion) and density-aware reweighting for low-NC1 classes (absorption). **delta from paper**: Paper treats loss choice as global; this proposes per-class, geometry-conditioned loss selection or interpolation. **initial method**: For each class c , compute $NC1_{c/}$ and neighbor entropy $H_{c/}$ on frozen embeddings; define gating weight $g_{c/} = \sigma(\alpha \cdot NC1_{c/} + \beta \cdot H_{c/})$; blend LDAM (for high NC1) and class-balanced (for low NC1) via $g_{c/}$. **validation**: Train on MS; compare F1 for oligodendrocyte C (high NC1) and phagocyte (low NC1) vs. baseline LDAM/class-balanced. **failure modes**: Gating weights may be unstable with tiny n ; requires reliable NC1 estimation from few samples. **innovation status**: unverified

- **name**: Probe-guided Loss Synthesis

originating limitation/observation: Linear probe recovers non-trivial F1 on entangled classes, exceeding best trained classifiers, proving signal exists but is unused [Paper] [Paper: PDF p. 6]. **core hypothesis:** The gradient update direction of standard losses misaligns with the direction of maximal separability revealed by the probe; synthesizing a loss that directly minimizes the probe's classification error on frozen embeddings will close the gap. **delta from paper:** Paper uses probe for diagnosis; this uses probe gradients to *design* a new loss term. **initial method:** Extract frozen embeddings Z ; train linear probe $w^{\sup} = \argmin_{w^{\sub}} \ell_{\text{probe}}(w^{\sup} T^{\sup} Z, y)$; define new loss $\ell_{\text{new}} = \ell_{\text{CE}} + \lambda \cdot \ell_{\text{probe}}(w^{\sup} T^{\sup} Z, y)$, where ℓ_{probe} is hinge or logistic loss. **validation:** On MS oligodendrocyte C, measure if ℓ_{new} lifts F1 above probe's 0.465. **failure modes:** $w^{\sup}$ is fixed; may not generalize to unseen samples; adds computational overhead. **innovation status:** unverified

- **name:** Spatial-Anchor Contrastive Alignment

originating limitation/observation: Phagocyte's confusion with oligodendrocyte A reflects real transcriptional overlap from ingested myelin RNA [Paper] [Paper: PDF p. 6], suggesting biological proximity should inform loss design. **core hypothesis:** Incorporating spatial transcriptomics priors (e.g., from Visium) as contrastive anchors can disentangle transcriptionally overlapping but spatially segregated rare classes, mitigating absorption. **delta from paper:** Paper uses only scRNA-seq; this fuses spatial context to reshape embedding geometry *during* fine-tuning. **initial method:** For MS, obtain spatial data; identify oligodendrocyte A and phagocyte spots; use their averaged spatial gene expression as positive anchors in a contrastive loss alongside scRNA-seq embeddings. **validation:** Train scGPT on MS with/without spatial anchors; compare NC1 and UMAP absorption (Figure 4) for phagocyte. **failure modes:** Requires matched spatial data for rare classes; anchor quality depends on spot purity. **innovation status:** unverified