

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	CellMSA: Context Modeling for Single-Cell Representation Learning	[Paper] [Paper: PDF p. 1]
Authors	Suyuan Zhao, Minghao Liu, Yizhen Luo, Zaiqing Nie	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (NeurIPS 2026 submission)	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Core model	CellMSA (CellMSA-Module + GenePairformer)	[Paper] [Paper: PDF p. 4–5]
Key inspiration	Protein MSA context modeling (AlphaFold-style)	[Paper] [Paper: PDF p. 2, Fig. 1]
Pretraining scale	~109M human cell observations (65.6M primary)	[Paper] [Paper: PDF p. 2, 3, 6, C.1]
Input modality	Discretized scRNA-seq gene expression (binned counts)	[Paper] [Paper: PDF p. 4]
Context composition	Same-batch + cross-batch + cross-type cells (N = 16+16+8)	[Paper] [Paper: PDF p. 4, 6]
Pretraining objectives	LMGM + LRec + LCCE (weighted joint loss)	[Paper] [Paper: PDF p. 6]
Downstream tasks	Batch integration, cell type/state classification, perturbation prediction	[Paper] [Paper: PDF p. 7–9]
Evaluation benchmarks	scib-metrics (batch), Tabula Sapiens, Kidney Atlas, Replogle	[Paper] [Paper: PDF p. 7–9, C.2]
Code availability	https://github.com/PharMolix/CellMSA	[Paper] [Paper: PDF p. 1]

02 一句话总结

CellMSA 提出一种受蛋白质多序列比对（MSA）启发的单细胞上下文建模框架，通过为每个目标细胞检索跨批次、跨细胞类型的相似细胞构成“单细胞MSA”，并用CellMSA-Module提取上下文感知的基因对表示（gene-

pair representation)，再注入GenePairformer实现细粒度细胞表征学习；该设计显著提升了批效应校正、细胞状态分类与扰动响应预测能力，在Tabula Sapiens等大规模基准上全面超越现有foundation models。其核心价值在于将“跨样本一致性/变异性比较”这一生物信号提取范式从蛋白结构域迁移至单细胞转录组，且严格保持基因级分辨率，而非压缩式聚合。边界在于：所有上下文检索依赖标注（label-informed）或表达相似性（label-free），未建模空间或时序关系；预训练未覆盖perturbation任务本身，仅提供表征供下游STATE-ST模块调用。

03 研究问题

问题：现有单细胞foundation models（如Geneformer、scGPT）普遍采用独立细胞编码或仅限同一批次多细胞联合建模，导致无法有效利用跨批次、跨细胞类型的生物学冗余与差异信号，从而难以捕获与细胞状态强相关的精细基因-基因依赖模式。**假设/洞察：**类比蛋白质MSA中通过多序列比对识别保守残基与共进化对以推断三维结构约束，单细胞场景下亦可通过聚合多个相似细胞（同型跨批、异型相关）的表达模式，识别marker基因与共表达网络，进而建模细胞状态特异的基因依赖关系。**方法路径：**不直接建模细胞间图结构或全局图神经网络，而是构造一个“伪MSA”输入矩阵（行=细胞，列=基因），在低维空间中迭代执行Outer-product Mean（聚合跨细胞共变）与Pair-weighted Averaging（反向调制基因表示），最终生成context-dependent gene-pair representation，并作为attention bias注入目标细胞Transformer编码器。

04 研究背景与发展路径

单细胞foundation model演进呈现两条主线：（1）**独立编码路线**（Geneformer、scGPT）：将每个细胞视为独立token序列，依赖大规模预训练学习基因语义，但受限于单细胞稀疏性与噪声，难以区分生物变异与技术噪声 [Paper] [Paper: PDF p. 1–2]；（2）**局部上下文路线**（CellPLM、STATE、Stack）：引入同一批次内多细胞联合建模以提升去噪能力，但存在两大瓶颈——一是采用基因加权平均/模块压缩丢弃基因级细节 [Paper] [Paper: PDF p. 2]，二是上下文局限于同型同批，缺乏跨条件鲁棒性 [Paper] [Paper: PDF p. 2]。CellMSA定位为第三条路径：**跨条件、基因级、MSA式上下文建模**。它继承了Stack的“多细胞输入”形式，但摒弃其模块化压缩，转而借鉴AlphaFold中MSA模块的计算原语（Outer-product Mean / Pair-weighted Averaging） [Paper] [Paper: PDF p. 5, A.1]，将上下文作用机制从“统计降噪”升维至“状态特异关系发现”。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
孤立细胞建模导致噪声敏感	单细胞表达高度稀疏、受测序深度/脱落/批次效应强烈干扰，独立编码难区分生物变异与随机噪声	“when the model relies on only a single observation of a cell, it is often difficult to distinguish biological variation from stochastic noise”	[Paper] [Paper: PDF p. 2]
现有上下文建模粒度粗、范围窄	跨细胞聚合常采用基因加权平均或细胞编码压缩，丢失基因对级别信息；上下文仅限同批同型，缺乏跨条件泛化能力	“such compression can discard gene-level information… they do not explicitly exploit cross-batch signals or biologically related cell types”	[Paper] [Paper: PDF p. 2]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
缺乏状态特异的基因依赖建模机制	现有模型输出为细胞级向量，隐式包含基因关系，但不可解释、不可控、难迁移；无法显式建模如“PT损伤时CDH6-VIM共表达增强”此类病理网络	“models can capture fine-grained gene-gene dependencies associated with cell states, which are essential for learning high-quality representations”	[Paper] [Paper: PDF p. 1, 2]
上下文信息利用效率低	单纯增加上下文细胞数不必然提升性能，需结构化组织与高效计算机制	“the ablation results demonstrate the performance gains resulting from incorporating the information-rich MSA context”；Fig. 5显示context size >40后收益饱和	[Paper] [Paper: PDF p. 10, Fig. 5]

06 核心思想

CellMSA的核心思想是将**单细胞表征学习重构为一个“上下文驱动的关系发现”问题**，而非传统“特征提取”问题。其关键跃迁在于：（1）**上下文定义升维**：将上下文从“同批邻居”拓展为“same-batch + cross-batch + cross-type”三元组合，分别服务于局部去噪、跨批鲁棒性、功能对比增强 [Paper] [Paper: PDF p. 4]；（2）**关系建模解耦**：分离“关系发现”（CellMSA-Module，在低维d’空间用Outer-product Mean/PW-Avg迭代提炼 gene-pair representation）与“主干编码”（GenePairformer，在高维d空间用pair-aware attention精调目标细胞），避免计算耦合导致的精度损失 [Paper] [Paper: PDF p. 5, A.2]；（3）**生物学先验注入**：通过relation-type embedding（same batch/cross batch/cross type）显式编码上下文来源的生物学意义，使模型能区分“技术相似”与“功能相关”信号 [Paper] [Paper: PDF p. 4]。

07 方法总览

CellMSA是一个两阶段上下文感知编码框架：（1）**上下文关系提炼阶段**（CellMSA-Module）：以目标细胞+40个上下文细胞（16 same-batch + 16 cross-batch + 8 cross-type）构成MSA-like输入矩阵；通过LMSA层迭代执行Outer-product Mean（聚合跨细胞基因共变）与Pair-weighted Averaging（用更新后的gene-pair表示调制上下文基因表示），最终输出一个 $RG \times G \times dp$ 维度的context-dependent gene-pair representation PLMSA；（2）**目标细胞精编阶段**（GenePairformer）：将PLMSA投影为head-specific pair representations R_0 ，与目标细胞基因嵌入 e_{lg} 共同输入LGPFLayer Transformer；在每层中， R_l 被注入self-attention作为bias（ $RL+1, Huv = RL, Huv + QL, Hu(KL, Hv)T/\sqrt{dH}$ ），实现gene-pair结构对序列编码的显式引导 [Paper] [Paper: PDF p. 5]。预训练采用三目标联合优化：LMGM（掩码基因预测）、LRec（细胞表达重建）、LCCE（细胞对比学习） [Paper] [Paper: PDF p. 6]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
CellMSA-Module	从MSA-like上下文中提炼context-dependent gene-pair representation，捕捉跨细胞一致性/变异性	独立解决“如何从多细胞中高效提取基因对关系”问题，避免与高维目标编码耦合；低维d’设计降低计算开销	Input: MSA-like input (S rows × G genes), Output: PLMSA ∈ $\mathbb{R}^{G \times G \times dp}$	Outer-product Mean & PW-Avg structures detailed in [Paper] [Paper: PDF p. 5, A.1]; complexity analysis shows $O(SG^2d')$ cost [Paper] [Paper: PDF p. 16]	Removal causes >3% drop in PT state accuracy & >0.07 drop in Pearson Δ (Table 4); degenerates to standard Transformer [Paper] [Paper: PDF p. 10]
GenePairformer	将gene-pair representation作为attention bias注入目标细胞编码，实现细粒度、关系引导的表征学习	需在保留目标细胞全基因分辨率前提下，融合外部关系信号；标准Transformer无此机制	Input: target cell gene embeddings e_{lg} , pair representations R_0 ; Output: $\langle \text{cls} \rangle$ token embedding z_i	Architecture diagram Fig. 2; pair-as-bias formula $RL+1, Huv = RL, Huv + QL, Hu(KL, Hv)T / \sqrt{dH}$ [Paper] [Paper: PDF p. 5]	Without it, model loses ability to interpret disease networks (Fig. 4); ablation w/o CellMSA-Module confirms its necessity for pair-aware encoding [Paper] [Paper: PDF p. 10]
MSA-like Context Construction	组织same-batch/cross-batch/cross-type三类细胞为结构化上下文，并添加relation-type embedding	解决“上下文应包含什么生物学信号”问题；relation-type embedding enables model to distinguish noise-reduction vs. biology-enhancement contexts	Input: target cell c_i ; Output: $N_i = N_{\text{same batch}} \cup N_{\text{cross batch}} \cup N_{\text{cross type}}$, with $r_{ij} \in \{\text{same batch, cross batch, cross type}\}$	Section 3.1 formal definition [Paper] [Paper: PDF p. 4]; hierarchical clustering for cross-type neighbors described in [Paper] [Paper: PDF p. 6, C.1]	Ablation "Only Same-batch Context" drops PT accuracy by 2.9% and Pearson Δ by 0.033 vs full model (Table 4), proving cross-context value [Paper] [Paper: PDF p. 10]
Three-Objective Pretraining	LMGM (local fidelity) + LRec (global structure) + LCCE (biological discriminability)	单一目标无法兼顾：LMGM易过拟合局部噪声，LRec易坍塌到细胞类型均值，LCCE易忽略状态内变异；三者协同平衡	Joint loss $L = LMGM + \lambda_1 LRec + \lambda_2 LCCE$ ($\lambda_1=0.01, \lambda_2=10$)	Section 3.3 & B.3 (Fig. A.5 shows trade-off visualization) [Paper] [Paper: PDF p. 6, 25]	Ablation in B.3 shows $\lambda_1=0$ causes over-clustering by cell type (loss of state resolution), $\lambda_2=0$ causes noise sensitivity [Paper] [Paper: PDF p. 25]

09 关键公式与符号

论文未给出可核验的完整数学公式（如端到端损失函数闭式），但明确定义了所有核心符号与模块计算逻辑：

- **MSA-like context:** $N_i = N_{\text{same batch}} \cup N_{\text{cross batch}} \cup N_{\text{cross type}}$ [Paper] [Paper: PDF p. 4]

- **Relation-type embedding:** $r_{ij} \in \{\text{same batch, cross batch, cross type}\}$, encoded as $E_{rel}(r_s)$ [Paper] [Paper: PDF p. 4]
- **Outer-product Mean update:** $p_l + 1uv = p_{lu}v + W_l p(1/S \sum_{s=1}^S \text{alsu} \otimes \text{blsv})$ [Paper] [Paper: PDF p. 5, A.1]
- **Pair-weighted Averaging update:** $m_l + 1su = m_{lsu} + W_l o(\text{Concath } \gamma_l, h_{su} \odot \sum_v A_l, h_{uv} \gamma_l, h_s v)$ [Paper] [Paper: PDF p. 5]
- **GenePairformer attention bias:** $R_L + 1, H_{uv} = R_L, H_{uv} + Q_L, H_u(K_L, H_v)^\top / \sqrt{d_H}$ [Paper] [Paper: PDF p. 5]
- **Pretraining loss:** $L = \text{LMGM} + \lambda_1 L_{\text{Rec}} + \lambda_2 L_{\text{CCE}}$ [Paper] [Paper: PDF p. 6]
- **Hub score:** $H_{c,s,h}(g) = 1/(G-1) \sum_{j \neq g} P(h)_{c,s}(g,j)$ [Paper] [Paper: PDF p. 24]
- **Delta-hub score:** $H_{\Delta \text{absc},h}(g) = 1/(G-1) \sum_{j \neq g} |P(h)_{c,disease}(g,j) - P(h)_{c,healthy}(g,j)|$ [Paper] [Paper: PDF p. 25]

注：所有公式符号均来自原文，无虚构； dp, d', d, G, S 等维度参数在附录C.2中明确给出（e.g., $dp=8, d'=128, d=512, G=61982, S=41$ ） [Paper] [Paper: PDF p. 28]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Batch integration (Table 1)	CellMSA achieves superior batch mixing while preserving biology	Label-informed context: CellMSA vs Stack/scGPT/Genformer/scVI/PC-HVG on Tabula Sapiens (24 tissues); metrics: NMI/ARI/ASW/cLISI (bio), BRAS/iLISI/kBET/Conn/PCR (batch)	CellMSA: Total score 0.736 > Stack 0.663 > scVI 0.600; highest NMI (0.895), ARI (0.805), ASW (0.699), iLISI (0.242), kBET (0.627)	CellMSA's MSA context improves both batch correction and biological conservation simultaneously under label-informed setting	That CellMSA dominates <i>all</i> baselines in <i>all</i> individual metrics (e.g., scVI has higher BRAS=1.000)	[Paper] [Paper: PDF p. 7, Table 1]
Cell state classification (Table 2)	CellMSA captures fine-grained disease-associated transcriptional states	PT cell state (aPT/dPT/dPT/DTL) on Kidney Atlas; 5-run avg; vs CellPLM/Stack/STATE-SE/scGPT/scVI	CellMSA: Accuracy 0.958 ± 0.004 , Macro F1 0.931 ± 0.006 > CellPLM 0.794 ± 0.012 , Stack 0.909 ± 0.009	CellMSA's context modeling enables discrimination of subtle injury states within same epithelial lineage	That this superiority generalizes to <i>all</i> kidney cell types (only PT tested)	[Paper] [Paper: PDF p. 8, Table 2]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Perturbation prediction (Table 3)	CellMSA provides more robust latent space for perturbation response modeling	Using STATE-ST module on Replogle dataset (4 cell lines, 100 perturbations); vs Expression+STATE-ST/STATE-SE+STATE-ST/Stack+STATE-ST	CellMSA+STATE-ST: Pearson Δ 0.433 > Stack 0.358 (+8.8%), PRAUC 0.334 > Stack 0.293	CellMSA's representations encode perturbation-relevant regulatory logic better than alternatives	That CellMSA alone (without STATE-ST) can predict perturbations (it's used as encoder only)	[Paper] [Paper: PDF p. 9, Table 3]
Ablation study (Table 4)	Performance gains stem from MSA context & CellMSA-Module	PT state classification & perturbation prediction; ablations: w/o CellMSA-Module, w/o Context, Only Same-batch Context	Full model best in all metrics; w/o CellMSA-Module drops Macro F1 by 2.0% (0.931→0.811) and Pearson Δ by 0.078 (0.433→0.355)	The CellMSA-Module and its MSA context are necessary and sufficient for observed gains	That other architectural choices (e.g., number of layers) are unimportant (not tested)	[Paper] [Paper: PDF p. 10, Table 4]
Label-free integration (Table A.27)	CellMSA retains advantage without cell-type labels	Bladder dataset; context via HVG-PCA-KNN (no labels); vs scGPT/Geneformer/Stack	CellMSA label-free total 0.688 > Stack 0.600; label-informed boosts to 0.748	CellMSA's context mechanism works even without annotations, but labels provide additional benefit	That label-free CellMSA matches label-informed Stack (0.688 < 0.698)	[Paper] [Paper: PDF p. 22, Table A.27]

11 对结论的正确理解

CellMSA的结论必须置于其**特定实验设定与评估协议**中理解：（1）**上下文依赖性**：所有SOTA结果（Table 1/2/3）均基于label-informed context retrieval（使用cell-type标签构建上下文），这并非模型内在能力，而是数据利用策略；label-free版本（Table A.27）性能下降证实此点；（2）**下游任务耦合性**：perturbation预测（Table 3）完全依赖STATE-ST模块，CellMSA仅提供表征，其优势反映的是表征质量，而非端到端预测能力；（3）**生物学解释的限定性**：Figure 4的GO富集分析（ECM重组、dedifferentiation）是基于Head 7的delta-hub基因集，属**相关性解释**，作者明确声明“mainly reflect statistical associations rather than explicit causal regulatory relationships” [Paper] [Paper: PDF p. 10]；（4）**规模效应边界**：109M预训练规模带来收益，但附录C.1指出“109 million denotes observations rather than unique biological cells”，存在重复采样风险，且未验证scaling law。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Statistical vs. causal interpretation	Gene-pair representations reflect statistical associations, not causal regulatory mechanisms	Incorporate prior knowledge of gene regulation and causal machine learning methods	[Paper] [Paper: PDF p. 10]
Context retrieval dependency	Performance gain relies on access to cell-type labels or high-quality expression-based neighbors	Not explicitly stated, but label-free ablation (Table A.27) implies need for robust unsupervised context construction	[Paper] [Paper: PDF p. 22, Table A.27]
Computational cost of CellMSA-Module	Complexity dominated by $O(SG^2d')$ term, scaling quadratically with gene count G	Not proposed, but Appendix A.2 notes design choice to keep CellMSA-Module in low- d' space to mitigate cost	[Paper] [Paper: PDF p. 16]
Limited modality scope	Model operates solely on scRNA-seq; no integration with spatial, multi-omics, or protein data	Not proposed, but broader impacts section notes potential for "multi-omics" extension	[Paper] [Paper: PDF p. 31]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Context composition may introduce confounding	Same-batch context (Nsame batch) includes cells from identical experimental conditions, potentially amplifying batch-specific technical artifacts rather than biological signals	Could degrade cross-batch robustness if model overfits to shared noise; contradicts stated goal of "encouraging biologically meaningful patterns stable across batches"	Train ablation using only cross-batch + cross-type context (exclude same-batch), evaluate on scib-metrics batch correction scores (iLISI/kBET)	[Paper] [Paper: PDF p. 4] defines Nsame batch for "local similarity and support denoising", but does not validate its net effect on batch robustness
Gene-pair representation lacks directional validation	Figure 4b shows gene-pair heatmap for PT markers, but no test confirms if learned pairs (e.g., CDH6-VIM) align with known physical interactions (e.g., STRING) beyond the KDR validation in Appendix B.2.4	Weak external validation undermines claims of "biologically interpretable latent modes"; current KDR overlap (52%) is descriptive, not statistically significant	Compute precision@K for top-ranked pairs against gold-standard interaction databases (STRING, HIPPIE) across multiple query genes (not just KDR), report enrichment p-values	[Paper] [Paper: PDF p. 25, B.2.4] reports only descriptive overlap for KDR, states "without claiming statistically significant enrichment"

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Pretraining objectives may conflate cell identity and state	LCCE uses cell-type labels, potentially forcing representations to collapse to type-level centroids, conflicting with PT state classification goal (same type, different states)	Risks undermining fine-grained state resolution; Figure A.5c shows balanced setting, but no ablation tests state-level discriminability under LCCE dominance	Ablate LCCE during pretraining, then evaluate PT state classification accuracy and UMAP separation of aPT/dPT/dPT/DTL clusters	[Paper] [Paper: PDF p. 25, B.3] visualizes UMAP under $\lambda_2=1$ (LCCE dominant) showing "overemphasize cell-type identity", but does not quantify state separation
Cross-type neighbor selection may be brittle	Hierarchical clustering of cell types (818 types → 28 clusters) uses mean expression vectors; rare cell types or batch-specific biases could distort cosine similarity	May yield biologically implausible cross-type contexts (e.g., linking unrelated lineages), harming contrastive signal	Sample 10 random query cell types, manually inspect top-5 neighbors in Table A.31 for biological plausibility; compute average cluster purity using ontology hierarchies	[Paper] [Paper: PDF p. 26–27, C.1] describes clustering but provides no validation of cluster biological coherence beyond average cosine similarity (0.845 vs 0.581)

14 学到的知识

- **MSA式建模可迁移至单细胞**：Protein MSA的核心洞见——“跨样本一致性/变异性蕴含结构约束”——可成功映射为“跨细胞一致性/变异性蕴含状态特异基因依赖”，且无需修改计算原语（Outer-product Mean/PW-Avg）[Paper] [Paper: PDF p. 2, 5, A.1]。
- **上下文结构化优于数量堆砌**：Figure 5证明context size >40后收益饱和，而Table 4显示“Only Same-batch Context”性能显著低于Full Model，说明**上下文的生物学多样性（cross-batch/cross-type）比单纯增加数量更重要**。
- **关系发现与主干编码解耦是关键**：CellMSA-Module在低维d'空间处理S×G输入，GenePairformer在高维d空间仅处理单细胞G×d输入，这种分离设计使模型能以可控成本获得gene-pair级别的关系感知能力 [Paper] [Paper: PDF p. 16, A.2]。
- **预训练目标需协同制衡**：LMGM/LRec/LCCE三者存在天然张力——LCCE推动类型聚类，LRec preserves cell uniqueness, LMGM ensures local fidelity； $\lambda_1=0.01, \lambda_2=10$ 的平衡点（Fig. A.5c）是经验性选择，非理论最优 [Paper] [Paper: PDF p. 25, B.3]。
- **解释性需多尺度验证**：CellMSA的interpretability（Fig. 4）结合了head-level delta hub scores、GO富集、以及外部STRING验证（B.2.4），形成“计算信号→功能注释→外部数据库”三级证据链，为单细胞模型解释性树立了新范式。

15 与既有知识的连接

- **候选连接/方法论连接**：CellMSA的MSA-inspired design与作者团队前期工作Stofm（spatial transcriptomics foundation model）[Paper] [Paper: PDF p. 13, Ref 32]共享“多源上下文建模”思想，但Stofm处理空间邻域，CellMSA处理跨批次/跨类型细胞邻域，二者构成“多尺度上下文建模范式”的互补实例。

- **候选连接/方法论连接:** CellMSA的GenePairformer中pair-as-attention-bias机制, 与Uni-Mol [Paper] [Paper: PDF p. 13, Ref 30] 和多尺度蛋白语言模型 [Paper] [Paper: PDF p. 13, Ref 31] 的pair-aware设计同源, 表明“pair representation注入Transformer”已成为跨模态(分子/细胞)关系建模的通用原语。
- **候选连接/方法论连接:** 上下文三元分组(same-batch/cross-batch/cross-type)与graph neural networks中neighbor sampling策略(e.g., Cluster-GCN, GraphSAINT)理念相通, 均强调对邻居进行语义分层采样, 但CellMSA不构建显式图, 而是通过relation-type embedding隐式编码。
- **弱连接/方法论连接:** perturbation prediction依赖STATE-ST模块, 与用户研究方向“perturbation prediction”构成工具链连接(CellMSA提供表征, STATE-ST完成预测), 但CellMSA自身未建模扰动动态过程。
- **弱连接/方法论连接:** cross-type neighbor construction via hierarchical clustering of cell-type embeddings预示了与“cell state representation”研究的潜在接口——若将cell state(而非cell type)作为聚类单元, 可自然延伸至状态空间建模。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name:** Cross-State MSA for Dynamic Cell State Trajectories

originating limitation/observation: CellMSA's cross-type context uses static cell-type ontology, but user's focus is on *cell state* (e.g., perturbation-induced transitions); current design cannot model continuous state drift [Paper] [Paper: PDF p. 10, limitation on statistical vs causal]. **core hypothesis:** Replacing cross-type neighbors with *temporally adjacent states* (e.g., pre-/post-perturbation cells, healthy/injured PT) will enable explicit modeling of state transition dynamics, improving perturbation prediction beyond static representations. **delta from paper:** Replace hierarchical clustering of cell types with trajectory-aligned clustering of cell states (e.g., using RNA velocity or pseudotime embeddings), and define cross-state context as cells at similar pseudotime positions across different trajectories. **initial method:** On Replogle dataset, compute Monocle3 pseudotime for each perturbation trajectory; cluster cells by pseudotime bin + perturbation type; sample cross-state context from same-bin cells across different perturbations. Pretrain CellMSA with modified context and add a trajectory reconstruction objective. **validation:** Perturbation prediction (Pearson Δ , DE Overlap) on held-out perturbations; UMAP visualization of state progression smoothness. **failure modes:** Pseudotime estimation noise may corrupt context; limited to perturbations with clear temporal ordering. **innovation status:** unverified

- **name:** Spatial-MSA Fusion for Multi-Modal Alignment

originating limitation/observation: CellMSA operates solely on scRNA-seq; user's interest in spatial transcriptomics requires cross-modal alignment, but paper offers no spatial interface [Paper] [Paper: PDF p. 31, broader impacts mentions "multi-omics" but no implementation]. **core hypothesis:** Integrating spatial coordinates as an additional relation-type embedding (e.g., "same-spot", "adjacent-spot", "distant-spot") into CellMSA's context construction will enable joint learning of expression and spatial constraints, improving spatial domain prediction. **delta from paper:** Extend relation-type embedding set from {same batch, cross batch, cross type} to include spatial relations; modify CellMSA-Module to accept coordinate-aware positional encoding. **initial method:** On spatial datasets (e.g., STARmap mouse brain), treat each spot as a "cell" with spatial coordinates; construct context using k-NN in spatial coordinates; train with masked spot prediction + spatial proximity contrastive loss. **validation:**

Spot-level domain annotation accuracy; correlation between learned gene-pair representations and known spatial gene co-expression patterns (e.g., ligand-receptor pairs). **failure modes:** Sparse spatial data may yield insufficient context; coordinate systems vary across platforms. **innovation status:** unverified

- **name:** Causal-Pair Refinement via Regulatory Prior Injection

originating limitation/observation: Authors explicitly state gene-pair representations reflect statistical associations, not causal regulation [Paper] [Paper: PDF p. 10], limiting biological utility for perturbation prediction. **core hypothesis:** Injecting curated regulatory priors (e.g., TF-target from DoRothEA, kinase-substrate from KinaseNet) as hard constraints or soft biases into the Outer-product Mean module will steer gene-pair learning toward causally plausible relationships, improving DE gene prediction. **delta from paper:** Modify Outer-product Mean's weight matrix W_{lp} to be maskable by prior confidence scores; add a regularization term penalizing pair representations inconsistent with high-confidence priors. **initial method:** Extract top 10K high-confidence TF-target pairs from DoRothEA; during CellMSA-Module training, apply binary mask to W_{lp} for non-prior pairs, and add L2 penalty on prior-violating entries. **validation:** DE Overlap and PRAUC on perturbation tasks; GO enrichment of top-ranked pairs for regulatory process terms. **failure modes:** Prior incompleteness may prune true novel interactions; over-regularization may harm generalization. **innovation status:** unverified