

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Towards Scalable Context-Aware Single-Cell Spatial Transcriptomics Prediction from Histology Images	[Paper] [Paper: PDF p. 1]
Authors	Zijun Gao, Chunbin Gu, Jinxi Xiang, Xiangde Luo, Pheng-Ann Heng	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (NeurIPS 2026 submission)	[Paper] [Paper: PDF p. 1]
Code	github.com/zjgao02/CELLO	[Paper] [Paper: PDF p. 1]
Model	hf.co/gaozijun/CELLO	[Paper] [Paper: PDF p. 1]
Data	hf.co/datasets/gaozijun/cello_data; 10X-Xenium-52 subset of HEST-1k	[Paper] [Paper: PDF p. 1], [Paper] [Paper: PDF p. 6], [Paper] [Paper: PDF p. 13]
Core task	Predicting single-cell spatial gene expression vectors $\hat{x}_i \in \mathbb{R}^{G_{\geq 0}}$ from H&E image V and cell location s_i	[Paper] [Paper: PDF p. 4, Eq. 1]
Key model	CELLO: grid-sampling + distance-decay cross-attention over PFM token map	[Paper] [Paper: PDF p. 2–4], [Figure 1D], [Figure 2]
Benchmark	10X-Xenium-52: 52 paired Xenium–H&E samples across 12 organs, ~10M cells	[Paper] [Paper: PDF p. 6], [Figure 5], [Table 2]
Evaluation metric	Mean Pearson Correlation Coefficient (PCC) over gene subsets: MPG, HVG, SVG, full panel	[Paper] [Paper: PDF p. 5], [Table 1], [Table 5], [Figure 6]

02 一句话总结

本文提出 CELLO，首个端到端、单次 PFM 前向传播的单细胞分辨率 H&E→基因表达预测框架，解决现有方法在尺度匹配（patch vs. cell）、形态保真（cropping distortion）、上下文建模（global vs. local）三重矛盾；在 10X-Xenium-52 上实现 ID/OD 设置下平均 HVG PCC 提升 58.5%/71.3%，推理速度达 DeepSpot2Cell 的 14.0×；其核心创新在于位置感知双线性查询 + 距离衰减交叉注意力，将细胞定位与局部组织形态解耦建模。边界在于：依赖上游细胞定位（非端到端分割）、未覆盖 subcellular resolution、OOD 泛化基于单样本器官验证。

03 研究问题

问题：如何在不牺牲细胞形态保真度与计算可扩展性的前提下，从 H&E 图像中直接、准确地预测单细胞空间基因表达？**作者洞察：**现有范式存在根本性张力——PFM 天然输出 patch-level 特征（含多细胞混合信号），而 per-cell cropping 扰乱局部微环境且引入 $O(N)$ 推理开销；mask-based 模型（如 UNet3+）缺乏强预训练视觉表征，且继承分割误差。因此，问题本质是**如何在单次 PFM 前向传播约束下，为任意坐标 s_i 构造既锚定精确位置、又融合局部形态上下文的细胞嵌入 z_i** 。**方法路径：**放弃“为每个细胞运行一次 PFM”，转而利用 PFM 输出的 2D token map $T \in \mathbb{R}^{L_g \times L_g \times d}$ 作为共享视觉场，通过可微分网格采样（bilinear interpolation）获取初始位置特征，再以距离衰减为先验进行跨 token 注意力精炼——将“位置”与“上下文”解耦为两个正交设计阶段。

04 研究背景与发展路径

该工作扎根于两大演进脉络：（1）**空间转录组学预测范式升级：**从 spot-level（Visium）→ super-resolution（iStar, scstGCN）→ 单细胞级（DeepSpot2Cell, GHIST），但后者仍受限于 per-cell crop 或 mask 依赖；（2）**病理基础模型（PFM）能力迁移瓶颈：**UNI/Virchow2/H-Optimus-0 等在 patch 分类/生存预测上表现优异，但其 token 粒度（ 14×14 – 16×16 px）与细胞尺度（常 >50 px）不匹配，直接用于细胞级任务需重新对齐。CELLO 的发展路径是**逆向工程 PFM 的归纳偏置：**不强行压缩 token 到细胞，而是将细胞视为 query，在 token map 上执行空间软对齐（soft alignment）——这既复用 PFM 的强表征，又规避了硬裁剪的形态失真。图1B/C/D 直观呈现了该路径对前代方法的替代逻辑。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Scale mismatch between PFM tokens and cells	Per-cell cropping/resizing distorts morphology and removes local microenvironmental context	PFMs are pretrained on patches, not cells; their receptive fields mix multiple cells, making direct per-cell application ill-posed	[Paper] [Paper: PDF p. 2], [Figure 1B], [Paper] [Paper: PDF p. 3]
Segmentation dependency without strong visual priors	UNet3+-based models lack morphological representation capacity and inherit errors from imperfect cell masks	Mask-based architectures (e.g., UNet3+) do not leverage pretrained pathology foundation models, limiting their ability to capture fine-grained tissue structure	[Paper] [Paper: PDF p. 2], [Figure 1C], [Paper] [Paper: PDF p. 6]
Computational intractability at WSI scale	DeepSpot2Cell requires N independent PFM forward passes per slide, scaling linearly with cell count (up to millions)	Naive adaptation of PFM to cell-level targets ignores amortization opportunity; each cell crop is treated as an independent input	[Paper] [Paper: PDF p. 2], [Figure 1B], [Paper] [Paper: PDF p. 8]
Ambiguous context scope for gene prediction	Global CLS token degrades performance, contradicting intuition that “whole-slide context helps”	Gene expression is shaped by immediate cellular neighborhood, not abstract slide-level semantics; CLS dilutes local signal	[Paper] [Paper: PDF p. 7], [Figure 3B], [Paper] [Paper: PDF p. 18]

06 核心思想

核心思想不是“让 PFM 输出细胞特征”，而是“让细胞去查询 PFM 的视觉场”。具体包含三层解耦设计：(1) **位置解耦**：用双线性插值 (Eq. 3) 从连续 token map T 中提取亚像素级初始特征 $q^{(0)}_i$ ，使 z_i 严格锚定于 s_i ，摆脱离散 token 网格束缚；(2) **上下文解耦**：引入距离衰减偏置 (Eq. 4) 调控 cross-attention logits，强制模型优先关注空间邻近 token，将生物学直觉（细胞状态受局部微环境调控）编码为可学习先验；(3) **训练目标解耦**：联合优化 cell-level Huber loss L_{cell} 和 patch-level aggregate loss L_{patch} (Eq. 5)，前者驱动单细胞精度，后者提供粗粒度一致性约束，缓解稀疏表达噪声。三者共同构成“精准定位 + 局部聚焦 + 全局校准”的闭环。

07 方法总览

CELLO 是一个两阶段特征精炼架构：第一阶段 (**Query Initialization**) 将细胞坐标 s_i 映射为 patch-local normalized coordinate $\tilde{s}_i$ ，通过 GridSample (Eq. 3) 从 PFM 的 2D token map T 中提取初始特征 $q^{(0)}_i$ ；第二阶段 (**Context Refinement**) 以 $q^{(0)}_i$ 为 query，所有 spatial tokens $\{t_m\}$ 为 key/value，经 2D RoPE 编码相对位置后，叠加 Gaussian 距离衰减偏置 $b_{i,m}$ (Eq. 4) 进行 multi-head cross-attention，输出 refined embedding z_i ；最终经 MLP 解码为 $\hat{x}_i$ 。整个流程仅需一次 PFM 前向传播 (per patch)，所有细胞特征并行生成。关键设计选择 (Virchow2 encoder, no CLS fusion, $\lambda=0.5$) 均经消融验证 ([Figure 3A/B], [Table 6/7/8])。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Bilinear Query Initialization	Extract continuous, sub-patch feature $q^{(0)}_i$ by interpolating four nearest tokens around s_i	To anchor cell representation to precise pixel location, avoiding discretization error of token-grid indexing	Input: $T \in \mathbb{R}^{L_g \times L_g \times d}$, $\tilde{s}_i \in [-1,1]^2$; Output: $q^{(0)}_i \in \mathbb{R}^d$	[Paper] [Paper: PDF p. 4, Eq. 3], [Figure 2]	Removal forces hard assignment to nearest token $\rightarrow$ loss of sub-pixel precision $\rightarrow$ degraded localization (e.g., blurred expression boundaries in Fig.4)

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal		
Distance-Decay Cross-Attention	Refine $q^{(0)}_i$ using spatially biased attention over all patch tokens, where $b_{i,m} = -\sqrt{2/p^2}$	$s^{\text{loc}}_i - c_m$	$\sqrt{2/p^2}$	To inject biologically grounded prior that a cell's transcriptome is shaped by its immediate morphological neighborhood, not distant regions	Input: $q^{(0)}_i, \{t_m\}_{m=1}^M, s^{\text{loc}}_i, c_m$; Output: z_i in $\mathbb{R}^d$	[Paper] [Paper: PDF p. 5, Eq. 4], [Figure 2], [Table 1: Grid vs. CELLO gap]	Removal (Grid baseline) causes 18.6% (ID) / 16.2% (OOD) HVG PCC-50 drop → proves local context is non-redundant [Paper] [Paper: PDF p. 6]
2D RoPE Position Encoding	Encode relative spatial relationships between s_i and c_m into attention logits without extra parameters	To provide explicit geometric inductive bias for attention, aligning positional scales between cell queries and image tokens	Input: s^{loc}_i, c_m ; Output: rotary embeddings for Q/K	[Paper] [Paper: PDF p. 5], [Ref. 32]	Not ablated separately, but integral to distance-decay module; removal would weaken spatial awareness beyond distance bias alone		
Dual-Level Training Loss ($L_{\text{cell}} + \lambda L_{\text{patch}}$)	Jointly optimize per-cell prediction and patch-aggregate consistency	To regularize cell-level predictions using coarse-grained ground truth, mitigating noise/sparsity in single-cell measurements	Input: $\hat{x}_i, x_i, \hat{x}_{\text{patch}} = \sum_i \hat{x}_i, x_{\text{patch}} = \sum_i x_i$; Output: scalar loss	[Paper] [Paper: PDF p. 5, Eq. 5], [Table 7: λ sensitivity]	Setting $\lambda=0$ reduces ID HVG PCC-50 by 0.0072 vs. $\lambda=0.5 \rightarrow$ shows auxiliary patch loss stabilizes training [Table 7]		

09 关键公式与符号

论文未给出完整可核验的端到端公式，但明确提取以下关键符号与关系：

- **Task mapping:** $f_{\theta} : (V, s_i) \mapsto \hat{x}_i \in \mathbb{R}^{G_{\geq 0}}$ ([Paper] [Paper: PDF p. 4, Eq. 1])

- **Bilinear query:** $q^{(0)}_i = \text{GridSample}(T, \tilde{s}_i)$, where $\tilde{s}_i = 2 s^{\text{loc}}_i / L - 1$ ([Paper] [Paper: PDF p. 4, Eq. 3])
- **Distance-decay bias:** $b_{i,m} = -|s^{\text{loc}}_i - c_m|^2 / p^2$, with c_m token center in pixel coordinates ([Paper] [Paper: PDF p. 5, Eq. 4])
- **Training objective:** $L = L_{\text{cell}} + \lambda L_{\text{patch}}$, using Huber loss ([Paper] [Paper: PDF p. 5, Eq. 5])
- **Key symbols:** V (H&E patch), s_i (cell coordinate), T (2D token map), z_i (refined cell embedding), p (token stride in pixels), λ (loss weight, set to 0.5). No closed-form expression for final $\hat{x}_i$ beyond MLP(z_i).

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
ID/OOD benchmark (Table 1/5/6/8)	CELLO outperforms baselines on diverse organs and generalization settings	CELLO vs. DeepSpot2Cell/ UNet3+/Grid on 10X-Xenium-52; ID: 6 organs seen in train; OOD: 4 unseen organs + 2 new disease states	CELLO achieves +58.5% (ID) / +71.3% (OOD) HVG PCC-50 over DeepSpot2Cell; +18.6% over Grid (ID)	CELLO' s design (grid sampling + distance-attention) yields superior accuracy and robustness	CELLO generalizes to <i>all</i> unseen organs — OOD tests use only 1 sample per organ, insufficient for organ-level claims [Paper] [Paper: PDF p. 23]	[Table 1], [Table 5], [Paper] [Paper: PDF p. 6]
Encoder ablation (Fig.3A, Table 6/8)	Stronger PFM encoders improve cell embedding quality	Virchow2 vs. H-Optimus-0 vs. UNI, same CELLO architecture	Virchow2 gives +28.9% avg HVG PCC-50 over H0 in ID; +41.9% in OOD	Pathology foundation model strength is a key scaling axis for single-cell prediction	Virchow2 is universally optimal — performance varies by gene subset (e.g., weaker on SVG PCC-200 in OOD) [Table 8]	[Figure 3A], [Table 6], [Table 8]
CLS token fusion (Fig.3B, Table 6/8/E)	Global CLS context harms single-cell prediction	CELLO with/without CLS fusion, across encoders and settings	CLS fusion reduces avg ID PCC by 13.6% (Virchow2); consistent degradation in OOD	Fine-grained local morphology, not global semantics, drives gene expression prediction	CLS is always harmful — one OOD entry (HVG PCC-200) improves marginally [Paper] [Paper: PDF p. 18]	[Figure 3B], [Table 6], [Paper] [Paper: PDF p. 18]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Efficiency benchmark (Fig.3C, Table 9/J)	CELLO achieves 14.0× speed-up over per-cell PFM methods	Inference time on 12 test slides; excludes segmentation	CELLO: 67.5±48.8s/slide; DeepSpot2Cell: 947.2±1068.3s /slide; ratio median 11.7×	Single PFM pass + grid sampling eliminates per-cell bottleneck	Speed-up holds for <i>all</i> WSIs — variance is high (3.5–26.3×), correlating with cell density ($\rho=0.97$) [Paper] [Paper: PDF p. 9]	[Figure 3C], [Table 9], [Paper] [Paper: PDF p. 9]
External validation (Table 10)	CELLO transfers to held-out HEST-1k samples without adaptation	CELLO trained on 10X-Xenium-52 applied to 5 new Xenium samples	PCC ranges: MPG-10=0.454–0.700, HVG-10=0.470–0.700 across samples	CELLO’ s representations generalize beyond training distribution	Performance is stable across subtypes — e.g., SKCM (TENX158) shows large HVG-10 drop (0.470 vs. 0.700) [Table 10]	[Table 10], [Paper] [Paper: PDF p. 22]

11 对结论的正确理解

CELLO 的核心贡献是证明了“单次 PFM + 位置感知查询 + 局部上下文精炼”这一范式在单细胞 H&E→ST 预测上的有效性与高效性，而非宣称其解决了所有挑战。其 SOTA 结果（如 +71.3% OOD gain）是在特定 benchmark（10X-Xenium-52）和评估协议（HVG PCC-50）下取得的，不能泛化为“对所有基因或所有 tissues 都绝对最优”。速度优势（14.0×）明确限定于与 DeepSpot2Cell 的比较，且排除了细胞分割耗时；当计入 CellViT-SAM-H 分割（382.5s/slide），CELLO 仅比 DeepSpot2Cell 快 2.5×。其“context-aware”特指距离衰减引导的局部形态上下文，并非多尺度或跨模态上下文；论文明确否定全局 CLS 的价值（[Paper] [Paper: PDF p. 18]）。所有结论均基于配对 Xenium-H&E 数据，不适用于无空间坐标的 bulk RNA-seq 或非配对图像。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited OOD evaluation scale	Several OOD organs (Brain, Bone, Heart, Ovary) are represented by only one slide each	Collect more paired data across wider tissue/organ range to improve generalization estimation	[Paper] [Paper: PDF p. 23]
Dependence on upstream cell localization	CELLO requires cell centroids $\$s_i\$$ at inference; predictions inherit segmentation errors	Improve accuracy of cell segmentation to reduce bad predictions	[Paper] [Paper: PDF p. 23]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Single-sample OOD validation	Kidney and Liver appear in training under different health conditions; OOD results are case studies, not robust estimates	Treat OOD results as indicative stress tests rather than quantitative generalization metrics	[Paper] [Paper: PDF p. 23]
Benchmark scope	10X-Xenium-52 covers 12 organs but omits key tissues (e.g., brain subregions, rare cancers)	Expand benchmark to include more heterogeneous and clinically nuanced samples	[Paper] [Paper: PDF p. 23]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
CELLO' s distance-decay bias uses fixed Gaussian kernel (σ^2 denominator)	The optimal decay scale may vary across tissue types (e.g., dense tumor vs. sparse stroma) or magnifications; fixed σ could under/over-smooth	Using a universal decay scale may limit adaptability to heterogeneous morphologies, hurting generalization	Replace fixed σ^2 with learnable scale parameter per tissue type or add tissue-aware gating to $\mathbf{b}_{\{i,m\}}$; compare on multi-tissue ablation	[Paper] [Paper: PDF p. 5, Eq. 4], [Figure 5B] shows large variation in cell density across organs
Virchow2 superiority is consistent but unexplained	The gain may stem from larger architecture (1280-d vs. 1024-d) or broader pretraining data, not inherent “pathology-awareness” ; UNI' s lower performance could reflect suboptimal fine-tuning	Attributing gains solely to “stronger PFM” overlooks confounding factors like capacity or data scale, risking misallocation of engineering effort	Train all encoders with identical hyperparameters (LR, unfreezing schedule) and report parameter counts; ablate architecture size independently	[Paper] [Paper: PDF p. 7] notes architectural differences but doesn' t control for them
Sensitivity analysis (Table 11) uses Gaussian jitter only	Real-world segmentation errors are systematic (e.g., boundary under-segmentation in crowded regions), not isotropic Gaussian noise	Gaussian perturbation may underestimate failure modes in morphologically challenging areas (e.g., mitotic figures, necrosis)	Apply realistic error patterns: (1) shift centroids toward nearest nucleus centroid, (2) remove centroids in low-contrast regions; measure PCC drop	[Paper] [Paper: PDF p. 22, Table 11], [Figure 4] shows CELLO struggles with fine structures (e.g., MYH11 in smooth muscle)

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
External validation (Table 10) reports only PCC, no uncertainty	Five samples are too few for reliable confidence intervals; large variance in PCC (e.g., TENX158 HVG-10=0.470 vs. TENX94=0.700) suggests high sample-specific bias	Overinterpreting external validation as “robust transfer” ignores sampling variance and potential dataset shift	Bootstrap resampling over the 5 samples to compute 95% CI for mean PCC; report per-sample standard deviation	[Table 10], [Paper] [Paper: PDF p. 22]

14 学到的知识

- **单细胞预测的尺度对齐新范式**: 无需将 PFM 降维至细胞粒度，而可将细胞视为 query 在 token map 上软对齐——此思路可迁移到 spatial proteomics 或 multi-omics integration，只要存在配对的空间坐标。
- **距离衰减注意力的有效性边界**: 它在组织形态预测中优于全局 CLS，但其固定高斯核可能不适应跨模ality (如 H&E + IF)，提示在 multi-modal alignment 中需设计 modality-adaptive decay。
- **效率-精度权衡的实证**: CELLO 证明 “单次 backbone pass + lightweight refinement” 可同时提升精度与速度，这对部署 biomedical AI 到临床 WSI pipeline 具有直接指导意义——避免为追求 SOTA 而堆叠计算。
- **评估协议的关键性**: HVG/MPG/CSV subsets reveal different model behaviors (e.g., CELLO excels on HVG but lags on SVG in OOD [Table 8]); 用户在评估自己的模型时，必须报告多基因集结果，而非仅选最优子集。
- **外部验证的脆弱性**: 5个额外样本的 PCC 差异达 0.23 (0.47–0.70)，警示 “external validation” 不等于 “robust generalization”；真正可靠的验证需独立机构、多中心数据。

15 与既有知识的连接

- **single-cell foundation models**: CELLO 不是 foundation model，而是 **foundation model 的下游适配器**；其 grid sampling + distance-attention 可视为一种轻量级 cell-level adapter，启发我们为 scFoundation 设计类似 spatial adapter，避免全参数微调。
- **spatial transcriptomics**: 直接对标 Xenium 数据，验证了 H&E-to-ST 的单细胞可行性；但 CELLO 未建模基因间相关性 (如 co-expression networks)，可与 COMMOT [43] 的 ligand-receptor context 结合，构建细胞-细胞通信感知的表达预测。
- **graph neural networks**: CELLO 的距离衰减可视为 implicit spatial graph construction；未来可显式构建 k-NN graph over cell centroids and apply GNN on top of z_i ，增强 cell-cell interaction modeling。
- **multi-omics**: 论文强调 “morphology-to-molecular translation”，其 dual-level loss ($L_{\text{cell}} + L_{\text{patch}}$) 提供模板：在 multi-omics prediction 中，可设计 $L_{\text{modalityA}} + \lambda L_{\text{modalityB}}$ 强制跨模态一致性。
- **perturbation prediction & cell state representation**: CELLO 预测的是 steady-state expression；若将 s_i 替换为 perturbation-conditioned latent (e.g., drug dose, CRISPR KO), 其 query-refinement pipeline 可扩展为 perturbation-aware cell state predictor。

- **cross-modal alignment:** CELLO 的 bilinear query is a form of cross-modal alignment (image coordinate $\rightarrow$ token space); this geometric alignment principle can be generalized to align histology with MRI or CT via shared spatial coordinate systems.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** AdaptiveScale-CELLO

originating limitation/observation: Fixed Gaussian decay scale σ^2 in Eq.4 may not suit heterogeneous tissues ([Analysis] in Sec.13) **core hypothesis:** Tissue-type-specific decay scales improve OOD generalization across morphologically distinct organs **delta from paper:** Replace σ^2 with learnable σ_t^2 per tissue t , predicted from patch-level statistics (e.g., cell density, texture entropy) **initial method:** Add tissue classifier head to PFM; output σ_t as function of patch features; modify Eq.4 to $b_{i,m} = -\|s^{\text{loc}}_i - c_m\|^2 / \sigma_t^2$ **validation:** Train on 10X-Xenium-52; evaluate OOD PCC gain on Brain/Bone/Heart; ablate tissue classifier **failure modes:** Classifier misprediction leads to wrong σ_t ; high variance in small organs (e.g., Ovary $n=1$) **innovation status:** unverified

- **name:** CELLO-GNN

originating limitation/observation: CELLO models each cell in isolation; no explicit cell-cell interaction modeling despite biological importance ([Paper] [Paper: PDF p. 2] mentions “intricate cell-cell interactions”) **core hypothesis:** Explicit GNN on top of z_i captures intercellular communication signals missing from local morphology alone **delta from paper:** Replace final MLP with 2-layer GAT using k -NN graph built on s_i ; edge features = relative position + morphology similarity **initial method:** For each patch, build $k=5$ graph; GAT layers aggregate neighbor z_j weighted by attention; final readout = MLP(GAT output) **validation:** Compare PCC on ligand-receptor gene pairs (e.g., VEGFA-FLT1) vs. non-interacting genes; ablate GNN **failure modes:** Graph sparsity in low-cell-density patches; computational overhead negating CELLO’s speed advantage **innovation status:** unverified

- **name:** UniLoc-CELLO

originating limitation/observation: CELLO depends on upstream cell segmentation; real-world deployment needs end-to-end localization ([Paper] [Paper: PDF p. 23]) **core hypothesis:** Jointly predicting cell centroids and expression from H&E is feasible by extending CELLO’s query mechanism to detection **delta from paper:** Add parallel branch predicting centroid heatmap $H \in \mathbb{R}^{L_g \times L_g}$ from T ; use detected peaks as s_i for expression branch **initial method:** Append lightweight decoder to T ; supervise H with Gaussian-blurred ground-truth centroids; expression branch uses detected s_i **validation:** Measure centroid detection AP and expression PCC jointly; compare to cascaded CellViT-SAM-H + CELLO **failure modes:** Error propagation: false positives in H create spurious s_i ; training instability from joint optimization **innovation status:** unverified

- **name:** MultiModal-CELLO

originating limitation/observation: CELLO uses only H&E; integrating IF or RNA scope data could boost accuracy ([Paper] [Paper: PDF p. 1] mentions “molecular depth”) **core hypothesis:** Cross-modal alignment via shared spatial query space improves prediction over uni-modal baselines **delta from**

paper: Extend grid sampling to multi-modal token maps: $T_{\text{H\&E}}$, T_{IF} ; fuse via cross-attention before z_i refinement **initial method:** Encode H&E and IF patches separately; for each s_i , query both T maps; cross-attend between modalities before distance-attention **validation:** Test on public H&E+IF Xenium datasets (if available); measure PCC gain on low-signal genes **failure modes:** Modality misalignment (requires precise co-registration); increased inference latency **innovation status:** unverified