

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-05	[Paper: URL metadata]
Authors	Youngmin Chung et al. (21 authors, co-first and co-senior marked)	[Paper] [Paper: PDF p. 1]
Core contribution	First large-scale, standardized, multi-platform benchmark for virtual ST models, with unified PFM encoding, gene-level interpretability analysis, downstream biological utility evaluation, and robustness testing	[Paper] [Paper: PDF p. 2–4, Fig. 1]
Data scale	STP-BENCH-INTERNAL: 609,024 spots across 6 cancer types, 202 slides; STP-BENCH-EXTERNAL: 185,831 spots across same 6 types, 73 slides	[Paper] [Paper: PDF p. 4, Fig. 1b]
Models evaluated	21 models: 14 regression-based, 4 bi-modal retrieval, 3 generative	[Paper] [Paper: PDF p. 6, Fig. 1c]
Key metrics	PCC (Equation 1), MAE (Equation 2), SSIM	[Paper] [Paper: PDF p. 31–32]
Code & data	Publicly released at https://github.com/NEXGEM/STP-Bench and Hugging Face	[Paper] [Paper: PDF p. 37]

02 一句话总结

该论文提出了 STP-BENCH —— 首个面向 virtual spatial transcriptomics（虚拟空间转录组）的统一、系统性基准，覆盖 Visium 和 Xenium 双平台、六种癌症的大规模数据（超 79 万 spots），强制统一使用 pathology foundation model（PFM）作为图像编码器以解耦架构与表征能力。其核心发现是：多数现有模型在统一编码下无法超越线性探针基线；基因可预测性存在强普适性天花板（某些基因对所有模型均难预测），而多尺度架构（如 TRIPLEX、DeepSpot）仅在特定生物学通路（如基质重塑、免疫浸润）上提供边际增益；下游任务（cell

deconvolution、spatial domain ID) 性能与 spot-level PCC 高度一致, 且严重受限于原始 ST 数据质量 (Xenium > Visium)。该工作不提出新模型, 而是通过严格控制变量揭示领域真实瓶颈。

03 研究问题

论文直面 virtual ST 领域的评估危机: 当不同研究采用异构小数据集、私有训练流程、混杂的图像编码器 (ImageNet vs. pathology PFM)、且仅报告 aggregate PCC 时, 模型进步是否真实? [Paper] [Paper: PDF p. 2–3] 这一问题背后隐含三个子问题: (1) 若剥离图像编码器差异, 哪些模型架构真正具备泛化优势? (2) spot-level 预测精度能否可靠传导至细胞类型丰度、空间结构等生物学粒度? (3) 模型在跨机构、跨组织、跨平台等现实分布偏移下的鲁棒性边界何在? [Paper] [Paper: PDF p. 4, 14, 17] 论文将这些问题转化为可操作的 benchmark 设计目标, 而非停留在方法论批评层面。

04 研究背景与发展路径

virtual ST 的发展已形成三条技术主线: 回归式 (ST-Net → TRIPLEX/DeepSpot)、双模态对齐式 (BLEEP → mclSTExp)、生成式 (Stem/STFlow) [Paper] [Paper: PDF p. 3, 6]。但评估始终滞后: Wang et al. 2024 [50] 用原生编码器评测, 混淆了 encoder 与 architecture 贡献; HEST-1K [51] 构建了大规模配对数据, 却仅用简单回归评测 PFM embedding 与基因的相关性, 未覆盖主流模型家族 [Paper] [Paper: PDF p. 3–4]。STP-BENCH 的演进路径正是对这两条失败路径的修正——它继承 HEST-1K 的数据规模与多平台思想, 但彻底重构评估范式: 强制统一 encoder (UNiv2)、重实现全部 21 模型、引入基因级/通路级/下游任务级多维验证, 并将“鲁棒性”从口号变为可量化的 cross-institution/tissue/platform 实验 [Paper] [Paper: PDF p. 4–5, Fig. 1]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Evaluation unfairness	Model rankings shift dramatically when swapping native encoders for UNiv2 (e.g., CFANet jumps from 16th to 6th)	Prior works conflate architectural innovation with image encoder quality; encoders differ in pretraining scale, domain, and paradigm [Paper] [Paper: PDF p. 3, 9]	Figure 2b shows rank reversal; [Paper] [Paper: PDF p. 9] states “evaluations in previous works [...] are likely unfair comparisons”
Biological interpretability gap	Aggregate PCC masks which genes/pathways are recoverable; marker genes (e.g., CD3E, PDCCD1) show consistently lower predictability than HMMVGs	Morphology-to-expression mapping is gene-specific; some programs (e.g., immune checkpoints) depend on long-range tissue context invisible to local patches [Paper] [Paper: PDF p. 9, 13]	Figure 2a shows PCC ≈0.2 for markers vs. ≈0.4 for HMMVGs; Figure 3a heatmap reveals universal gene-wise concordance across models
Downstream utility unverified	Spot-level accuracy does not guarantee utility for cell-type deconvolution or spatial domain identification	Predicted profiles may preserve statistical correlation but lose spatial coherence or biological structure required by downstream tools [Paper] [Paper: PDF p. 14]	Figure 4a–c shows TRIPLEX/DeepSpot top-performing on Cell2location/SpaGCN, but performance drops sharply on Visium vs. Xenium cohorts, mirroring gene-level gap

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Robustness under domain shift poorly characterized	Models trained on one institution/tissue/platform fail unpredictably on others; inter-cohort scaling causes negative transfer	Morphology-to-expression mappings are highly tissue-specific; simple data aggregation ignores biological heterogeneity [Paper] [Paper: PDF p. 17, 19]	Figure 5b shows cross-tissue gap up to -0.35 PCC; Figure 5d shows adding LUAD/PRAD to BRCA training <i>lowers</i> BRCA test performance

06 核心思想

论文的核心思想不是“如何构建更好的 virtual ST 模型”，而是“如何科学地定义 ‘更好’”。其逻辑链为：**评估失准 → 归因混乱 → 解耦必要 → 多维验证 → 揭示本质瓶颈**。具体而言：（1）指出当前评估中 encoder choice 是主要混杂因子，故必须强制统一（UNiv2）以隔离 architecture effect；（2）发现 gene-wise predictability 具有跨模型强一致性，暗示瓶颈在于 morphology-gene biology coupling，而非模型 capacity；（3）证明下游任务性能是 spot-level PCC 的单调函数，且受原始 ST 平台质量（Xenium’ s higher sensitivity）主导，从而将问题锚定在数据层而非算法层；（4）揭示跨组织泛化是最大挑战，反向提示未来工作需建模 tissue-aware morphological priors，而非追求通用架构 [Paper] [Paper: PDF p. 17–19]。

07 方法总览

STP-BENCH 的方法论是“控制变量 + 多维穿透”：在统一 PFM 编码（UNiv2）前提下，对 21 个代表性模型进行三层次评估：（1）**基础性能层**：在 STP-BENCH-INTERNAL 上用 PCC/MAE/SSIM 评测 HMHVGs 和 TME marker genes，识别 baseline vs. architecture gain；（2）**生物学解释层**：基因级 heatmap（Fig. 3a）、通路级 singscore（Fig. 3c–e）、下游任务（Cell2location/SpaGCN，Fig. 4）验证预测是否承载真实生物学信号；（3）**鲁棒性层**：在 STP-BENCH-EXTERNAL 上设计 cross-institution/tissue/platform 三类迁移实验（Fig. 5a–b），并量化 intra-/inter-cohort scaling 效应（Fig. 5c–d），将 benchmark 从静态评测升维为动态压力测试 [Paper] [Paper: PDF p. 4–5, Fig. 1]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Unified PFM Encoder (UNiv2)	Extract fixed-dim histology embeddings from 224×224 H&E patches	To isolate architectural contribution by eliminating encoder variability — the central confounder in prior work [Paper] [Paper: PDF p. 3, 7]	Input: H&E patch; Output: 1024-dim vector	Figure 2b shows rank reversal with native encoders; Figure 2e confirms UNiv2 > CTransPath > ResNet50	Removal would revert to unfair comparison; models like CFANet would drop ~10 ranks (Fig. 2b)

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Gene Set Scoring (singscore)	Compute per-spot activity score for GO Biological Process terms from predicted expression	To bridge gene-level accuracy and functional biology — aggregate PCC cannot reveal if immune pathways are preserved [Paper] [Paper: PDF p. 13]	Input: spot-by-gene matrix; Output: spot-by-gene-set matrix	Figure 3c–e shows TRIPLEX/DeepSpot top on T Cell Activation & Cell-Matrix Adhesion pathways; Spearman $\rho=0.902$ with gene-level PCC [Paper] [Paper: PDF p. 13]	Removal would leave evaluation at statistical correlation level, missing functional coherence validation
Cross-Platform Pseudo-Spot Binning	Aggregate Xenium single-molecule coordinates into $100\mu\text{m}\times 100\mu\text{m}$ pseudo-spots aligned with Visium grid	To enable fair benchmarking across Visium (spot-based) and Xenium (single-molecule) platforms — a key design for multi-platform validity [Paper] [Paper: PDF p. 22]	Input: Xenium transcript coords + registered H&E; Output: pseudo-spot expression + matching 224×224 patch	Figure 1b shows combined Visium/Xenium distribution; Online Methods details binning to match Visium spacing [Paper] [Paper: PDF p. 22]	Removal would exclude Xenium data, collapsing benchmark to single-platform and missing critical platform-gap insight (Fig. 2c vs. 2d)
Downstream Task Pipeline (Cell2location/SpaGCN)	Apply standard scRNA-seq reference-based deconvolution and spatial clustering to predicted profiles	To test if virtual ST outputs are <i>biologically actionable</i> , not just statistically correlated — the ultimate utility test [Paper] [Paper: PDF p. 14]	Input: predicted spot-by-gene matrix; Output: cell-type abundance / spatial domain labels	Figure 4a–c shows consistent ranking preservation (TRIPLEX/DeepSpot best) and Xenium>Visium performance gap mirroring Fig. 2	Removal would render benchmark purely computational, unable to answer “does this help biologists?”
Generalization Gap Quantification	Compute $\Delta\text{PCC} = \text{External_PCC} - \text{Internal_PCC}$ for each model under cross-institution/tissue/platform	To move beyond “model A beats B” to “how fragile is A’s advantage?” — essential for real-world deployment guidance [Paper] [Paper: PDF p. 17]	Input: internal & external PCC scores; Output: scalar gap per model/scenario	Figure 5b visualizes gaps; text notes cross-tissue gap (-0.2 to -0.35) >> cross-institution (-0.05 to -0.10) [Paper] [Paper: PDF p. 17]	Removal would hide critical failure modes; e.g., inability to detect that cross-tissue is the dominant bottleneck

09 关键公式与符号

论文明确给出两个核心公式，均用于 spot-level 评估：

- **Equation 1 (PCC):**
$$\text{PCC}_{g,s} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$$
 [Paper] [Paper: PDF p. 31]

- 符号： $\hat{y}_{i,g}$ = predicted log-normalized expression of gene g at spot i ; $y_{i,g}$ = ground-truth; $\bar{\hat{y}}_g$, $\bar{y}_g$ = means across spots in section s .
- **Equation 2 (MAE):** $\text{MAE}_{g,s} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$ [Paper] [Paper: PDF p. 32]
- 符号：同上，但 operates in $\log(1+x)$ -transformed space.
- 其他关键指标：SSIM (structural similarity index, [Paper] [Paper: PDF p. 32])、ARI (Adjusted Rand Index, [Paper] [Paper: PDF p. 36])、singscore ([Paper] [Paper: PDF p. 13])。
- 无其他可核验公式；所有模型架构描述均为文字性（如 “TRIPLEX has three branches” [Paper] [Paper: PDF p. 25]），未提供数学形式化。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Figure 2a (Internal HMMVG/Marker PCC)	Unified PFM standardization reveals true architectural ranking	21 models, UNIV2 encoder (w/ PFM) vs. native encoders (w/o PFM), 7 datasets, HMMVGs (200 genes) vs. TME markers (16 genes)	Most models $\leq$ linear probing baseline (PCC ≈ 0.4 for HMMVG, ≈ 0.2 for markers); TRIPLEX/DeepS pot top	PFM choice dominates architecture; marker genes are intrinsically harder to predict	“All marker genes are biologically uncoupled from morphology” — contradicted by high PCC in Xenium (Fig. 2c)	[Paper] [Paper: PDF p. 7–9, Fig. 2a]
Figure 2c–d (Dataset-level stratification)	Data sparsity (not morphology) drives marker gene gap	NCCHE-LUAD-Xenium (high counts) vs. NCCHE-LUAD-Visium (low counts), same models, same genes	Xenium: PCC ≈ 0.58 for both HMMVG/marker; Visium: PCC ≈ 0.19 for markers	Low transcript counts, not morphological invisibility, limit marker prediction	“Xenium eliminates all virtual ST limitations” — contradicted by persistent gene-wise ceiling (Fig. 3a)	[Paper] [Paper: PDF p. 9–10, Fig. 2c–d]
Figure 3a (Gene-wise heatmap)	Gene predictability is model-agnostic	20 models, union of HMMVG+markers, STP-BENCH-INTERNAL	Smooth separation of high/low-PCC genes; consistent ordering across models	A universal morphology-gene coupling ceiling exists; architecture only shifts boundary marginally	“Architecture can overcome fundamental biological limits” — unsupported; gains are marginal ($\Delta\text{PCC} \geq 0.1$ for only 8–85 genes/cohort)	[Paper] [Paper: PDF p. 11, Fig. 3a]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Figure 4a–c (Downstream tasks)	Spot-level PCC predicts downstream utility	Cell2location (Fig. 4a) and SpaGCN (Fig. 4b–c) applied to predicted profiles vs. ground truth, 3 cohorts	TRIPLEX/DeepSpot top on both tasks; Xenium cohorts >> Visium cohorts	Downstream utility is a direct function of spot-level accuracy and raw data quality	“Virtual ST enables novel biological discovery beyond measured ST” — unsupported; no new biology claimed, only fidelity assessment	[Paper] [Paper: PDF p. 14–15, Fig. 4]
Figure 5a–b (Cross-domain generalization)	Internal ranking preserves under domain shift	Cross-institution/tissue/platform transfers, STP-BENCH-EXTERNAL, UNiv2 encoder	Spearman $\rho>0.86$ for institution/tissue; cross-tissue gap up to -0.35 PCC	Architectural superiority is robust to technical batch effects but fragile to biological heterogeneity	“Cross-tissue generalization is solvable with bigger models” — contradicted by negative transfer in Fig. 5d	[Paper] [Paper: PDF p. 17, Fig. 5a–b]

11 对结论的正确理解

论文结论必须严格限定在其实证范围内：（1）“多数模型不超越线性探针” 仅在 **UNiv2 编码、HMHVG/marker 基因集、spot-level PCC** 下成立；若换用更难基因集或单细胞分辨率，结论可能不同 [Paper] [Paper: PDF p. 20]；（2）“基因可预测性天花板” 指 **200 HMHVG + 16 markers 在当前数据和评估协议下的跨模型一致性**，不否定未来发现新 morphology-sensitive genes 的可能性；（3）“Xenium 优于 Visium” 是 **针对所用 cohort 的 transcript count 和 SNR 差异**，非平台绝对优劣；（4）“负向迁移” 指在 **Fig. 5d 的特定 inter-cohort scaling 协议下 (BRCA→+LUAD→+PRAD)**，不否定 domain-adaptive 或 tissue-aware 训练策略的有效性 [Paper] [Paper: PDF p. 19]。所有结论均基于统计显著性 ($p<10^{-5}$ for ρ , Kruskal-Wallis $p<10^{-12}$) 和多数数据集复现 (7 internal datasets, 3 external cohorts)。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer/tissue scope	STP-BENCH covers only 6 cancer types and 2 ST platforms (Visium/Xenium)	Extend benchmark to additional tumor types, tissue contexts, and emerging sequencing platforms	[Paper] [Paper: PDF p. 20]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Restricted gene set analysis	Evaluations focused only on HMHVGs (200 genes) and 16 TME markers; lowly expressed or functionally diverse genes not systematically assessed	Systematic investigation of low-expression genes and broader functional categories	[Paper] [Paper: PDF p. 20]
Spot-level granularity	All evaluations performed at spot-level (aggregated transcripts), not single-cell resolution	Future benchmarking efforts should extend to single-cell ST datasets and virtual ST models	[Paper] [Paper: PDF p. 20]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
UNiv2 as sole PFM may overstate encoder dominance	Using only UNiv2 ignores potential complementarity between encoder families (e.g., Virchow2' s superior cross-tissue rank preservation in Extended Data Fig. 5–6) [Paper] [Paper: PDF p. 17]	Over-reliance on one PFM could mask encoder-specific strengths for certain tasks (e.g., tissue generalization), leading to suboptimal model selection	Re-run core experiments (Fig. 2a, 5a) with Virchow2 and H-Optimus1 as primary encoders; compare rank correlation across encoders	[Paper] [Paper: PDF p. 17] states Virchow2/H-Optimus1 “maintained moderate-to-strong correlations” under tissue shift while ResNet/CTransPath did not
singscore-based gene set scoring conflates ranking with magnitude	singscore uses gene ranks within each spot, discarding absolute expression levels — may inflate scores for genes with flat but correctly ranked profiles	Downstream utility claims (e.g., “immune programs recovered”) may be overstated if predictions capture rank order but not dynamic range	Replace singscore with GSVA or AUCell (which use expression magnitudes) and recompute Fig. 3c–e; compare correlation with spot-level PCC	[Paper] [Paper: PDF p. 13] explicitly states singscore computes “averaging the ranks of member genes” , and Online Methods confirms rank-based implementation
Cross-platform transfer (Visium→Xenium) confounds platform difference with data quality	Performance “improvement” in Fig. 5b (right) likely stems from Xenium' s higher sensitivity, not model capability to bridge platforms	Misattribution could misdirect engineering effort toward platform-agnostic architectures instead of data-quality-aware modeling	Train models <i>only on Xenium</i> and test on Visium (reverse direction); if asymmetry persists, it confirms data-quality bias	[Paper] [Paper: PDF p. 17] admits “higher sensitivity and transcript counts from Xenium dataset compensating for the domain shift” , but does not test reverse direction

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Negative transfer in inter-cohort scaling may reflect poor cohort alignment, not inherent incompatibility	The BRCA→+LUAD→+PRAD sequence in Fig. 5d uses raw cohorts without harmonization (e.g., batch correction, platform normalization)	Concluding “simple aggregation is detrimental” overlooks preprocessing as a confounder; harmonized multi-tissue training might succeed	Apply ComBat or BBKNN to harmonize expression matrices across cohorts before training; compare Fig. 5d results	[Paper] [Paper: PDF p. 22] describes preprocessing per-cohort but no cross-cohort harmonization step; Online Methods lacks batch correction mention

14 学到的知识

- 评估优先级重排：在 virtual ST 中，选择强大的 pathology foundation model（如 UNiv2）比设计复杂架构更能提升性能；benchmark 必须强制统一 encoder 才能公平比较 [Paper] [Paper: PDF p. 7–9]。
- 生物学瓶颈定位：基因可预测性存在强普适性（Fig. 3a），提示瓶颈在 morphology-gene biology coupling（如 stromal/immune genes needing macro-scale context），而非模型 capacity — 这直接支持用户研究中 **cell state representation** 应融合多尺度 spatial context（graph + image patches）。
- 下游任务是终极验证：Cell2location/SpaGCN 性能与 spot-level PCC 高度一致（Fig. 4），证明 **cross-modal alignment** 的价值不在 pixel-level fidelity，而在 preserving spatial biological structure for downstream inference。
- 鲁棒性真相：跨机构（technical）泛化稳健，跨组织（biological）泛化脆弱（Fig. 5b），说明 **multi-omics** 或 **perturbation prediction** 模型必须显式建模 tissue-specific morphological priors, not assume universality。
- 数据质量即天花板：Xenium 与 Visium 的性能鸿沟（Fig. 2c vs. 2d）贯穿所有层级（gene → pathway → cell type），警示 **spatial transcriptomics** benchmarking 必须报告原始数据质量指标（mean counts, detection rate）。

15 与既有知识的连接

- 候选连接/方法论连接：STP-BENCH 的 multi-granularity evaluation (gene → gene set → cell type → spatial domain) mirrors the hierarchical validation strategy in single-cell foundation model papers (e.g., scGPT, scFoundation), but adapts it to spatial context — suggesting user’ s **single-cell foundation models** work could adopt similar downstream task pipelines (e.g., spatial deconvolution as a fine-tuning objective)。
- 候选连接/方法论连接：TRIPLEX/DeepSpot 的多尺度架构 (local + neighbor + global patches) conceptually aligns with graph neural networks (**graph neural networks**) where nodes are spots and edges encode spatial proximity — user’ s GNN work could formalize this as a heterogeneous graph (spot nodes + exemplar nodes + coordinate nodes) inspired by EGGN [Paper] [Paper: PDF p. 24]。
- 候选连接/方法论连接：singscore-based gene set scoring (Fig. 3c–e) provides a lightweight, scalable alternative to heavy permutation-based methods for **biomedical AI**, directly applicable to user’ s

cross-modal alignment projects where gene set activity is a natural alignment target between modalities.

- **弱连接/方法论连接**: 论文未涉及 perturbation prediction 或 explicit cell state dynamics, 但其揭示的 “morphology-to-expression mapping is tissue-specific” (Fig. 5b) 为用户 **perturbation prediction** 研究提供了关键约束: 任何 perturbation model must be conditioned on tissue context.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name**: Tissue-Aware PFM Adapter

originating limitation/observation: Cross-tissue generalization gap is severe (Fig. 5b, -0.35 PCC), and PFMs like Virchow2 show better rank preservation than ResNet (Paper: PDF p. 17) — suggesting encoder adaptation matters. **core hypothesis**: Lightweight, tissue-specific adapters grafted onto frozen UNiv2 can preserve cross-tissue ranking while avoiding full encoder retraining. **delta from paper**: STP-BENCH uses static UNiv2; this inserts trainable LoRA-style adapters per tissue type. **initial method**: For each cancer type, add two 8-rank LoRA layers to UNiv2’ s last transformer block; freeze UNiv2 backbone; train adapters + TRIPLEX head end-to-end. **validation**: Test on cross-tissue transfer (e.g., train on LUAD, test on BRCA); metric: Spearman ρ of model rankings vs. internal validation. **failure modes**: Adapter overfitting to tissue-specific noise; no improvement if tissue differences are orthogonal to UNiv2’ s learned features. **innovation status**: unverified

- **name**: Gene-Set Guided Contrastive Learning

originating limitation/observation: Retrieval models (BLEEP/mclSTExp) underperform on immune/stromal genes (Fig. 3a,b), yet these genes form coherent pathways (Fig. 3e) — suggesting contrastive loss should operate at pathway level, not spot level. **core hypothesis**: Aligning histology patches with *gene set activity vectors* (not raw expression) in contrastive space improves recovery of biologically structured programs. **delta from paper**: STP-BENCH uses spot-level expression vectors for BLEEP/mclSTExp; this replaces them with singscore-derived pathway vectors. **initial method**: Precompute singscore for 50 GO pathways per spot; use these 50-dim vectors as contrastive targets; modify BLEEP’ s spot projection head to output 50-dim pathway embeddings. **validation**: Compare pathway-level PCC (Fig. 3c) and downstream Cell2location performance (Fig. 4a) against original BLEEP. **failure modes**: Pathway vectors may be too coarse, losing gene-specific signal; singscore noise amplifies in contrastive loss. **innovation status**: unverified

- **name**: SSIM-Guided Diffusion Refinement

originating limitation/observation: Generative models (STFlow/Stem) have lower spot-level PCC (Fig. 2a) but SSIM is consistent with PCC (Paper: PDF p. 11) — suggesting they capture spatial structure better than regression models, but current metrics don’ t reward this. **core hypothesis**: Incorporating SSIM as an auxiliary loss during diffusion training steers generated expression toward spatially coherent patterns, improving downstream spatial tasks. **delta from paper**: STP-BENCH evaluates SSIM post-hoc; this integrates it into STFlow’ s training objective. **initial method**: Add SSIM loss term (weighted 0.1) to STFlow’ s hybrid MSE+KL loss; compute SSIM on 2D spatial grids of predicted vs. ground-truth expression per gene. **validation**: Measure ARI on SpaGCN (Fig. 4b–c) and SSIM itself; compare against

vanilla STFlow. **failure modes:** SSIM optimization may degrade spot-level PCC (trade-off); computational overhead of grid projection. **innovation status:** unverified