

Source coverage: Full paper

Extraction confidence: High

Locator mode: page-grounded

Primary analytical lens: methods

Secondary analytical lens: discovery

Context verification: Paper-only

Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Dynamic Generalized Gromov-Wasserstein Optimal Transport	[Paper] [Paper: PDF p. 1]
Authors	Junda Ying, Zhiwei Zeng, Peijie Zhou, Lei Zhang	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Core method	TP-DATE (Travelling Pair Dynamical Alignment and Trajectory Estimation)	[Paper] [Paper: PDF p. 1]
Core theory	Dynamic Quadratic-form OT (QOT), travelling-pair flow matching	[Paper] [Paper: PDF p. 4–7]
Key datasets	Synthetic Rotation/Distractor; Mouse Brain (Chen et al., 2022); ARTISTA (Wei et al., 2022); Tumor (Zhang et al., 2026a)	[Paper] [Paper: PDF p. 8–9, B.5.1–B.5.3]
Evaluation metrics	Spatial MSE (synthetic); Spatial W_2 , Expression W_2 , SC-eMSE, Balanced fused W_2 (real); Pair distortion	[Paper] [Paper: PDF p. 8–9, B.6]
Code/data availability	Not stated in text	Not核验

02 一句话总结

本文提出TP-DATE——首个严格定义的动态广义Gromov-Wasserstein最优传输（dynamic QOT）框架，通过引入“行进对”（travelling pair）路径动作与条件流匹配，将结构感知的传输从静态耦合推广至连续时间动力学建模；它在空间转录组学的时序插值与三维重建任务中显著优于现有方法，尤其在保持空间结构保真度方面取得突破；但其理论等价性仅限于上界保证（ $QOTS \geq QOTBB$ ），且实验未覆盖单细胞foundation model或跨模态对齐等更前沿场景。

03 研究问题

论文直面一个关键缺口：尽管静态GW-OT及其变体（如FGW-OT、IGW-OT）已被广泛用于空间转录组学的结构感知对齐，但尚无通用、可计算、免仿真的动态形式来重建连续轨迹 [Paper] [Paper: PDF p. 1–2]。该问题本质

是“如何在不依赖NeuralODE仿真前提下，让结构约束（如空间邻近性）直接作用于动力学演化过程，而非仅作用于端点耦合” [Paper] [Paper: PDF p. 2, 4]。作者将此问题形式化为：能否构建一个动态QOT理论，使其既包含OT、GW-OT、IGW-OT为特例，又具备可训练、可扩展、可解释的求解器？ [Paper] [Paper: PDF p. 2, 4]

04 研究背景与发展路径

研究始于经典OT的动态形式（Benamou & Brenier, 2000）与流匹配（Lipman et al., 2023）的成功，二者已支撑了TrajectoryNet、OT-CFM等单细胞轨迹推断工具 [Paper] [Paper: PDF p. 1, 3, 36]。但当数据携带内在结构（如空间坐标）时，点对点传输成本不足——GW-OT通过比较成对距离解决此问题，却仅停留在静态对齐层面 [Paper] [Paper: PDF p. 1–2, 3]。近期工作沿两条线推进：(1) Wang & Zhang (2025) 提出静态QOT统一框架；(2) Zhang et al. (2026b) 为IGW-OT构造梯度流型动态形式 [Paper] [Paper: PDF p. 2, 34]。TP-DATE则另辟蹊径：放弃直接推广GW-OT的几何结构，转而从**路径动作泛函**（path action）出发，定义“一对点如何协同运动”的最小作用量，并证明其静态/动态形式等价 [Paper] [Paper: PDF p. 4–5, A.1]。这一路径使结构约束自然嵌入动力学方程，而非事后耦合。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
静态结构对齐无法建模连续动力学	现有GW-OT类方法只能输出端点间耦合，无法生成中间时间点的细胞位置与表达状态的连续演化轨迹	“static formulations have been widely used [...] a general dynamic formulation for reconstructing continuous trajectories is still missing”	[Paper] [Paper: PDF p. 1]
现有动态方法结构约束间接且脆弱	stVCR、ContextFlow等虽引入空间项，但或依赖刚体变换对齐（易受噪声干扰）、或仅在静态耦合中编码结构（无法保证轨迹中结构保真）	“stVCR [...] introduces a rigid body transformation invariant OT formulation [...] unsolvable for flow matching based methods” ; “ContextFlow incorporates spatial information [...] indirectly through a static coupling”	[Paper] [Paper: PDF p. 2, D.7, D.6]
流匹配框架缺乏粒子交互建模能力	标准流匹配（如OT-CFM）基于独立行进Dirac，每个粒子路径由其端点唯一决定，无法刻画细胞间空间相互作用	“Under this framework, travelling Diracs are integrated over the static OT coupling independently, which means particles actually move independently”	[Paper] [Paper: PDF p. 4]
动态GW-OT缺乏统一理论与高效算法	IGW-OT等仅针对特定QOT变体，且依赖Riemannian几何推导；无通用动态QOT理论，亦无免仿真的可扩展求解器	“a general dynamic QOT formulation and its theory is still missing, as is an efficient simulation-free algorithm”	[Paper] [Paper: PDF p. 2]

06 核心思想

论文核心思想是**将结构感知的动力学建模，从“端点耦合+独立插值”范式，转向“成对协同运动+联合优化”范式**。其洞察在于：空间结构的本质是细胞间的相对关系（如距离、内积），因此动力学建模不应只关注单个细胞轨迹，而应关注**细胞对 (x,y) 的联合轨迹 (x_t,y_t)**。为此，作者定义“行进对” (travelling pair) 路径动作 $A(z,z')$ ，其最小化不仅考虑各自动能 ($\| \dot{x}_t \|^2 + \| \dot{y}_t \|^2$)，更显式惩罚相对位移变化（如 $\| x_t - y_t \|$ 或 (x_t, y_t) 的导数） [Paper] [Paper: PDF p. 4–5]。该动作泛函天然诱导出结构保持的动态：当 $\lambda \rightarrow \infty$ 时， $A(z,z')$ 退化为 GW-OT 成本；当 $\lambda=0$ 时退化为标准 OT [Paper] [Paper: PDF p. 5, D.1.1–D.1.2]。最终，通过将 $A(z,z')$ 嵌入静态 QOT 目标函数，并用流匹配学习其对应的联合速度场，实现了结构约束与连续动力学的无缝融合。

07 方法总览

TP-DATE是一个两阶段框架：(1) **静态QOT求解**：给定初始/终末分布 μ_0, μ_1 ，求解最优耦合 $\gamma \in \Pi(\mu_0, \mu_1)$ ，最小化 $QOTS(\mu_0, \mu_1) = \int \int A(z,z') \gamma(z) \gamma(z') dz dz'$ ，其中 $A(z,z')$ 为行进对路径动作 [Paper] [Paper: PDF p. 4, Eq. 9]；(2) **动态QOT流学习**：以 γ 为条件变量，采样 $z=(x_0, x_1), z'=(y_0, y_1)$ ，生成行进对路径 (x_t, y_t) ，并用流匹配训练神经网络 $v_\theta(x, t)$ 拟合其边际速度 $v_t(x) = \mathbb{E}[y_t | x_t = x] u'_t(x, y_t | z, z')$ [Paper] [Paper: PDF p. 7, Eq. 22]。关键创新在于： $A(z,z')$ 的设计使行进对路径能解析求解（如 C-Q 分解），且其诱导的速度场天然编码空间结构约束，无需额外正则化。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Travelling Pair Path Action $A(z,z')$	定义一对点 (x_0, x_1) 与 (y_0, y_1) 协同运动的最小作用量，含动能项与结构交互项 Φ	为动态QOT提供物理意义明确的泛函基础，使结构约束直接驱动动力学演化，而非仅影响端点匹配	Input: $z=(x_0, x_1), z'=(y_0, y_1)$; Output: scalar path action	Eq. 7–9, Prop. 4.2–4.3, Thm. 4.4 [Paper] [Paper: PDF p. 4–5]; analytic solution in A.3 [Paper] [Paper: PDF p. 15–16]	移除 Φ 项（即 $\lambda=0$ ）则退化为 OT-CFM，丧失空间结构保真能力 [Paper] [Paper: PDF p. 5, D.1.1]
Modality-Separated Lagrangian	将 L 分解为基因表达与空间坐标的独立项，并仅在空间项添加 Φ 交互项 ($\lambda_{\text{spatial}} > 0, \lambda_{\text{gene}} = 0$)	解耦不同模态的物理特性（表达变化快/空间变化慢），避免过强耦合导致优化困难，提升生物学可解释性	Input: $(x, s), (y, h), t$; Output: scalar L	Eq. 75–76 [Paper] [Paper: PDF p. 21]; ablation in Table 4 [Paper] [Paper: PDF p. 28]	若在表达空间也加 Φ ，可能导致表达轨迹过度平滑，损害基因动态细节 [Paper] [Paper: PDF p. 21]
Sparse KNN Coupling Solver	在求解静态QOT时，仅在 K 近邻图 E 上优化耦合 Γ ，大幅降低 $O(M^2 N^2)$ 复杂度	应对大规模空间转录组数据 ($>10^4$ 细胞) 的计算瓶颈，保证算法可扩展性	Input: cell clouds $\{X_i\}, \{Y_i\}$; Output: sparse $\Gamma \in \mathbb{R}^{M \times N}$	B.8.3 [Paper] [Paper: PDF p. 26–27]; Figs. 5–6 & Tables 5–6 [Paper] [Paper: PDF p. 29–30]	移除稀疏化 ($K=2000$) 在简单合成数据上性能略降，在真实数据上内存溢出 (CytoBridge) [Paper] [Paper: PDF p. 29, Fig. 5]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Velocity Decomposition ($\mathbf{b_t} + \mathbf{f_t}$)	将联合速度 $\mathbf{u^1_t(x,y)}$ 分解为自驱项 $\mathbf{b_t(x)}$ 与交互项 $\mathbf{f_t(x,y)}$ ，支持mean-field动力学模拟	提供可解释性： $\mathbf{b_t}$ 反映细胞固有行为， $\mathbf{f_t}$ 反映微环境影响；并支持NeuralODE式群体模拟	Input: $\mathbf{x,y}$; Output: $\mathbf{b_t(x), f_t(x,y)}$	Sec. 5.2, Eq. 18, 23 [Paper] [Paper: PDF p. 7]; Thm. 5.6 [Paper] [Paper: PDF p. 20]	移除分解则失去对交互机制的显式建模与模拟能力，退化为黑箱速度场 [Paper] [Paper: PDF p. 7]
Conditional Path Ablation (QOT + straight path)	使用相同QOT耦合 γ^* ，但替换为标准位移插值 $\mathbf{x_t=(1-t)x_0+tx_1}$ ，而非行进对路径	隔离验证行进对路径的贡献，排除性能提升仅来自更好耦合的可能	Input: $\gamma^*, (x_0,x_1)$; Output: straight path $\mathbf{x_t}$	Table 7 [Paper] [Paper: PDF p. 30]; C.1.3 [Paper] [Paper: PDF p. 28]	移除后所有指标下降（尤其Expression $\mathbf{W_2}$, SC-eMSE），证明行进对路径是关键增益来源 [Paper] [Paper: PDF p. 30, Table 7]

09 关键公式与符号

论文未给出单一主导公式，但核心是路径动作泛函 $\mathbf{A(z,z')}$ 及其诱导的QOT框架。关键符号与公式如下：

- $\mathbf{A(z,z')}$ ：行进对路径动作，定义为 $\mathbf{A(z,z')} = \inf_{\mathbf{x_t,y_t}} \int_0^1 \mathbf{L(t,x_t,y_t,\dot{x_t},\dot{y_t})} \, dt$ ，其中 $\mathbf{L = 1/2 \parallel \dot{x} \parallel^2 + 1/2 \parallel \dot{y} \parallel^2 + \lambda \Phi(x-y, \dot{x}-\dot{y})}$ [Eq. 12, Paper: PDF p. 5]。
- $\mathbf{QOTS(\mu_0,\mu_1)}$ ：静态QOT， $\mathbf{QOTS = \inf_{\gamma \in \Pi(\mu_0,\mu_1)} \int \int A(z,z') \gamma(z)\gamma(z') \, dzdz'}$ [Eq. 9, Paper: PDF p. 4]。
- **C-Q decomposition**：关键解析技巧，令 $\mathbf{c_t=(x_t+y_t)/2}$ （质心）， $\mathbf{q_t=y_t-x_t}$ （相对位移），则 $\mathbf{L = \parallel \dot{c_t} \parallel^2 + 1/4 \parallel \dot{q_t} \parallel^2 + \lambda \Phi(q_t,q_t)}$ [Eq. 13, Paper: PDF p. 5]。
- **Analytic solution for $\Phi=|d/dt \parallel q_t \parallel|^2$** ： $\mathbf{q_t}$ 的极坐标解为 $\mathbf{q_t = r_t(\cos \theta_t, \sin \theta_t)}$ ，其中 $\mathbf{r_t = \sqrt{[(1-t)^2 r_0^2 + t^2 r_1^2 + 2t(1-t)r_0 r_1 \cos(k\alpha)]}}$ ， $\mathbf{k=1/\sqrt{(1+4\lambda)}}$ [Eq. 46–47, Paper: PDF p. 16]。
- **SC-eMSE**：空间耦合表达MSE， $\mathbf{SC-eMSE(\rho,\rho') = (1/D_x) \int \parallel x-x' \parallel^2 \gamma(z,z') \, dzdz'}$ ，其中 γ 仅用空间坐标 $\mathbf{s}$ 拟合 [Eq. 80, Paper: PDF p. 24]。
- $\mathbf{\eta_{spatial}, \lambda_{spatial}}$ ：Lagrangian超参数，控制空间动能与交互强度的权重 [Eq. 75–76, Paper: PDF p. 21]。
- $\mathbf{K}$ ：稀疏KNN图的邻居数，控制耦合求解的计算开销 [B.8.3, Paper: PDF p. 26]。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Synthetic Rotation/Distractor (Table 1)	TP-DATE preserves spatial structure better than baselines under rigid rotation	Hold-one-out on 3-cell-type synthetic data; metrics: Spatial MSE, Pair distortion, Balanced fused W_2	TP-DATE achieves lowest errors (e.g., Spatial MSE: 0.02269 vs OT-CFM's 0.11015)	TP-DATE's travelling-pair dynamics inherently preserve pairwise distances during interpolation	TP-DATE generalizes to arbitrary non-rigid deformations (not tested)	[Paper] [Paper: PDF p. 8, Table 1]
Mouse Brain & ARTISTA (Table 2)	TP-DATE improves spatiotemporal dynamics reconstruction on real data	Hold-one-out on E14.5/E16.5→E15.5 & Day2/Day10→Day5; metrics: Spatial W_2 , Expression W_2 , SC-eMSE, Balanced fused W_2	TP-DATE outperforms all baselines on Mouse Brain & most metrics on ARTISTA (e.g., SC-eMSE: 0.878 vs stVCR's 1.468)	TP-DATE's structure-aware dynamics improve recovery of spatial gene expression patterns	TP-DATE is universally superior across all spatial transcriptomics datasets (only 2 tested)	[Paper] [Paper: PDF p. 8–9, Table 2]
Tumor 3D Reconstruction (Table 3)	TP-DATE enables accurate continuous 3D tissue reconstruction from serial sections	Interpolation along depth axis (subQ-3/subQ-5→subQ-4); same metrics as Table 2	TP-DATE achieves best Balanced fused W_2 (7.3748) and SC-eMSE (1.0459)	TP-DATE's dynamic QOT framework is applicable beyond temporal dynamics to spatial depth interpolation	TP-DATE scales to whole-organ 3D reconstruction (no large-scale test)	[Paper] [Paper: PDF p. 9, Table 3]
Conditional Path Ablation (Table 7)	Performance gain comes from travelling-pair paths, not just QOT coupling	Same QOT coupling γ^* as TP-DATE, but replace travelling-pair path with straight line interpolation	QOT+straight path consistently worse (e.g., Mouse Brain Expression W_2 : 6.458 vs TP-DATE's 6.410)	The travelling-pair conditional path is essential for TP-DATE's advantage	The QOT coupling itself is inferior to FGW-OT coupling (not compared)	[Paper] [Paper: PDF p. 30, Table 7]
K Ablation (Tables 5–6)	Sparse KNN maintains accuracy while improving scalability	Vary K from 64 to 2000 on Distractor/Tumor; measure Spatial MSE/ W_2	Performance stable across K (e.g., Distractor Spatial MSE unchanged for K=64–1024); memory/time scale linearly with K	Sparse KNN is robust and enables scaling to large datasets	K=64 is optimal for all datasets (performance identical, but no efficiency gain shown)	[Paper] [Paper: PDF p. 28–29, Tables 5–6, Figs. 5–6]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Hyperparameter Sensitivity (Table 4)	TP-DATE is robust to $(\eta_{\text{spatial}}, \lambda_{\text{spatial}})$ choice	Grid search on ARTISTA; vary $\eta_{\text{spatial}}, \lambda_{\text{spatial}}$ over 5 orders of magnitude	Best performance at (100, 0.01); most settings within $\pm 5\%$ of best	TP-DATE does not require meticulous hyperparameter tuning	(100, 0.01) is optimal for all datasets (only ARTISTA tested)	[Paper] [Paper: PDF p. 28, Table 4]

11 对结论的正确理解

论文结论需严格限定于其证据范围：(1) **TP-DATE**确实在所测试的合成与真实空间转录组数据上，优于对比方法，尤其在空间结构保真度（Spatial MSE/ W_2 ）和空间耦合表达重建（SC-eMSE）上；(2) 其优势源于**行进对路径动作 $A(z,z')$** 的设计与**流匹配实现**，而非单纯耦合质量提升（Table 7证实）；(3) **动态QOT理论**提供了**OT、GW-OT、IGW-OT的统一动态视角**，但其等价性仅为上界（ $QOTS \geq QOTBB$ ），并非严格相等 [Paper] [Paper: PDF p. 4, A.1, F]；(4) **“better preserves spatial structure”**是**定量结论**（Table 1–3中Spatial MSE/ W_2 更低），非主观描述；(5) 所有实验均为“hold-one-out”，即仅用两个端点训练，预测中间点，**不涉及多时间点联合建模或长期外推**。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Computational cost of static QOT solver	Frank-Wolfe + Sinkhorn on full coupling has $O(M^2N^2)$ complexity, prohibitive for large N, M	Use sparse KNN graph (E) to restrict coupling support, reducing complexity to $O(RK(M+N))$	[Paper] [Paper: PDF p. 26–27, B.8.3]
Theoretical gap: $QOTS \geq QOTBB$, not equality	Static QOT minimizes an upper bound of the true BB-form action, not the action itself	Acknowledge it's "essentially hard to improve" and focus on practical utility of the tractable upper bound	[Paper] [Paper: PDF p. 39, F.1]

Limitation	Specific manifestation	Future direction proposed by authors	Source			
Lack of unbalanced dynamics modeling	TP-DATE assumes mass conservation ($\rho_0 \rightarrow \rho_1$), cannot model cell proliferation/apoptosis	Extend dynamic QOT framework to unbalanced setting, e.g., incorporating WFR-like growth terms	[Paper] [Paper: PDF p. 37, D.7]			
1D case pathology	For GW-OT and IGW-OT, the analytic path action $A(z, z')$ does not reduce to the correct static cost when dimension $d=1$	Note the requirement $d \geq 2$ for equivalence, and discuss geometric reasons (impossibility of continuous reflection in 1D)	[Paper] [Paper: PDF p. 34–35, D.1.4, D.2.1]			
Velocity decomposition identifiability	Conditional velocity decomposition $u^1_t(x, y)$	$z, z') = b_t(x \setminus$	$z, z') + f_t(x, y \setminus$	$z, z')$ does not guarantee marginal decomposition $u^1_t(x, y) = b_t(x) + f_t(x, y)$ without extra condition	Propose "conditional mean-independence" condition (Eq. 124) as a sufficient gauge for learnability	[Paper] [Paper: PDF p. 38–39, E]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis		
Markovian projection vs true endpoint- conditioned process	TP-DATE learns a Markovian velocity field $v_t(x)$, but the underlying dynamic QOT construction is non-Markovian (depends on future state x_1). The learned flow matches $\pi_t(x,y)$ but may misrepresent pathwise properties like acceleration or curvature.	For perturbation prediction or causal inference, non-Markovianity (memory of endpoints) may be biologically essential; a Markov approximation could blur transient states.	Compare TP-DATE's predicted trajectories against ground-truth synthetic dynamics with known non-Markovian features (e.g., oscillatory motion), measuring higher-order derivatives (jerk, snap) error.	[Paper] [Paper: PDF p. 19, A.8 Remark]		
Φ -term design prioritizes distance preservation over topology	The chosen $\Phi =$	$d/dt \parallel q_t \parallel$	2 penalizes changes in <i>magnitude</i> of relative displacement, but not changes in <i>topological relations</i> (e.g., crossing events, knotting in 3D space).	In developing tissues, topological constraints (e.g., cell layer integrity, lumen formation) may be more fundamental than pairwise distances. Current Φ cannot enforce them.	Design a topological Φ (e.g., based on persistent homology of point cloud $\{x_t, y_t\}$) and benchmark on synthetic data where topology changes (e.g., merging/splitting clusters).	[Paper] [Paper: PDF p. 5, 33; no topological Φ discussed]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
SC-eMSE metric conflates alignment and expression error	SC-eMSE uses spatial OT coupling $\gamma(s,s')$ to weight expression error $\ x-x'\ ^2$. If spatial alignment is poor, SC-eMSE may be low simply because γ assigns mass to wrong pairs, masking true expression mismatch.	This could falsely suggest good expression reconstruction when spatial misalignment is severe, undermining the metric's validity for evaluating joint fidelity.	Compute SC-eMSE using both the predicted coupling γ_{pred} and the ground-truth coupling γ_{gt} (if available in synthetic data), and compare discrepancies.	[Paper] [Paper: PDF p. 24, B.6.3]
Sparse KNN may fail on highly heterogeneous tissues	KNN assumes local homogeneity, but tumor or regenerating brain tissues may have sharp boundaries between niches. A cell's true transport partner might be distant across a boundary, violating KNN assumption.	This could lead to suboptimal couplings and degraded performance in complex real tissues, limiting clinical applicability.	Test TP-DATE on a synthetic dataset with explicit tissue compartments and inter-compartment transport, varying K and measuring coupling accuracy within/between compartments.	[Paper] [Paper: PDF p. 26, B.8.3]
No ablation on velocity decomposition utility	While decomposition is theoretically proposed (Sec. 5.2, E), no experiment validates its biological interpretability (e.g., linking b_t to cell-intrinsic programs, f_t to niche signals).	Without empirical validation, the decomposition remains a mathematical convenience, not a biological insight generator.	On Mouse Brain data, correlate learned $b_t(x)$ with known cell-type markers and $f_t(x,y)$ with spatial proximity to specific niche types (e.g., vasculature), testing enrichment.	[Paper] [Paper: PDF p. 7, 38–39]

14 学到的知识

- **动态结构建模的新范式**：结构感知不应止于静态对齐，而应通过“行进对”路径动作 ($A(z, z')$) 将约束直接注入动力学方程，这比在耦合或损失函数中添加正则项更根本。
- **C-Q分解是处理高维交互的关键**：将联合运动分解为质心(c_t)与相对位移(q_t)，使原本耦合的Lagrangian解耦，从而获得解析解（如 q_t 的极坐标形式），规避了高维数值优化灾难。
- **流匹配的扩展边界**：标准流匹配处理独立粒子，TP-DATE通过在二维粒子空间(X^2)上定义联合流 $\pi_t(x, y)$ ，并利用边际化定理 (Thm. 5.1–5.2)，成功将流匹配拓展至交互系统，为多智能体/多细胞建模开辟新路。
- **稀疏化是大规模OT的必由之路**：KNN图不仅是工程技巧，更是理论可行性的保障——它将 $O(M^2N^2)$ 问题转化为 $O(K(M+N))$ ，且实验证明在合理 K 下精度无损，为临床级数据应用铺平道路。
- **指标设计反映科学意图**：SC-eMSE的构造（先空间对齐，再评估表达）精准对应“空间位置正确性是表达解读的前提”这一生物学信条，比单纯Wasserstein距离更具领域意义。

15 与既有知识的连接

- **候选连接/方法论连接**：TP-DATE的“行进对”思想与single-cell foundation models中的pairwise contrastive learning（如scGPT的cell-cell attention）存在方法论共鸣，二者均强调细胞间关系而非孤立表征；但TP-DATE是确定性动力学，而foundation models是概率生成，尚未建立形式化桥梁。
- **候选连接/方法论连接**：其velocity decomposition ($b_t + f_t$) 与multi-omics中常见的“cell-intrinsic + microenvironment-extrinsic”建模范式一致，但TP-DATE的 f_t 是空间坐标显式函数，而multi-omics分解常基于隐变量，如何将后者融入TP-DATE框架是开放问题。
- **候选连接/方法论连接**：C-Q分解与graph neural networks中的message passing有相似性： c_t 类似全局聚合， q_t 类似边消息；但TP-DATE的 q_t 是连续轨迹，GNN是离散迭代，如何将GNN的归纳偏置注入TP-DATE的 q_t 动力学是潜在方向。
- **弱连接/方法论连接**：与perturbation prediction任务相关，因TP-DATE建模的是“未扰动”下的自然轨迹，其学到的 f_t 可视为微环境扰动响应的基线；但论文未设计perturbation实验（如knockout模拟），故为弱连接。
- **弱连接/方法论连接**：与cross-modal alignment（如spatial + scRNA-seq）存在概念关联，因TP-DATE的modality-separated Lagrangian天然支持多模态，但论文仅用于同一细胞的表达/空间，未跨样本/跨模态对齐，故为弱连接。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Topo-TP-DATE

originating limitation/observation: [Analysis] TP-DATE's Φ -term preserves distances but not topology (Section 13). **core hypothesis**: Replacing $\Phi = |d/dt \parallel q_t \parallel|^2$ with a topological penalty Φ_{top} based on persistent homology (e.g., bottleneck distance between PH of $\{x_t, y_t\}$ and $\{x_o, y_o\}$) will better preserve tissue-level structures (e.g., lumens, layers) during interpolation. **delta from paper**: Uses topological summary statistics instead of Euclidean norm; requires differentiable PH computation (e.g., via soft-persistence). **initial method**: Implement soft-PH loss; train TP-DATE on synthetic data with known topological transitions (e.g., sphere $\rightarrow$ torus deformation). **validation**: Quantify topological fidelity via

PH distance between predicted/ground-truth point clouds at intermediate time; compare to standard TP-DATE. **failure modes:** Soft-PH gradients may be noisy; topological features may be too coarse-grained for single-cell resolution. **innovation status:** unverified

- **name:** Perturb-TP-DATE

originating limitation/observation: Author limitation: lacks unbalanced dynamics (Section 12); user interest: perturbation prediction. **core hypothesis:** Augmenting TP-DATE's Lagrangian with a perturbation-aware term Φ_{pert} that depends on external intervention signals (e.g., drug dose d) will enable counterfactual trajectory prediction under perturbations. **delta from paper:** Introduces exogenous control variable d into $L(t, x, y, \dot{x}, \dot{y}; d)$; modifies velocity decomposition to include perturbation response $f_t^{\text{pert}}(x, y, d)$. **initial method:** Extend velocity net v_{θ} to take (x, t, d) ; define $\Phi_{\text{pert}} = \lambda_{\text{pert}} |d/dt \langle x_t, d \rangle|^2$; train on synthetic perturbed rotation data. **validation:** Predict trajectories under unseen d ; measure error in perturbed state vs ground truth; compare to baseline fine-tuning. **failure modes:** Requires paired perturbed/unperturbed data; d may interact non-linearly with intrinsic dynamics. **innovation status:** unverified

- **name:** Graph-TP-DATE

originating limitation/observation: Weak connection to GNNs (Section 15); sparse KNN is ad-hoc graph. **core hypothesis:** Learning the interaction graph E (instead of fixing KNN) end-to-end, where edge weights encode functional interaction strength, will yield more biologically meaningful and adaptive spatial constraints. **delta from paper:** Replaces fixed KNN graph with learnable adjacency matrix $A \in \mathbb{R}^{M \times N}$, optimized jointly with coupling Γ . **initial method:** Parameterize A via GNN on initial cell features; use A to mask Γ ($\Gamma_{ij} = 0$ if $A_{ij} < \tau$); optimize A, Γ, v_{θ} jointly. **validation:** On Mouse Brain, check if learned A correlates with known spatial niches (e.g., high A within cortical layers); ablate A -learning. **failure modes:** Increased parameters may cause overfitting; graph learning may ignore long-range interactions crucial in development. **innovation status:** unverified

- **name:** Cross-Modal TP-DATE

originating limitation/observation: Weak connection to cross-modal alignment (Section 15); modality separation is internal. **core hypothesis:** Extending the modality-separated Lagrangian to handle *heterogeneous* modalities (e.g., spatial coordinates s and scRNA-seq expression x from *different* cells) will enable direct alignment of spatial and dissociated transcriptomic data. **delta from paper:** Defines $L = L_{\text{spatial}}(s, s', s, \dot{s}) + L_{\text{expr}}(x, x', x, \dot{x})$ where s, s' are from spatial data, x, x' from scRNA-seq; couples them via shared latent z . **initial method:** Use shared encoder to map s, x to z ; define $A(z, z')$ on z -space; train on paired spatial/scRNA-seq data (e.g., STARmap + 10x). **validation:** Evaluate alignment quality via mutual nearest neighbor (MNN) recall; compare to Seurat/SCALEX. **failure modes:** Modality gap may prevent meaningful z -space coupling; requires careful normalization across platforms. **innovation status:** unverified