

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Authors	Youngmin Chung, Ji Hun Ha, Andrew H. Song, et al.	[Paper] [Paper: PDF p. 1]
Venue	arXiv (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-05	[Paper] [Paper: PDF p. 1]
Core contribution	A standardized, large-scale benchmark (STP-BENCH) for virtual ST models, with unified PFM encoding, multi-granularity evaluation (gene/gene-set/cell-type/domain), and robustness analysis across cross-institution/tissue/platform shifts	[Paper] [Paper: PDF p. 2–4], [Paper] [Paper: PDF p. 5 Fig.1], [Paper] [Paper: PDF p. 18–19]
Key datasets	STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium+Xenium); STP-BENCH-EXTERNAL (185,831 spots, same 6 cancers, independent sources)	[Paper] [Paper: PDF p. 4], [Figure 1b], [Paper] [Paper: PDF p. 21]
Evaluated models	21 models: 14 regression-based, 4 bi-modal retrieval, 3 generative	[Paper] [Paper: PDF p. 6], [Figure 1c], [Paper] [Paper: PDF p. 22]
Primary encoder	UNiv2 pathology foundation model (PFM), used as default where architecturally compatible	[Paper] [Paper: PDF p. 7], [Figure 2a], [Paper] [Paper: PDF p. 22–23]
Main metrics	Pearson Correlation Coefficient (PCC) [Equation 1], Mean Absolute Error (MAE) [Equation 2], SSIM	[Paper] [Paper: PDF p. 31–32], [Paper] [Paper: PDF p. 7]
Code & data	Publicly released at https://github.com/NEXGEM/STP-Bench and Hugging Face (https://huggingface.co/datasets/nexgem/STP-Bench)	[Paper] [Paper: PDF p. 37]

02 一句话总结

该论文构建了STP-BENCH——首个统一、大规模、多维度的虚拟空间转录组（virtual ST）系统性基准，覆盖6种癌症、2种平台（Visium/Xenium）、超79万spots；它通过强制统一病理基础模型（UNiv2）作为图像编码器，剥离了编码器性能对架构评估的干扰，揭示多数复杂模型未超越线性探针基线；进一步从基因级可预测性、通路级功能保真度、细胞类型丰度推断、空间结构识别及跨域泛化能力五个层面，系统刻画了当前方法的能力边界与根本瓶颈。其核心价值在于将“benchmarking”从零散报告升维为可控实验范式，为single-cell foundation models、spatial transcriptomics和multi-omics建模提供了可复现的评估基础设施。

03 研究问题

论文直面虚拟ST领域长期存在的**评估失焦问题**：当不同研究使用异构数据集、私有训练流程、混杂的图像编码器（如ResNet50 vs. UNiv1）时，模型性能比较失去可比性。作者追问：若剥离图像编码器差异，真实架构创新是否仍具优势？哪些基因/通路/生物学粒度能被可靠恢复？模型在真实临床场景（跨机构、跨组织、跨平台）中是否鲁棒？这些问题无法由单个模型论文回答，必须通过受控的系统性基准实验来检验。

04 研究背景与发展路径

虚拟ST技术演进呈现“三支并行”格局：（1）**回归类**（如ST-Net→TRIPLEX→DeepSpot），从局部patch预测扩展至多尺度上下文融合；（2）**双模态对齐类**（如BLEEP→STco→mclSTExp），借鉴CLIP范式学习形态-表达联合嵌入空间；（3）**生成类**（如STFlow→Stem），用扩散/流匹配建模表达分布而非点估计。但评估始终滞后：Wang et al. [50] 保留原生编码器导致架构与编码器效应混淆；HEST-1K [51] 仅测试PFM嵌入与简单回归器的关联，未覆盖完整模型族。STP-BENCH正是对这一断裂的修复——它不提出新模型，而是构建一个“控制变量”的评估实验室，将PFM作为公共接口，让所有模型在相同输入表征上竞争，从而锚定真正可迁移的架构知识。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
评估不可比	模型排名随所用图像编码器剧烈波动（如CFANet从第16跃至第6）	原有工作未标准化编码器，而PFM性能主导下游表现	[Paper] [Paper: PDF p. 9], [Figure 2b], [Paper] [Paper: PDF p. 18]
生物学解释性缺失	报告平均PCC掩盖基因级差异：HMHVGs (PCC≈0.4) 与TME marker genes (PCC≈0.2) 预测难度悬殊	数据稀疏性（尤其Visium低计数）与形态-表达耦合强度共同限制	[Paper] [Paper: PDF p. 9–10], [Figure 2a,c,d], [Paper] [Paper: PDF p. 10 box plots]
下游效用验证空白	虚拟ST是否支持Cell2location或SpaGCN等真实分析工具？现有工作未检验	仅spot-level指标无法保证生物学结构保真；需在细胞组成、空间域等粒度验证	[Paper] [Paper: PDF p. 14], [Figure 4a–c], [Paper] [Paper: PDF p. 19]
鲁棒性未经检验	模型在跨机构（batch effect）、跨组织（morphology shift）、跨平台（Visium→Xenium）下性能崩溃或不稳定	形态-表达映射高度组织特异性；平台间技术差异（如Xenium更高灵敏度）引入非平稳性	[Paper] [Paper: PDF p. 17], [Figure 5a–b], [Paper] [Paper: PDF p. 19]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
数据扩展悖论	增加训练数据量（intra-cohort）收益递减；跨癌种聚合（inter-cohort）常致负迁移	组织特异性形态特征主导预测，简单拼接破坏特征分布一致性	[Paper] [Paper: PDF p. 18], [Figure 5c–d], [Paper] [Paper: PDF p. 19]

06 核心思想

论文的核心思想是：**虚拟ST的评估必须解耦“形态表征力”与“架构推理力”，并将评价尺度从统计指标延伸至生物学效用与现实鲁棒性。**它拒绝将高PCC等同于高价值，转而主张：（1）UNiv2等PFM是当前形态理解的“天花板”，模型应在此基础上证明增量；（2）基因级可预测性存在普适排序（e.g., COL1A1易预测，CD19难预测），反映形态信息固有限制；（3）真正的进步体现在能否提升对空间结构敏感通路（如ECM remodeling, T-cell activation）的恢复能力，而非平均分提升；（4）鲁棒性不是附加项，而是部署前提——跨组织泛化失败暴露了当前模型对组织特异性先验的过度依赖。

07 方法总览

STP-BENCH是一个三层评估框架：（1）**统一表征层**：强制使用UNiv2（或Virchow2等）提取spot级H&E patch嵌入，消除编码器偏差；（2）**多粒度验证层**：除spot-level PCC/MAE/SSIM外，新增gene-set（singscore）、cell-type abundance（Cell2location）、spatial domain（SpaGCN+ARI）三级验证；（3）**鲁棒性压力测试层**：设计Cross-Institution（同癌种不同医院）、Cross-Tissue（LUAD→BRCA）、Cross-Platform（Visium→Xenium）三类泛化任务，并量化generalization gap。所有21模型均按此协议重实现，确保比较公平。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
UNiv2 PFM Encoder	Extracts morphology-aware embeddings from 224×224 H&E patches	To isolate architectural contribution by standardizing input representation; UNiv2 outperforms ResNet50/CTransPath on HMMVG+marker genes	Input: H&E patch; Output: d-dim vector (d=1024)	[Paper] [Paper: PDF p. 10], [Figure 2e], [Paper] [Paper: PDF p. 22–23]	Severe ranking inversion (e.g., CFANet drops from #6 to #16) and ~0.2 PCC drop for most models [Figure 2b]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Gene Set Scoring (singscore)	Computes per-spot activity score for GO Biological Process terms via rank-based aggregation	To test if gene-level predictions preserve functional coherence beyond individual genes	Input: spot×gene matrix; Output: spot×gene_set matrix	[Paper] [Paper: PDF p. 13], [Figure 3c–e], [Paper] [Paper: PDF p. 35]	Loss of biological interpretability: TRIPLEX/DeepSpot ’ s advantage on immune/stromal pathways would be invisible [Figure 3e]
Cell2location Deconvolution	Estimates spatial cell-type abundances from expression matrix using scRNA-seq reference	To validate if virtual ST supports downstream cellular inference, not just gene recovery	Input: spot×gene matrix + scRNA ref; Output: spot×cell_type matrix	[Paper] [Paper: PDF p. 14], [Figure 4a], [Paper] [Paper: PDF p. 35]	Failure to detect architecture superiority: TRIPLEX/DeepSpot lead in epithelial/T-cell abundance correlation, but linear probe fails on rare populations (plasma/mast cells) [Figure 4a]
SpaGCN Spatial Clustering	Identifies spatial domains via graph neural network on expression+coordinates	To assess preservation of tissue-level spatial organization	Input: spot×gene matrix + coordinates; Output: domain labels per spot	[Paper] [Paper: PDF p. 14], [Figure 4b–c], [Paper] [Paper: PDF p. 36]	Collapse of spatial structure fidelity: STFlow shows lowest ARI, consistent with its weak gene-level PCC [Figure 4c]
Cross-Tissue Generalization Protocol	Trains on LUAD-Visium, tests on BRCA-Visium (or vice versa)	To stress-test morphological generalizability beyond technical batch effects	Input: train set (cancer A), test set (cancer B); Output: PCC gap	[Paper] [Paper: PDF p. 17], [Figure 5a–b], [Paper] [Paper: PDF p. 19]	Masking of tissue-specificity bottleneck: Cross-tissue gap (−0.2 to −0.35) is 3× larger than cross-institution gap, revealing fundamental limitation [Figure 5b middle]

09 关键公式与符号

论文明确给出两个核心公式：

- **Equation 1** ([Paper] [Paper: PDF p. 31])：Pearson Correlation Coefficient (PCC) for gene *g* in section *s*:

$$\text{PCC}_{g,s} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$$
 其中 $\hat{y}_{i,g}, y_{i,g}$ 为 spot i 上 gene g 的预测与真实 log-normalized 表达值; $\bar{\hat{y}}_g, \bar{y}_g$ 为其均值。PCC 是全文主指标, 用于 gene-level、section-level、dataset-level 逐级聚合。

- **Equation 2** ([Paper] [Paper: PDF p. 32]): Mean Absolute Error (MAE) for gene g in section s :

$$\text{MAE}_{g,s} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$$
 MAE 在 $\log(1+x)$ -transformed 空间计算, 反映绝对误差大小, 与 PCC 互补。

其他关键符号:

- **HMHVG**: High-Mean Highly-Variable Genes (200 genes selected by joint rank-sum of mean & std) [Paper] [Paper: PDF p. 33]
- **TME markers**: 16 marker genes (e.g., CD3E, ACTA2, PDCD1) covering epithelial/stromal/immune lineages [Paper] [Paper: PDF p. 7, 33]
- **STP-BENCH-INTERNAL/EXTERNAL**: Internal training/validation cohort (609k spots) vs. external test cohort (186k spots), strictly disjoint [Paper] [Paper: PDF p. 4, 21]
- **PCC gap**: External PCC – Internal PCC, quantifying generalization degradation [Figure 5b]
- **singscore**: Rank-based gene set scoring method used for functional analysis [Paper] [Paper: PDF p. 13, 35]

无其他可核验公式; 所有模型架构细节见 Online Methods, 但未以公式形式呈现。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
UNlv2 vs Native encoders	Standardizing encoder reshapes model rankings	Compare PCC of 21 models using their original encoder vs. UNlv2 on STP-BENCH-INTERNAL (HMHVG+markers)	CFANet jumps from #16 to #6; many w/o PFM models fall below linear probe baseline	Encoder choice dominates reported architectural gains; prior comparisons are confounded	UNlv2 is universally optimal — Virchow2/H-Optimus1 show comparable performance [Figure 2e]	[Paper] [Paper: PDF p. 9], [Figure 2b], [Paper] [Paper: PDF p. 10]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Gene-level predictability stratification	Genes exhibit universal predictability ranking across models	Compute PCC per gene for 20 models; bin genes into 5 quantiles by mean PCC; compare model rankings within bins	Rankings stable across all bins (e.g., TRIPLEX/DeepSpot top in "Very High" and "Medium"); Kruskal-Wallis $p < 1e-12$ for expression-level effect	Predictability is gene-intrinsic, not model-dependent; morphology-expression coupling strength is primary constraint	All genes are equally predictable — low-expression genes (e.g., CD19) consistently underperform [Figure 2c-d, 38]	[Paper] [Paper: PDF p. 9], [Figure 2c-d], [Extended Data Fig.1]
Multi-scale models on stromal/immune genes	Architectures integrating multi-scale context gain on spatially structured programs	Select genes with $\Delta PCC \geq 0.1$ over linear probe & $PCC \geq 0.4$; manually annotate functional categories	Top gains for COL1A1/COL3A1 (stromal), LAG3/IGKC (immune), SFTPC (epithelial); TRIPLEX/DeepSpot dominate	Multi-scale reasoning (neighbor/global branches) is necessary for genes requiring meso-macro scale morphology	Single-scale models are useless — some (e.g., EGN) still beat baseline marginally [Figure 3b]	[Paper] [Paper: PDF p. 11–13], [Figure 3b]
Cell2location on virtual ST	Virtual ST profiles support cell-type deconvolution	Apply Cell2location to ground-truth vs. predicted matrices (6 models $\times$ 3 cohorts); compute PCC per cell type	TRIPLEX/DeepSpot achieve highest avg PCC; malignant epithelial/T-cells well-recovered; plasma/mast cells poorly recovered	Gene-level accuracy translates to cellular inference; rare populations remain challenging	Virtual ST enables clinical-grade deconvolution — performance on rare cells is near-random [Figure 4a]	[Paper] [Paper: PDF p. 14], [Figure 4a], [Paper] [Paper: PDF p. 35]
Cross-tissue generalization	Morphology-to-expression mapping is highly tissue-specific	Train on NCCHE-LUAD-Visium, test on WUSTL-BRCA-Visium; compute PCC gap	Gap = -0.20 to -0.35 ; Spearman $\rho = 0.876$ for internal vs external ranking preservation	Architectural superiority generalizes, but absolute performance plummets due to tissue heterogeneity	Cross-tissue transfer is feasible with fine-tuning — no such experiment performed	[Paper] [Paper: PDF p. 17], [Figure 5a–b middle], [Paper] [Paper: PDF p. 19]

11 对结论的正确理解

论文结论不可简化为“现有模型都不行”，而应精确理解为：（1）在UNiv2统一表征下，多数模型的架构增益有限且高度条件依赖——TRIPLEX/DeepSpot仅在特定基因（stromal/immune）、特定平台（Xenium高计数）、特定下游任务（domain identification）上稳定胜出；（2）预测瓶颈本质是生物学的，而非纯工程的：HMVGs与marker genes的PCC差距（0.4 vs 0.2）主要源于Visium数据稀疏性，而非模型缺陷；当Xenium提供更高计数时，两者PCC均升至0.58+ [Figure 2c]；（3）鲁棒性失效揭示了根本假设冲突：当前模型隐含“形态-表达映射跨组织通用”，但跨组织泛化失败证明该映射是组织特异的，需新范式（如tissue-aware

adaptation); (4) **STP-BENCH本身是方法论贡献**：它定义了虚拟ST评估的黄金标准——必须包含multi-granularity validation与cross-domain stress testing，否则任何PCC报告都缺乏临床意义。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer/tissue scope	STP-BENCH covers only 6 cancer types and 2 platforms (Visium/Xenium), missing rarer cancers and emerging modalities (e.g., Stereo-seq)	Extend benchmark to additional tumor types, tissue contexts, and sequencing platforms for broader generalizability	[Paper] [Paper: PDF p. 20]
Restricted gene panel	Analyses focus on HMHVGs (200 genes) and 16 TME markers; lowly expressed or functionally diverse genes not systematically evaluated	Systematic investigation of low-expression genes and broader functional gene sets remains an open direction	[Paper] [Paper: PDF p. 20]
Spot-level resolution only	Evaluation is at Visium/Xenium pseudo-spot level (aggregating multiple cells), not single-cell resolution	Future benchmarking efforts should extend principles to single-cell ST datasets and virtual ST models as they become available	[Paper] [Paper: PDF p. 20]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
UNlv2 as “ground truth” encoder may mask modality-specific biases	UNlv2 is trained on generic H&E WSIs; its features might underrepresent cancer-specific morphologies (e.g., necrosis, mitotic figures) critical for certain genes	If UNlv2 misses cancer-relevant features, even perfect architectures would fail, falsely attributing failure to model design	Train cancer-type-specific PFMs (e.g., LUAD-UNlv2) and re-run STP-BENCH; compare ranking stability	[Paper] [Paper: PDF p. 10] notes UNlv2/Virchow2/H-Optimus1 perform similarly, but all are generalist PFMs
singscore-based gene set analysis ignores gene-gene correlations	singscore uses rank-based averaging, discarding co-expression structure; a model could recover ranks but miss functional modules requiring covariance	Overestimates functional fidelity: high singscore PCC doesn’t guarantee recovered pathways behave coherently in downstream perturbation simulations	Replace singscore with PCA-based pathway scores or GSEA-like enrichment; correlate pathway loadings between true/predicted matrices	[Paper] [Paper: PDF p. 13] states singscore is "well suited for efficient computation", but doesn't validate its biological fidelity vs. correlation-aware methods

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Cross-platform (Visium→Xenium) "improvement" may reflect data quality, not model capability	Figure 5b right shows some models have positive gaps; this likely stems from Xenium's higher sensitivity (more transcripts), not better generalization	Misleadingly suggests models bridge platform gaps, when in reality they merely benefit from richer targets	Control for transcript count: subsample Xenium to Visium-level depth and re-evaluate; or use spike-in normalized metrics	[Paper] [Paper: PDF p. 10] explicitly links prediction quality to "basal gene expression levels" and "transcript detection quality"
Negative transfer in inter-cohort scaling assumes homogeneous mixing	Figure 5d shows BRCA+LUAD+PRAD hurts BRCA performance; but this assumes naive concatenation, not domain-adaptive weighting	Overlooks viable solutions: domain-aware sampling or adversarial domain alignment could mitigate negative transfer	Implement domain classifier-guided loss weighting during inter-cohort training; compare to naive mixing on STP-BENCH-EXTERNAL	[Paper] [Paper: PDF p. 19] calls for "domain-adaptive or tissue-aware learning strategies" but doesn't test any

14 学到的知识

- **评估即设计**：STP-BENCH证明，严谨的基准设计（统一编码器、多粒度验证、鲁棒性压力测试）本身就是对领域认知的深化，其价值不亚于新模型。
- **形态表征是瓶颈天花板**：UNiv2等PFM已逼近H&E图像蕴含的形态信息上限；后续创新必须聚焦于如何更高效地利用这些表征（如TRIPLEX的跨尺度融合），而非堆砌编码器。
- **基因可预测性存在普适谱系**：COL1A1（stromal）> CD3E（T-cell）> CD19（B-cell）的预测难度排序在所有模型和数据集中稳定，表明这是形态-表达耦合的固有属性，可指导靶向优化。
- **下游效用是终极标尺**：Cell2location和SpaGCN的性能与spot-level PCC强相关（Spearman=0.902），证实提升基因预测质量是解锁生物学价值的必要条件。
- **组织特异性是泛化核心障碍**：Cross-tissue gap（-0.35）远大于cross-institution gap（-0.10），说明解决跨组织泛化需重构模型先验（如引入组织类型嵌入），而非调优超参。

15 与既有知识的连接

- **候选连接/方法论连接**：STP-BENCH的“统一编码器+多粒度验证”范式，与single-cell foundation models（如scGPT、CellLM）的评估逻辑一致——均强调在固定表征上测试下游任务能力，而非端到端训练。但本文未引用或对比任何scFM工作，故为弱连接。
- **候选连接/方法论连接**：其跨平台（Visium↔Xenium）分析与spatial transcriptomics中multi-resolution integration（如SPATA、SpatialGLM）目标相通，均需处理不同分辨率/灵敏度数据的对齐，但本文未采用图神经网络（GNN）或几何深度学习技术，故为弱连接。
- **候选连接/方法论连接**：对multi-omics的启示在于：STP-BENCH揭示了“模态对齐”的脆弱性——当形态（H&E）与表达（ST）的耦合强度随组织变化时，简单对比学习（BLEEP）失效；这警示multi-omics对齐需显式建模模态间关系的条件性，而非全局对齐。

- **候选连接/方法论连接**: 其发现的“组织特异性瓶颈”直接关联biomedical AI中的domain generalization挑战; 论文提议的“tissue-aware learning”与现有医学AI的domain adaptation方法(如DANN、MMD)形成方法论呼应, 但未实证对比。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name**: Tissue-Aware Adapter for Cross-Tissue Virtual ST

originating limitation/observation: Cross-tissue generalization gap is severe (-0.35) and stems from tissue-specific morphology-expression mappings [Paper] [Paper: PDF p. 17, 19] **core hypothesis**: Injecting lightweight, tissue-type-specific adapters into UNiv2 encoder outputs can recalibrate morphology representations for each tissue, enabling knowledge transfer without full fine-tuning **delta from paper**: STP-BENCH identifies the problem but proposes no solution; this adds parameter-efficient adapters (LoRA-style) conditioned on tissue label **initial method**: For each tissue t , learn adapter $\$A_t\$$ that transforms UNiv2 embedding $\$z\$$: $\$z' = z + A_t(z)\$$. Train $\$A_t\$$ on tissue-specific data with frozen UNiv2 and TRIPLEX backbone **validation**: Test on STP-BENCH cross-tissue tasks (e.g., LUAD $\rightarrow$ BRCA); measure PCC gap reduction vs. baseline TRIPLEX **failure modes**: Adapter overfitting to small tissue cohorts; inability to generalize to unseen tissues **innovation status**: unverified

- **name**: SingScore-Guided Gene Selection for Virtual ST Training

originating limitation/observation: HMMVGs and marker genes show divergent predictability; current gene panels are static and ignore functional coherence [Paper] [Paper: PDF p. 7, 9] **core hypothesis**: Optimizing training loss to maximize singscore PCC on key pathways (e.g., T-cell activation) yields better downstream utility than maximizing average gene PCC **delta from paper**: STP-BENCH evaluates singscore post-hoc; this integrates it into training objective **initial method**: Replace MSE loss with hybrid loss: $\mathcal{L} = \lambda \cdot \text{MSE} + (1 - \lambda) \cdot (1 - \text{singscore_PCC})$. Optimize λ on validation set **validation**: Compare Cell2location PCC and SpaGCN ARI of models trained with hybrid vs. MSE loss on STP-BENCH-INTERNAL **failure modes**: Degraded performance on individual genes not in top pathways; increased training instability **innovation status**: unverified

- **name**: Graph-Augmented Spot Context for Sparse Marker Gene Prediction

originating limitation/observation: Marker genes (e.g., CD19) suffer from low counts in Visium, causing poor prediction; their spatial expression is highly correlated with neighbors [Paper] [Paper: PDF p. 10, Figure 2d] **core hypothesis**: Modeling spot-level expression as a graph signal (using spatial adjacency) improves prediction of sparse genes more than patch-level regression alone **delta from paper**: STP-BENCH uses spot-level features but not explicit graph structure for regression; this adds GNN layers to DeepSpot's neighbor branch **initial method**: Extend DeepSpot's neighbor branch with GraphSAGE layer over spatial ego-graph (6-hop Visium neighbors); fuse with target/sub-spot embeddings **validation**: Evaluate on Visium-based cohorts (NCCHE-LUAD-Visium, WUSTL-BRCA-Visium) for marker gene PCC; compare to original DeepSpot **failure modes**: Over-smoothing on sparse graphs; computational overhead for large cohorts **innovation status**: unverified

- **name**: Foundation Model Distillation for Lightweight Virtual ST

originating limitation/observation: UNiv2 is large (ViT-L); deploying TRIPLEX/DeepSpot with it is costly; STP-BENCH shows smaller PFMs (CTransPath) underperform [Figure 2e] **core hypothesis:** Distilling UNiv2' s morphology knowledge into a smaller student model (e.g., ViT-T) preserves most predictive power while enabling edge deployment **delta from paper:** STP-BENCH compares PFMs but doesn' t attempt distillation **initial method:** Train ViT-T student to mimic UNiv2' s patch embeddings on STP-BENCH-INTERNAL patches using MSE + KL divergence on attention maps **validation:** Plug distilled encoder into TRIPLEX; compare PCC on STP-BENCH-INTERNAL vs. UNiv2-TRIPLEX; measure latency/FLOPs **failure modes:** Distillation collapse losing fine-grained morphology; poor generalization to external cohorts **innovation status:** unverified