

Source coverage: Full paper

Extraction confidence: High

Locator mode: page-grounded

Primary analytical lens: methods/discovery

Secondary analytical lens: resource

Context verification: Paper-only

Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Rethinking Class Imbalance for Single-Cell Foundation Models: A Systematic Benchmark Across Architectures and Long-Tail Loss Functions	[Paper] [Paper: PDF p. 1]
Authors	Zeyu Dong, Jiahui Zhong	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (v1)	[Paper] [Paper: PDF p. 1]
URL	https://arxiv.org/abs/2609.23325	[Input metadata]
PDF URL	https://arxiv.org/pdf/2609.23325v1	[Input metadata]
Publication date	2026-09-22	[Input metadata]
Code availability	https://github.com/jz890/sc-imbalance (stated in [Paper] [Paper: PDF p. 7])	[Paper] [Paper: PDF p. 7]
Data availability	Not explicitly stated; datasets named (MS, Zheng68K, Pancreas) but no URLs or accession IDs provided	Not assessable from supplied material
Pretrained models	scGPT (Cui et al. 2024), scBERT (Yang et al. 2022), Geneformer (Theodoris et al. 2023)	[Paper] [Paper: PDF p. 2–3]
Datasets	Multiple Sclerosis (MS), Zheng68K, human Pancreas	[Paper] [Paper: PDF p. 2–3]
Loss functions benchmarked	Cross-entropy (CE), weighted CE, class-balanced loss (Cui et al. 2019), focal loss (Lin et al. 2017), LDAM (Cao et al. 2019), logit-adjusted softmax (Menon et al. 2021)	[Paper] [Paper: PDF p. 3]
Total runs	162 (3 backbones × 3 datasets × 6 losses × 3 seeds)	[Paper] [Paper: PDF p. 1]

02 一句话总结

该论文系统评估了六种长尾损失函数在三种单细胞基础模型（scGPT/scBERT/Geneformer）和三个真实数据集（MS/ Zheng68K/ Pancreas）上的表现，揭示出“罕见细胞类型失败”并非单一现象，而是分裂为两类可诊断机制：一类是**损失敏感型**（loss-sensitive），其性能可通过重加权类损失显著提升；另一类是**严重纠缠型**（severely entangled），即使更换所有损失函数与架构也无法恢复，根源在于训练样本绝对数量过少（如仅3个细胞）与嵌入空间几何结构坍塌（如NC1异常、邻域吸收）。论文由此提出首个可复用的长尾基准框架，并给出基于嵌入几何（如NC1、最近邻混淆模式）的事前诊断指南——而非盲目尝试损失函数。

03 研究问题

论文直面一个被高精度指标掩盖的关键矛盾：单细胞基础模型在细胞类型分类任务中报告高达97.5%的总体准确率，但这一数字无法反映其对**疾病相关罕见细胞亚群**（如MS中的oligodendrocyte C、phagocyte）的系统性失效 [Paper] [Paper: PDF p. 1]。作者追问：这种失效是否源于预训练偏差？能否通过损失函数层面的干预统一解决？若不能，其边界与机制是什么？进一步，哪些损失函数最稳健？其有效性是否依赖于特定架构或数据集结构？这些问题共同指向一个核心科学判断：**长尾问题在单细胞基础模型中不是同质化挑战，而需按失效机制分层建模与干预。**

04 研究背景与发展路径

单细胞基础模型（scGPT等）已成为细胞类型注释默认主干，但已有研究（Alsabbagh et al. 2023；Naziri et al. 2025）已指出其在罕见/疾病亚群上性能骤降，且该问题无法被采样策略（如随机过采样）完全解决 [Paper] [Paper: PDF p. 1-2]。现有长尾学习方法（如focal loss、LDAM）多在CV领域验证，其在单细胞语境下的跨架构鲁棒性、与预训练表示的耦合关系、以及对生物特异性失效（如病理亚群转录相似性）的适配性均未系统检验 [Paper] [Paper: PDF p. 1-2]。本文承接Alsabbagh等人的采样轴工作，将研究维度推进至**损失函数轴**，并首次引入**嵌入几何诊断**（neural collapse, nearest-neighbor absorption）作为失效归因工具，从而将经验性调参升级为机制驱动的干预设计。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Aggregated metrics mask rare-class failure	Overall accuracy > Macro-F1 > rare-class recall across all 9 (backbone, dataset) settings [Paper] [Paper: PDF p. 3]	Dataset imbalance structure —not pretraining—drives the gap; rare classes are systematically underserved despite high aggregate scores [Paper] [Paper: PDF p. 1, 3]	Figure 2 (left): Pancreas has highest accuracy but largest accuracy-to-rare-recall drop; MS shows greatest reweighting benefit despite comparable imbalance ratio to Zheng68K [Paper] [Paper: PDF p. 3-4]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Loss-level interventions are not universally effective	Two rare classes (oligodendrocyte C, phagocyte in MS) achieve near-zero F1 under <i>all</i> six losses and <i>all</i> three backbones [Paper] [Paper: PDF p. 5]	Insufficient training samples (n=3 each) prevent learning discriminative representations; geometric signatures (NC1, neighbor absorption) confirm embedding-space collapse [Paper] [Paper: PDF p. 5–6]	Figure 3 (left): two darkest rows show near-zero F1 across all three backbone columns; Figure 4: UMAP shows 116 test cells of these classes absorbed into unrelated clusters under both CE and LDAM [Paper] [Paper: PDF p. 5, 7]
Reweighting efficacy is misattributed to relative frequency	Weighted CE performs best on MS (most imbalanced by ratio), yet worst on Zheng68K (less imbalanced) [Paper] [Paper: PDF p. 3–4]	Absolute training-set size—not class share or dataset imbalance ratio—predicts reweighting gain ($r = -0.77$, $p < 0.001$) [Paper] [Paper: PDF p. 4]	Figure 3 (right): $\Delta F1$ strongly negatively correlated with $\log(\text{training-set size})$; MS rare classes have smallest absolute counts, explaining its largest gain (+9.9%) [Paper] [Paper: PDF p. 4]
Loss functions make hidden trade-offs obscured by Macro-F1	Logit adjustment achieves highest rare-class recall on Zheng68K (0.685) but lowest rare-class precision among all six losses [Paper] [Paper: PDF p. 4]	It shifts decision thresholds rather than improving feature separability, increasing false positives [Paper] [Paper: PDF p. 4]	Figure 2 (right): logit-adjusted point lies far below $y=x$ line; Table 1 shows its rare-class precision is lowest (0.632 vs. class-balanced’s 0.685) [Paper] [Paper: PDF p. 4, 5]

06 核心理念

论文的核心洞见是：**单细胞长尾失效存在结构性二分法，必须解耦为“可优化”与“不可优化”两类问题**。前者（loss-sensitive）源于损失函数对少数类梯度的压制，可通过重加权（如class-balanced loss）或边界调整（LDAM）缓解；后者（severely entangled）则根植于数据稀缺导致的嵌入几何坍缩——即使最优损失也无法从3个样本中学习鲁棒表征，此时瓶颈不在优化目标，而在数据本身或分类器设计。因此，论文主张将“选择损失函数”升级为“诊断失效机制”：先用NC1、最近邻混淆等几何指标筛查严重纠缠类，再对剩余类施加损失优化。这一思想将长尾问题从统计偏差修正，转向对**表示空间拓扑完整性**的诊断与修复。

07 方法总览

论文采用**控制变量+多维诊断**范式：固定数据划分、预处理、微调协议（除scBERT冻结策略外），系统遍历3 backbone × 3 dataset × 6 loss × 3 seed = 162次训练；评估指标覆盖宏观（accuracy, Macro-F1）、罕见类专属（rare-class recall/precision/AUPRC）及几何（NC1, nearest-neighbor entropy）；诊断路径为三阶递进：(1) 统计失效（Figure 2/3）→ (2) 几何归因（Figure 4, Equation 4, Section 5.2）→ (3) 信号定位（linear probe in Section 5.3）。关键创新在于将神经坍缩理论（Papayan et al. 2020）的NC1指标直接应用于冻结测试嵌入，使其成为事前可计算的失效预警信号，而非事后解释工具。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Loss-function grid	Systematically compare six long-tail losses (CE, weighted CE, class-balanced, focal, LDAM, logit-adjusted)	To isolate loss-level effects from architecture/dataset confounds and identify most robust choices	Input: logits + labels; Output: scalar loss per sample	Table 1 reports Macro-F1/rare-recall per loss; Figure 2 (right) plots precision-recall trade-offs [Paper] [Paper: PDF p. 3–5]	Without this grid, claims about "class-balanced loss being most consistent" (mean rank 2.4) would be unsubstantiated [Paper] [Paper: PDF p. 3]
Embedding geometry analyzer	Compute NC1 (Equation 4), nearest-neighbor confusion patterns, and linear probe F1 on frozen embeddings	To distinguish data-scarcity-driven failure (geometric collapse) from optimization-driven failure (suboptimal loss)	Input: frozen test-set embeddings + true labels; Output: NC1 scalar, confusion matrix, probe F1	Figure 4 visualizes absorption; Equation 4 defines NC1; Section 5.2–5.3 report NC1 values (e.g., oligodendrocyte C: 1.19–1.79) and probe gains (e.g., +13.6 F1 points) [Paper] [Paper: PDF p. 6–7]	Removing this module would conflate "unrecoverable" and "loss-sensitive" classes, invalidating the two-regime conclusion [Paper] [Paper: PDF p. 5]
Rare-class definition & filtering	Define rare classes as those with <5% training frequency; exclude classes with mean F1<0.2 under best loss for regression	To separate severely entangled classes (floor performance) from recoverable ones for clean correlation analysis	Input: training-set class counts; Output: set R of rare classes, filtered subset for Δ F1 regression	Section 3 defines R; Section 4.3 excludes n=4 classes with mean F1<0.2 before computing $r=-0.77$ correlation [Paper] [Paper: PDF p. 3, 4]	Without filtering, the Δ F1 vs. size correlation weakens ($r=-0.53$), obscuring the core predictive relationship [Paper] [Paper: PDF p. 4]
Cross-architecture agreement checker	Analyze misclassification patterns across scGPT/scBERT/Genformer for same rare classes	To confirm failure is data-driven (transcriptional overlap) not architecture-specific artifact	Input: per-backbone confusion matrices; Output: dominant confusion partners (e.g., phagocyte→oligodendrocyte A)	Section 5.2: "Oligodendrocyte A and mixed glial type jointly account for 91–97% of all phagocyte misclassifications across all three backbones" [Paper] [Paper: PDF p. 6]	Without cross-architecture validation, observed confusion could be dismissed as scGPT-specific bug, not biological signal [Paper] [Paper: PDF p. 6]

09 关键公式与符号

- **No verifiable closed-form equations are presented in the paper.** All equation identifiers (Equation 1–4) are fragments embedded in text without full derivation or standalone presentation.
- Key symbols/variables extracted:
- c : total number of classes [Paper] [Paper: PDF p. 3]
- $R \subseteq \{1, \dots, c\}$: set of rare classes (training frequency <5%) [Paper] [Paper: PDF p. 3]
- $F1_{c}$: F1 score for class c [Paper] [Paper: PDF p. 3]
- Recall_c : recall for class c [Paper] [Paper: PDF p. 3]
- $\Delta F1_{c} = \max_{\ell \in L} F1_{\ell, c} - F1_{(CE)_{\ell, c}}$: gain in class- c F1 from best loss over CE [Paper] [Paper: PDF p. 4, Eq. 3]
- $NC1 = \text{tr}(\Sigma W) / \text{tr}(\Sigma B)$: neural collapse trace ratio; ΣW = avg within-class scatter, ΣB = between-class scatter of centroids [Paper] [Paper: PDF p. 6, Eq. 4]
- AUPRC : area under precision-recall curve, macro-averaged over rare classes [Paper] [Paper: PDF p. 3]
- Metrics reported: Accuracy, Macro-F1 (Eq. 1), rare-class recall (Eq. 2), rare-class precision, rare-class macro-AUPRC.

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
162-run benchmark	Which loss function is most robust across architectures and datasets?	3 backbones $\times$ 3 datasets $\times$ 6 losses $\times$ 3 seeds; all other hyperparameters fixed per backbone [Paper] [Paper: PDF p. 2–3]	Class-balanced loss (mean rank 2.4) and LDAM (2.6) most consistent; weighted CE best on MS (0.721), LDAM best on Pancreas (0.819) [Paper] [Paper: PDF p. 3, Table 1]	Class-balanced loss and LDAM are top-tier generalists for rare-class recovery	That either loss is universally superior—weighted CE outperforms both on MS Macro-F1 [Paper] [Paper: PDF p. 3, Table 1]	[Paper] [Paper: PDF p. 3, Table 1]
$\Delta F1$ vs. training size regression	Does absolute sample count predict reweighting gain better than relative frequency?	Correlate $\Delta F1_{c}$ (Eq. 3) with $\log(\text{training-set size})$ for all rare classes; exclude floor-performance classes ($n=4$) [Paper] [Paper: PDF p. 4]	Strong negative Pearson correlation ($r=-0.77$, $p<0.001$, $n=19$); robust to exclusion thresholds [Paper] [Paper: PDF p. 4, Figure 3 (right)]	Absolute training-set size—not imbalance ratio—drives reweighting efficacy	That this holds for <i>all</i> rare classes—excluded 4 severely entangled classes show no such trend [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4, Figure 3 (right)]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
UMAP + linear probe on frozen embeddings	Is discriminative signal present for severely entangled classes?	Fit class-balanced logistic regression on frozen CE-fine-tuned embeddings (5-fold CV); compare to best trained classifier F1 [Paper] [Paper: PDF p. 6]	Probe recovers non-trivial F1 (0.175–0.465) exceeding best trained classifier (0.000–0.329) for oligodendrocyte C/phagocyte [Paper] [Paper: PDF p. 6]	Signal exists in representation but is unused by current loss+classifier pipelines	That a nonlinear probe would close the gap—no test of nonlinear classifiers performed [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6]
NC1 computation on rare classes	Does neural collapse geometry differ between severely entangled and other rare classes?	Compute NC1 (Eq. 4) on MS rare classes' frozen CE embeddings across all three backbones [Paper] [Paper: PDF p. 6]	Oligodendrocyte C shows high NC1 (1.19–1.79, 2nd highest); phagocyte shows low NC1 (0.17–0.32, 8th of 11) [Paper] [Paper: PDF p. 6]	NC1 distinguishes geometric failure modes: oligodendrocyte C lacks tight clustering; phagocyte suffers from small-sample absorption	That NC1 alone suffices for diagnosis—phagocyte requires nearest-neighbor entropy to reveal concentrated absorption [Paper] [Paper: PDF p. 6]	[Paper] [Paper: PDF p. 6, Eq. 4]

11 对结论的正确理解

- “Class-balanced loss is most consistent” means it ranks near the top across *all nine* (backbone, dataset) combinations—not that it wins every column (weighted CE wins MS Macro-F1; LDAM wins Pancreas Macro-F1) [Paper] [Paper: PDF p. 3, Table 1].
- “Severely entangled classes are unrecoverable” refers specifically to the *six evaluated losses* and *three architectures*; it does not preclude recovery via other methods (e.g., generative replay [Li et al. 2026], contrastive learning [Zhai et al. 2024], or decoupled calibration [Kang et al. 2020]) [Paper] [Paper: PDF p. 5, 7].
- “Absolute training-set size predicts reweighting gain” is an empirical correlation ($r=-0.77$) for *recoverable* rare classes—not a causal law applicable to all regimes [Paper] [Paper: PDF p. 4]. The four severely entangled classes ($n=3$ samples) lie outside this trend.
- “Logit adjustment trades precision for recall” is demonstrated *only for rare classes*; non-rare class precision/recall vary by <2.1 points across losses, confirming the trade-off is rare-class specific [Paper] [Paper: PDF p. 4].

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited backbone coverage	Only scGPT, scBERT, Geneformer tested; scFoundation and CellPLM untested [Paper] [Paper: PDF p. 7]	Extend benchmark to other existing single-cell foundation models (scFoundation, CellPLM) [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]
Classifier expressivity ceiling	Linear probe on frozen embeddings recovers signal unused by trained heads, suggesting current losses+linear heads may be suboptimal [Paper] [Paper: PDF p. 6]	Test more expressive, nonlinear classifier heads beyond the six losses evaluated [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]
Isolated imbalance axis	Study focuses solely on cell-type class imbalance; ignores compounding variables like demographic composition or batch effects [Paper] [Paper: PDF p. 7]	Investigate interactions between cell-type imbalance and demographic composition (Al Amin et al. 2025) or batch effects (Maan et al. 2024) [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The paper attributes phagocyte’ s misclassification to "ingested myelin/oligodendrocyte RNA" (Schirmer et al. 2019), but this biological explanation is not validated against gene expression profiles (e.g., myelin gene enrichment in phagocyte vs. oligodendrocyte A)	Misclassification could stem from technical artifacts (e.g., ambient RNA contamination during droplet-based sequencing) rather than true transcriptional overlap	Confusing technical noise with biology risks misdirecting therapeutic targeting or data curation efforts	Re-analyze raw counts (not HVG-filtered) for phagocyte: quantify % reads mapping to myelin genes (e.g., MBP, PLP1) and compare to oligodendrocyte A; simulate ambient RNA contamination to see if it reproduces absorption pattern	[Paper] [Paper: PDF p. 6] cites Schirmer et al. 2019 for biological interpretation but provides no direct transcriptomic evidence in this work

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
NC1 is computed only on <i>frozen test-set embeddings</i> , yet the paper uses it to diagnose <i>training-data scarcity</i> . However, NC1 reflects final representation geometry, which integrates both pretraining and fine-tuning effects	High NC1 for oligodendrocyte C could arise from poor pretraining (e.g., insufficient myelin-related context in scGPT’ s corpus) rather than just n=3 training samples	Attributing failure solely to data scarcity overlooks opportunities to improve pretraining for disease-relevant states	Fine-tune scGPT on a synthetic MS lesion dataset (enriched for myelin/phagocytosis genes) and recompute NC1 for oligodendrocyte C; if NC1 drops, pretraining matters	[Paper] [Paper: PDF p. 6] computes NC1 post-fine-tuning but interprets it as evidence of training-data insufficiency without isolating pretraining contribution
The linear probe uses <i>class-balanced logistic regression</i> , but the paper does not test whether standard (unbalanced) logistic regression or SVMs yield different recovery rates for severely entangled classes	Class-balancing in the probe itself may artificially inflate apparent signal detectability, masking true linear separability limits	Overstating residual signal could delay adoption of necessary architectural changes (e.g., contrastive learning)	Run identical linear probes with unbalanced logistic regression and RBF-SVM; compare F1 gain over trained heads; if gains vanish, class-balancing—not signal—is the driver	[Paper] [Paper: PDF p. 6] specifies "class-balanced logistic regression" for probes but doesn’ t justify this choice or test alternatives

14 学到的知识

- **长尾失效必须分层诊断**：不能只看Macro-F1或accuracy；需结合罕见类专属指标（recall/precision/AUPRC）与嵌入几何（NC1、最近邻熵）区分“可优化”与“不可优化”两类。
- **绝对样本量比相对频率更关键**：对可优化类，重加权收益由训练集绝对大小（而非占比）决定——这提示在数据收集阶段应优先补足绝对数量极低的类（如<10 cells），而非追求整体平衡。
- **损失函数有隐性trade-off**：Macro-F1 hides precision-recall conflicts; logit adjustment boosts recall at precision cost, while class-balanced loss improves both—choosing requires clinical context (e.g., false negative cost > false positive cost).
- **几何指标可事前预警**：NC1和最近邻混淆模式在CE训练后即可计算，无需重训所有损失；它们是比重新训练更快的失效筛查工具。
- **信号存在 ≠ 被利用**：线性探针在冻结嵌入上恢复性能，证明当前损失+分类器组合未充分利用表示能力——这为解耦表示学习与分类器校准（Kang et al. 2020）提供了强实证支持。

15 与既有知识的连接

- **候选连接/方法论连接**：本文的“嵌入几何诊断”（NC1, nearest-neighbor absorption）与计算机视觉中神经坍缩（neural collapse）理论（Papayan et al. 2020）、不平衡学习的几何分析（Fang et al. 2021）形成跨领域呼应，但首次将其锚定于单细胞生物学语境下的病理亚群。
- **候选连接/方法论连接**：线性探针验证残余信号的思路，直接继承自Alain & Bengio (2017)，但本文将其用于诊断长尾瓶颈，而非仅解释中间层功能。

- **候选连接/方法论连接**：将“绝对样本量”作为预测因子，呼应通用长尾学习中的effective-number-of-samples框架（Cui et al. 2019）和医学影像研究（Buda et al. 2018），但首次在单细胞基础模型上实证。
- **弱连接/方法论连接**：与用户研究方向中“cell state representation”和“perturbation prediction”存在方法论接口——本文揭示的几何坍塌（如oligodendrocyte C的高NC1）可能泛化至扰动响应状态空间，提示需在扰动建模中显式约束嵌入几何。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Geometry-Guided Data Augmentation for Severely Entangled Classes

originating limitation/observation: Severely entangled classes (e.g., oligodendrocyte C, $n=3$) fail due to geometric collapse (high NC1, neighbor absorption), and linear probes confirm signal exists but is unused [Paper] [Paper: PDF p. 6]. **core hypothesis**: Synthetic augmentation that preserves the *embedding geometry* of the dominant confusion partner (e.g., oligodendrocyte A) will teach the classifier to disentangle transcriptionally overlapping states without introducing artificial signals. **delta from paper**: Paper identifies the problem and confirms signal exists; this idea proposes a geometry-aware augmentation strategy instead of accepting data scarcity as fatal. **initial method**: Use scGPT's frozen encoder to embed oligodendrocyte A cells; apply PCA to their embedding subspace; generate synthetic oligodendrocyte C cells by perturbing oligodendrocyte A embeddings along directions orthogonal to the oligodendrocyte A centroid-subspace, scaled by the distance to phagocyte's centroid. **validation**: Train class-balanced loss on augmented MS dataset; measure $\Delta F1$ for oligodendrocyte C vs. baseline (no aug) and vs. SMOTE; compute NC1 reduction. **failure modes**: Augmentation may amplify ambient RNA artifacts; orthogonality constraint may not capture true biological transition paths. **innovation status**: unverified

- **name**: NC1-Aware Loss Scheduling

originating limitation/observation: NC1 is computed post-hoc on frozen embeddings, but loss choice is made pre-training; no mechanism links geometry to dynamic loss adaptation [Paper] [Paper: PDF p. 6]. **core hypothesis**: Monitoring NC1 *during training* (on validation embeddings) enables adaptive loss switching—e.g., start with CE, switch to LDAM when NC1 exceeds threshold, then to logit adjustment if recall plateaus. **delta from paper**: Paper uses NC1 for *diagnosis*; this idea uses it for *online control* of optimization dynamics. **initial method**: Compute NC1 on validation embeddings every 2 epochs; define thresholds τ_1 (switch to LDAM), τ_2 (switch to logit adjustment); implement in PyTorch Lightning callback. **validation**: Compare final rare-class F1 and training stability (epoch-to-epoch NC1 variance) against fixed-loss baselines on MS dataset. **failure modes**: NC1 estimation noise on small validation sets may trigger premature switching; thresholds may not generalize across datasets. **innovation status**: unverified

- **name**: Cross-Dataset Entanglement Transfer

originating limitation/observation: Severely entangled classes recur across datasets (MS, Zheng68K, Pancreas) with similar geometric signatures (e.g., low sample count + high NC1) [Paper] [Paper: PDF p. 5, Figure 3 (right)] — suggesting shared failure mechanisms. **core hypothesis**: Entanglement patterns (e.g., phagocyte $\leftrightarrow$ oligodendrocyte A absorption) learned on one dataset can be transferred as *geometric*

priors to improve rare-class recovery on another, even without shared cell types. **delta from paper:** Paper observes cross-dataset recurrence but treats datasets in isolation; this idea exploits recurrence for knowledge transfer. **initial method:** Extract the nearest-neighbor confusion matrix for severely entangled classes on MS; use it to regularize the classifier head's weight matrix on Zheng68K (e.g., penalize logits for classes that are top-2 neighbors in MS). **validation:** Measure Δ F1 for rare classes on Zheng68K with/without MS-derived regularization; ablate by shuffling the MS confusion matrix. **failure modes:** Confusion patterns may be dataset-specific (e.g., driven by platform effects); regularization may over-constrain non-entangled classes. **innovation status:** unverified